

WHITE MINERAL OIL 70

Light Food Grade White Oil

White Mineral Oil 70 is refined by high pressure hydrotreating of select feed stocks to produce a minimum of technical grade white mineral oil of the highest quality and is stabilized with Vitamin E.

White Mineral Oil 70 exceeds the requirements of U.S. FDA regulation 21 CFR 178.3620 (b), for use as a component of non-food articles in contact with food for human consumption, and is registered as a H1 lubricant for incidental food contact by NSF, for use in food plants under the jurisdiction of the USDA.

White Mineral Oil 70 is used as a lubricant for drawing, stamping, forming and rolling of aluminum foil used in food packaging, as defoamers in the manufacture of paper and adhesives intended for food packaging, and as a lubricant for textile fibers/fabric used to process food.

White Mineral Oil 70 can be used as a plasticizer for rubber used on conveyor belts, hoses, rollers, and as a lubricant cleaner and rust preventive for machinery and other equipment in food processing plants.

TYPICAL PROPERTIES:

Gravity, ASTM D 4052, °API	33.5
Specific Gravity at 25°C, ASTM D 1298	0.858
Flash Point, ASTM D 92, °F (°C)	360 (182)
Pour Point, ASTM D 97, °F (°C)	-20 (-29)
Viscosity, ASTM D 445, cSt. at 40°C	13.9
ASTM D 2161, SUS at 100°F	73
NSF Registered H1	

Note: This Oil is colorless (Saybolt +20 Color, minimum), odorless and tasteless and surpasses requirements of FDA for Technical Grade White Mineral Oil. (21 CFR 178.3620(b))