FFmpeg Bitstream Filters Documentation

Table of Contents

- 1 Description
- 2 Bitstream Filters
 - 2.1 aac_adtstoasc
 - 2.2 chomp
 - 2.3 dump_extra
 - 2.4 h264_mp4toannexb
 - 2.5 imxdump
 - 2.6 mjpeg2jpeg
 - 2.7 mjpega_dump_header
 - O 2.8 movsub
 - 2.9 mp3_header_decompress
 - 2.10 noise
 - 2.11 remove extra
- 3 See Also
- 4 Authors

1 Description

This document describes the bitstream filters provided by the libavcodec library.

A bitstream filter operates on the encoded stream data, and performs bitstream level modifications without performing decoding.

2 Bitstream Filters

When you configure your FFmpeg build, all the supported bitstream filters are enabled by default. You can list all available ones using the configure option --list-bsfs.

You can disable all the bitstream filters using the configure option --disable-bsfs, and selectively enable any bitstream filter using the option --enable-bsf=BSF, or you can disable a particular bitstream filter using the option --disable-bsf=BSF.

The option -bsfs of the ff* tools will display the list of all the supported bitstream filters included in your build.

Below is a description of the currently available bitstream filters.

2.1 aac_adtstoasc

Convert MPEG-2/4 AAC ADTS to MPEG-4 Audio Specific Configuration bitstream filter.

This filter creates an MPEG-4 AudioSpecificConfig from an MPEG-2/4 ADTS header and removes the ADTS header.

This is required for example when copying an AAC stream from a raw ADTS AAC container to a FLV or a MOV/MP4 file.

2.2 chomp

Remove zero padding at the end of a packet.

2.3 dump_extra

Add extradata to the beginning of the filtered packets.

The additional argument specifies which packets should be filtered. It accepts the values:

```
'a'
add extradata to all key packets, but only if <code>local_header</code> is set in the flags2 codec context field
'k'
add extradata to all key packets
'e'
add extradata to all packets
```

If not specified it is assumed 'k'.

For example the following ffmpeg command forces a global header (thus disabling individual packet headers) in the H.264 packets generated by the libx264 encoder, but corrects them by adding the header stored in extradata to the key packets:

```
ffmpeg -i INPUT -map 0 -flags:v +global_header -c:v libx264 -bsf:v dump_extra out.ts
```

2.4 h264_mp4toannexb

Convert an H.264 bitstream from length prefixed mode to start code prefixed mode (as defined in the Annex B of the ITU-T H.264 specification).

This is required by some streaming formats, typically the MPEG-2 transport stream format ("mpegts").

For example to remux an MP4 file containing an H.264 stream to mpegts format with ffmpeg, you can use the command:

```
ffmpeg -i INPUT.mp4 -codec copy -bsf:v h264_mp4toannexb OUTPUT.ts
```

2.5 imxdump

Modifies the bitstream to fit in MOV and to be usable by the Final Cut Pro decoder. This filter only applies to the mpeg2video codec, and is likely not needed for Final Cut Pro 7 and newer with the appropriate -tag:v.

For example, to remux 30 MB/sec NTSC IMX to MOV:

```
ffmpeg -i input.mxf -c copy -bsf:v imxdump -tag:v mx3n output.mov
```

2.6 mjpeg2jpeg

Convert MJPEG/AVI1 packets to full JPEG/JFIF packets.

MJPEG is a video codec wherein each video frame is essentially a JPEG image. The individual frames can be extracted without loss, e.g. by

```
ffmpeg -i ../some_mjpeg.avi -c:v copy frames_%d.jpg
```

Unfortunately, these chunks are incomplete JPEG images, because they lack the DHT segment required for decoding. Quoting from http://www.digitalpreservation.gov/formats/fdd/fdd000063.shtml:

Avery Lee, writing in the rec.video.desktop newsgroup in 2001, commented that "MJPEG, or at least the MJPEG in AVIs having the MJPG fource, is restricted JPEG with a fixed – and *omitted* – Huffman table. The JPEG must be YCbCr colorspace, it must be 4:2:2, and it must use basic Huffman encoding, not arithmetic or progressive. . . . You can indeed extract the MJPEG frames and decode them with a regular JPEG decoder, but you have to prepend the DHT segment to them, or else the decoder won't have any idea how to decompress the data. The exact table necessary is given in the OpenDML spec."

This bitstream filter patches the header of frames extracted from an MJPEG stream (carrying the AVI1 header ID and lacking a DHT segment) to produce fully qualified JPEG images.

```
ffmpeg -i mjpeg-movie.avi -c:v copy -bsf:v mjpeg2jpeg frame_%d.jpg
exiftran -i -9 frame*.jpg
ffmpeg -i frame_%d.jpg -c:v copy rotated.avi
```

2.7 mjpega_dump_header

2.8 movsub

2.9 mp3_header_decompress

2.10 noise

Damages the contents of packets without damaging the container. Can be used for fuzzing or testing error resilience/concealment.

ffmpeg -i INPUT -c copy -bsf noise output.mkv

2.11 remove_extra

3 See Also

ffmpeg, ffplay, ffprobe, ffserver, libavcodec

4 Authors

The FFmpeg developers.

For details about the authorship, see the Git history of the project (git://source.ffmpeg.org/ffmpeg), e.g. by typing the command git log in the FFmpeg source directory, or browsing the online repository at http://source.ffmpeg.org.

Maintainers for the specific components are listed in the file MAINTAINERS in the source code tree.

This document was generated on November 4, 2014 using makeinfo.

FFmpeg Bitstream Filters Documentation

Table of Contents

- 1 Description
- 2 Bitstream Filters
 - 2.1 aac_adtstoasc
 - O 2.2 chomp
 - 2.3 dump_extra
 - 2.4 h264_mp4toannexb
 - O 2.5 imxdump
 - 2.6 mjpeg2jpeg
 - O 2.7 mjpega_dump_header
 - O 2.8 movsub
 - 2.9 mp3_header_decompress
 - 2.10 noise
 - 2.11 remove_extra
- 3 See Also
- 4 Authors

1 Description

This document describes the bitstream filters provided by the libavcodec library.

A bitstream filter operates on the encoded stream data, and performs bitstream level modifications without performing decoding.

2 Bitstream Filters

When you configure your FFmpeg build, all the supported bitstream filters are enabled by default. You can list all available ones using the configure option --list-bsfs.

You can disable all the bitstream filters using the configure option --disable-bsfs, and selectively enable any bitstream filter using the option --enable-bsf=BSF, or you can disable a particular bitstream filter using the option --disable-bsf=BSF.

The option -bsfs of the ff* tools will display the list of all the supported bitstream filters included in your build.

Below is a description of the currently available bitstream filters.

2.1 aac_adtstoasc

Convert MPEG-2/4 AAC ADTS to MPEG-4 Audio Specific Configuration bitstream filter.

This filter creates an MPEG-4 AudioSpecificConfig from an MPEG-2/4 ADTS header and removes the ADTS header.

This is required for example when copying an AAC stream from a raw ADTS AAC container to a FLV or a MOV/MP4 file.

2.2 chomp

Remove zero padding at the end of a packet.

2.3 dump_extra

Add extradata to the beginning of the filtered packets.

The additional argument specifies which packets should be filtered. It accepts the values:

```
'a'
add extradata to all key packets, but only if <code>local_header</code> is set in the flags2 codec context field
'k'
add extradata to all key packets
'e'
add extradata to all packets
```

If not specified it is assumed 'k'.

For example the following ffmpeg command forces a global header (thus disabling individual packet headers) in the H.264 packets generated by the libx264 encoder, but corrects them by adding the header stored in extradata to the key packets:

```
ffmpeg -i INPUT -map 0 -flags:v +global_header -c:v libx264 -bsf:v dump_extra out.ts
```

2.4 h264_mp4toannexb

Convert an H.264 bitstream from length prefixed mode to start code prefixed mode (as defined in the Annex B of the ITU-T H.264 specification).

This is required by some streaming formats, typically the MPEG-2 transport stream format ("mpegts").

For example to remux an MP4 file containing an H.264 stream to mpegts format with ffmpeg, you can use the command:

```
ffmpeg -i INPUT.mp4 -codec copy -bsf:v h264_mp4toannexb OUTPUT.ts
```

2.5 imxdump

Modifies the bitstream to fit in MOV and to be usable by the Final Cut Pro decoder. This filter only applies to the mpeg2video codec, and is likely not needed for Final Cut Pro 7 and newer with the appropriate -tag:v.

For example, to remux 30 MB/sec NTSC IMX to MOV:

```
ffmpeg -i input.mxf -c copy -bsf:v imxdump -tag:v mx3n output.mov
```

2.6 mjpeg2jpeg

Convert MJPEG/AVI1 packets to full JPEG/JFIF packets.

MJPEG is a video codec wherein each video frame is essentially a JPEG image. The individual frames can be extracted without loss, e.g. by

```
ffmpeg -i ../some_mjpeg.avi -c:v copy frames_%d.jpg
```

Unfortunately, these chunks are incomplete JPEG images, because they lack the DHT segment required for decoding. Quoting from http://www.digitalpreservation.gov/formats/fdd/fdd000063.shtml:

Avery Lee, writing in the rec.video.desktop newsgroup in 2001, commented that "MJPEG, or at least the MJPEG in AVIs having the MJPG fource, is restricted JPEG with a fixed – and *omitted* – Huffman table. The JPEG must be YCbCr colorspace, it must be 4:2:2, and it must use basic Huffman encoding, not arithmetic or progressive. . . . You can indeed extract the MJPEG frames and decode them with a regular JPEG decoder, but you have to prepend the DHT segment to them, or else the decoder won't have any idea how to decompress the data. The exact table necessary is given in the OpenDML spec."

This bitstream filter patches the header of frames extracted from an MJPEG stream (carrying the AVI1 header ID and lacking a DHT segment) to produce fully qualified JPEG images.

```
ffmpeg -i mjpeg-movie.avi -c:v copy -bsf:v mjpeg2jpeg frame_%d.jpg
exiftran -i -9 frame*.jpg
ffmpeg -i frame_%d.jpg -c:v copy rotated.avi
```

2.7 mjpega_dump_header

2.8 movsub

2.9 mp3_header_decompress

2.10 noise

Damages the contents of packets without damaging the container. Can be used for fuzzing or testing error resilience/concealment.

ffmpeg -i INPUT -c copy -bsf noise output.mkv

2.11 remove_extra

3 See Also

ffmpeg, ffplay, ffprobe, ffserver, libavcodec

4 Authors

The FFmpeg developers.

For details about the authorship, see the Git history of the project (git://source.ffmpeg.org/ffmpeg), e.g. by typing the command git log in the FFmpeg source directory, or browsing the online repository at http://source.ffmpeg.org.

Maintainers for the specific components are listed in the file MAINTAINERS in the source code tree.

This document was generated on November 4, 2014 using makeinfo.