EXP 4: Create UDF in PIG

Step-by-step installation of Apache Pig on Hadoop cluster on Ubuntu Pre-requisite:

- · Ubuntu 16.04 or higher version running (I have installed Ubuntu on Oracle VM (Virtual Machine) VirtualBox),
- · Run Hadoop on ubuntu (I have installed Hadoop 3.2.1 on Ubuntu 16.04). You may refer to my blog "How to install Hadoop installation" click <u>here</u> for Hadoop installation).

Pig installation steps

Step 1: Login into Ubuntu

Step 2: Go to https://pig.apache.org/releases.html and copy the path of the latest version of pig that you want to install. Run the following comment to download Apache Pig in Ubuntu:

\$ wget https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz

Step 3: To untar pig-0.16.0.tar.gz file run the following command:

\$ tar xvzf pig-0.16.0.tar.gz

Step 4: To create a pig folder and move pig-0.16.0 to the pig folder, execute the following command:

\$ sudo mv /home/hdoop/pig-0.16.0 /home/hdoop/pig

Step 5: Now open the .bashrc file to edit the path and variables/settings for pig. Run the following command:

\$ sudo nano .bashrc

Add the below given to .bashrc file at the end and save the file.

#PIG settingsexport PIG_HOME=/home/hdoop/pigexport
PATH=\$PATH:\$PIG_HOME/binexport
PIG_CLASSPATH=\$PIG_HOME/conf:\$HADOOP_INSTALL/etc/hadoop/export
PIG_CONF_DIR=\$PIG_HOME/confexport JAVA_HOME=/usr/lib/jvm/java-8openjdkamd64export PIG_CLASSPATH=\$PIG_CONF_DIR:\$PATH#PIG setting ends

Step 6: Run the following command to make the changes effective in the .bashrc file:

\$ source .bashrc

Step 7: To start all Hadoop daemons, navigate to the hadoop-3.2.1/sbin folder and run the following commands:

\$./start-dfs.sh\$./start-yarn\$ jps

Step 8: Now you can launch pig by executing the following command: \$ pig
Step 9: Now you are in pig and can perform your desired tasks on pig. You can come out of the pig by the quit command:
> quit;
CREATE USER DEFINED FUNCTION(UDF)
Aim: To create User Define Function in Apache Pig and execute it on map reduce.
Procedure:
Create a sample text file
hadoop@Ubuntu:~/Documents\$ nano sample.txt
Paste the below content to sample.txt
Hello
World vidhiya
hadoop@Ubuntu:~/Documents\$ hadoop fs -put sample.txt /home/hadoop/piginput/
Create PIG File
hadoop@Ubuntu:~/Documents\$ nano demo_pig.pig
paste the below the content to demo_pig.pig
Load the data from HDFS
data = LOAD '/home/hadoop/piginput/sample.txt' USING PigStorage(',') AS (id:int>
Dump the data to check if it was loaded correctly DUMP data;
Run

......

Create udf file an save as uppercase_udf.py

```
uppercase_udf.py
------
def uppercase(text): return text.upper()

if __name__ == "__main__":
import sys for line
in sys.stdin:
    line = line.strip() result
    = uppercase(line)
    print(result)
```

OUTPUT

