GE23131-Programming Using C-2024

Quiz navigation

1 2 3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Tuesday, 3 December 2024, 3:01 PM
Duration	20 days 2 hours

Question **1**

Correct

Marked out of 3.00

Flag question

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.

The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Input:

2

3

Output:

WBW

BWB

WBW

WBWBW

BWBWB

WBWBW

BWBWB

WBWBW

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main()
{
    int n,a;
    scanf("%d",&n);
    while(n!=0)
    {
        scanf("%d",&a);
        for(int i=0;i<a;i++){
        for(int j=0;j<a;j++)
        {
            if((i+j)%2==0)
            printf("W");
            else
            printf("B");
            }
        printf("\n");
    }
n--;
}
}
```

	Input	Expected	Got	
✓	2 3 5	WBW BWB WBW WBWBW BWBWB WBWBW BWBWB WBWBW	WBW BWB WBW WBWBW BWBWB WBWBW BWBWB WBWBW	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of 5.00

Flag question

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

2

2 W

3 B

Output:

WB

BW

BWB

WBW

BWB

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int t,n,i,j;
    char start,other;
    scanf("%d",&t);
    while(t--){
        scanf("%d %c",&n,&start);
        if(start=='W'||start=='w'){
            other='B';
        }
        else
        {
            other='W';
        }
        for(i=0;i<n;i++){
            for(j=0;j<n;j++){
```

```
                else{
                    printf("%c",other);
                }
            }
            printf("\n");
        }
    }
    return 0;
}
```

	Input	Expected	Got	
✓	2 2 W 3 B	WB BW BWB WBW BWB	WB BW BWB WBW BWB	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of 7.00

Flag question

Decode the logic and print the Pattern that corresponds to given input.

If N= 3

then pattern will be :

10203010011012

**4050809

If N= 4, then pattern will be:

10203040170180190200

**50607014015016

****809012013

******10011

Constraints

2 <= N <= 100

Input Format

First line contains T, the number of test cases

Each test case contains a single integer N

Output

First line print Case #i where i is the test case number

In the subsequent line, print the pattern

Test Case 1

3

5

Output

Case #1

10203010011012

**4050809

****607

Case #2

1020304017018019020

**50607014015016

****809012013

******10011

Case #3

102030405026027028029030

**6070809022023024025

****10011012019020021

******13014017018

********15016

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
    int t;
    scanf("%d",&t);
    for(int x=1;x<=t;x++){
        printf("Case #%d\n",x);
```

```
        int f=1, b=n*(n+1);
        for(int i=0;i<n;i++){
            for(int k=0;k<2*i;k++){
                printf("*");
            }
            printf("%d",f);
            f++;
            for(int j=2;j<=n-i;j++){
                printf("0%d",f);
                f++;
            }
            for(int l=b-(n-i)+1;l<=b;l++){
                printf("0%d",l);

            }
            b-=n-i;
            printf("\n");
        }
    }
    return 0;
}
```

	Input	Expected	Got	
✓	3 3 4 5	Case #1 10203010011012 **4050809 ****607 Case #2 1020304017018019020 **50607014015016 ****809012013	Case #1 10203010011012 **4050809 ****607 Case #2 1020304017018019020 **50607014015016 ****809012013	✓

		**6070809022023024025 ****10011012019020021 ******13014017018 ********15016	**6070809022023024025 ****10011012019020021 ******13014017018 ********15016	

Passed all tests! ✓

Finish review