

## EXERCISE - 7

### Displaying data from multiple tables

#### Objective

After the completion of this exercise, the students will be able to do the following:

- Write SELECT statements to access data from more than one table using equality and nonequality joins
- View data that generally does not meet a join condition by using outer joins
- Join a table to itself by using a self join

Sometimes you need to use data from more than one table.

#### Cartesian Products

- A Cartesian product is formed when:
  - A join condition is omitted
  - A join condition is invalid
  - All rows in the first table are joined to all rows in the second table
- To avoid a Cartesian product, always include a valid join condition in a WHERE clause.

A Cartesian product tends to generate a large number of rows, and the result is rarely useful. You should always include a valid join condition in a WHERE clause, unless you have a specific need to combine all rows from all tables.

Cartesian products are useful for some tests when you need to generate a large number of rows to simulate a reasonable amount of data.

#### Example:

To display employee last name and department name from the EMPLOYEES and DEPARTMENTS tables.

```
SELECT last_name, department_name dept_name  
FROM employees, departments;
```

#### Types of Joins

- Equijoin
- Non-equijoin
- Outer join
- Self join
- Cross joins
- Natural joins
- Using clause
- Full or two-sided outer joins
- Arbitrary join conditions for outer joins

#### Joining Tables Using Oracle Syntax

```
SELECT table1.column, table2.column  
FROM table1, table2  
WHERE table1.column1 = table2.column2;
```

Write the join condition in the WHERE clause.

- Prefix the column name with the table name when the same column name appears in more than one table.

## EXERCISE-7

### Displaying data from multiple tables

#### Objective

After the completion of this exercise, the students will be able to do the following:

- Write SELECT statements to access data from more than one table using equality and nonequality joins

- View data that generally does not meet a join condition by using outer joins

- Join a table to itself by using a self join

Sometimes you need to use data from more than one table.

#### Cartesian Products

- A Cartesian product is formed when:

- A join condition is omitted

- A join condition is invalid

- All rows in the first table are joined to all rows in the second table

- To avoid a Cartesian product, always include a valid join condition in a WHERE clause.

A Cartesian product tends to generate a large number of rows, and the result is rarely useful. You should always include a valid join condition in a WHERE clause, unless you have a specific need to combine all rows from all tables.

Cartesian products are useful for some tests when you need to generate a large number of rows to simulate a reasonable amount of data.

#### Example:

To displays employee last name and department name from the EMPLOYEES and DEPARTMENTS tables.

```
SELECT last_name, department_name dept_name
FROM employees, departments;
```

#### Types of Joins

- Equijoin
- Non-equijoin
- Outer join
- Self join
- Cross joins
- Natural joins
- Using clause
- Full or two sided outer joins
- Arbitrary join conditions for outer joins

#### Joining Tables Using Oracle Syntax

```
SELECT table1.column, table2.column
FROM table1, table2
WHERE table1.column1 = table2.column2;
```

Write the join condition in the WHERE clause.

- Prefix the column name with the table name when the same column name appears in more than one table.



This query retrieves all rows in the EMPLOYEES table, even if there is no match in the DEPARTMENTS table. It also retrieves all rows in the DEPARTMENTS table, even if there is no match in the EMPLOYEES table.

Find the Solution for the following:

1. Write a query to display the last name, department number, and department name for all employees.

Select last\_name, e.department\_id, d.department\_name  
from employees  
Join department on e.department\_id = d.department\_id.

2. Create a unique listing of all jobs that are in department 80. Include the location of the department in the output.

Select Distinct (e.job\_id, l.location\_id, l.city) from employees  
Join department on e.department\_id = d.department\_id  
Join location on d.location\_id = l.location\_id  
where l.department\_id = 80;

3. Write a query to display the employee last name, department name, location ID, and city of all employees who earn a commission

Select e.last\_name, d.department\_name, l.location\_id, l.city from  
employees Join department on e.department\_id = d.department\_id  
Join location on d.location\_id = l.location\_id where commission\_pct is not null.

8. Display the employee last name and department name for all employees who have an a(lowercase) in their last names. P

Select e.last\_name, d.department\_name from employees  
Join department on e.department\_id = d.department\_id.

5. Write a query to display the last name, job, department number, and department name for all employees who work in Toronto.

Select e.last\_name, e.job\_id, d.department\_id, d.department\_name  
Join location on d.location\_id = l.location\_id  
where l.city = 'Toronto'.

6. Display the employee last name and employee number along with their manager's last name and manager number. Label the columns Employee, Emp#, Manager, and Mgr#, Respectively

Select e.last\_name as Employee, e.emp\_id as 'Emp #',  
m.last\_name as Manager, m.employee\_id as 'Mgr #',  
from employees  
left Join employees on e.manager\_id = m.employee\_id.



7. Modify lab4\_6.sql to display all employees including King, who has no manager. Order the results by the employee number.

Select last name as employee, e.employee\_id as 'Emp ID',  
m.last name as manager, m.employee\_id as 'Mgr ID',  
from employee left join employee m on e.manager\_id =  
m.employee\_id order by e.employee\_id.

8. Create a query that displays employee last names, department numbers, and all the employees who work in the same department as a given employee. Give each column an appropriate label

Select e1.last name as 'Employee', e1.department\_id as  
"dept", e2.last name as 'Colleague' from employee e1,  
order by e1.department\_id, e2.last name.

9. Show the structure of the JOB\_GRADES table. Create a query that displays the name, job, department name, salary, and grade for all employees

Dis job-grades

10. Create a query to display the name and hire date of any employee hired after employee Davies.

Select last name, hire date  
from employees  
where hire date > (select hire date from employees  
where last name = 'Davies');

11. Display the names and hire dates for all employees who were hired before their managers, along with their manager's names and hire dates. Label the columns Employee, Emp Hired, Manager, and Mgr Hired, respectively.

Select last name as 'Employee', e.hire date as  
"Emp Hired" from employees  
Join employees e2 on e2.manager\_id = m.employee\_id  
where e.hire date < (m.hire date);



Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	