

Non-Preemptive Priority Scheduling algorithm

Write a C program to implement the Non-Preemptive Priority Scheduling algorithm. The program should accept number of processes their Arrival Time (AT), Burst Time (BT), and Priority for each process. The process with the highest priority (lowest numerical value) must be executed first among those that have arrived. Calculate the Average Waiting Time and Average Turnaround Time.

Input Format

The first line contains an integer representing the number of processes.

The next lines contain three integers for each process, where

- The first integer denotes the Arrival Time (AT)
- The second integer denotes the Burst Time (BT)
- The third integer denotes the Priority of the process.

A lower numerical value indicates a higher priority.

Select Language: C (GCC 9.2.0)

```

1 #include <stdio.h>
2
3 int main() {
4     int n, i, time = 0, completed = 0, pos;
5     int at[50], bt[50], pr[50];
6     int ct[50], tat[50], wt[50];
7     int done[50] = {0};
8     float avg_tat = 0, avg_wt = 0;
9
10    printf("Enter number of processes: \n");
11    scanf("%d", &n);
12
13    for(i = 0; i < n; i++) {
14        printf("Enter AT, BT and Priority for P%d: \n", i+1);
15        scanf("%d %d %d", &at[i], &bt[i], &pr[i]);
16    }
17
18    while(completed < n) {
19        pos = -1;
20        int highest = 9999;
21
22        for(i = 0; i < n; i++) {
23            if(at[i] <= time && done[i] == 0) {

```

Non-Preemptive Priority Scheduling algorithm

Write a C program to implement the Non-Preemptive Priority Scheduling algorithm. The program should accept number of processes their Arrival Time (AT), Burst Time (BT), and Priority for each process. The process with the highest priority (lowest numerical value) must be executed first among those that have arrived. Calculate the Average Waiting Time and Average Turnaround Time.

Input Format

The first line contains an integer representing the number of processes.

The next lines contain three integers for each process, where

- The first integer denotes the Arrival Time (AT)
- The second integer denotes the Burst Time (BT)
- The third integer denotes the Priority of the process.

A lower numerical value indicates a higher priority.

Select Language: C (GCC 9.2.0)

```

33     } else {
34         ct[pos] = time + bt[pos];
35         time = ct[pos];
36
37         tat[pos] = ct[pos] - at[pos];
38         wt[pos] = tat[pos] - bt[pos];
39
40         avg_tat += tat[pos];
41         avg_wt += wt[pos];
42
43         done[pos] = 1;
44         completed++;
45     }
46 }
47
48 avg_tat /= n;
49 avg_wt /= n;
50
51 printf("\nAverage Turnaround Time = %.2f\n", avg_tat);
52 printf("Average Waiting Time = %.2f\n", avg_wt);
53
54 return 0;
55 }

```

Input :

```

3
0 5 2
1 3 1
2 2 3

```

Expected Output :

```

Enter number of processes:
Enter AT, BT and Priority for P1:
Enter AT, BT and Priority for P2:
Enter AT, BT and Priority for P3:

Average Turnaround Time = 6.67
Average Waiting Time = 3.33

```

Output :

```

Enter number of processes:
Enter AT, BT and Priority for P1:
Enter AT, BT and Priority for P2:
Enter AT, BT and Priority for P3:

Average Turnaround Time = 6.67
Average Waiting Time = 3.33

```