Page 2

Reset, oscillators, JTAG I2C-E2PROM, SPI-Flash

Page 3

Power supplies

Page 4

DDR RAM, NAND FLASH, buffers

Page 5

Peripheral interface

Page 6

Ethernet interface

Page 7

USB interface

Page 8

SODIMM edge connector interface

UL = UnLoaded = normally not mounted component.

Default jumper settings are indicated in the schematic. However, always check jumper positions on actual boards since there is no guarantee that all jumpers are in default place.

Rev 1.4

Added U20 (alternative pad). Added R100-R105. Added fix for LPC3250 DDR.2 errata.

Rev 1.3

Added U19 (74LVC1G125) and C114 (100nF), and changed R17 to 33K (from UL), see schematic page 2.

Rev 1.2

Added R95, R96 pulldows. Clarified U10 part number. Added R97-R99, C112, C113 to prepare for LPC3250 DDR errata, but not needed. R17 not mounted.

Rev 1.1

Changed control pins for LED3-5 to P2.10-12. Added voltage test points.

Rev 1.0

Original revision



(C) Embedded Artists AB


TITLE: LPC32x0 OEM Board v1.4


Document Number:


REU:


Date: 2010-10-28 22:23:07


Sheet: 1/8












OTG USB Channel





(C) Embedded Artists AB

TITLE: LPC32x0 OEM Board v1.4

Document Number:

REV:

Date: 2010-10-28 22:23:07

Sheet: 7/8

SODIMM-200 Edge Connector

