Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Aim: Perform dynamic routing protocol (OSPF) and analyze the results

Connect PC and Switches and routers.



Then we will assign IP address and gateway to all the PCs.



Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**







Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**






```
Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int g0/0/0
Router(config-if)#ip add 10.0.0.1 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/0/0, changed state to up

Router(config-if)#exit
Router(config)#int s0/1/0
Router(config-if)#ip add 13.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface Serial0/1/0, changed state to down
Router(config-if)#exit
Router(config)#int s0/1/1
Router(config-if)#ip add 15.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface Serial0/1/1, changed state to down
Router(config-if)#exit
Router(config)#
```

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

```
Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int g0/0/0
Router(config-if)#ip add 11.0.0.1 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/0/0, changed state to up

Router(config-if)#exit
Router(config)#int s0/1/1
Router(config-if)#ip add
% Incomplete command.
Router(config-if)#ip add 14.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface Serial0/1/1, changed state to down
Router(config-if)#exit
Router(config)#int s0/1/0
Router(config-if)#
Router(config-if)#ip add 13.0.0.2 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface Serial0/1/0, changed state to up

Router(config-if)#exit
Router(config)#
```

```
Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#intg0/0/0
               ^
% Invalid input detected at '^' marker.

Router(config)#int g0/0/0
Router(config-if)#ip add 12.0.0.1 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/0/0, changed state to up

Router(config-if)#exit
Router(config)#int s0/1/0
Router(config-if)#ip add 14.0.0.2 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface Serial0/1/0, changed state to up

Router(config-if)#exit
Router(config)#
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial0/1/0, changed state to up

Router(config)#int s0/1/1
Router(config-if)#ip add 15.0.0.2 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface Serial0/1/1, changed state to up

Router(config-if)#exit
Router(config)#
```

Enable OSPF on Each RouterThe wildcard mask is the inverse of a subnet mask. It specifies which bits in an IP address should be considered for OSPF matching.

The Area ID organizes the OSPF domain into smaller, manageable sections to improve scalability and reduce routing overhead.

All routers in the same area share the same Area ID and maintain identical link-state databases.

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Area 0 is mandatory and acts as the central hub to which all other areas must connect.

Non-backbone areas like area 1, area 2 are used for networks that connect to the backbone.

```
Router#
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#
Router(config)#router ospf 1
Router(config-router)#network 10.0.0.0 0.0.0.255 area 0
Router(config-router)#network 13.0.0.0 0.0.0.255 area 0
Router(config-router)#network 15.0.0.0 0.0.0.255 area 1
Router(config-router)#
```

```
Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#router ospf 2
Router(config-router)#network 11.0.0.0 0.0.0.255 area 2
Router(config-router)#network 13.0.0.0 0.0.0.255 area 0
Router(config-router)#network 14.0.0.0 0.0.0.255 area 2
Router(config-router)#
Router(config-router)#exit
Router(config)#
Router(config)#
```

```
Router>enable
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)# router ospf 3
Router(config-router)#network 12.0.0.0 0.0.0.255 area 1
Router(config-router)#network 14.0.0.0 0.0.0.255 area 2
Router(config-router)#network 15.0.0.0 0.0.0.255 area 1
Router(config-router)#
Router(config-router)#exit
Router(config)#
Router(config)#
```

OSPF neighbors using **`show ip ospf neighbor`** to ensure adjacencies are established and check states, priorities, timers, and interfaces.

```
Router#
Router#sh ip ospf neighbor


Neighbor ID     Pri   State           Dead Time   Address         Interface
15.0.0.2          0   FULL/  -        00:00:38    14.0.0.2        Serial0/1/1
15.0.0.1          0   FULL/  -        00:00:31    13.0.0.1        Serial0/1/0
Router#
Router#
Router#
Router#
Router#
Router#
Router#
```

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Run *show ip ospf database* to verify OSPF's link-state database, checking router link states, advertised routers, and area details for accurate OSPF operation.

```
Router#sh ip ospf neighbor


Neighbor ID     Pri   State           Dead Time   Address         Interface
15.0.0.2          0   FULL/  -        00:00:38    14.0.0.2        Serial0/1/1
15.0.0.1          0   FULL/  -        00:00:31    13.0.0.1        Serial0/1/0
Router#
Router#
Router#
Router#
Router#
Router#
Router#sh ip ospf database
            OSPF Router with ID (14.0.0.1) (Process ID 1)

                Router Link States (Area 0)

Link ID         ADV Router      Age         Seq#       Checksum Link count
14.0.0.1        14.0.0.1        7           0x80000007 0x00ff0c 5
15.0.0.1        15.0.0.1        498         0x8000000c 0x00ce86 3
15.0.0.2        15.0.0.2        465         0x80000007 0x00cf25 4

                Summary Net Link States (Area 0)
Link ID         ADV Router      Age         Seq#       Checksum
15.0.0.0        15.0.0.1        488         0x80000001 0x0042fc
            OSPF Router with ID (13.0.0.2) (Process ID 2)

                Router Link States (Area 2)

Link ID         ADV Router      Age         Seq#       Checksum Link count
13.0.0.2        13.0.0.2        401         0x80000001 0x0061e4 0
Router#
```

Verify OSPF routers have discovered their neighbors.

```
Router#
Router#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

O    10.0.0.0/8 [110/65] via 13.0.0.1, 00:30:22, Serial0/1/0
     11.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       11.0.0.0/8 is directly connected, GigabitEthernet0/0/0
L       11.0.0.1/32 is directly connected, GigabitEthernet0/0/0
O    12.0.0.0/8 [110/2] via 14.0.0.2, 00:30:42, Serial0/1/1
     13.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       13.0.0.0/8 is directly connected, Serial0/1/0
L       13.0.0.2/32 is directly connected, Serial0/1/0
     14.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       14.0.0.0/8 is directly connected, Serial0/1/1
L       14.0.0.1/32 is directly connected, Serial0/1/1
O    15.0.0.0/8 [110/65] via 14.0.0.2, 00:08:34, Serial0/1/1
                [110/65] via 13.0.0.1, 00:08:34, Serial0/1/0

Router#
```

To determine the route packets take from the source to the destination, use the command: tracert <destination IP address>

This command displays the path packets follow as they traverse through various routers to reach their destination. It also provides the time taken to reach each hop along the route.

If the bandwidth of one path is higher, even if another route is shorter, the packets will prefer the high-bandwidth path for transmission.



CONCLUSION:

In conclusion, this experiment shows how OSPF works to choose the best path for sending packets. Using the tracert command, we can see the path packets take and how OSPF prefers routes with higher bandwidth, even if they are not the shortest. This makes the network work better and sends data faster, proving OSPF is good for handling big and complicated networks.

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**

Marwadi University Marwadi Chandarana Group	**Marwadi University** **Faculty of Engineering and Technology** **Department of Information and Communication Technology**	
Subject: Computer Networks (01CT0503)	**Aim:** Perform dynamic routing protocol (OSPF) and analyze the results.	
Experiment No: 07	**Date:**	**Enrolment No: 92200133021**