What is published, and what it regenerates

The study is built so that a third party can reproduce it without access to any proprietary code

PUBLISHED

spec/
The frozen specification and the conformance suite

cpp/ rust/
The parity-tested pair of implementations

bench/
Harness, campaign scripts, and the testbed protocol

faults/
The seven-program defect catalogue and its runner

ffi/
The C-ABI seam and its C++ host prototype

ONE COMMAND

bench/refresh_thesis.sh

Reruns the analysis over the raw logs and rebuilds the PDF, then fails loudly if LaTeX reports an error or an unresolved reference.

It calls

plot_figures.py: figures, tables, and gen_macros.tex
complexity.py: size and cyclomatic-complexity proxies

REGENERATED VERBATIM

Every figure, table, and quoted number in the evaluation, straight from the logs.

figures/*.pdf

figures/tab_*.tex

figures/gen_macros.tex

The environment record (CPU model, kernel, and toolchain versions) is captured by capture_env.sh and stored with each result set, so the conditions of a measurement travel with its data.

Not required: no proprietary source. The implementations are driven entirely by the public specification, and the subsystem is modelled on production code rather than copied from it.

Separating environment-sensitive results from environment-insensitive ones is what lets the thesis label the first preliminary and the second final without ambiguity.