



Co-funded by the
Erasmus+ Programme
of the European Union

Individual tree segmentation

Viet Nguyen
Faculty of Forest and Environment
University for Sustainable Development
Eberswalde, Germany

These Teaching/Learning materials may be used freely for non-profit purposes with proper recognition of the authors and the project



Introduction

For extracting tree attributes at a single tree scale, a segmentation of tree crowns is required. The Individual Tree Segmentation (ITS) classifies LiDAR point clouds into single trees with corresponding IDs. After segmentation, each point has an ID corresponding to the tree it belongs to. ITS methods can be generally grouped into two types, raster-based method and point cloud-based method.

Introduction

Raster-based algorithms detect trees (e.g., local maximum, image binarization, or template matching) and delineate crowns from the CHMs (e.g., valley-following, region-growing, or watershed segmentation) ([Dalponte et al., 2018](#); [Dalponte & Coomes, 2016](#); [Pirotti et al., 2017](#); [Puliti et al., 2020](#); [Vandendaele et al., 2021](#)).

To directly detect individual trees from the point cloud, a **point cloud-based algorithm** often requires Kmeans clustering, graph-based ([Strîmbu & Strîmbu, 2015](#)), kernel-based (Ferraz et al., [2012](#), [2016](#)), or voxel-based tree segmentation techniques.



Introduction

For the purpose of individual tree crown detection and delineation (ITCD), numerous semi- and fully-automatic algorithms have been developed (Zhen et al., 2016). While one algorithm works well for a certain application, it might not be optimal for others. Some methods that performed well in softwood stands have shown to be less accurate in hardwood or mixed forests, especially in environments with significant variation in tree spacing, age, or size, or when the crowns overlap (Zhen et al., 2015). Although previous studies have made tremendous progress, ITCD research is still developing.






Content

1. Raster-based approach

- Watershed
- Silva2016 (see [Silva et al., 2016](#))
- Dalponte2016

2. Point cloud-based approach

- Li2012 (see [Li et al., 2012](#))
- AMS3D




Watershed algorithm

- The watershed algorithm has been used in image processing primarily for object segmentation purposes
- The basic idea here is inverting the canopy height model (CHM), the treetops now become basins, and then starting to pour water into each basin. The water level then keeps rising, and at some point, they will touch each other, we can draw a separating line where water from basins touching, it becomes the border between tree crowns.




Watershed algorithm



Source: Duan et al., 2021 <https://doi.org/10.3390/s21041365>


Dalponte2016 algorithm (seeded region growing)

1. Local Maximum Filter (LMF) algorithm finds treetops (red dots in the figure). A point is considered as a treetop if it is the highest point inside the predefined search window. The search window is an area where the LMF algorithm analyzes the neighborhood points. For example, if the window size is set to 5 m, the algorithm checks the neighboring points within a 2.5 m radius around the given point to see if the point is the highest in the local window.



Dalponte2016 algorithm (seeded region growing)

2. Then the treetops were overlaid with CHM, and the crown will then grow around the treetops. The algorithm checks the (height) value of neighboring pixels around the treetops.
3. If the height values of neighboring pixels fulfill certain criteria, these pixels get included in the crown. If not, exclude the pixel



Dalponte2016 algorithm (seeded region growing)


NOTE!

the raster-based approach relies on 2D CHM which only presents the top trees that are visible from above. Therefore, the subcanopy trees may not be detected.

Recommended materials:


[Tree-centric mapping of forest carbon density from airborne laser scanning and hyperspectral data](#)

(Dalponte & Coomes, 2016)




The point cloud-based algorithm is expected to detect trees in all canopy layers. For every point in the point cloud, the algorithm builds a search window in cylinder kernel around them as in figure a and b. Then it finds all the points that fall inside the kernel and calculates the center of these points. The kernel is then shifted to the new center. From the new center, it again calculates a new center and keeps moving.

Mean shift algorithm




This procedure is repeated until the kernel's center reaches a stable position which is a local maximum of point density and this position is assumed to be the center of a tree crown. In the end, as in figure c the lines represent the moving paths of the kernels. Many points will have kernels stop in the same location and these points are labeled as a tree.

Mean shift algorithm




2. Point cloud-based approach



Source: Ferraz et al., 2012 <https://doi.org/10.1016/j.rse.2012.01.020>

a,b: Build kernels around points => calculate centers of points inside kernels => kernels move to new centers
c: Points have kernels stop at the same location form a tree

Mean shift algorithm




The size of kernel search windows (kernel length and diameter) is referred to as “kernel bandwidth”, which is different for each point because it is dependent on the height of the point. The higher the point is, the larger kernel is created.

This height dependence assures to detect large crown clusters in the upper canopy by bigger kernels and small crown clusters in the lower canopy by smaller kernels (Cao et al., 2022)


Source: Ferraz et al., 2016 <https://doi.org/10.1016/j.rse.2016.05.028>

Mean shift algorithm



Source: Ferraz et al., 2012 <https://doi.org/10.1016/j.rse.2012.01.020>

Mean shift algorithm



Recommended materials:

[3-D mapping of a multi-layered Mediterranean forest using ALS data](#) (Ferraz et al., 2012)

[Lidar detection of individual tree size in tropical forests](#) (Ferraz et al., 2016)



Co-funded by the
Erasmus+ Programme
of the European Union

¡Thank you for your reading!



References

- Bretar, F., Jacquemoud, S., Gonçalves, G., Pereira, L., Tomé, M., & Soares, P. (2012b, June). 3-D mapping of a multi-layered Mediterranean forest using ALS data. *Remote Sensing of Environment*, 121, 210–223. <https://doi.org/10.1016/j.rse.2012.01.020>
- Cao, Y., Ball, J. G. C., Coomes, D. A., Steinmeier, L., Knapp, N., Wilkes, P., Disney, M., Calders, K., Burt, A., Lin, Y., & Jackson, T. D. (2022). Tree segmentation in airborne laser scanning data is only accurate for canopy trees (p. 2022.11.29.518407). *bioRxiv*. <https://doi.org/10.1101/2022.11.29.518407>
- Dalponte, M., & Coomes, D. A. (2016). Tree-centric mapping of forest carbon density from airborne laser scanning and hyperspectral data. *Methods in Ecology and Evolution*, 7(10), 1236–1245. <https://doi.org/10.1111/2041-210X.12575>

References

- Dalponte, M., Frizzera, L., Ørka, H. O., Gobakken, T., Næsset, E., & Gianelle, D. (2018). Predicting stem diameters and aboveground biomass of individual trees using remote sensing data. *Ecological Indicators*, 85, 367–376.
<https://doi.org/10.1016/j.ecolind.2017.10.066>
- Duan, Z., Wang, J., Lu, G., Li, S., & Yu, Z. (2021, February 15). Research on Distance Transform and Neural Network Lidar Information Sampling Classification-Based Semantic Segmentation of 2D Indoor Room Maps. *Sensors*, 21(4), 1365.
<https://doi.org/10.3390/s21041365>
- Ferraz, A., Bretar, F., Jacquemoud, S., Gonçalves, G., Pereira, L., Tomé, M., & Soares, P. (2012). 3-D mapping of a multi-layered Mediterranean forest using ALS data. *Remote Sensing of Environment*, 121, 210–223. <https://doi.org/10.1016/j.rse.2012.01.020>

References

- Ferraz, A., Saatchi, S., Mallet, C., & Meyer, V. (2016). Lidar detection of individual tree size in tropical forests. *Remote Sensing of Environment*, 183, 318–333.
<https://doi.org/10.1016/j.rse.2016.05.028>
- Li, W., Guo, Q., Jakubowski, M. K., & Kelly, M. (2012). A New Method for Segmenting Individual Trees from the Lidar Point Cloud. *Photogrammetric Engineering & Remote Sensing*, 78(1), 75–84. <https://doi.org/10.14358/PERS.78.1.75>
- Nikolai, Knapp. (2021, October). *Introduction to tree delineation* [Paper presentation]. Module: Collection & analysis of lidar data, Eberswalde, Brandenburg, Germany.

References

- Pirotti, F., Kobal, M., & Roussel, J. R. (2017). A COMPARISON OF TREE SEGMENTATION METHODS USING VERY HIGH DENSITY AIRBORNE LASER SCANNER DATA. The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences, XLII-2/W7, 285–290. <https://doi.org/10.5194/isprs-archives-XLII-2-W7-285-2017>
- Puliti, S., Breidenbach, J., & Astrup, R. (2020). Estimation of Forest Growing Stock Volume with UAV Laser Scanning Data: Can It Be Done without Field Data? Remote Sensing, 12(8), 1245. <https://doi.org/10.3390/rs12081245>
- Silva, C. A., Hudak, A. T., Vierling, L. A., Loudermilk, E. L., O'Brien, J. J., Hiers, J. K., Jack, S. B., Gonzalez-Benecke, C., Lee, H., Falkowski, M. J., & Khosravipour, A. (2016). Imputation of Individual Longleaf Pine (*Pinus palustris* Mill.) Tree Attributes from Field and LiDAR Data. Canadian Journal of Remote Sensing, 42(5), 554–573. <https://doi.org/10.1080/07038992.2016.1196582>

References

- Strîmbu, V. F., & Strîmbu, B. M. (2015). A graph-based segmentation algorithm for tree crown extraction using airborne LiDAR data. *ISPRS Journal of Photogrammetry and Remote Sensing*, 104, 30–43. <https://doi.org/10.1016/j.isprsjprs.2015.01.018>
- Vandendaele, B., Fournier, R. A., Vepakomma, U., Pelletier, G., Lejeune, P., & Martin-Ducup, O. (2021). Estimation of Northern Hardwood Forest Inventory Attributes Using UAV Laser Scanning (ULS): Transferability of Laser Scanning Methods and Comparison of Automated Approaches at the Tree- and Stand-Level. *Remote Sensing*, 13(14), 2796. <https://doi.org/10.3390/rs13142796>
- Zhen, Z., Quackenbush, L., & Zhang, L. (2016). Trends in Automatic Individual Tree Crown Detection and Delineation—Evolution of LiDAR Data. *Remote Sensing*, 8(4), 333. <https://doi.org/10.3390/rs8040333>