



**SCHOOL OF
COMPUTING**

**DESIGN AND ANALYSIS OF ALGORITHMS
LAB WORKBOOK
WEEK - 4**

NAME : VIGHRANTH SK
ROLL NUMBER : CH.SC.U4CSE24149
CLASS : CSE-B

Question 1: Write a C program that reads N integers from the user and sorts it using Merge Sort.

CODE:

```
// Write a C program that reads N integers from the user and sorts it using Merge Sort.
```

```
#include <stdio.h>
```

```
void merge(int arr[], int left, int mid, int right) {
```

```
    int i, j, k;
```

```
    int n1 = mid - left + 1;
```

```
    int n2 = right - mid;
```

```
    int L[50], R[50];
```

```
    for (i = 0; i < n1; i++)
```

```
        L[i] = arr[left + i];
```

```
    for (j = 0; j < n2; j++)
```

```
        R[j] = arr[mid + 1 + j];
```

```
    i = 0;
```

```
    j = 0;
```

```
    k = left;
```

```
    while (i < n1 && j < n2) {
```

```
        if (L[i] <= R[j]) {
```

```
            arr[k] = L[i];
```

```
            i++;
```

```
        } else {
```

```
            arr[k] = R[j];
```

```
            j++;
```

```
        }
```

```
        k++;
```

```
    }
```

```
    while (i < n1) {
```

```
        arr[k] = L[i];
```

```
        i++;
```

```
        k++;
```

```
    }
```

```
    while (j < n2) {
```

```

        arr[k] = R[j];
        j++;
        k++;
    }
}

void mergeSort(int arr[], int left, int right) {
    if (left < right) {
        int mid = (left + right) / 2;
        mergeSort(arr, left, mid);
        mergeSort(arr, mid + 1, right);
        merge(arr, left, mid, right);
    }
}

int main() {
    int arr[50], n;
    printf("CH.SC.U4CSE24149 VIGHRANTH SK\n");
    printf("Enter number of elements: ");
    scanf("%d", &n);
    printf("Enter the elements:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }
    mergeSort(arr, 0, n - 1);
    printf("Sorted array:\n");
    for (int i = 0; i < n; i++) {
        printf("%d ", arr[i]);
    }
    return 0;
}

```

OUTPUT:

```
D:\AVV CHENNAI\Semester 4\Vighranth>gcc WEEK4Q1.C

D:\AVV CHENNAI\Semester 4\Vighranth>a
CH.SC.U4CSE24149 – VIGHRANTH S K
Enter number of elements: 12
Enter the elements:
157 110 147 122 111 149 151 141 123 112 117 133
Sorted array:
110 111 112 117 122 123 133 141 147 149 151 157
```

Space Complexity: $O(N)$

Time Complexity: $O(N \log N)$

Justification:

- The array is divided into two equal halves at each step, and the merge operation compares all n elements. Since this division continues for $\log n$ levels, the overall **Time Complexity** becomes $O(N \log N)$.
- An extra array is used during the merging process to temporarily store elements. This additional storage requires space proportional to the number of elements, resulting in **$O(n)$ Space Complexity**.

Question 2: Create a C program that implements Quick Sort to sort an array of integers.

CODE:

```
//Create a C program that implements Quick Sort to sort an array of integers
#include <stdio.h>

void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

int partition(int arr[], int low, int high) {
    int pivot = arr[high];
    int i = low - 1;
    for (int j = low; j < high; j++) {
        if (arr[j] < pivot) {
            i++;
            swap(&arr[i], &arr[j]);
        }
    }
    swap(&arr[i + 1], &arr[high]);
    return i + 1;
}

void quickSort(int arr[], int low, int high) {
    if (low < high) {
        int pi = partition(arr, low, high);
        quickSort(arr, low, pi - 1);
        quickSort(arr, pi + 1, high);
    }
}

int main() {
    int arr[50], n;
    printf("CH.SC.U4CSE24149 VIGHRANTH SK\n");
    printf("Enter number of elements: ");
```

```

scanf("%d", &n);
printf("Enter the elements:\n");
for (int i = 0; i < n; i++) {
    scanf("%d", &arr[i]);
}
quickSort(arr, 0, n - 1);
printf("Sorted array:\n");
for (int i = 0; i < n; i++) {
    printf("%d ", arr[i]);
}
return 0;
}

```

OUTPUT:

```

D:\AVV CHENNAI\Semester 4\Vighranth>gcc WEEK4Q2.C
D:\AVV CHENNAI\Semester 4\Vighranth>a
CH.SC.U4CSE24149 - VIGHRANTH S K
Enter number of elements: 12
Enter the elements:
157 110 147 122 111 149 151 141 123 112 117 133
Sorted array:
110 111 112 117 122 123 133 141 147 149 151 157

```

Space Complexity: $O(N)$

Time Complexity: $O(N^2)$

Justification:

- In the worst case, Quick Sort makes highly unbalanced recursive calls, reducing the problem size by only one element at each step. As a result, the recursion depth becomes n , and the recursion stack stores up to n function calls, leading to **$O(N)$ Space Complexity**.

- This occurs when the pivot divides the array into highly unbalanced parts, such as in already sorted or reverse sorted array. Hence the **Time Complexity** is $O(N^2)$.