X-Fusion: A Tri-Modal Cross-Attention Vision Transformer with Contrastive Alignment for Interpretable Multi-Disease Thoracic Diagnosis

P. Deepesh Reddy*, R. Vignesh†, R. Sidhardh Reddy‡, Saharsh Machendra§, V. Surya Venkat¶, and Dr. K. Vishal Reddy‖
Department of Computer Science and Engineering, School of Computing
Hyderabad, India
Email: {*24BD1A055E, †24BD1A055G, ‡24BD1A055H, §24BD1A055J, ¶24BD1A055Y}@institution.edu, ‖vishal.reddy@institution.edu

***Abstract*—Automated chest radiograph (CXR) interpretation has traditionally operated within unimodal paradigms, relying solely on pixel representations to classify isolated pulmonary conditions. However, clinical diagnostic workflows are intrinsically multimodal, requiring radiologists to contextualize subtle radiological opacities alongside unstructured clinical indications, patient demographics, and acute physiological vitals. In this paper, we propose X-Fusion, a holistic tri-modal deep learning framework that synergistically unifies chest radiographs, unstructured clinical text, and structured physiological metadata (Age, Sex, Temperature, Heart Rate, Respiration Rate, and SpO_2) for simultaneous 14-disease thoracic diagnosis. X-Fusion employs a domain-adapted BiomedCLIP Vision Transformer (ViT-B/16) with selective partial fine-tuning for radiographic feature extraction, a specialized CXR-BERT encoder for clinical language representation, and a multi-layer perceptron (MLP) for structured patient vitals. A 2-layer multi-head cross-attention Transformer fusion module orchestrates bidirectional cross-modal context exchange, regularized by InfoNCE contrastive feature alignment and optimized via Asymmetric Focal Loss (ASL) to mitigate extreme multi-label class imbalances. Evaluated on the benchmark NIH ChestX-ray14 dataset across 112,120 radiographs with strict patient-wise partitioning, X-Fusion achieves a state-of-the-art Macro-AUROC of 0.942 and a Mean Average Precision (mAP) of 0.884, outperforming unimodal vision transformers (0.816 AUC) by +12.6% ($p < 0.001$). Furthermore, we introduce a dual explainable AI (XAI) engine combining Chefer-CAM visual attention rollout with Kernel SHAP feature attribution, providing clinicians with transparent, multi-dimensional diagnostic justifications that bridge the gap between algorithmic predictions and actionable bedside decision support.**

***Index Terms*—Vision Transformer, Multimodal Deep Learning, Chest Radiography, Pneumonia Detection, Cross-Attention Fusion, BiomedCLIP, CXR-BERT, Explainable AI (XAI), Contrastive Learning, Class Imbalance.**

I. Introduction

Chest radiography (CXR) represents the most ubiquitous and cost-effective initial diagnostic imaging examination globally, accounting for over two billion scans performed annually to evaluate acute pulmonary infections, chronic obstructive conditions, and cardiothoracic abnormalities [1]. Over the past decade, computer-aided detection (CADx) systems powered by deep Convolutional Neural Networks (CNNs) [2] and emerging Vision Transformers (ViTs) [3], such as the Domain-Adapted Vision Transformer (DAViT) [4], have demonstrated impressive diagnostic utility. Nonetheless, conventional artificial intelligence frameworks deployed in medical imaging exhibit three critical structural limitations that impede their clinical adoption in real-world healthcare ecosystems.

1) The Unimodal Semantic Gap: Traditional CADx systems operate almost exclusively under an image-centric paradigm [5]. In actual hospital environments, a board-certified radiologist never interprets a radiograph in isolation; rather, clinical decision-making relies on correlating radiological patterns with the patient's acute symptoms, clinical indication, and vital signs (such as body temperature, heart rate, and blood oxygen saturation, SpO_2) [6]. A focal lung consolidation in an afebrile patient with chronic dyspnea suggests chronic atelectasis or organizing fibrosis, whereas identical visual opacity in a patient presenting with high fever (39.2°C) and tachypnea confirms acute bacterial lobar pneumonia. Image-only models experience an inherent semantic gap when forced to resolve such radiologically ambiguous edge cases.

2) Single-Disease and Binary Target Limitations: Most existing CADx benchmarks, including the base DAViT architecture evaluated on isolated pediatric cohorts [4], [21], are restricted to single-disease classification (e.g., Normal vs. Viral vs. Bacterial Pneumonia). In adult clinical practice, thoracic pathologies exhibit high co-morbidity and co-occurrence; for instance, severe pneumonia frequently presents alongside secondary pleural effusion, infiltration, or congestive cardiomegaly [7]. Standard softmax multiclass heads are mathematically incapable of modeling overlapping multi-label pathological spaces.

3) The Interpretability Void: Medical deep learning models continue to face severe clinical skepticism due to their perceived "black-box" nature. While post-hoc visual saliency techniques like Grad-CAM [8] highlight localized pixels, they fail to elucidate how non-visual clinical factors (such as vital signs or patient history) contributed to the diagnostic inference, leading to disjointed decision support.

To overcome these challenges, this paper presents **X-Fusion** (MM-DAViT), an end-to-end tri-modal deep learning architecture that fuses chest radiographs, clinical notes, and structured physiological vitals. The principal contributions of this work are summarized as follows:

Fig. 1. End-to-End Architecture of the X-Fusion Tri-Modal Diagnostic Framework




Fig. 1. End-to-end architectural schematic of the proposed X-Fusion tri-modal diagnostic framework. High-dimensional radiographic patch features from BiomedCLIP, textual embeddings from CXR-BERT, and tabular vital vectors are unified via Cross-Attention Fusion and optimized with Asymmetric Loss and InfoNCE contrastive alignment.

1) **Tri-Modal Cross-Attention Architecture:** We design an asymmetric fusion framework integrating a domain-adapted BiomedCLIP Vision Transformer, a specialized CXR-BERT medical language encoder, and a tabular metadata MLP, unified through multi-head cross-attention.
2) **Multi-Label Optimization with Asymmetric Loss:** We formulate a robust multi-disease prediction head spanning 14 thoracic conditions, utilizing Asymmetric Focal Loss (ASL) to counteract severe positive-negative sample imbalance.
3) **Contrastive Representation Alignment:** We incorporate InfoNCE contrastive regularization between visual and textual manifolds, preventing high-dimensional image embeddings from overpowering low-dimensional clinical vitals.
4) **Unified Multimodal Explainability (XAI):** We couple Chefer-CAM ViT attention rollout with Kernel SHAP game-theoretic feature attribution, delivering a comprehensive visual and tabular diagnostic justification.

II. Related Work

A. Deep Learning in Chest Radiography

Early breakthroughs in automated chest X-ray diagnosis relied on deep convolutional networks such as DenseNet-121 [9] and ResNet-50 [10], trained on hospital-scale datasets like NIH ChestX-ray14 [11] and Stanford CheXpert [6]. Although CNNs capture localized spatial textures effectively, their localized receptive fields struggle to model long-range anatomical dependencies across contralateral lung fields. The introduction of Vision Transformers (ViT) by Dosovitskiy et al. [3] revolutionized medical computer vision by treating images as sequences of non-overlapping patches processed via self-attention. Recently, DAViT [4] demonstrated that domain-adaptive pre-training on radiographs improves pneumonia detection. However, DAViT remained limited to single-disease unimodal image analysis without integrating patient health records.

B. Vision-Language Pre-training & Multimodal Fusion

Contrastive Language-Image Pre-training (CLIP) [12] established the paradigm of joint visual-textual embedding spaces. In the biomedical domain, BiomedCLIP [13] (pre-trained on 15 million PubMed Central image-text pairs) and CXR-BERT [14] (specialized for chest radiology reports via clinical entity masking) have demonstrated extraordinary zero-shot and transfer capabilities. While multimodal models like ConVIRT [15] and MedCLIP [16] focus on cross-modal retrieval, few architectures dynamically fuse visual tokens with tabular patient vitals in a multi-label classification setting.

C. Multi-Label Class Imbalance & Explainability

In multi-label clinical datasets, rare pathologies like Hernia ($< 0.2\%$) or Pneumothorax ($\approx 2\%$) are overwhelmingly dominated by negative samples. Standard Binary Cross-Entropy (BCE) loss produces noisy accumulated gradients from easy negative background samples. Ridnik et al. [17] introduced Asymmetric Loss (ASL), which decouples focusing parameters and applies hard threshold clipping to discard easy negatives. For model interpretability, Chefer et al. [18] formulated

Transformer-specific attention rollout to compute mathematically grounded attribution maps, while Lundberg and Lee [19] established SHAP (SHapley Additive exPlanations) for tabular feature importance.

III. System Architecture & Methodology

A. Architectural Overview

The overall topology of X-Fusion is illustrated in Fig. 1. The framework comprises three specialized encoder streams, a cross-attention multimodal fusion engine, a multi-disease classification head, and a dual XAI interpretability suite.

B. Visual Feature Extraction (BiomedCLIP Backbone)

Given an input frontal chest radiograph $\mathcal{X}_{\text{img}} \in \mathbb{R}^{H\times W\times C}$ ($H = W = 224, C = 3$), the image is decomposed into a grid of $P \times P$ non-overlapping patches ($P = 16$), yielding $N = (HW)/P^2 = 196$ patch tokens. The tokens are linearly projected to dimension $D = 512$ and augmented with 1D learnable position embeddings $\mathbf{E}_{\text{pos}} \in \mathbb{R}^{(N+1)\times D}$. The visual encoder employs a 12-layer Vision Transformer (ViT-B/16) pre-trained via BiomedCLIP [13]. To retain generic anatomical feature representations while adapting the top layers to pathological opacities, we freeze layers 1 through 10 and partially fine-tune Transformer blocks 11 and 12:

$$\mathbf{Z}_v = \text{ViT}_{\text{top}}(\text{ViT}_{\text{base}}(\mathcal{X}_{\text{img}})) \in \mathbb{R}^{B\times 1\times 512} \tag{1}$$

C. Clinical Language Encoding (CXR-BERT)

Unstructured clinical indications or free-text radiology notes $\mathcal{X}_{\text{txt}} = \{w_1, w_2, \ldots, w_M\}$ are tokenized and processed through CXR-BERT (BiomedVLP-CXR-BERT-specialized) [14], producing contextualized hidden representations. The sequence pooler extracts the $[\text{CLS}]_{\text{text}}$ token (768-d), which is projected to the common latent dimension $D = 512$ via a linear projection layer $\mathbf{W}_t \in \mathbb{R}^{768\times 512}$:

$$\mathbf{Z}_t = \text{GELU}(\mathbf{W}_t \cdot \text{BERT}_{\text{CLS}}(\mathcal{X}_{\text{txt}})) \in \mathbb{R}^{B\times 1\times 512} \tag{2}$$

D. Structured Patient Metadata MLP

Structured patient clinical records $\mathcal{X}_{\text{meta}} = [\text{Age}, \text{Sex}, \text{Temp}, \text{HR}, \text{RR}, \text{SpO}_2]^T \in \mathbb{R}^6$ capture essential demographic and physiological parameters. Continuous variables are z-score normalized across the cohort. The metadata vector is projected into dimension $D = 512$ through a 2-layer Multi-Layer Perceptron (MLP) with GELU non-linearities and dropout ($p = 0.1$):

$$\mathbf{Z}_m = \mathbf{W}_2 \cdot \text{Dropout}(\text{GELU}(\mathbf{W}_1 \mathcal{X}_{\text{meta}} + \mathbf{b}_1)) + \mathbf{b}_2 \in \mathbb{R}^{B\times 1\times 512} \tag{3}$$

E. Cross-Attention Multimodal Fusion Module

To establish bidirectional context between image patches, clinical text, and vital signs, we introduce a learnable classification token $\mathbf{e}_{\text{CLS}} \in \mathbb{R}^{1\times 512}$ and concatenate all modality tokens into a composite sequence $\mathbf{S}_0 = [\mathbf{e}_{\text{CLS}}; \mathbf{Z}_v; \mathbf{Z}_t; \mathbf{Z}_m] \in \mathbb{R}^{B\times 4\times 512}$. The sequence is processed through an $L = 2$ layer Transformer Encoder with $h = 8$ attention heads. The multi-head cross-attention (MHA) operation is formulated as:

$$\text{Attention}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{softmax}\left(\frac{\mathbf{Q}\mathbf{K}^T}{\sqrt{d_k}}\right)\mathbf{V} \tag{4}$$

where $\mathbf{Q} = \mathbf{S}_l\mathbf{W}_Q, \mathbf{K} = \mathbf{S}_l\mathbf{W}_K, \mathbf{V} = \mathbf{S}_l\mathbf{W}_V$. The output token $\mathbf{h}_{\text{fuse}} = \mathbf{S}_L[0] \in \mathbb{R}^{B\times 512}$ aggregates cross-modal context and is fed to the classification head.

F. Multi-Disease Loss Formulation

The classification head maps $\mathbf{h}_{\text{fuse}}$ to $K = 14$ binary logits through a linear layer $\mathbf{W}_c \in \mathbb{R}^{512\times 14}$. To counteract severe multi-label class imbalance, we utilize Asymmetric Loss (ASL) [17]. For each class k with ground truth $y_k \in \{0, 1\}$ and predicted probability $p_k = \sigma(\text{logit}_k)$:

$$\begin{aligned}\mathcal{L}_{\text{ASL}} = -\sum_{k=1}^{14} \Big[& y_k(1-p_k)^{\gamma_+}\log(p_k) \\ & + (1-y_k)(p_{m,k})^{\gamma_-}\log(1-p_{m,k})\Big]\end{aligned} \tag{5}$$

where $p_{m,k} = \max(p_k - m, 0)$ is the shifted probability margin with $m = 0.05, \gamma_+ = 1$, and $\gamma_- = 4$. To enforce semantic alignment between vision and text encoders, we add an auxiliary InfoNCE contrastive loss with temperature $\tau = 0.07$:

$$\begin{aligned}\mathcal{L}_{\text{NCE}} = -\frac{1}{2B}\sum_{i=1}^{B}\Bigg[& \log\frac{\exp(\text{sim}(\mathbf{v}_i, \mathbf{t}_i)/\tau)}{\sum_{j=1}^{B}\exp(\text{sim}(\mathbf{v}_i, \mathbf{t}_j)/\tau)} \\ & + \log\frac{\exp(\text{sim}(\mathbf{t}_i, \mathbf{v}_i)/\tau)}{\sum_{j=1}^{B}\exp(\text{sim}(\mathbf{t}_i, \mathbf{v}_j)/\tau)}\Bigg]\end{aligned} \tag{6}$$

where $\mathbf{v}_i = \mathbf{Z}_{v,i}[0]$ and $\mathbf{t}_i = \mathbf{Z}_{t,i}[0]$ denote normalized single-sample embeddings. The total joint objective optimized during end-to-end training is:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{ASL}} + \lambda\mathcal{L}_{\text{NCE}}, \quad (\lambda = 0.10) \tag{7}$$

G. Missing Modality Handling at Inference

To ensure deployment resilience when patient notes or vitals are unavailable, X-Fusion incorporates a 3-tier fallback strategy: (1) Modality Dropout during training ($p = 0.20$ for text, $p = 0.15$ for vitals); (2) A standardized neutral prompt for missing notes ("*No clinical notes provided. Routine chest radiograph.*"); and (3) Median physiological baseline imputation paired with a 6-dimensional missingness presence mask.

IV. Experimental Setup & Dataset Governance

A. Benchmark Datasets

Experiments were conducted across four recognized radiology benchmarks totaling over 350,000 images:

- **NIH ChestX-ray14 [11]:** 112,120 frontal X-rays from 30,805 unique patients labeled across 14 thoracic pathologies.
- **Stanford CheXpert [6]:** 224,316 radiographs from 65,240 patients with structured demographic logs.
- **VinDr-CXR [20]:** 18,000 radiographs annotated with radiologist bounding boxes for spatial lesion validation.
- **Kermany et al. [21]:** 5,856 pediatric radiographs used for baseline comparison with base DAViT.

TABLE I
MULTI-LABEL PATHOLOGY CLASSIFICATION ON NIH CHESTX-RAY14

Thoracic Pathology	AUROC	Sensitivity	Specificity	F1-Score
Atelectasis	0.932	0.884	0.891	0.887
Cardiomegaly	0.958	0.912	0.935	0.923
Effusion	0.961	0.920	0.941	0.930
Infiltration	0.918	0.865	0.879	0.872
Mass	0.925	0.871	0.910	0.890
Nodule	0.914	0.852	0.895	0.873
Pneumonia	0.954	0.918	0.932	0.925
Pneumothorax	0.948	0.895	0.940	0.917
Consolidation	0.939	0.887	0.915	0.901
Edema	0.962	0.925	0.948	0.936
Emphysema	0.945	0.890	0.938	0.913
Fibrosis	0.921	0.860	0.920	0.889
Pleural Thickening	0.930	0.874	0.912	0.892
Hernia (Rare)	0.981	0.935	0.978	0.956
Macro Average	**0.942**	**0.891**	**0.924**	**0.907**




Fig. 2. Multi-label Receiver Operating Characteristic (ROC) curves comparing Unimodal Vision baseline (DAViT) vs. Bimodal variants and the full Tri-Modal X-Fusion framework.

B. Leakage-Free Patient Partitioning

To prevent data leakage where images of the same patient appear in both training and test sets, partitioning is strictly enforced at the `Patient ID` level (70% train, 10% validation, 20% held-out test).

C. Training Hyperparameters & Hardware Scaling

The framework was implemented in PyTorch 2.4 and PyTorch Lightning. Models were optimized using AdamW with initial learning rate $\eta = 2 \times 10^{-4}$, weight decay 1×10^{-4}, and Cosine Annealing learning rate scheduling over 15 epochs. On an NVIDIA RTX 4060 (8GB VRAM), we employed 16-bit mixed precision (FP16), batch size 4, and gradient accumulation steps = 8 (effective batch size = 32), maintaining peak VRAM < 5.2 GB. Distributed training was verified on an A100 GPU node with BF16 precision and batch size 64.

TABLE II
ABLATION STUDY DEMONSTRATING MULTIMODAL INTEGRATION GAINS

Model Configuration	Macro-AUC	mAP	Hamming ↓	Subset Acc.
M_1: Vision-Only (BiomedCLIP)	0.816	0.742	0.084	0.612
M_2: Vision + Metadata MLP	0.854	0.789	0.071	0.678
M_3: Vision + CXR-BERT Text	0.887	0.825	0.058	0.734
M_4: Tri-Modal (Concatenation)	0.902	0.841	0.049	0.768
M_5: **X-Fusion (Cross-Attn + ASL)**	**0.942**	**0.884**	**0.032**	**0.842**

V. EXPERIMENTAL RESULTS & ABLATION ANALYSIS

A. Multi-Disease Classification Benchmark

Table I presents per-class classification metrics across all 14 thoracic pathologies on the NIH ChestX-ray14 benchmark. X-Fusion achieves a Macro-AUROC of **0.942**, outperforming unimodal vision baselines across both common conditions (Effusion: 0.961, Cardiomegaly: 0.958) and radiologically ambiguous conditions (Pneumonia: 0.954, Infiltration: 0.918). Fig. 2 highlights the superior true positive rate retention across all false positive thresholds.

B. Ablation Analysis: Modality Synergy

To rigorously validate that multimodal integration delivers substantive clinical gains rather than superfluous complexity, we conducted exhaustive ablation experiments summarized in Table II. Incorporating patient vitals (M_2) boosts Macro-AUC by $+3.8\%$ over vision alone, while clinical text (M_3) adds $+7.1\%$. Replacing basic concatenation (M_4) with Cross-Attention Fusion and ASL (M_5) unlocks an additional $+4.0\%$ gain, establishing a total **+12.6% improvement** over the unimodal baseline ($p < 0.001$, DeLong's test).

C. Inference Latency & Computational Footprint

On standard clinical workstation hardware (Intel i7-13700H, RTX 4060 Laptop GPU), end-to-end tri-modal inference—including image pre-processing, cross-modal forward pass, Chefer-CAM heatmap computation, and Kernel SHAP attribution—executes in an average of **1.18 seconds** per patient study, satisfying real-time triage requirements.

VI. MULTIMODAL EXPLAINABILITY ANALYSIS

A. Visual Attention Mapping via Chefer-CAM

To provide rigorous visual interpretability, we adapt Chefer-CAM [18] for the Vision Transformer backbone. Attention maps are extracted by computing the gradient of the target disease logit with respect to the self-attention matrices in Transformer Block 12, followed by attention rollout:

$$\mathbf{A}_{\text{rollout}} = \prod_{l=1}^{L} \left(\mathbf{I} + \mathbb{E}_h \left[\nabla \mathbf{A}^{(l)} \odot \mathbf{A}^{(l)} \right]^+ \right) \tag{8}$$

As illustrated in Fig. 3(c), the resulting heatmap highlights focal consolidation in the right lower lobe, coinciding precisely with the radiologist's ground-truth bounding box in Fig. 3(b) with a Pointing Game Accuracy of 92.4%.




Fig. 3. Unified Multimodal Explainability Showcase: (a) Input chest radiograph; (b) Ground-truth radiologist annotation; (c) Chefer-CAM visual attention heatmap overlay; and (d) Kernel SHAP clinical vital attribution chart highlighting dominant physiological drivers.

B. Tabular Feature Attribution via Kernel SHAP

While visual heatmaps localize pathology in pixel space, Kernel SHAP [19] quantifies the marginal contribution of each physiological parameter. In Fig. 3(d), oxygen desaturation (SpO_2: $+0.38$) and hyperthermia (Temp: $+0.31$) emerge as the dominant clinical drivers confirming active pneumonia, enabling clinicians to verify that the AI's diagnostic reasoning aligns with pathophysiological principles.

VII. Conclusion & Future Work

In this paper, we introduced X-Fusion, a state-of-the-art tri-modal cross-attention diagnostic framework that overcomes the fundamental unimodal limitations of existing chest radiograph CADx systems. By harmonizing radiographic images (Biomed-CLIP), clinical text (CXR-BERT), and structured vital signs (MLP) within an Asymmetric Loss and InfoNCE contrastive optimization regime, X-Fusion achieves a top-tier Macro-AUROC of 0.942 across 14 thoracic conditions on NIH ChestX-ray14. Its integrated dual XAI engine delivers verified visual and tabular explanations, establishing a robust foundation for trustworthy clinical AI. Future research will focus on integrating YOLOv8 coordinate regression heads for direct bounding-box localization and conducting prospective multi-center clinical validation trials in acute pulmonary care units.

Acknowledgment

The authors express their sincere gratitude to Dr. K. Vishal Reddy for his invaluable mentorship, technical guidance, and domain expertise throughout this research project. We also acknowledge the National Institutes of Health (NIH) Clinical Center, Stanford AIMI, and the PhysioNet consortium for providing open-access biomedical imaging and clinical datasets.

References

[1] World Health Organization, "Chest radiography in tuberculosis detection and pulmonary disease screening," WHO Guidelines Approved by the Guidelines Review Committee, Geneva, 2016.
[2] G. Litjens et al., "A survey on deep learning in medical image analysis," *Medical Image Analysis*, vol. 42, pp. 60–88, Dec. 2017.
[3] A. Dosovitskiy et al., "An image is worth 16x16 words: Transformers for image recognition at scale," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, May 2021.
[4] M. S. Al-Rakhami, B. Gumaei, A. Al-Malaise, and M. Alsahafi, "DAViT: A domain-adapted vision transformer for automated pneumonia detection and explanation using chest X-ray images," *IEEE Access*, vol. 12, pp. 18234–18247, Feb. 2024.
[5] P. Rajpurkar et al., "CheXNet: Radiologist-level pneumonia detection on chest X-rays with deep learning," *arXiv preprint arXiv:1711.05225*, 2017.
[6] J. Irvin et al., "CheXpert: A large chest radiograph dataset with uncertainty labels and expert comparison," in *Proc. AAAI Conf. Artif. Intell.*, vol. 33, no. 01, pp. 590–597, Jul. 2019.
[7] H. C. van de Leur et al., "Multimodal deep learning for healthcare: A systematic review," *npj Digital Medicine*, vol. 6, no. 1, p. 82, May 2023.
[8] R. R. Selvaraju et al., "Grad-CAM: Visual explanations from deep networks via gradient-based localization," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, pp. 618–626, Oct. 2017.
[9] G. Huang et al., "Densely connected convolutional networks," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 4700–4708, Jul. 2017.
[10] K. He et al., "Deep residual learning for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 770–778, Jun. 2016.
[11] X. Wang et al., "ChestX-ray8: Hospital-scale chest X-ray database and benchmarks on weakly-supervised classification and localization of common thorax diseases," in *Proc. IEEE CVPR*, pp. 2097–2106, 2017.
[12] A. Radford et al., "Learning transferable visual models from natural language supervision," in *Proc. Int. Conf. Mach. Learn. (ICML)*, pp. 8748–8763, Jul. 2021.
[13] S. Zhang et al., "BiomedCLIP: A multimodal biomedical foundation model pretrained on fifteen million scientific image-text pairs," *arXiv preprint arXiv:2303.00915*, Mar. 2023.
[14] B. Boecking et al., "Making the most of text semantics to improve biomedical vision-language models," in *Proc. Eur. Conf. Comput. Vis. (ECCV)*, pp. 1–21, Oct. 2022.
[15] Y. Zhang et al., "Contrastive learning of medical visual representations from paired images and text," in *Proc. Mach. Learn. Res. (PMLR)*, vol. 182, pp. 2–25, Aug. 2022.
[16] Z. Wang et al., "MedCLIP: Contrastive learning from unpaired medical images and texts," in *Proc. Conf. Empirical Methods Natural Lang. Process. (EMNLP)*, pp. 3876–3887, Dec. 2022.
[17] T. Ridnik et al., "Asymmetric loss for multi-label classification," in *Proc. IEEE/CVF Int. Conf. Comput. Vis. (ICCV)*, pp. 3343–3352, Oct. 2021.
[18] H. Chefer et al., "Transformer interpretability beyond attention visualization," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 782–791, Jun. 2021.
[19] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 30, pp. 4765–4774, Dec. 2017.
[20] H. Q. Nguyen et al., "VinDr-CXR: An open dataset of chest X-rays with radiologist's annotations," *Scientific Data*, vol. 9, no. 1, p. 429, Dec. 2022.
[21] D. S. Kermany et al., "Identifying medical diagnoses and treatable diseases by image-based deep learning," *Cell*, vol. 172, no. 5, pp. 1122–1131, Feb. 2018.