Lab₁

Exercise 1: nslookup

1. Which is the IP address of the website www.koala.com.au? In your opinion, what is the reason of having several IP addresses as an output?

```
wagner % nslookup www.koala.com.au
Server: 129.94.242.2
Address: 129.94.242.2#53

Non-authoritative answer:
Name: www.koala.com.au
Address: 104.18.61.21
Name: www.koala.com.au
Address: 104.18.60.21
```

The IP address of the website www.koala.com.au is 104.18.60.21 and 104.18.61.21. As for why there are several IP addresses outputs, this is to achieve load balancing, which aims to optimize resource use, maximize throughput, minimize response time, and avoid overload of any single resource.

2. Find out the name of the IP address 127.0.0.1. What is special about this IP address?

```
[wagner % nslookup 127.0.0.1
Server: 129.94.242.2
Address: 129.94.242.2#53
1.0.0.127.in-addr.arpa name = localhost.
```

This is so-call Loopback Address, which is the IP address of localhost.

Exercise 2: Use ping to test host reachability

Are the following hosts reachable from your machine by using ping:

- www.unsw.edu.au
- www.getfittest.com.au
- www.mit.edu
- www.intel.com.au
- www.tpg.com.au
- www.hola.hp
- www.amazon.com
- www.tsinghua.edu.cn
- www.kremlin.ru
- 8.8.8.8

If you observe that some hosts are not reachable, then can you explain why? Check if the addresses unreachable by the ping command are reachable from the Web browser.

www.unsw.edu.au reachable

www.getfittest.com.au unreachable (the host not exist)

www.mit.edu reachable

www.intel.com.au reachable

www.tpg.com.au reachable

www.hola.hp unreachable (the host not exist)

www.amazon.com reachable

www.tsinghua.edu.cn reachable

www.kremlin.ru

Unreachable. The output is time out but it is reachable from the web browser. This is probably because the ping command sends data using the ICMP protocol. ICMP response is disabled or ICMP filtering is enabled on the server

8.8.8.8 reachable

Exercise 3: Use traceroute to understand network topology

1. Run traceroute on your machine to www.columbia.edu. How many routers are there between your workstation and www.columbia.edu? How many routers along the path are part of the UNSW network? Between which two routers do packets cross the Pacific Ocean? Hint: compare the round trip times from your machine to the routers using ping.

```
wagner % traceroute www.columbia.edu
traceroute to www.columbia.edu (128.59.105.24), 30 hops max, 60 byte packets
1 cserouter1-server.cse.unsw.EDU.AU (129.94.242.251) 0.114 ms 0.112 ms 0.113 ms
  2 \quad 129.94.39.17 \; (129.94.39.17) \quad 0.855 \; \text{ms} \quad 0.875 \; \text{ms} \quad 0.863 \; \text{ms}
          libudnex1-vl-3154.gw.unsw.edu.au (149.171.253.34) 1.452 ms ombudnex1-vl-3154.gw.unsw.edu.au (149
 .171.253.35) 1.349 ms libudnex1-vl-3154.gw.unsw.edu.au (149.171.253.34) 1.453 ms
 4 libcr1-po-6.gw.unsw.edu.au (149.171.255.201) 1.074 ms 1.066 ms ombcr1-po-6.gw.unsw.edu.au (149.
171.255.169) 1.110 ms
  5 unswbr1-te-2-13.gw.unsw.edu.au (149.171.255.105) 1.153 ms unswbr1-te-1-9.gw.unsw.edu.au (149.171
 .255.101) 1.167 ms 1.065 ms 6 138.44.5.0 (138.44.5.0) 1.257 ms 1.243 ms 1.258 ms
          et-1-3-0.pe1.sxt.bkvl.nsw.aarnet.net.au (113.197.15.149) 2.279 ms 2.143 ms 2.104 ms
        et-0-0-0.pel.a.hnl.aarnet.net.au (113.197.15.99) 95.205 ms 95.090 ms 95.101 ms
9 et-2-1-0.bdr1.a.sea.aarnet.net.au (113.197.15.201) 146.974 ms 146.955 ms 146.949 ms 10 abilene-1-lo-jmb-706.sttlwa.pacificwave.net (207.231.240.8) 147.089 ms 147.112 ms 147.105 ms
11 ae-1.4079.rtsw.minn.net.internet2.edu (162.252.70.173) 179.854 ms 179.723 ms 179.607 ms 12 ae-1.4079.rtsw.eqch.net.internet2.edu (162.252.70.106) 187.628 ms 187.740 ms 187.858 ms 13 ae-0.4079.rtsw3.eqch.net.internet2.edu (162.252.70.163) 187.817 ms 188.403 ms 188.577 ms
         ae-1.4079.rtsw.clev.net.internet2.edu (162.252.70.130) 196.145 ms 196.320 ms 197.566 ms
14 ae-1.4079.1tsw.clev.net.internetz.edu (102.252.70.130) 190.145 ms 190.320 ms 197.50 buf-9208-I2-CLEV.nysernet.net (199.109.11.33) 200.568 ms 200.515 ms 200.534 ms 190.320 ms 190.320 ms 200.505 ms 190.105 ms 200.505 ms
          columbia.nyc-9208.nysernet.net (199.109.4.14) 212.978 ms 212.901 ms 213.027 ms cc-core-1-x-nyser32-gw-1.net.columbia.edu (128.59.255.5) 213.232 ms 213.180 ms 213.225 ms
          cc-conc-1-x-cc-core-1.net.columbia.edu (128.59.255.21) 213.344 ms 213.443 ms 213.465 ms ccnmtl.columbia.edu (128.59.105.24) 213.149 ms 213.208 ms 213.101 ms
```

- (1) There are 21 routers between my working station and the sever of <u>www.columbia.edu</u>. (the last one is the destination router)
- (2) There are 5 routers that are part of UNSW network.
- (3) the 7th (162.252.70.173) router travel across the Pacific Ocean

2. Run traceroute from your machine to the following destinations:

(i) www.ucla.edu (ii) www.u-tokyo.ac.jp and (iii) www.lancaster.ac.uk . At which router do the paths from your machine to these three destinations diverge? Find out further details about this router. (HINT: You can find out more about a router by running the Whois command: Whois router-IP-address). Is the number of hops on each path proportional the physical distance? HINT: You can find out the geographical location of a server using the following tool - http://www.yougetsignal.com/tools/network-location/

the output as follows:

```
pner % traceroute www.ucla.edu
nceroute to www.ucla.edu
nceroute to www.ucla.edu
nceroute to www.ucla.edu (164.67.228.152), 30 hops max, 60 byte packets
cserouter!-server.cse.unsw.EDU.AU (129.94.242.251) 0.116 ms 0.131 ms 0.101 ms
129.94.39.17 (129.94.39.17) 0.805 ms 0.934 ms 0.795 ms
nbudnex!-v!-3154.0%.unsw.edu.au (149.171.253.35) 2.025 ms 1.981 ms 1.980 ms
libcr1-po-5.gw.unsw.edu.au (149.171.255.165) 1.166 ms libcr1-po-6.gw.unsw.edu.au (149.171.255.201) 1.221 ms 1.187 ms
unswbr1-te-2-13.gw.unsw.edu.au (149.171.255.165) 1.195 ms 1.128 ms 1.166 ms
138.44.5.0 (138.46.5.0) 1.259 ms 1.388 ms 1.298 ms
et-1-3-0.pel.sxt.bkvl.nsw.aarnet.net.au (113.197.15.149) 2.162 ms 2.288 ms 2.272 ms
et-1-0-0.pel.s..hnl.sarnet.net.au (113.197.15.19) 9.91.92 ms 95.162 ms 95.269 ms
et-2-1-0.bdr1.a.sea.aarnet.net.au (113.197.15.201) 146.970 ms 146.947 ms 146.942 ms
cenichpr-1-is-jmb-778.snvaca.pacificwave.net (207.231.245.129) 164.257 ms 163.433 ms 164.211 ms
hpr-lax-hpr3--svl-hpr3-100ge.cenic.net (137.164.25.73) 160.306 ms 160.711 ms 160.186 ms
**
bd1f1.anderson--cr00f2.csb1.ucla.net (169.232.8.183) 161.216 ms 161.276 ms 160.694 ms
cr00f2.csb1--rtr12f4.mathsci.ucla.net (169.232.8.183) 161.216 ms 161.240 ms cr00f1.anderson--rtr11f4.mathsci.ucla.net (169.232.8.185) 160.664 ms
**
**
```

```
erouts mem.u-tokyo.ac.jp

wem.u-tokyo.ac.jp

210.152.243.234), 30 hops max, 40 byte packets

L-server.ceg.unsm.50U.4U (129.94.242.251) a.118 as 8.894 ms 9.891 ms

L-server.ceg.unsm.50U.4U (129.94.242.251) a.118 as 8.894 ms 9.891 ms

17 (129.94.19.17) 8.821 ms 8.837 ms 9.880 ms

-vl-3164.gw.unsw.edu.au (149.171.253.35) 19.422 ms 19.572 ms libudnost-vl-3154.gw.unsw.edu.au (149.171.253.34) 1.261 ms

-vl-3164.gw.unsw.edu.au (149.171.253.193.1 le65 ms libudnost-po-5.gw.unsw.edu.au (149.171.255.165) 1.183 ms libudnost-po-6.gw.unsw.edu.au (149.171.255.161) 1.164 ms unswbri-te-1-9.gw.unsw.edu.au (149.171.255.161) 1.164 ms unswbri-te-2-13.gw.unsw.edu.au (149.171.255.161) 1.164 ms unswbri-te-2-13.gw.unsw.

pol.bkvl.naw.asrnet.net.au (113.197.15.147) 154.979 ms 155.466 ms 155.809 ms

115].net (198.32.176.24) 156.379 ms 156.430 ms 156.467 ms

1.113.Net (58.138.88.189) 269.275 ms osk8045062.113.Net (58.138.88.185) 287.286 ms osk8045062.113.Net (38.138.88.189) 287.783 ms

7.113.Net (58.138.88.189 269.534 ms 278.113 ms 276.175 ms

8.58 (124.83.228.58) 269.436 ms 278.137 ms 277.1061 ms

8.58 (124.83.228.58) 269.436 ms 278.137 ms 277.1061 ms

8.58 (124.83.228.168) 269.753 ms 278.137 ms 277.1061 ms

8.58 (124.83.228.168) 269.753 ms 278.137 ms 277.1061 ms

8.58 (124.83.228.163) 269.753 ms 278.137 ms 277.1061 ms

8.58 (124.83.228.163) 269.753 ms 278.137 ms 277.1061 ms
```

1. The three paths diverge at the 6th router (138.44.5.0). Using whois command to find more detail:

```
wagner % whois 138.44.5.0
# ARIN WHOIS data and services are subject to the Terms of Use
# available at: https://www.arin.net/resources/registry/whois/tou/
# If you see inaccuracies in the results, please report at
# https://www.arin.net/resources/registry/whois/inaccuracy_reporting/
#
# Copyright 1997-2020, American Registry for Internet Numbers, Ltd.
                       138.44.0.0 - 138.44.255.255
138.44.0.0/16
APNIC-ERX-138-44-0-0
NET-138-44-0-0-1
NetRange:
CIDR:
NetName:
NetHandle:
Parent:
                       NET138 (NET-138-0-0-0-0)
NetType:
                       Early Registrations, Transferred to APNIC
OriginAS:
Organization:
                       Asia Pacific Network Information Centre (APNIC)
                       2003-12-11
2009-10-08
RegDate:
Updated:
                       This IP address range is not registered in the ARIN database.
Comment:
                       This range was transferred to the APNIC Whois Database as part of the ERX (Early Registration Transfer) project. For details, refer to the APNIC Whois Database via WHOIS.APNIC.NET or http://wq.apnic.net/apnic-bin/whois.pl
Comment:
Comment:
Comment:
Comment:
Comment:
                       ** IMPORTANT NOTE: APNIC is the Regional Internet Registry for the Asia Pacific region. APNIC does not operate networks using this IP address range and is not able to investigate spam or abuse reports relating to these addresses. For more help, refer to http://www.apnic.net/apnic-info/whois_search2/abuse-and-spamming
Comment:
Comment:
Comment:
Comment:
Comment:
Ref:
                       https://rdap.arin.net/registry/ip/138.44.0.0
                     http://wq.apnic.net/whois-search/static/search.html whois.apnic.net
ResourceLink:
ResourceLink:
OrgName:
                       Asia Pacific Network Information Centre
OrgId:
                       APNIC
Address:
City:
                       PO Box 3646
                       South Brisbane
StateProv:
                       QLD
PostalCode:
                       4101
Country:
                       AU
RegDate:
Updated:
                       2012-01-24
                       https://rdap.arin.net/registry/entity/APNIC
Ref:
```

```
ReferralServer: whois://whois.apnic.net
ResourceLink: http://wq.apnic.net/whois-search/static/search.html
OrgAbuseHandle: AWC12-ARIN
OrgAbuseName: APNIC Whois Contact
OrgAbusePhone: +61 7 3858 3188
OrgAbuseEmail: search-apnic-not-arin@apnic.net
OrgAbuseRef:
                https://rdap.arin.net/registry/entity/AWC12-ARIN
OrgTechHandle: AWC12-ARIN
OrgTechName: APNIC Whois Contact
OrgTechPhone: +61 7 3858 3188
OrgTechEmail: search-apnic-not-arin@apnic.net
OrgTechRef:
              https://rdap.arin.net/registry/entity/AWC12-ARIN
# ARIN WHOIS data and services are subject to the Terms of Use
  available at: https://www.arin.net/resources/registry/whois/tou/
 If you see inaccuracies in the results, please report at
# https://www.arin.net/resources/registry/whois/inaccuracy_reporting/
# Copyright 1997-2020, American Registry for Internet Numbers, Ltd.
Found a referral to whois.apnic.net.
% [whois.apnic.net]
                                 http://www.apnic.net/db/dbcopyright.html
% Whois data copyright terms
% Information related to '138.44.0.0 - 138.44.255.255'
% Abuse contact for '138.44.0.0 - 138.44.255.255' is 'abuse@aarnet.edu.au'
inetnum:
                138.44.0.0 - 138.44.255.255
netname:
                AARNET
                Australian Academic and Research Network
descr:
descr:
                Building 9
descr:
                Banks Street
country:
                All
                ORG-AAAR1-AP
org:
admin-c:
                SM6-AP
                ANOC-AP
tech-c:
notify:
                irrcontact@aarnet.edu.au
mnt-by:
                APNIC-HM
                MAINT-AARNET-AP
mnt-lower:
                MAINT-AARNET-AP
mnt-routes:
mnt-irt:
                IRT-AARNET-AU
status:
                ALLOCATED PORTABLE
remarks:
                                      -+-++-+-+-+-+-+-+-+-+-+-+-+
```

2. The number of hops can only depict the number of routers on a path, which is not related to the physical distance. For example, a hop may travel the whole Pacific Ocean, while there may be multiple routers passed by when I visit a IP address on Melbourne from Sydney.

3. Several servers distributed around the world provide a web interface from which you can perform a traceroute to any other host in the Internet. Here are two examples: (i) http://www.speedtest.com.sg/tr.php and (ii) https://www.telstra.net/cgi-bin/trace. Run traceroute from both these servers towards your machine and in the reverse direction (i.e. From your machine to these servers). You may also try other traceroute servers from the list at www.traceroute.org. What are the IP addresses of the two servers that you have chosen. Does the reverse path go through the same routers as the forward path? If you observe common routers between the forward and the reverse path, do you also observe the same IP addresses? Why or why not?

To do this, using the ifconfig command to get my IP address: (129.94.8.97)

Then get a forward path to these two server:

(1) http://www.speedtest.com.sg/tr.php

```
Traceroute to speedtest.com.sg (202.150.221.170), 30 hops max, 60 byte packets

1 cserouter1-server.cse.unsw.EDU.AU (129.94.242.251) 0.130 ms 0.113 ms 0.107 ms

2 129.94.39.17 (129.94.39.17) 0.840 ms 0.871 ms 0.894 ms

3 ombudnex1-v1-3154.gw.unsw.edu.au (149.171.253.35) 1.474 ms libudnex1-v1-3154.gw.unsw.edu.au (149.171.253.34) 1.300 ms ombudnex1-v1-3154.gw.unsw.edu.au (149.171.253.35) 1.291 ms

4 libcr1-po-6.gw.unsw.edu.au (149.171.255.201) 1.121 ms ombcr1-po-6.gw.unsw.edu.au (149.171.255.16)

9) 1.093 ms libcr1-po-5.gw.unsw.edu.au (149.171.255.165) 1.071 ms

5 unswbr1-te-1-9.gw.unsw.edu.au (149.171.255.101) 1.093 ms 1.118 ms 1.125 ms

6 138.44.5.0 (138.44.5.0) 1.256 ms 1.299 ms 1.250 ms

7 et-0-3-0.pe1.alxd.nsw.aarnet.net.au (113.197.15.153) 1.713 ms 1.631 ms 1.645 ms

8 xe-0-2-7.bdr1.a.lax.aarnet.net.au (202.158.194.173) 147.648 ms 147.627 ms 147.604 ms

9 singtel.as7473.any2ix.coresite.com (206.72.210.63) 147.619 ms 147.698 ms 147.821 ms

10 203.208.171.117 (203.208.171.117) 147.953 ms 147.993 ms 203.208.182.153 (203.208.182.153) 330.

179 ms

11 203.208.177.110 (203.208.177.110) 328.320 ms 321.125 ms 203.208.182.41 (203.208.182.41) 237.16

5 ms

12 ** 203.208.158.17 (203.208.158.17) 330.115 ms

13 202-150-221-170.rev.ne.com.sg (202.150.221.170) 214.371 ms 212.308 ms 203.208.158.185 (203.208.158.185) 329.865 ms
```

(2) https://www.telstra.net/cgi-bin/trace

```
wagner % traceroute www.telstra.net
traceroute to www.telstra.net (203.50.5.178), 30 hops max, 60 byte packets
 1 cserouter1-server.cse.unsw.EDU.AU (129.94.242.251) 0.164 ms 0.138 ms 0.109 ms
 2 129.94.39.17 (129.94.39.17) 0.879 ms 0.868 ms 0.864 ms
3 ombudnex1-vl-3154.gw.unsw.edu.au (149.171.253.35) 29.003 ms 29.026 ms 28.977 ms
4 libcr1-po-5.gw.unsw.edu.au (149.171.255.165) 1.145 ms libcr1-po-6.gw.unsw.edu.au (149.171.255.20 1.124 ms ombcr1-po-6.gw.unsw.edu.au (149.171.255.169) 1.098 ms
5 unswbr1-te-2-13.gw.unsw.edu.au (149.171.255.105) 1.131 ms 1.140 ms unswbr1-te-1-9.gw.unsw.edu.a
u (149.171.255.101) 1.165 ms
6 138.44.5.0 (138.44.5.0) 1.253 ms 1.367 ms 1.338 ms
    xe-0-0-0.bdr1.rsby.nsw.aarnet.net.au (113.197.15.33) 1.569 ms 1.637 ms 1.564 ms gigabitethernet3-11.ken37.sydney.telstra.net (139.130.0.77) 2.341 ms 2.509 ms 2.631 ms bundle-ether13.ken-core10.sydney.telstra.net (203.50.11.94) 3.899 ms bundle-ether2.chw-edge901.s
ydney.telstra.net (203.50.11.103) 2.227 ms 2.259 ms
10 bundle-ether13.chw-core10.sydney.telstra.net (203.50.11.98) 2.473 ms bundle-ether10.win-core10.m
elbourne.telstra.net (203.50.11.123) 13.761 ms 13.260 ms
11 203.50.6.40 (203.50.6.40) 13.908 ms 13.682 ms bundle-ether8.exi-core10.melbourne.telstra.net (2
03.50.11.125) 13.056 ms
12 bundle-ether2.exi-ncprouter101.melbourne.telstra.net (203.50.11.209) 13.019 ms 12.824 ms 13.13
13 www.telstra.net (203.50.5.178) 12.443 ms 12.729 ms 12.608 ms
```

Then the reverse path:

(1) http://www.speedtest.com.sg/tr.php

(2) https://www.telstra.net/cgi-bin/trace

```
1 gigabitethernet3-3.exi2.melbourne.telstra.net (203.50.77.53) 0.240 ms 0.203 ms 0.240 ms bundle-ether3-100.win-core10.melbourne.telstra.net (203.50.80.129) 1.986 ms 1.353 ms 2.239 ms bundle-ether12.ken-core10.sydney.telstra.net (203.50.11.122) 12.611 ms 12.474 ms 12.983 ms bundle-ether1.ken-edge901.sydney.telstra.net (203.50.11.95) 11.861 ms 11.848 ms 11.988 ms aarnet6.lnk.telstra.net (139.130.0.78) 11.608 ms 11.600 ms 11.863 ms xe-5-2-2.pel.brwy.nsw.aarnet.net.au (113.197.15.32) 11.858 ms 11.849 ms 11.860 ms 138.44.5.1 (138.44.5.1) 45.341 ms 50.579 ms 27.726 ms liber1-te-1-5.gw.unsw.edu.au (149.171.255.102) 11.984 ms 11.973 ms 11.983 ms ombudnex1-po-1.gw.unsw.edu.au (149.171.255.202) 12.360 ms 12.349 ms 12.236 ms 12.360 ms 12.349 ms 12.236 ms 12.994.39.23 (129.94.39.23) 12.858 ms 12.974 ms 12.860 ms
```

By observation, I find that the reverse path may not go through the same routers as the forward path. Because a same website server may have multiple IP addresses. To maintain the load balance, a different IP address may be assigned on the reverse path even though it is the same router. Also, to minimise latency, packet may be transmitted to different router on the way

Exercise 4: Use ping to gain insights into network performance

Chosen location and the direct distance:

```
(i) www.uq.edu.au distance: 734.3 km

(ii) www.upm.edu.my distance: 6606.5 km


(iii) www.tu-berlin.de distance: 16104.8 km
```

1. For each of these locations find the (approximate) physical distance from UNSW using Google Maps and compute the shortest possible time T for a packet to reach that location from UNSW. You should assume that the packet moves (i.e. propagates) at the speed of light, 3×10^8 m/s. Note that the shortest possible time will simply be the distance divided by the propagation speed. Plot a graph where the x-axis represents the distance to each city (i.e. Brisbane, Manila and Berlin), and the y-axis represents the ratio between the minimum delay (i.e. RTT) as measured by the ping program (select the values for 50 byte packets) and the shortest possible time T to reach that city from UNSW. (Note that the y-values are no smaller than 2 since it takes at least 2*T time for any packet to reach the destination from UNSW and get back). Can you think of at least two reasons why the y-axis values that you plot are greater than 2?

The result of script file execution can be found in the attached support file(.pdf, .txt)

computing the shortest possible time:

$$\begin{array}{l} t_i = \left(734.3 \times 10^3\right) / \left(3 \times 10^8\right) = 0.00244s = 2.44 \ ms \\ t_{ii} = \left(6606.5 \times 10^3\right) / \left(3 \times 10^8\right) = 0.02202s = 22.02 \ ms \\ t_{iii} = \left(16104.8 \times 10^3\right) / \left(3 \times 10^8\right) = 0.05368s = 53.68 \ ms \end{array}$$



Here is the plotted picture using Excel. There are a lot of reasons that the ratio greater than 2:

- (1) The path is usually not straight. The actual distance is highly greater than ideal situations.
- (2) The propagation rate may cannot reach 3×10^8 m/s.
- (3) This algorithm overlooks the impact of transmission delay, queueing delay and the processing delay.

2. Is the delay to the destinations constant or does it vary over time? Explain why.

yes, because the status of routers on a path is usually consistently changing. Sometimes, there may be congestions occurs or server shut down. Even the path (the routers on the path) may vary each time we send a packet. All of these issue would influence the delay.

3. Explore where the website for www.epfl.ch is hosted. Is it in Switzerland?

```
grieg % nslookup www.epfl.ch
                129.94.242.2
Server:
                129.94.242.2#53
Address:
Non-authoritative answer:
www.epfl.ch canonical name = www.epfl.ch.cdn.cloudflare.net.
Name: www.epfl.ch.cdn.cloudflare.net
Address: 104.20.229.42
Name: www.epfl.ch.cdn.cloudflare.net
Address: 104.20.228.42
grieg % whois 104.20.229.42
# ARIN WHOIS data and services are subject to the Terms of Use
# available at: https://www.arin.net/resources/registry/whois/tou/
# If you see inaccuracies in the results, please report at
# https://www.arin.net/resources/registry/whois/inaccuracy_reporting/
  Copyright 1997-2020, American Registry for Internet Numbers, Ltd.
NetRange:
                104.16.0.0 - 104.31.255.255
CIDR:
                104.16.0.0/12
NetName:
                CLOUDFLARENET
NetHandle:
                NET-104-16-0-0-1
                NET104 (NET-104-0-0-0-0)
Parent:
NetType:
                Direct Assignment
OriginAS:
                AS13335
Organization:
                Cloudflare, Inc. (CLOUD14)
                2014-03-28
RegDate:
                2017-02-17
Updated:
Comment:
                All Cloudflare abuse reporting can be done via https://www.cloudflare.com/abuse
Ref:
                https://rdap.arin.net/registry/ip/104.16.0.0
OrgName:
                Cloudflare, Inc.
OrgId:
                CLOUD14
Address:
                101 Townsend Street
City:
                San Francisco
StateProv:
                CA
PostalCode:
                94107
Country:
                US
                2010-07-09
RegDate:
                2019-09-25
Updated:
                https://rdap.arin.net/registry/entity/CLOUD14
Ref:
```

```
OrgTechHandle: ADMIN2521-ARIN
OrgTechName: Admin
OrgTechPhone: +1-650-319-8930
OrgTechEmail: rir@cloudflare.com
OrgTechRef: https://rdap.arin.net/registry/entity/ADMIN2521-ARIN
OrgAbuseHandle: ABUSE2916-ARIN
OrgAbuseName: Abuse
OrgAbusePhone: +1-650-319-8930
OrgAbuseEmail: abuse@cloudflare.com
                    https://rdap.arin.net/registry/entity/ABUSE2916-ARIN
OrgAbuseRef:
OrgNOCHandle: NOC11962-ARIN
OrgNOCName: NOC
OrgNOCPhone: +1-650-319-8930
OrgNOCEmail: noc@cloudflare.com
OrgNOCRef:
                 https://rdap.arin.net/registry/entity/NOC11962-ARIN
RTechHandle: ADMIN2521-ARIN
RTechName: Admin
RTechPhone: +1-650-319-8930
RTechEmail: rir@cloudflare.com
                https://rdap.arin.net/registry/entity/ADMIN2521-ARIN
RTechRef:
RAbuseHandle: ABUSE2916-ARIN
RAbuseName: Abuse
RAbusePhone: +1-650-319-8930
RAbuseEmail: abuse@cloudflare.com
RAbuseRef: https://rdap.arin.net/registry/entity/ABUSE2916-ARIN
RNOCHandle: NOC11962-ARIN
RNOCName:
               NOC
RNOCPhone: +1-650-319-8930
RNOCEmail: noc@cloudflare.com
               https://rdap.arin.net/registry/entity/NOC11962-ARIN
RNOCRef:
# ARIN WHOIS data and services are subject to the Terms of Use
  available at: https://www.arin.net/resources/registry/whois/tou/
  If you see inaccuracies in the results, please report at
  https://www.arin.net/resources/registry/whois/inaccuracy_reporting/
  Copyright 1997-2020, American Registry for Internet Numbers, Ltd.
```

No, the server located in San Francisco

4. The measured delay (i.e., the delay you can see in the graphs) is composed of propagation delay, transmission delay, processing delay and queuing delay. Which of these delays depend on the packet size and which do not?

Only the transmission delay and processing delay depends on the packet. Propagation delay, and queueing delay depend on other factors. The queueing delay depends on the congestion level of routers and the propagation delay depends on the propagation rate on physical links and distance.