

```

1  #include <stdio.h>
2  int main() {
3      int a,b;
4      scanf("%d %d",&a,&b);
5      int c=a%10;
6      int d=b%10;
7      if (c==d){
8          printf("true");
9      }
10     else{
11         printf("false");
12     }
13 }

```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

```

1  #include <stdio.h>
2  int main() {
3      int a;
4      scanf("%d",&a);
5      if (a%2!=0){
6          printf("Weird");
7      }
8      else if (a>=2 && a<=5) {
9          printf("Not Weird");
10     }
11     else if (a>=20) {
12         printf("Not Weird");
13     }
14     else {
15         printf("Weird");
16     }
17 }

```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

```

1  #include <stdio.h>
2  int main() {
3      int a,b,c;
4      scanf("%d %d %d",&a,&b,&c);
5      if ((a*a)==((b*b)+(c*c)))
6          printf("yes");
7      else if ((b*b)==((a*a)+(c*c)))
8          printf("yes");
9      else if ((c*c)==((a*a)+(b*b)))
10         printf("yes");
11     else
12         printf("no");
13 }

```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓