

```

1  #include <stdio.h>
2  #include <string.h>
3  int main() {
4      int t;
5      scanf("%d",&t);
6      while(t--){
7          int flag=1;
8          char s[100000];
9          scanf("%s",s);
10         int k=strlen(s);
11
12         if(k==10){
13             for(int i=0;i<10;i++){
14                 if(s[i]=='0'){
15                     flag=0;
16                     break;
17                 }
18                 if(s[i]<'0' || s[i]>'9'){
19                     flag=0;
20                     break;
21                 }
22             }
23         }
24         else
25             flag=0;
26         if(flag==1){
27             printf("YES\n");
28         }
29         else
30             printf("NO\n");
31     }
32     return 0;
33 }

```

	Input	Expected	Got	
✓	3	YES	YES	✓
	1234567890	NO	NO	
	0123456789	NO	NO	
	0123456.87			

Passed all tests! ✓

```

1  /*
2   * Complete the 'fourthBit' function below
3   *
4   * The function is expected to return an
5   * The function accepts INTEGER number as
6   */
7
8  int fourthBit(int number)
9  {
10     int binary[32];
11     int i=0;
12     while(number>0){
13         binary[i]=number%2;
14         number/=2;
15         i++;
16     }
17     if(i>=4){
18         return binary[3];
19     }
20     else
21     return 0;
22 }

```

	Test	Expected	Got	
✓	printf("%d", fourthBit(32))	0	0	✓
✓	printf("%d", fourthBit(77))	1	1	✓

Passed all tests! ✓

```

1  /*
2  * Complete the 'pthFactor' function below
3  *
4  * The function is expected to return a LONG_INTEGER
5  * The function accepts following parameters:
6  * 1. LONG_INTEGER n
7  * 2. LONG_INTEGER p
8  */
9
10 long pthFactor(long n, long p)
11 {
12     int count=0;
13     for(long i=1;i<=n;i++){
14         if(n%i==0){
15             count++;
16             if(count==p)
17                 return i;
18         }
19     }
20     return 0;
21 }

```

	Test	Expected	Got
✓	printf("%ld", pthFactor(10, 3))	5	5
✓	printf("%ld", pthFactor(10, 5))	0	0
✓	printf("%ld", pthFactor(1, 1))	1	1

Passed all tests! ✓