

```

1  #include <stdio.h>
2  int main() {
3      int i,arr[10],count=0;
4      for(i=0;i<=10;i++){
5          scanf("%d",&arr[i]);
6      }
7      for(int n=0;n<=10;n++){
8          if (arr[n]%2!=0){
9              count+=1;
10         }
11     }
12     printf("%d",count);
13     return 0;
14 }

```

	Input	Expected	Got
✓	5 10 15 20 25 30 35 40 45 50	5	5

Passed all tests! ✓

```

1  #include <stdio.h>
2  int main() {
3      int a,x,y=1;
4      scanf("%d",&a);
5      while(a!=0&&y==1){
6          x=a%10;
7          if(x==3||x==7||x==4||x==2){
8              y++;
9          }
10         a=a/10;
11     }
12     if(y==1){
13         printf("true");
14     }
15     else{
16         printf("false");
17     }
18     return 0;
19 }

```

	Input	Expected	Got	
✓	6	true	true	✓
✓	89	true	true	✓
✓	25	false	false	✓

Passed all tests! ✓

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main() {
3     long int n,t,i,nut=0;
4     scanf("%ld %ld",&n,&t);
5     for(i=1;i<=n;i++){
6         nut=nut+i;
7         if(nut==t){
8             nut=nut-1;
9         }
10    }
11    printf("%ld",nut%1000000007);
12    return 0;
13 }
```

	Input	Expected	Got	
✓	2 2	3	3	✓
✓	2 1	2	2	✓
✓	3 3	5	5	✓

Passed all tests! ✓

Finish review