

```

1  #include <stdio.h>
2  int main() {
3      int n,k;
4      scanf("%d",&n);
5      int arr[n];
6      for(int i=0;i<n;i++){
7          scanf("%d",&arr[i]);
8      }
9      scanf("%d",&k);
10     for(int a=0;a<=n-k;a++){
11         int max=arr[a];
12         for(int b=a;b<a+k;b++){
13             if(arr[b]>max){
14                 max=arr[b];
15             }
16         }
17         printf("%d ",max);
18     }
19     return 0;
20 }

```

	Input	Expected	Got
✓	8 1 3 5 2 1 8 6 9 3	5 5 5 8 8 9	5 5 5
✓	10 3 7 5 1 2 9 8 5 3 2 3	7 7 5 9 9 9 8 5	7 7 5

Passed all tests! ✓

```

1 #include <stdio.h>
2 int main() {
3     int n,t,count=0;
4     scanf("%d",&n);
5     int arr[n];
6     for(int i=0;i<n;i++){
7         scanf("%d",&arr[i]);
8     }
9     scanf("%d",&t);
10    for(int j=0;j<n;j++){
11        while(arr[j]>0){
12            arr[j]-=t;
13            count++;
14        }
15    }
16    printf("%d",count);
17    return 0;
18 }

```

	Input	Expected	Got	
✓	6 5 8 10 13 6 2 3	17	17	✓
✓	7 20 35 57 30 56 87 30 10	33	33	✓

Passed all tests! ✓

```

1 #include <stdio.h>
2 int main() {
3     int a,b;
4     scanf("%d",&a);
5     int arr1[a];
6     for(int i=0;i<a;i++)
7     {
8         scanf("%d",&arr1[i]);
9     }
10    scanf("%d",&b);
11    int arr2[b];
12    for(int i=0;i<b;i++)
13    {
14        scanf("%d",&arr2[i]);
15    }
16    int p=0,q=0;
17    while((p<a)&&(q<b))
18    {
19        if(arr1[p]<arr2[q])
20        {
21            printf("%d ",arr1[p]);
22            p++;
23        }
24        else if(arr1[p]>arr2[q])
25        {
26            printf("%d ",arr2[q]);
27            q++;
28        }
29        else
30        {
31            printf("%d ",arr1[p]);
32            p++;
33            q++;
34        }
35    }
36    for(int j=p;j<a;j++)
37    {
38        printf("%d ",arr1[j]);
39    }
40    for(int j=q;j<b;j++)
41    {
42        printf("%d ",arr2[j]);
43    }
44 }

```

	Input	Expected	Got
✓	5 1 2 3 6 9 4 2 4 5 10	1 2 3 4 5 6 9 10	1 2 3 4 5 6 9 10

Passed all tests! ✓