

```

1  #include <stdio.h>
2  #include <string.h>
3  int main() {
4      char str1[100000],str2[100000];
5      int flag=1;
6      scanf("%s",str1);
7      scanf("%s",str2);
8      int a=strlen(str1);
9      int b=strlen(str2);
10     if(a==b){
11         for(int i=a;i>=0;i--){
12             while(str1[i]!=str2[i]){
13                 for(int j=0;j<=i;j++){
14                     if(str1[j]<'z')
15                         str1[j]++;
16                     else{
17                         flag=0;
18                         break;
19                     }
20                 }
21             }
22         }
23     }
24     else
25         flag=0;
26
27     if(flag==0)
28         printf("NO");
29     else
30         printf("YES");
31     return 0;
32 }

```

	Input	Expected	Got	
✓	abaca cdbda	YES	YES	✓

Passed all tests! ✓

```

1 #include <stdio.h>
2 #include <string.h>
3 int main() {
4     int n,flag=0;
5     char temp;
6     scanf("%d",&n);
7     char words[n][14];
8     for(int i=0;i<n;i++)
9         scanf("%s",words[i]);
10    char reverse[14];
11    for(int i=0;i<n-1;i++){
12        strcpy(reverse,words[i]);
13        int size=strlen(reverse);
14
15        for(int k=0;k<size/2;k++){
16            temp=reverse[k];
17            reverse[k]=reverse[size-k-1];
18            reverse[size-k-1]=temp;
19        }
20        for(int j=1;j<n;j++){
21            if(strcmp(reverse,words[j])==
22                flag=1;
23                break;
24            }
25        }
26        if(flag==1)
27            break;
28    }
29    int len=strlen(reverse);
30    printf("%d %c ",len,reverse[len/2]);
31    return 0;
32 }

```

	Input	Expected	Got	
✓	4 abc def feg cba	3 b	3 b	✓

Passed all tests! ✓

```

1  #include <stdio.h>
2  #include <string.h>
3  int main() {
4      int n;
5      scanf("%d",&n);
6      char res[n][21];
7      int rate[n];
8      for(int i=0;i<n;i++){
9          scanf("%s",res[i]);
10         scanf("%d",&rate[i]);
11     }
12     int max=rate[0];
13     char ans[20];
14     strcpy(ans,res[0]);
15     for (int i=1;i<n;i++){
16         if (rate[i]>max){
17             max=rate[i];
18             strcpy(ans,res[i]);
19         }
20         else if(rate[i]==max){
21             if(strcmp(res[i],ans)<0)
22                 strcpy(ans,res[i]);
23         }
24     }
25     printf("%s",ans);
26     return 0;
27 }

```

	Input	Expected	Got	
✓	3 Pizzeria 108 Dominos 145 Pizzapizza 49	Dominos	Dominos	✓

Passed all tests! ✓

```

1  #include <stdio.h>
2  #include <string.h>
3  int main() {
4      int t;
5      scanf("%d",&t);
6      while(t--){
7          int flag=1;
8          char s[100000];
9          scanf("%s",s);
10         int k=strlen(s);
11
12         if(k==10){
13             for(int i=0;i<10;i++){
14                 if(s[i]!='0'){
15                     flag=0;
16                     break;
17                 }
18                 if(s[i]<'0' || s[i]>'9'){
19                     flag=0;
20                     break;
21                 }
22             }
23         }
24         else
25             flag=0;
26         if(flag==1){
27             printf("YES\n");
28         }
29         else
30             printf("NO\n");
31     }
32     return 0;
33 }

```

	Input	Expected	Got	
✓	3	YES	YES	✓
	1234567890	NO	NO	
	0123456789	NO	NO	
	0123456.87			

Passed all tests! ✓