

Question 2 Objective Correct Marked out of 5.00 This challenge will help you to learn how to take a character, Flag question a string and a sentence as input in C. To take a single character ch as input, you can use scanf("%c", &ch); and printf("%c", ch) writes a character specified by the argument char to stdout: char ch; scanf("%c", &ch); printf("%c", ch); This piece of code prints the character ch. Task You have to print the character, ch. Input Format Take a character, ch as input. **Output Format** Print the character, ch. Answer: (penalty regime: 0 %) 1 |#include<stdio.h> 2 v int main() { char ch; 3 scanf("%c",&ch); 4 5 printf("%c",ch); 6 } Input Expected Got

Passed all tests! <

Question **3**Correct
Marked out of 7.00

Friag question

# Objective

respectively.

The fundamental data types in c are int, float and char.

Today, we're discussing int and float data types.

The printf() function prints the given statement to the console. The syntax is printf("format string",argument\_list);. In the function, if we are using an integer, character, string or float as argument, then in the format string we have to write %d (integer), %c (character), %s (string), %f (float)

The scanf() function reads the input data from the console.
The syntax is scanf("format string",argument\_list);. For ex:
The scanf("%d",&number) statement reads integer number from the console and stores the given value in variable *number*.

To input two integers separated by a space on a single line, the command is scanf("%d %d", &n, &m), where *n* and *m* are the two integers.

#### Task

Your task is to take two numbers of int data type, two numbers of float data type as input and output their sum:

- Declare 4 variables: two of type int and two of type float.
- 2. Read 2 lines of input from stdin (according to the sequence given in the 'Input Format' section below) and initialize your 4 variables.
- Use the + and operator to perform the following operations:
- o Print the sum and difference of two int variable on a new line.
- Print the sum and difference of two float variable rounded to one decimal place on a new line.

#### Input Format

The first line contains two integers.

The second line contains two floating point numbers.

#### Constraints

- 1 ≤ integer variables ≤ 10<sup>4</sup>
- 1 ≤ float variables ≤ 10<sup>4</sup>

## Output Format

Print the sum and difference of both integers separated by a

- 2. Read **2** lines of input from stdin (according to the sequence given in the 'Input Format' section below) and initialize your **4** variables.
- 3. Use the + and operator to perform the following operations:
- o Print the sum and difference of two int variable on a new line.
- o Print the sum and difference of two float variable rounded to one decimal place on a new line.

## Input Format

The first line contains two integers.

The second line contains two floating point numbers.

#### Constraints

- 1 ≤ integer variables ≤ 10<sup>4</sup>
- . 1 ≤ float variables ≤ 10<sup>4</sup>

### **Output Format**

Print the sum and difference of both integers separated by a space on the first line, and the sum and difference of both float (scaled to 1 decimal place) separated by a space on the second line.

## Sample Input

104

4.0 2.0

#### Sample Output

146

6.0 2.0

## Explanation

When we sum the integers 10 and 4, we get the integer 14. When we subtract the second number 4 from the first number 10, we get 6 as their difference.

When we sum the floating-point numbers **4.0** and **2.0**, we get **6.0**. When we subtract the second number **2.0** from the first number **4.0**, we get **2.0** as their difference.

#### Sample Input

104

4.0 2.0

#### Sample Output

146

6.0 2.0

#### Explanation

When we sum the integers 10 and 4, we get the integer 14. When we subtract the second number 4 from the first number 10, we get 6 as their difference.

When we sum the floating-point numbers **4.0** and **2.0**, we get **6.0**. When we subtract the second number **2.0** from the first number **4.0**, we get **2.0** as their difference.

### Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
  2
     int main()
 3 + {
  4
           int i1, i2, s1, d1;
           float f1, f2, s2, d2;
  5
          scanf("%d %d",&i1,&i2);
scanf("%f %f",&f1,&f2);
 6
 7
 8
          s1 = i1+i2;
 9
          d1 = i1-i2;
          s2 = f1+f2;
10
          d2 = f1-f2;
printf("%d %d \n",s1,d1);
printf("%.1f %.1f",s2,d2);
11
12
13
14
           return 0;
15 }
```

	Input	Expected	Got	
~	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	~
~	100000000000000000000000000000000000000	28 12 12.0 4.0	28 12 12.0 4.0	~

Passed all tests! <

Status Finished Monday, 23 December 2024, 5:33 PM Started Completed Friday, 18 October 2024, 2:10 PM Duration 66 days 3 hours Question 1 Write a program to input a name (as a single character) and Correct marks of three tests as m1, m2, and m3 of a student considering all the three marks have been given in integer Marked out of 3.00 format. Flag question Now, you need to calculate the average of the given marks and print it along with the name as mentioned in the output format section. All the test marks are in integers and hence calculate the average in integer as well. That is, you need to print the integer part of the average only and neglect the decimal part. Input format: Line 1: Name(Single character) Line 2: Marks scored in the 3 tests separated by single space. Output format: First line of output prints the name of the student. Second line of the output prints the average mark. Constraints Marks for each student lie in the range 0 to 100 (both inclusive) Sample Input 1: Α 346 Sample Output 1: Α 4 Sample Input 2:

```
346
Sample Output 1:
Α
4
Sample Input 2:
Т
738
Sample Output 2:
Т
6
Answer: (penalty regime: 0 %)
      |#include<stdio.h>
    2
       int main()
   3 ₹ {
   4
            char a;
           int m1,m2,m3,avg;
   5
           scanf("%c",&a);
scanf("%d %d %d",&m1,&m2,&m3);
   6
   7
   8
           avg = (m1+m2+m3)/3;
           printf("%c",a);
   9
           printf("\n%d",avg);
  10
  11
           return 0;
  12 }
       Input
                 Expected
                           Got
                           Α
       Α
       3 4 6
                 4
                           4
       Τ
                 Τ
                           T
       7 3 8
                 6
                           6
                 R
                           R
       0 100 99
                 66
                           66
 Passed all tests! <
```

Sample Input 1:

Α

Some C data types, their format specifiers, and their most

common bit widths are as follows:

Int ("%d"): 32 Bit integer

Long ("%ld"): 64 bit integer

Char ("%c"): Character type Float ("%f"): 32 bit real value Double ("%lf"): 64 bit real value

To read a data type, use the following syntax:

To print a data type, use the following syntax:

Note: You can also use cin and cout instead

int, long, char, float, and double, respectively.

3 12345678912345 a 334.23 14049.30493

For example, to print a character followed by a double:

of scanf and printf; however, if you are taking a million numbers as input and printing a million lines, it is faster to

Input consists of the following space-separated values:

Print each element on a new line in the same order it was received as input. Note that the floating point value should be correct up to 3 decimal places and the double to 9

For example, to read a character followed by a double:

For the moment, we can ignore the spacing between format

scanf("`format\_specifier`", &val)

scanf("%c %lf", &ch, &d);

printf("`format\_specifier`", val)

Reading

char ch; double d;

specifiers.

Printing

char ch = 'd':

double d = 234.432; printf("%c %lf", ch, d);

use scanf and printf.

**Input Format** 

**Output Format** 

decimal places. Sample Input

Sample Output

12345678912345

14049.304930000

followed by char a

followed by long 12345678912345,

a

334.230

Explanation Print int 3,

Question 2

Correct

Marked out of

Flag question

5.00

## Input Format

Input consists of the following space-separated values: *int, long, char, float,* and *double,* respectively.

### **Output Format**

Print each element on a new line in the same order it was received as input. Note that the floating point value should be correct up to 3 decimal places and the double to 9 decimal places.

#### Sample Input

3 12345678912345 a 334.23 14049.30493

## Sample Output

2

12345678912345

а

334.230

14049.304930000

#### Explanation

Print int 3,

followed by long 12345678912345,

followed by char a,

followed by float 334.23,

followed by double 14049.30493.

## Answer: (penalty regime: 0 %)

```
1
  #include<stdio.h>
    int main()
 2
3 +
        int a;
4
5
        long b;
        char c;
6
7
        float d;
8
        double e;
        scanf("%d %ld %c %f %lf",&a,&b,&c,&d,
9
        printf("%d \n%ld \n%c \n%.3f \n%.9lf"
10
11
        return 0;
   }
12
```

Input			
3 12345678912345 a 334.23 14049.30493	3 12345 a 334.2 14049		
	100 ■ 200000		

Question **3**Correct
Marked out of 7.00

Flag question

Write a program to print the ASCII value and the two adjacent characters of the given character.

Input

Ε

Output

69

DF

## Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    char a;
    scanf("%c",&a);
    printf("%d",a);
    printf("\n%c %c",(a-1),(a+1));
    return 0;
}
```

	Input	Expected	Got	
~	Е	69 D F	69 D F	~

Passed all tests! <