

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x 1000, y 219

PC-PT PC0

Router0

Physical Config CLI Attributes

IOS Command Line Interface

```
Router#
Router#
Router#
Router#
Router#
Router#
Router#
Router#config ter
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#
Router(config)#
Router(config)#
Router(config)#
Router(config)#username CCNA password Vijay
Router(config)#
Router(config)#
Router(config)#line console 0
-
% Invalid input detected at '^' marker.

Router(config)#exit
Router#
*SYS-6-CONFIG_1: Configured from console by console

Router#
Router#
Router#
Router#show ip interface brief
Interface      IP-Address      OK? Method Status      Protocol
FastEthernet0/0 50.0.0.10       YES manual up          up
FastEthernet0/1 unassigned      YES unset  administratively down down
GigabitEthernet0/0/0 unassigned      YES unset  administratively down down
Vlan1          unassigned      YES unset  administratively down down
Router#
Router#
Router#
Router#
Router#
```

Copy Paste

Top

Time: 00:18:30

Realtime Simulation

type Color Time(sec) Periodic Num Edit Delete

28°C Mostly sunny

Search

ENG IN

09:09 AM 19-08-2026

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x 254, y: 145

PC-PT
PC0

Time: 00:45:07

30°C Sunny

Router0

Physical Config CLI Attributes

IOS Command Line Interface

```
Press RETURN to get started!

User Access Verification

Username:
Username:
Username:

Press RETURN to get started!

User Access Verification

Username: CCNA
Password:

Router>
Router>
Router>
Router>
Router>
```

Copy Paste

Top

Root

22:41:30

Realtime Simulation

Type Color Time(sec) Periodic Num Edit Delete

% Invalid input detected at '^' marker.

Router#config ter

Enter configuration commands, one per line. End with CNTL/Z.

Router(config)#

Router(config)#

Router(config)#

Router(config)#line vty 0 4

Router(config-line)#transport input telnet

Router(config-line)#

Router(config-line)#

Router(config-line)#

Router(config-line)#login local

Router(config-line)#exit

Router(config)#

Router(config)#

Router(config)#exit

Router#

%SYS-5-CONFIG_I: Configured from console by console

Router#

Router#

Router#

Router#

Router#

