

tcb/boxtcb/boxSecttcb/box/begin0tcb/box/begindefaultminipage/beforenoopminipage/afternoop
tag=tcb/boxtcb/box/begindefaulttcb/box/end0tcb/box/enddefault
tcb/box/enddefaulttcb/box/titletcb/box/titleCaptiontcb/box/title0tcb/box/titledefaultpara/semantictcb/box/titletcb/box/
tcb/box/drawdefaulttcb/box/upper0tcb/box/upperdefaultminipage/beforetag/dflminipage/aftertag/dflttcb/box/upperdefa

CollabBench: Benchmarking and Unleashing Collaborative Ability of LLMs with Diverse Players via Proactive Engagement

Hong Qian^{1,2} Yuanhao Liu^{1,3} Zihan Zhou¹ Zongbao Zhang^{1,2} Hanjie Ge¹ Haotian Shi¹ Liang Dou¹
Xiangfeng Wang¹ Jingwen Yang^{*3} Aimin Zhou^{1,2}

Abstract

While LLM-based agents excel at individual tasks, effective collaboration with realistic human partners remains challenging. Most of the existing conversation-level collaborative studies lack grounded interaction and behavioral execution, motivating the need for cooperative game environments that enable contextualized and immersive collaboration. To this end, this paper proposes CollabBench, a benchmark for evaluating and training collaborative agents in cooperative games. CollabBench features a Diverse Player Profile Simulation pipeline to model varied players behaviors, and a Collaborative Agentic Training paradigm that unifies reasoning, communication, and action via agentic rollouts, optimized with a hybrid reward balancing task efficiency and affective adaptation. We further extend classic environments to CWAH-MultiPlayer and Cook-MultiPlayer for systematic evaluation under diverse personalities. Experiments with efficiency and affective metrics show that our trained models outperform base models, achieving 19.5% higher efficiency and 24.4% improved affective performance. Further analysis reveals key collaborative limitations of existing models and offers insights for future collaborative training.

1. Introduction

With the rapid advancement of Large Language Models (LLMs), LLM-based agents (Wang et al., 2024b; Xi et al., 2025a; Zhang et al., 2026) have demonstrated strong capabilities

in individual tasks such as deep research, mathematical reasoning, and coding. As these abilities expand, a critical research challenge is enabling agents to collaborate effectively with human partners exhibiting diverse personalities and behavioral patterns. Most existing human-agent collaboration studies focus on conversation-level tasks (Wang et al., 2024d; Wu et al., 2025; Zhang et al., 2025a), such as dialogue, document editing, and mathematical problem solving, which typically exhibit weak context and interaction, often detaching communication from the immediate shared situation and lacking grounded behavioral execution. This motivates the development of agents operating in immersive cooperative game environments (Hu et al., 2024) for context scaling (Wang et al., 2026), requiring agents to share a grounded environment and engage in proactive interaction beyond purely linguistic exchange, thereby unleashing agent’s contextualized collaborative intelligence in both efficient task execution and affectively adaptive engagement with diverse human partners.

Despite growing interest, several challenges remain. First, simulating players with diverse personalities and behavioral styles through LLMs in game environments remains difficult (*Challenge 1*). Existing role-playing and user profiling approaches (Wang et al., 2024c; Tu et al., 2024; Wang et al., 2025a; Salemi et al., 2024) largely rely on predefined characters or static user data, and fail to capture grounded, action-level behaviors in interactive games. Second, unleashing LLM-based agents collaboration with diverse partners in strong context such as game environments is largely unexplored (*Challenge 2*). Prior work predominantly focuses on improving single-agent capabilities (Feng et al., 2025; Wang et al., 2025b; Xi et al., 2026) or multi-agent architectures (Zhang et al., 2024b;a; Seo et al., 2025), with limited emphasis on learning collaborative awareness and adaptability within LLMs. Third, current criteria for LLM-based agents in game environments (Costarelli et al., 2024; Xi et al., 2025b; Hu et al., 2026) are often restricted to efficiency-based metrics, such as final game scores (*Challenge 3*), overlooking affective and social qualities that are essential for effective human-agent collaboration.

Therefore, this paper introduces CollabBench (CB), a bench-

¹Shanghai Institute of AI for Education, and School of Computer Science and Technology, East China Normal University, Shanghai, China ²Shanghai Innovation Institute, Shanghai, China ³Tencent Inc., Shenzhen, China. Correspondence to: Jingwen Yang <jingwenyang@tencent.com>.

Figure 1. The motivation of this work: challenges of collaboration between real human and agent. **(a) CB-Efficiency Challenge:** Introducing diverse players significantly increases task difficulty. The Personality-driven setting (red) degrades performance compared to standard homogeneous multi-agent cooperation (blue), resulting in more steps in CWAH (+9.3%) and lower scores in Overcook (-23.1%). **(b) CB-Affective Challenge:** The Default environment (left) prioritizes efficiency, leading to command-based, low-empathy interactions. In contrast, the Personality-driven environment (right) introduces diverse teammates, requiring the agent to optimize both efficiency and affective engagement. Detailed results on motivation are in Appendix A.

mark for systematically evaluating and training LLM-based agents to collaborate proactively with diverse players. To address Challenge 1, we develop a Diverse Players Profiles Simulation pipeline that generates heterogeneous behaviors grounded in Big Five personality theory, followed by high-fidelity profile modeling that enforces explicit personality-behavior mappings and applies interaction-based filtering to ensure realism and consistency. Based on this environment, we observe that player heterogeneity substantially increases task difficulty compared to standard homogeneous multi-agent settings (Figure 1(a)), and that efficiency-driven interaction strategies fail to satisfy affective needs of diverse partners (Figure 1(b)). Motivated by these findings, we propose Collaborative Agentic Training to address Challenge 2, featuring a unified agentic rollout that integrates reasoning, communication, and action, together with a hybrid reward mechanism that jointly optimizes trajectory-level task efficiency and step-level affective alignment via agentic RL.

Building on our diverse players profiles simulation, we extend two classic environments to construct CWAH-MultiPlayer and Cook-MultiPlayer for both training and evaluation, introducing substantially more challenging and realistic collaborative settings with heterogeneous players. To address Challenge 3, we design a comprehensive evaluation protocol combining efficiency metrics (e.g., game score, variance and token usage) with affective metrics (Helpfulness, Trustfulness, and Empathy). Empirical results show that our collaborative training paradigm yields substantial gains, improving average game scores and affective metrics by 19.5% and 24.4%, respectively, over the base model. We further provide detailed analyses revealing the collaborative

limitations of existing LLMs and offer extensive experimental insights into the efficacy of collaborative training.

2. Related Work

Personality-Aware Human Simulation. Traditional human simulators are learned from collected behavior data (Carroll et al., 2019). Recent work shows that LLMs can flexibly generate diverse personas, and has applied this capability to role-playing and personalized services using predefined character descriptions or user profiles (Kosinski, 2024; Salminen et al., 2024; Shin et al., 2024; Wang et al., 2024c; Tu et al., 2024; Wang et al., 2025a; Salemi et al., 2024). However, such approaches are limited for cooperative game environments, where data for diverse, grounded behaviors is scarce. Existing human-LLM collaboration systems rely on task-driven, conversation-level simulators with limited personality diversity (Wu et al., 2025), while domain-specific LLM-based simulations in dialogue, social activities, and education (Wang et al., 2024d; Zhang et al., 2025a; Park et al., 2023; Liu et al., 2024) do not readily transfer to cooperative game tasks.

Agentic Training for LLMs in Games. Recent work has demonstrated strong performance of agentic training for LLMs in domains such as deep research, mathematical reasoning, and coding (Jin et al., 2025; Guo et al., 2025; Jiang et al., 2026). Game environments provide a practical and realistic testbed for this paradigm (Chevalier-Boisvert et al., 2019; Carroll et al., 2019; Shridhar et al., 2021; Puig et al., 2021; Wang et al., 2024a). Prior studies predominantly focus on enhancing single-agent capabilities through

architecture design or agentic reinforcement learning, including VOYAGER (Wang et al., 2024a), RAGEN (Wang et al., 2025b), and AgentGym-RL (Xi et al., 2026). Research on collaborative agents remains largely architecture-centric, as exemplified by ProAgent (Zhang et al., 2024a) and CoELA (Zhang et al., 2024b), which improve coordination via specialized modules. However, these approaches generally lack explicit mechanisms for training collaboration awareness within LLMs and overlook the diversity of teammate personalities in real-world collaboration.

Evaluation of LLM-based Agent and Human Collaboration. As LLM capabilities advance, effective collaboration has become a critical objective, where efficiency alone is insufficient as an evaluation criterion (George, 1990; McAlister, 1995; Salas et al., 2005). Recent work has begun to adopt multidimensional evaluation frameworks, such as LLM-as-a-judge for assessing interactivity (Wu et al., 2025) and empathy (Zhang et al., 2025a). However, gamified evaluations of LLM-based agents still predominantly rely on efficiency-oriented metrics, including game scores and success rates (Costarelli et al., 2024; Hu et al., 2026; Sun et al., 2025; Zhang et al., 2025b). Although some cooperative game studies incorporate affective aspects via user surveys (Siu et al., 2021; Zhang et al., 2024b), the lack of systematic, scalable evaluation protocols limits large-scale benchmarking and complicates reward design for agentic reinforcement learning. Detailed related work can be found in the Appendix B.

3. Problem Formulation

Distinct from traditional homogeneous, performance-driven multi-agent game systems, we study a heterogeneous collaboration setting in which two agents cooperate to achieve a shared goal $G = \{g_1, \dots, g_K\}$ in a partially observable environment, where K means the number of subgoals in a task. One agent acts as a simulated player P_{sim} that exhibits diverse human personalities and behaviors, while the other is a target collaborative agent P_{target} whose policy is optimized. Interaction is represented by a trajectory $\tau = \{t_1, \dots, t_H\}$, where H means the number of turns in a trajectory and each turn $t_i = \{s_i, r_i, c_i, a_i\}$ involves a partial environment observation s_i , internal reasoning r_i , natural language communication c_i and executable actions a_i . To account for partner heterogeneity, P_{target} is optimized with respect to two objectives: a trajectory-level efficiency reward $R_e(\tau|G) = \text{score}(\tau, G)$, measuring overall goal completion, and a step-level affective reward $R_a(t_i|P_{sim})$ capturing alignment with the simulated players profile. The overall objective $R^* \simeq R_e + R_a$ balances task efficiency with per-step player affective experience.

4. CollabBench: Benchmark, Method and Evaluation

4.1. Diverse Players Profiles Simulation

To enable P_{target} to acquire collaborative competence in real-world scenarios, it is essential to simulate diverse players P_{sim} . However, cooperative game environments pose two key challenges: (1) the scarcity of real human gameplay trajectories limits the coverage and fidelity of teammate personality distributions, and (2) bridging abstract personality representations with concrete, game-specific behaviors across diverse games is inherently difficult. These challenges motivate a unified pipeline that converts personality distributions into executable behaviors for scalable, game-adaptive player simulation.

4.1.1. DIVERSE SIMULATED PLAYERS TRAJECTORY DATA CONSTRUCTION

Personality-Driven Players Profiles Construction. Simulating teammates with diverse personalities and behavioral styles in game environments is challenging due to the need for continuous, authentic interactions and the high cost and limited coverage of real player trajectories. To address this, we adopt the widely recognized Big Five personality theory (McCrae & Costa Jr, 1999) and assign low, medium, or high levels to each dimension in prompts to ensure broad behavioral coverage. Furthermore, each trait is grounded in expert-validated gameplay logic, allowing personality differences to consistently manifest as observable behavioral patterns during interaction. These personality descriptors are used solely to induce behavioral diversity during data generation, rather than serving as final player profiles.

Game-Specific Behavioral Trajectory Generation. To mitigate personality bias induced by a single LLM and enhance trajectory diversity, we employ multiple LLMs as diverse players P_{sim} instantiated from our personality-driven player profiles. These agents interact with diverse game environments via a ReAct-style mechanism, producing trajectories that include both internal reasoning and executable actions. Notably, the reasoning traces are critical for extracting high-quality behavioral patterns. This process yields a highly diverse behavior database, providing a solid foundation for constructing and validating mappings between personality profiles and behavioral patterns.

4.1.2. HIGH-FIDELITY PROFILE MODELING

Although diverse behavioral trajectories support fine-grained modeling of players diversity, they are generated solely from personality-based prompts and lack explicit alignment between personality traits and observed behaviors in specific games, which may introduce inconsistencies (a player with low openness frequently sending messages).

Figure 2. The framework of the proposed CollabBench. (a) **Diverse Players Profiles Simulation**: A pipeline that constructs high-fidelity, behaviorally diverse player profiles (P_{sim}). (b) **Collaborative Agentic Training**: A training paradigm for the target collaborative agent (P_{target}). (c) **Evaluation Protocol**: A comprehensive framework that assesses the interaction quality between the target collaborative agent (P_{target}) and diverse simulated teammates (P_{sim}) using both efficiency and affective metrics.

We therefore construct a high-quality mapping and apply rigorous filtering to obtain high-fidelity player profiles.

Personality-Behavior Mapping Construction. To construct personality-behavior mappings, we first encode collected textual trajectory segments and cluster the LLM-based embeddings to identify similar behavior patterns. For each cluster, an LLM summarizes the associated personality traits, reasoning content, and actions to produce a unified mapping that captures thinking patterns and action preferences. We then filter redundant mappings to ensure diversity, yielding the final high-fidelity player profiles. The clustering process and the prompts for summarizing profiles are detailed in Appendix C.1 and Appendix E.1, respectively.

Interaction-Based Filtering. We hypothesize that a high-fidelity player profile requires not only a well-constructed mapping between personality traits and behaviors, but also that when the profile serves as a prompt to a capable LLM, the reasoning and actions faithfully reflect its encoded personality traits and behavioral patterns. Therefore, we evaluate inconsistencies by deploying these profiles to drive player agents through ReAct-style game interactions, and apply two dimensions of criteria to further filter the profiles:

- **Personality-Reasoning Consistency:** The reasoning content of the player agent should accurately reflect the personality traits described in the corresponding profile.
- **Reasoning-Action Consistency:** The reasoning processes of the player agent during interactions should align with its actual action decisions.

Inspired by (Wang et al., 2025a), we employ a penalty-based LLM judge to automatically detect deviations during interactions. Specifically, an interaction trajectory is segmented

into multiple fixed-size time windows, each serving as the minimal evaluation unit. The judge evaluates each segment and assigns a severity score to each deviation, ranging from 1 (minor) to 5 (severe). The score can be formalized as:

$$S_\eta = \frac{1}{|\Omega_\eta|} \sum_{i=1}^{|\Omega_\eta|} 5 - \alpha_p \times D_i - \alpha_p^m \times D_i^m + \alpha_r \times L_i, \quad (1)$$

where Ω_η denotes the game set under profile η , while D_i and D_i^m denote the total and maximum deviation penalties for the i -th game, respectively. L_i denotes the number of LLM reasoning steps. α_p , α_p^m and α_r are their corresponding penalty and reward coefficients. The final term rewards longer reasoning trajectories to curb deviation accumulation, ensuring fairness across varying interaction lengths. The detailed scoring prompt can be found in the Appendix E.2.

Based on Eq.(1), we compute the personality-reasoning consistency score S_η^{P-R} and reasoning-action consistency score S_η^{R-A} for each profile η . The final filtering score is defined as $S_\eta^{ALL} = \beta \times S_\eta^{P-R} + (1 - \beta) \times S_\eta^{R-A}$, where β is a weighting coefficient. We retain the top- k highest-rated profiles for each game subtask to model diverse players P_{sim} by the final score S_η^{ALL} , which are subsequently verified by experts. Additional quantitative validation of filtering is provided in Appendix C.2. And detailed experiments for diversity, robustness and realism of our simulated players profiles are provided in Section 5.2.2 and Appendix D.3.

4.2. Collaborative Agentic Training

4.2.1. AGENTIC ROLLOUT

Environment Input. To train the collaborative agent P_{target} , our environment comprises a game environment

and a set of diverse players P_{sim} as described in Section 4.1. During training, P_{target} interacts and cooperates with players of varying personalities and behavior patterns. Focusing on improving the LLMs capabilities rather than the agent architecture, we adopt the same observation format s_i as in prior work (Zhang et al., 2024a;b).

Agent Output. To capture how LLM-based agents reason about collaboration, we adopt a single-pass rollout that unifies reasoning, communication, and action at each interaction step, marked by `<think>`, `<message>`, and `<action>`. Unlike prior segmented approaches (Zhang et al., 2024b), the agent generates all collaboration-relevant outputs simultaneously, including a message at every step to reflect communication reasoning even when final action does not choose to send message. This design reduces token usage and latency, encourages joint reasoning over communication and action, and provides interpretable signals of collaborative intent. Only the `<action>` output is executed in the environment.

4.2.2. REWARD MECHANISM

While prior work (Feng et al., 2025; Wang et al., 2025b; Xi et al., 2026) shows that optimizing trajectory-level efficiency rewards improves LLM-based agent performance, collaborative tasks require additional affective capabilities, such as communication willingness, partner awareness, and empathy. These local, context-sensitive skills cannot be captured by sparse trajectory-level rewards alone. We therefore decompose the reward into two components: a trajectory-level efficiency reward for global task performance and a step-level affective reward to guide collaborative behavior at each interaction step.

Efficiency Reward. Formally, given a trajectory τ and a task goal G , we define the efficiency reward as a sparse trajectory-level signal

$$R_e(\tau | G) = \text{score}(\tau, G), \quad (2)$$

where $\text{score}(\cdot)$ denotes the environment-specific task performance metric. This reward encourages efficient task completion but provides no direct supervision over intermediate collaborative behaviors.

Affective Reward. We define a dense, step-level affective reward to supervise the agents collaborative behaviors at each interaction step. At each time step $t_i \in \tau$, the affective reward is formulated as

$$R_a(t_i | P_{sim}) = R_{fmt}(t_i) + R_{com}(t_i) + R_{int}(t_i | P_{sim}). \quad (3)$$

We define the agents executable action space as $\mathcal{A} = \mathcal{A}_{int} \cup \mathcal{A}_{com}$, where $\mathcal{A}_{int}$ denotes interaction actions and $\mathcal{A}_{com}$ denotes communication actions (e.g. send message).

And three reward components can be jointly specified as

$$\begin{cases} R_{fmt}(t_i) = \mathbb{I}[f_{struct}(t_i) = 1 \wedge a_i \in \mathcal{A}] \\ R_{com}(t_i) = \mathbb{I}[a_i \in \mathcal{A}_{com}] \\ R_{int}(t_i | P_{sim}) = J_{LLM}(t_i, P_{sim}) \end{cases}. \quad (4)$$

The format reward $R_{fmt}(t_i)$ ensures output validity by verifying well-formed and executable responses, including required token structure via $f_{struct}(\cdot)$ and that the action $a_i \in \mathcal{A}$. The communication reward $R_{com}(t_i)$ encourages proactive dialogue by incentivizing actions in the communication space $\mathcal{A}_{com}$. The interactivity reward $R_{int}(t_i | P_{sim})$ assesses step-level collaboration using an LLM-based judge conditioned on the partner profile P_{sim} , scoring reasoning, messages, and actions on affective criteria such as helpfulness, trustfulness, and empathy, on a normalized $[0, 1]$ scale with ten discrete levels. By combining communication rewards with subjective affective judgments, these designs cross-validate communication frequency and quality, discouraging reward hacking such as excessive but uninformative communication. Details of the LLM judge prompt are provided in Appendix E.3.

4.2.3. OPTIMIZATION

To tune the model with structured rewards, we employ GIGPO (Feng et al., 2025), a variant of GRPO (Guo et al., 2025) that introduces a hierarchical advantage estimation structure combined with both trajectory-level and step-level rewards. We sample a group of N trajectories $\{\tau_1, \dots, \tau_N\}$ and combine a global trajectory-level relative advantage $A^T(\tau_n)$, which captures trajectory-level task efficiency $R_e(\tau_n | G_n)$, with the local step-level reward $R_a(t_i^{(n)} | P_{sim}^{(n)})$ directly, to provide a strong, unbiased signal for fine-grained affective performance. This can be formalized as

$$A(t_i^{(n)}) = A^T(\tau_n) + \omega \cdot R_a(t_i^{(n)} | P_{sim}^{(n)}), \quad (5)$$

where ω balances global task efficiency and local affective interaction quality. This advantage is then used to optimize the clipped policy objective:

$$\mathcal{J}(\theta) = \mathbb{E}_{\tau \sim \pi_{\theta_{old}}} \left[\frac{1}{NH} \sum_{n=1}^N \sum_{i=1}^H \min \left(\rho_{\theta} \left(t_i^{(n)} \right) A \left(t_i^{(n)} \right), \text{clip} \left(\rho_{\theta} \left(t_i^{(n)} \right), 1 - \epsilon, 1 + \epsilon \right) A \left(t_i^{(n)} \right) \right) \right], \quad (6)$$

where $\pi_{\theta}(t_i^{(n)})$ represent the current collaborative agent P_{target} 's policy, which is calculated over the entire generated sequence $t_i^{(n)}$ by P_{target} . And $\rho_{\theta}(t_i^{(n)}) = \frac{\pi_{\theta}(t_i^{(n)})}{\pi_{\theta_{old}}(t_i^{(n)})}$ is the importance sampling ratio.

4.3. Evaluation Protocol

Evaluating contextualized collaborative intelligence requires a holistic view beyond task performance. Grounded in organizational psychology and human-AI interaction theories (George, 1990; McAllister, 1995; Salas et al., 2005), we define collaboration along two dimensions: *Taskwork* (operational efficiency) and *Teamwork* (interpersonal interaction quality). Accordingly, CollabBench uses two major metrics with several submetrics, CB-Efficiency and CB-Affective, to assess whether agents balance efficient execution with affectively proactive collaboration across diverse partners.

CB-Efficiency. We assess task performance, robustness, and interaction cost. Specifically, CB-Efficiency reports task completion steps or final game scores, together with their standard deviations across diverse player profiles, as well as the average number of generated tokens per step as a proxy for communication and computational cost.

CB-Affective. We evaluate the affective quality of collaboration under CollabBench using three sub-dimensions widely adopted in psychological studies: **Helpfulness** evaluates whether P_{target} provides relevant, actionable, and clear outputs that accurately capture the players intentions to support task completion. **Trustfulness** evaluates whether P_{target} can reliably interpret and execute the players instructions, and respond in a stable and timely manner during interaction. **Empathy** evaluates whether P_{target} can perceive the simulated player P_{sim} ’s profile and emotional state, and adapt its behavior to offer supportive and encouraging responses under confusion or failure. All scores are computed using a penalty-based LLM judge (Wang et al., 2025a). Following Section 4.1.2, segment-level evaluations are aggregated into trajectory-level, dimension-wise scores to reduce fine-grained subjective bias (Appendix C.3).

Environments. CollabBench is built by extending two multi-agent games, Communicative Watch-And-Help (CWAH) (Zhang et al., 2024b) and Overcooked-AI (Cook) (Carroll et al., 2019), into CWAH-MultiPlayer and Cook-MultiPlayer for multi-turn collaboration with diverse player profiles. CWAH-MultiPlayer includes five tasks with two layouts and fifteen profiles each (150 trajectories), while Cook-MultiPlayer contains five layouts with a “send message” action and fifteen profiles per layout (75 trajectories).

5. Experiments

This section primarily presents the performance of mainstream LLMs on CollabBench, evaluated within prior SOTA agent frameworks. It also provides an analysis of CollabBench itself and compares LLM performance before and after our collaborative agentic training for future training insights. We will answer the following four key research questions:

- **RQ1:** How do mainstream foundation models perform alongside our trained models on CollabBench?
- **RQ2:** How does CollabBench capture the diversity, robustness, and realism of anthropomorphic collaboration behaviors?
- **RQ3:** What insights do persona diversity, efficiency and affective rewards provide for collaborative agentic training?
- **RQ4:** How does our trained agent perform compared with the base model in real human-AI collaboration?

The codes are available at <https://github.com/BW297/CollabBench>.

5.1. Experimental Setup

Players Simulator P_{sim} Settings. To build a two agent cooperative game environment, we employ DeepSeek-V3.1 as teammate simulator LLM to role-play diverse player behaviors, given observation s_i of each turn and different player profiles provided in Section 4.1.

Collaborative Agent P_{target} Baselines. For CWAH-MultiPlayer, We adopt CoELA (Zhang et al., 2024b) as the agent framework and instantiate it with GPT-5.2, DeepSeek-V3.1, and Qwen2.5-72B-Instruct as backbone LLMs. For Cook-MultiPlayer: We use ProAgent (Zhang et al., 2024a) as the underlying framework, instantiated with the same set of backbone LLMs. For our collaborative agentic training, we compare Qwen2.5-7B-Instruct before and after training to evaluate the effectiveness of our method.

Implementation Details. We apply full-parameter reinforcement learning without supervised fine-tuning. Agent 1 serves as P_{target} and Agent 2 as P_{sim} , with all trainable parameters inherited from P_{target} . We employ DeepSeek-V3.1 for affective evaluation. For Cook-MultiPlayer, all five scenarios are used for training, and final performance is measured by game scores. For CWAH-MultiPlayer, 40 scenarios are used for training and the remaining 10 for testing, with final performance measured by task completion steps. Notably, in CWAH-MultiPlayer, the player profiles in the 40 training scenarios are generated by slightly perturbing the behavior patterns of the 15 test profiles excluded from evaluation, ensuring no overlap with test-time player instances. Additional details are provided in Appendix D.1.

5.2. Experimental Results

5.2.1. MAIN RESULTS ON COLLABBENCH (TO RQ1)

We present the results in Table 1 and key findings are:

Limitations in Balancing Affective and Efficient Collaboration. Current LLMs struggle to balance efficiency and affective capabilities, with notably weak performance in

Table 1. Evaluation Results on CollabBench. **Blue Zone** : Performance of the base model and our trained model. **Red Zone** : Relative Improvements indicates the relative improvements of our trained model over the base model. Oracle: Affective performance upper bound with ground-truth opposite player profile and scoring principle. Agent 1 or 2 indicates the role assumed by the collaborative agent P_{target} in the game. All results are reported as averages over all evaluation trajectories. Detailed results are provided in Appendix D.2.

CWAH-MultiPlayer													
Metric		Step ↓		CB-Efficiency Std. ↓		#Tokens(k) ↓		Helpfulness ↑		CB-Affective Trustfulness ↑		Empathy ↑	
Method	LLMs	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2
Oracle	GPT-5.2	60.91	60.29	22.26	25.01	0.16	0.16	2.81	2.96	3.77	4.01	3.69	3.53
Base	GPT-5.2	67.49	62.98	25.84	20.70	0.21	0.21	2.66	2.72	3.74	3.66	3.07	3.32
	DeepSeek-V3.1	69.26	65.75	25.17	26.28	0.41	0.43	2.32	2.45	3.35	3.50	2.87	3.30
	Qwen2.5-72B-Instruct	68.68	66.54	24.36	23.65	0.29	0.29	2.41	2.51	3.61	3.71	3.23	3.39
	Qwen2.5-7B-Instruct	84.51	90.03	33.23	31.62	0.24	0.24	1.22	1.04	2.58	2.19	2.50	2.30
Trained	Qwen2.5-7B-Instruct	71.64	63.65	25.16	22.80	0.23	0.23	1.43	1.45	3.03	3.02	3.33	3.02
Relative Improvements		15.2%	29.3%	24.3%	27.9%	4.2%	4.2%	17.2%	39.4%	17.4%	37.6%	33.5%	31.5%

Cook-MultiPlayer													
Metric		Score ↑		CB-Efficiency Std. ↓		#Tokens(k) ↓		Helpfulness ↑		CB-Affective Trustfulness ↑		Empathy ↑	
Oracle	LLMs	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2
Oracle	GPT-5.2	143.47	134.90	53.02	33.56	0.30	0.20	2.68	2.34	3.84	3.45	3.47	3.46
Base	GPT-5.2	135.20	137.12	41.96	42.40	0.20	0.20	1.63	1.88	2.89	3.10	2.27	2.52
	DeepSeek-V3.1	136.53	136.80	40.30	46.24	0.31	0.31	1.79	2.07	2.97	3.04	2.67	2.77
	Qwen2.5-72B-Instruct	135.47	114.13	41.99	39.45	0.27	0.26	1.37	1.26	2.77	2.65	2.45	2.48
	Qwen2.5-7B-Instruct	86.93	85.87	33.30	33.73	0.23	0.23	0.45	0.53	1.92	1.87	1.86	1.88
Trained	Qwen2.5-7B-Instruct	99.20	102.40	34.03	34.76	0.23	0.22	0.74	0.55	2.26	1.99	2.12	2.08
Relative Improvements		14.1%	19.3%	-2.2%	-3.1%	0.0%	4.3%	62.7%	4.6%	17.7%	6.5%	14.0%	10.4%

helpfulness and empathy. Models often rely on superficial collaboration strategies and show limited sensitivity to communication timing and human partners intentions (Detailed case study in Appendix D.3.5). Trustfulness scores are relatively higher, likely due to instruction-following and alignment training. While game scores show no significant differences across models, proprietary models (e.g., GPT-5.2) outperform open-source ones on most affective dimensions. Increased token generation by open-source models does not translate into improved affective performance.

Affective Sensitivity to Interaction Dynamics. Game genre and interaction dynamics strongly influence affective performance. Models exhibit better affective behaviors in the slower-paced CWAH-MultiPlayer than in the time-critical Cook-MultiPlayer. In high-frequency interactions, ill-timed actions and disruptive error correction degrade gameplay flow and player experience.

Training for Joint Efficiency and Affective. After affect-aware collaborative training, Qwen2.5-7B-Instruct consistently improves across all evaluated dimensions, achieving a balanced gain in both efficiency and affective capabilities. Training dynamics and insights are analyzed in Section 5.2.3 and Appendix D.4.

5.2.2. ANTHROPOMORPHIC ANALYSIS ON COLLABBENCH (TO RQ2)

To evaluate the anthropomorphic behavior of CollabBench in diversity, robustness, and realism, we take CWAH-




Figure 3. Diversity and robustness analysis on CWAH-MultiPlayer.




Figure 4. Heatmap of score distributions on CWAH-MultiPlayer.

MultiPlayer as an example for analysis. By default, P_{sim} and P_{target} use DeepSeek-V3.1, with Agent 1 as P_{sim} and Agent 2 as P_{target} . Results for Cook-MultiPlayer are provided in the Appendix D.3.1.

Diversity Analysis. CollabBench leads to greater variabil-




Figure 5. Ablation study of collaborative agentic training on CWAH-MultiPlayer.

ity in performance than the baseline methods, evaluated using standard deviation. Due to space limitations, detailed results are provided in Appendix D.3.2. In addition, we embed and visualize trajectory segments of players using t-SNE (Van der Maaten & Hinton, 2008) in Figure 3 (a), showing that CollabBench covers a broader range of interaction patterns. The corresponding quantitative metrics and comparison results are provided in Appendix D.3.3. These results demonstrate that CollabBench captures high diversity in anthropomorphic collaborative behaviors.

Robustness Analysis. To evaluate the robustness, we use Qwen2.5-72B-Instruct and DeepSeek-V3.1 to drive the players, and compute the pearson correlation coefficients between their game scores. The results in Figure 3 (b) indicate that CollabBench maintains a consistent relative performance across LLMs, with 0.821 on Cwah-MultiPlayer.

Realism Analysis. To validate realism, we embed trajectory segments from different player profiles using Qwen3-Embedding-4B and employ K-means clustering to group them into five player types. For each cluster, we select representative profiles and visualize their game score distributions, where the player types are labeled by double uppercase letters. As shown in Figure 4, different player profiles lead to markedly distinct and reasonable performance. The results indicate that proactive communication and structured task allocation lead to superior performance. However, hesitant execution and communication-avoidant behaviors lead to degraded performance. In less collaboration-dependent settings, independent action preference can still perform well. These observations align well with intuitive collaborative dynamics. The corresponding player type descriptions and example profiles are provided in Appendix D.3.4.

Furthermore, we analyze the interaction records in lowest-performing scenarios to uncover causes of performance degradation and offer insights for improving LLM collaboration. The detailed analyses are provided in Appendix D.3.5.

5.2.3. ABLATION STUDY ON COLLABORATIVE AGENTIC TRAINING (TO RQ3)

In Figure 5, we present ablation studies of collaborative agentic training on Qwen-2.5-7B-Instruct in CWAH-




Figure 6. Human evaluation results of CWAH in the user study. Error bars denote standard error. Statistical significance is determined by t -tests: “*” means statistically significant ($p < 0.01$) and “ns” means non-significant.

MultiPlayer. Here, *w/o personality* indicates that during training of P_{target} , P_{sim} is not assigned any profile and was trained using standard self-play setting; *w/o affective* indicates that only the efficiency reward was used, omitting the affective reward. The average affective score is defined as the average over three affective dimensions. We find that both ablations exhibit a clear limitation: while efficiency improves substantially, affective performance drops sharply. In particular, models gradually lose their communication capability, treating the game as effectively single-player, which severely degrades the player experience. Further details on model types, model sizes, training behaviors and case study are provided in the Appendix D.4.

5.2.4. USER STUDY (TO RQ4)

To evaluate the practical effectiveness and user experience of collaborative agentic training in real-world human-AI collaboration, we conducted a user study with 15 participants (12 male, 3 female; mean age 21.8). Each participant was assigned to one of three tasks (Task 0, 20, 40) in CWAH, with assignments evenly balanced to control task difficulty. Participants interacted with three variants of Qwen2.5-7B-Instruct: the base model, a model without affective reward, and our fully trained model. Efficiency was measured by completion steps. After interacting with each model, participants completed a 5-point Likert-scale questionnaire assessing three affective dimensions: Helpfulness (2 items), Trustfulness (2 items), and Empathy (1 item). Detailed settings are provided in Appendix D.5.

As shown in Figure 6, both the ablation and fully trained models significantly reduced completion steps compared to the base model, indicating that affective rewards do not influence efficiency seriously. In contrast, subjective evaluations revealed that the fully trained model achieved substantially higher scores across all affective dimensions. Removing affective rewards led to a marked decline in user satisfaction, with participants describing the ablation model as efficient but cold, particularly in terms of trustfulness and empathy. These results demonstrate that collaborative agentic training is crucial for producing agents that are both efficient and affectively aligned.

6. Limitation and Discussion

Immersive Player Simulation and Behavioral Alignment.

While our work establishes a foundational and scalable paradigm for utilizing LLMs to generate high-quality, diverse player simulations, significant potential remains for further research in anthropomorphic modeling. Unlike standard dialogue scenarios, cooperative game environments require agents to align their self-cognition and persona not only within linguistic exchanges but also through embodied in-game actions. This “embodied” context, where communication is intertwined with execution, brings the simulation closer to real-world complexity. Future research could deepen this alignment by incorporating Reinforcement Learning or established other personality frameworks (e.g., MBTI) to create more consistent and nuanced behavioral patterns. We hope our findings provide valuable insights for subsequent work aiming to bridge the gap between conversational personas and action-oriented behavior in complex environments.

Challenges in Collaborative Agentic Training. There are also substantial opportunities for further exploration within collaborative agentic training. We observe a persistent gap in existing LLMs regarding the balance between maximizing task efficiency and maintaining a positive player experience. The complexity of game interactions often hinders the models ability to master communication timing and decipher the deeper intent behind user behaviors; consequently, LLMs can exhibit template-like communication with low information density. In an era dominated by task-efficiency-driven reinforcement learning, fostering such affective capabilities is inherently difficult.

A closely related challenge lies in mitigating reward hacking in affective optimization. Although our training objective jointly considers both efficiency and affective dimensions, and further introduces complementary mechanisms within the affective reward, such as combining communication rewards with subjective affective judgments to cross-validate communication frequency and quality, these designs primarily aim to reduce degenerate behaviors that optimize a single affective signal (e.g., excessive but uninformative communication). Nevertheless, our human evaluation indicates that, even after extensive affective training, the agents communication skills and empathetic understanding remain imperfect. This suggests that more robust and principled affective reward designs, capable of better resisting reward hacking while preserving genuine interaction quality, remain an open and important direction for future work.

Additionally, we note that in scenarios with high-frequency interactions, such as Cook-MultiPlayer, the training time overhead becomes substantial, highlighting the need for more computationally efficient optimization algorithms in future research.

Refinement of Evaluation Protocols. Regarding our evaluation protocol, while our affective metrics are grounded in psychological theory, they inevitably retain a degree of subjectivity that warrants further refinement. An important related aspect is the consistency between human judgments and LLM-based evaluations. In our setting, collaborative game trajectories are often long and complex, making exhaustive human annotation prohibitively time-consuming and costly. To alleviate this issue, we adopt an improved LLM-based evaluation strategy that segments long interaction trajectories into shorter, semantically coherent clips, which helps reduce fine-grained scoring bias in subjective assessment. Further discussions of the LLM judge for affective evaluation are provided in Appendix D.6.

Nevertheless, we believe that human calibration remains an essential component for validating affective and interaction-oriented metrics, particularly for nuanced qualities such as empathy and trustfulness. Addressing the high human labor cost associated with such calibration, and designing more efficient human-in-the-loop evaluation protocols, constitutes an important direction for our future work. For instance, this may be achieved by designing targeted interaction scenarios or specific end-game puzzles, where affective and collaborative outcomes are more clearly defined, thereby substantially mitigating the potential bias inherent in subjective LLM-based assessments.

Furthermore, regarding the breadth of our evaluation, constraints on time and resources limited our scope to a selection of representative models. Given that collaborative capability is a vital criterion for the evolution of LLMs, a more comprehensive assessment covering a wider spectrum of models remains an essential direction for future benchmarking efforts.

7. Conclusion

Genuine human-AI collaboration requires agents to move beyond solitary task execution and proactively adapt to the behavioral and affective needs of human partners. To overcome the limited grounding and interactivity of prior conversation-level studies, this paper proposes cooperative game environments as a principled testbed for immersive collaboration. We introduce CollabBench, a benchmark that enables collaborative agentic training through diverse player simulation and supports multi-dimensional evaluation of both efficiency and affective alignment. Extensive experiments show that agents can learn to balance task performance with empathy, offering actionable insights for future training strategies and establishing a benchmark for socially aware, proactive collaborators.

Acknowledgments

We thank the anonymous reviewers for their constructive comments. This work is supported by the National Key Research and Development Program of China under Grant 2024YFC3308503, Tencent, and the Shanghai Municipal Special Program for Basic Research on General AI Foundation Models under Grant No. 2025SHZDZX026D08.

Impact Statement

This paper aims to advance **socially aware** collaborative intelligent agents. In our user study, we collected participants’ behavioral data and feedback to assess the affective alignment of collaborative agents. During data collection, we strictly protected participants’ privacy by excluding any personally identifiable information (PII), ensuring that participation was entirely voluntary, and following principles of fair compensation.

We believe this work has a positive societal impact. First, by improving understanding and adaptability of LLMs in multi-agent collaborative tasks, it can facilitate more efficient and empathetic interactions in applications such as educational platforms and virtual assistants. More specifically, intelligent agents with social awareness and collaborative capabilities can support more affective communication, improving user engagement and learning experiences in educational settings (e.g., collaborative learning and intelligent tutoring). They may also help alleviate users’ psychological burden in emotionally sensitive interactions (e.g., complex decision-making and high-cognitive-load tasks). Second, we emphasize maintaining fairness and transparency throughout agent training and deployment, while mitigating potential biases and risks of emotional misalignment. These considerations are particularly important for socially interactive systems, as inappropriate affective behaviors or biased responses may influence users’ trust, motivation, and emotional experience.

By systematically including these considerations, our work offers a responsible reference for deploying collaborative intelligent agents in real-world applications.

References

- Carroll, M., Shah, R., Ho, M. K., Griffiths, T., Seshia, S. A., Abbeel, P., and Dragan, A. D. On the utility of learning about humans for human-ai coordination. In *Advances in Neural Information Processing Systems* 32, pp. 5175–5186, Vancouver, Canada, 2019.
- Chevalier-Boisvert, M., Bahdanau, D., Lahlou, S., Willems, L., Saharia, C., Nguyen, T. H., and Bengio, Y. BabyAI: A platform to study the sample efficiency of grounded language learning. In *Proceedings of the 7th International Conference on Learning Representations*, New Orleans, LA, 2019.
- Costarelli, A., Allen, M., Hauksson, R., Sodunke, G., Har-
iharan, S., Cheng, C., Li, W., Clymer, J., and Yadav, A. Gamebench: Evaluating strategic reasoning abilities of LLM agents. *arXiv preprint arXiv:2406.06613*, 2024.
- Feng, L., Xue, Z., Liu, T., and An, B. Group-in-group policy optimization for llm agent training. In *Advances in Neural Information Processing Systems* 39, San Diego, CA, 2025.
- George, J. M. Personality, affect, and behavior in groups. *Journal of Applied Psychology*, 75(2):107, 1990.
- Guo, D., Yang, D., Zhang, H., Song, J., Zhang, R., Xu, R., Zhu, Q., Ma, S., Wang, P., Bi, X., et al. Deepseek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.
- Hartigan, J. A. and Wong, M. A. Algorithm as 136: A k-means clustering algorithm. *Journal of the royal statistical society. series c (applied statistics)*, 28(1):100–108, 1979.
- Hu, E. J., Shen, Y., Wallis, P., Allen-Zhu, Z., Li, Y., Wang, S., Wang, L., and Chen, W. Lora: Low-rank adaptation of large language models. In *Proceedings of the 10th International Conference on Learning Representations*, Virtual Event, 2022.
- Hu, L., Huo, M., Zhang, Y., Yu, H., Xing, E. P., Stoica, I., Rosing, T., Jin, H., and Zhang, H. LMGAME-BENCH: How good are LLMs at playing games? In *Proceedings of the 14th International Conference on Learning Representations*, Rio de Janeiro, Brazil, 2026.
- Hu, S., Huang, T., Liu, G., Kompella, R. R., Ilhan, F., Tekin, S. F., Xu, Y., Yahn, Z., and Liu, L. A survey on large language model-based game agents. *arXiv preprint arXiv:2404.02039*, 2024.
- Huang, X., Huang, Y., Liu, W., Zeng, X., Wang, Y., Tang, R., Xie, H., and Lian, D. Advancing and benchmarking personalized tool invocation for llms. *arXiv preprint arXiv:2505.04072*, 2025.
- Jaderberg, M., Dalibard, V., Osindero, S., Czarnecki, W. M., Donahue, J., Razavi, A., Vinyals, O., Green, T., Dunning, I., Simonyan, K., et al. Population based training of neural networks. *arXiv preprint arXiv:1711.09846*, 2017.
- Jia, Z., Yue, S., Chen, W., Wang, S., Liu, Y., Song, Y., and Wei, Z. Ready jurist one: Benchmarking language agents for legal intelligence in dynamic environments. 2026.
- Jiang, J., Wang, F., Shen, J., Kim, S., and Kim, S. A survey on large language models for code generation. *ACM*

- Transactions on Software Engineering and Methodology*, 35(2):1–72, 2026.
- Jin, B., Zeng, H., Yue, Z., Yoon, J., Arik, S. O., Wang, D., Zamani, H., and Han, J. Search-R1: Training LLMs to reason and leverage search engines with reinforcement learning. In *Second Conference on Language Modeling*, Montreal, Canada, 2025.
- Korf, R. E. Planning as search: A quantitative approach. *Artif. Intell.*, 33(1):65–88, 1987.
- Kosinski, M. Evaluating large language models in theory of mind tasks. *Proceedings of the National Academy of Sciences*, 121(45):e2405460121, 2024.
- Li, Y., Zhang, S., Sun, J., Du, Y., Wen, Y., Wang, X., and Pan, W. Cooperative open-ended learning framework for zero-shot coordination. In *Proceedings of 40th International Conference on Machine Learning*, volume 202, pp. 20470–20484, Honolulu, Hawaii, 2023.
- Li, Y., Zhang, S., Sun, J., Zhang, W., Du, Y., Wen, Y., Wang, X., and Pan, W. Tackling cooperative incompatibility for zero-shot human-ai coordination. *J. Artif. Intell. Res.*, 80: 1139–1185, 2024.
- Liu, Z., Yin, S. X., Lin, G., and Chen, N. F. Personality-aware student simulation for conversational intelligent tutoring systems. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 626–642, Miami, FL, 2024.
- McAllister, D. J. Affect-and cognition-based trust as foundations for interpersonal cooperation in organizations. *Academy of Management Journal*, 38(1):24–59, 1995.
- McCrae, R. R. and Costa Jr, P. T. A five-factor theory of personality. *Handbook of Personality: Theory and Research*, 2(1999):139–153, 1999.
- Padmakumar, V. and He, H. Does writing with language models reduce content diversity? In *Proceedings of the 12th International Conference on Learning Representations*, Vienna, Austria, 2024.
- Park, J. S., O’Brien, J. C., Cai, C. J., Morris, M. R., Liang, P., and Bernstein, M. S. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, pp. 2:1–2:22, San Francisco, CA, 2023.
- Puig, X., Shu, T., Li, S., Wang, Z., Liao, Y., Tenenbaum, J. B., Fidler, S., and Torralba, A. Watch-And-Help: A challenge for social perception and human-ai collaboration. In *Proceedings of the 9th International Conference on Learning Representations*, Virtual Event, 2021.
- Salas, E., Sims, D. E., and Burke, C. S. Is there a big five in teamwork? *Small Group Research*, 36(5):555–599, 2005.
- Salemi, A., Mysore, S., Bendersky, M., and Zamani, H. Lamp: When large language models meet personalization. In Ku, L., Martins, A., and Srikumar, V. (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7370–7392, Bangkok, Thailand, 2024.
- Salminen, J., Liu, C., Pian, W., Chi, J., Häyhänen, E., and Jansen, B. J. Deus ex machina and personas from large language models: Investigating the composition of ai-generated persona descriptions. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pp. 510:1–510:20, Honolulu, HI, 2024.
- Seo, S., Noh, S., Lee, J., Lim, S., Lee, W. H., and Kang, H. REVECA: Adaptive planning and trajectory-based validation in cooperative language agents using information relevance and relative proximity. In *Proceedings of 39th AAAI Conference on Artificial Intelligence*, pp. 23295–23303, Philadelphia, PA, 2025.
- Sheng, G., Zhang, C., Ye, Z., Wu, X., Zhang, W., Zhang, R., Peng, Y., Lin, H., and Wu, C. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the 20th European Conference on Computer Systems*, pp. 1279–1297, Rotterdam, Netherlands, 2025.
- Shin, J., Hedderich, M. A., Rey, B. J., Lucero, A., and Oulasvirta, A. Understanding human-ai workflows for generating personas. In *Proceedings of the 2024 ACM Designing Interactive Systems Conference*, pp. 757–781, IT University of Copenhagen, Denmark, 2024.
- Shridhar, M., Yuan, X., Côté, M., Bisk, Y., Trischler, A., and Hausknecht, M. J. ALFWorld: Aligning text and embodied environments for interactive learning. In *Proceedings of 9th International Conference on Learning Representations*, Virtual Event, 2021.
- Siu, H. C., Peña, J. D., Chen, E., Zhou, Y., Lopez, V. J., Palko, K., Chang, K. C., and Allen, R. E. Evaluation of human-ai teams for learned and rule-based agents in hanabi. In *Advances in Neural Information Processing Systems 34*, pp. 16183–16195, Virtual Event, 2021.
- Strouse, D., McKee, K. R., Botvinick, M. M., Hughes, E., and Everett, R. Collaborating with humans without human data. In *Advances in Neural Information Processing Systems 34*, pp. 14502–14515, Virtual Event, 2021.
- Sun, H., Zhang, S., Niu, L., Ren, L., Xu, H., Fu, H., Zhao, F., Yuan, C., and Wang, X. Collab-Overcooked: Benchmarking and evaluating large language models as collaborative agents. In *Proceedings of the 2025 Conference on*

- Empirical Methods in Natural Language Processing*, pp. 4922–4951, Suzhou, China, 2025.
- Tesauro, G. TD-Gammon, a self-teaching backgammon program, achieves master-level play. *Neural Comput.*, 6 (2):215–219, 1994.
- Tu, Q., Fan, S., Tian, Z., Shen, T., Shang, S., Gao, X., and Yan, R. CharacterEval: A chinese benchmark for role-playing conversational agent evaluation. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 11836–11850, Bangkok, Thailand, 2024.
- Van der Maaten, L. and Hinton, G. Visualizing data using t-sne. *Journal of Machine Learning Research*, 9(11), 2008.
- Wang, G., Xie, Y., Jiang, Y., Mandlekar, A., Xiao, C., Zhu, Y., Fan, L., and Anandkumar, A. Voyager: An open-ended embodied agent with large language models. *Trans. Mach. Learn. Res.*, 2024, 2024a.
- Wang, L., Ma, C., Feng, X., Zhang, Z., Yang, H., Zhang, J., Chen, Z., Tang, J., Chen, X., Lin, Y., Zhao, W. X., Wei, Z., and Wen, J. A survey on large language model based autonomous agents. *Frontiers Comput. Sci.*, 18(6): 186345, 2024b.
- Wang, N., Peng, Z., Que, H., Liu, J., Zhou, W., Wu, Y., Guo, H., Gan, R., Ni, Z., Yang, J., Zhang, M., Zhang, Z., Ouyang, W., Xu, K., Huang, W., Fu, J., and Peng, J. RoleLLM: Benchmarking, eliciting, and enhancing role-playing abilities of large language models. In *Findings of the Association for Computational Linguistics*, pp. 14743–14777, Bangkok, Thailand, 2024c.
- Wang, R., Yu, H., Zhang, W., Qi, Z., Sap, M., Bisk, Y., Neubig, G., and Zhu, H. Sotopia- π : Interactive learning of socially intelligent language agents. In Ku, L., Martins, A., and Srikumar, V. (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12912–12940, Bangkok, Thailand, 2024d.
- Wang, X., Wang, H., Zhang, Y., Yuan, X., Xu, R., Huang, J., Yuan, S., Guo, H., Chen, J., Zhou, S., Wang, W., and Xiao, Y. Coser: Coordinating LLM-based persona simulation of established roles. In *Proceedings of 42nd International Conference on Machine Learning*, Vancouver, Canada, 2025a.
- Wang, Y., Huang, Y., Qian, H., Wei, Y., Ding, Y., Wang, W., Liu, Z., Huang, Z., Zhou, A., and Guo, J. Alphacontext: An evolutionary tree-based psychometric context generator for creativity assessment. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics*, San Diego, CA, 2026.
- Wang, Z., Wang, K., Wang, Q., Zhang, P., Li, L., Yang, Z., Jin, X., Yu, K., Nguyen, M. N., Liu, L., et al. RAGEN: Understanding self-evolution in LLM agents via multi-turn reinforcement learning. *arXiv preprint arXiv:2504.20073*, 2025b.
- Wu, S., Galley, M., Peng, B., Cheng, H., Li, G., Dou, Y., Cai, W., Zou, J., Leskovec, J., and Gao, J. CollabLLM: From passive responders to active collaborators. In *Proceedings of 42nd International Conference on Machine Learning*, Vancouver, Canada, 2025.
- Xi, Z., Chen, W., Guo, X., He, W., Ding, Y., Hong, B., Zhang, M., Wang, J., Jin, S., Zhou, E., Zheng, R., Fan, X., Wang, X., Xiong, L., Zhou, Y., Wang, W., Jiang, C., Zou, Y., Liu, X., Yin, Z., Dou, S., Weng, R., Qin, W., Zheng, Y., Qiu, X., Huang, X., Zhang, Q., and Gui, T. The rise and potential of large language model based agents: A survey. *Sci. China Inf. Sci.*, 68(2), 2025a.
- Xi, Z., Ding, Y., Chen, W., Hong, B., Guo, H., Wang, J., Guo, X., Yang, D., Liao, C., He, W., et al. AgentGym: Evaluating and training large language model-based agents across diverse environments. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 27914–27961, Vienna, Austria, 2025b.
- Xi, Z., Huang, J., Liao, C., Huang, B., Liu, J., Guo, H., yajie yang, Zheng, R., Ye, J., Zhang, J., Chen, W., He, W., Ding, Y., Li, G., Chen, Z., Du, Z., Yao, X., Xu, Y., Chen, J., Gui, T., Wu, Z., Zhang, Q., Huang, X., and Jiang, Y.-G. AgentGym-RL: An open-source framework to train LLM agents for long-horizon decision making via multi-turn RL. In *Proceedings of the 14th International Conference on Learning Representations*, Rio de Janeiro, Brazil, 2026.
- Zhang, C., Yang, K., Hu, S., Wang, Z., Li, G., Sun, Y., Zhang, C., Zhang, Z., Liu, A., Zhu, S., Chang, X., Zhang, J., Yin, F., Liang, Y., and Yang, Y. ProAgent: Building proactive cooperative agents with large language models. In *Proceedings of 38th AAAI Conference on Artificial Intelligence*, pp. 17591–17599, Vancouver, Canada, 2024a.
- Zhang, G., Geng, H., Yu, X., Yin, Z., Zhang, Z., Tan, Z., Zhou, H., Li, Z.-Z., Xue, X., Li, Y., Zhou, Y., Chen, Y., Zhang, C., Fan, Y., Wang, Z., Huang, S., Velez, F. P., Liao, Y., WANG, H., Yang, M., Ji, H., Wang, J., YAN, S., Torr, P., and BAI, L. The landscape of agentic reinforcement learning for LLMs: A survey. *Transactions on Machine Learning Research*, 2026. ISSN 2835-8856.
- Zhang, H., Du, W., Shan, J., Zhou, Q., Du, Y., Tenenbaum, J. B., Shu, T., and Gan, C. Building cooperative embodied

agents modularly with large language models. In *Proceedings of 12th International Conference on Learning Representations*, Vienna, Austria, 2024b.

Zhang, N., Sun, R., Su, R., Ma, S., Zhang, S., Weng, X., Zhang, X., Zhan, Y., Xu, Y., Chen, Z., et al. Echo-n1: Affective rl frontier. *arXiv preprint arXiv:2512.00344*, 2025a.

Zhang, S., Ma, X., Xu, Y., Cao, Z., Lu, P., Yuan, H., Shen, T., Zhang, Z., Zhao, H., and Yang, M.-H. ParaCook: On time-efficient planning for multi-agent systems. *arXiv preprint arXiv:2510.11608*, 2025b.

A. Details of Motivation Study

In this section, we provide the experimental setup and results for Efficiency Challenge in Figure 1 in Section 1. Both P_{sim} and P_{target} are powered by DeepSeek-V3.1. Under the default setting, we adopt CoELA as the game environment for CWAH-MultiPlayer and ProAgent for Cook-MultiPlayer. Here, we consistently adopt Agent 1 as P_{sim} and Agent 2 as P_{target} , and conduct experiments across all 30 filtered player profiles. The complete results are reported in Figure 7 and Figure 8.




Figure 7. The complete comparison results for Efficiency Challenge on CWAH-MultiPlayer.




Figure 8. The complete comparison results for Efficiency Challenge on Cook-MultiPlayer.

B. Related Work

B.1. Personality-Aware Human Simulation.

Realistic human simulation is essential across a wide range of interactive settings. Traditionally, human simulators are learned by fitting models to collected human behavior data (Carroll et al., 2019). With the emergence of LLMs, it has been shown that they can generate diverse and authentic personas (Kosinski, 2024; Salminen et al., 2024; Shin et al., 2024), enabling more flexible and scalable human simulation. This capability has been widely adopted in domains such as role-playing (Wang et al., 2024c; Tu et al., 2024; Wang et al., 2025a), where LLMs simulate characters from fictional narratives and films, and personalized services (Salemi et al., 2024; Jia et al., 2026; Huang et al., 2025), where agents are conditioned on user profiles including demographics, personality traits, interests and careers. However, these approaches typically rely on predefined character descriptions or user data. In simulated embodied cooperative game environments, data for players with diverse personalities and behavioral styles remains scarce. Existing collaboration systems between

human and LLM-based agents, such as CollabLLM (Wu et al., 2025), employ user simulators for tasks like document editing, mathematics and coding, but these simulators are largely task-driven, lack personality diversity, and operate at the conversation level, limiting their ability to capture realistic human behaviors and environmental dynamics. Researches in social science have explored human simulation through LLMs with diverse personalization and dynamic actions in specific domains such as daily dialogues (Wang et al., 2024d; Zhang et al., 2025a), social activity modeling (Park et al., 2023) and education (Liu et al., 2024). Despite their success, these approaches are often domain-specific and cannot be directly applied to embodied collaborative tasks between human and LLM-based agents.

B.2. Agentic Training for LLMs in Games.

Recent studies have demonstrated the impressive performance of LLM-based agentic training in fields like deep research (Jin et al., 2025), mathematical reasoning (Guo et al., 2025), and coding (Jiang et al., 2026). Game environments (Chevalier-Boisvert et al., 2019; Carroll et al., 2019; Shridhar et al., 2021; Puig et al., 2021; Wang et al., 2024a) offer significant practical value for applying this technology, providing a realistic platform to enhance agentic training and simulate complex real-world scenarios.

- **Single Player Training:** Early research on single agentic training primarily focused on the design of agent architectures, such as VOYAGER (Wang et al., 2024a), which introduces a novel agent architecture for embodied lifelong learning in Minecraft, combining an automatic curriculum and an evolving skill library. As agentic reinforcement learning has been validated in an increasing number of applications, recent work has also begun to apply agentic RL to train LLMs in simulated embodied game environments, such as RAGEN (Wang et al., 2025b) and AgentGym-RL (Xi et al., 2026). While these studies are crucial for enhancing the capabilities of LLMs themselves, the potential of using Agentic RL to improve the collaboration awareness remains underexplored.

- **Collaborative Teammate Training:** Most existing research on collaborative teammate agents still primarily focuses on agent architecture design (Zhang et al., 2024b;a; Seo et al., 2025). For example, in the Overcooked environment, ProAgent (Zhang et al., 2024a) employs a belief revision mechanism to create proactive agents that dynamically adapt their behaviors to enhance cooperation with teammates. In the C-WAH environment, CoELA (Zhang et al., 2024b) integrates perception, memory, execution, planning, and communication modules to cooperate with others in accomplishing long-horizon tasks. However, architecture-centric designs often lack explicit mechanisms for eliciting and training collaboration awareness within LLMs themselves, and they generally overlook the diversity of teammate personalities that commonly arises in real-world collaboration settings.

B.3. Evaluation of LLM-based Agent and Human Collaboration.

As the capabilities of LLMs continue to grow, the collaboration ability of LLM-based agents has become increasingly important. However, when it comes to collaboration, efficiency is often not the sole metric of evaluation (George, 1990; McAllister, 1995; Salas et al., 2005). Recently, an increasing number of studies have shifted the focus from traditional efficiency-based metrics to more multidimensional evaluation frameworks. For example, the LLM-as-a-judge approach has been adopted to evaluate interactivity (Wu et al., 2025) by assessing user engagement levels or empathy (Zhang et al., 2025a) to determine whether the model can provide timely emotional support to users. However, in current gamified evaluations (Costarelli et al., 2024; Xi et al., 2025b; Hu et al., 2026; Sun et al., 2025; Zhang et al., 2025b), most assessments still rely solely on efficiency metrics such as game scores or success rates to measure the capabilities of LLMs. While some research in cooperative games has expanded beyond efficiency metrics, it typically relies on subjective user feedback through surveys (Siu et al., 2021; Zhang et al., 2024b), lacking systematic evaluation criteria and methodologies. This limitation hampers large-scale evaluations and complicates reward feedback signals in current Agentic RL training.

C. Technical Details

C.1. Detailed process of clustering

Here, we provide the details of clustering process. We segment LLM-based high-level trajectories into units of three time windows to maintain reasoning coherence while controlling contextual overhead. Each segment is then embedded using Qwen3-Embedding-4B and grouped using K-means clustering (Hartigan & Wong, 1979), with each cluster of segments used to construct the corresponding candidate player profiles.

C.2. Quantitative Validation for Profile Filtering

Here, we compare the quantitative results before and after filtering to evaluate the fidelity of player profiles. The detailed metrics, implementation details, and the results analysis are as follows.

Quantitative Metrics.

• **Intra-Class Distance** measures the degree of clustering of trajectory segments generated by the same player profile. Assume there are Q embed trajectory segments $\mathbf{x}_i \in \mathbb{R}^d$, associated with the corresponding player profiles η_i . For profile η , let $C_\eta = \{\mathbf{x}_i \mid \eta_i = \eta\}$ denote the set of their trajectory segments. The pairwise cosine distance between segments is defined as:

$$d_{ij} = 1 - \frac{\mathbf{x}_i \cdot \mathbf{x}_j}{\|\mathbf{x}_i\| \|\mathbf{x}_j\|}, \quad \text{where } i, j \in C_\eta, i \neq j. \quad (7)$$

The average intra-class distance for profile η is:

$$D_{\text{Intra}_\eta} = \frac{2}{|C_\eta|(|C_\eta| - 1)} \sum_{i < j} d_{ij}, \quad \text{where } i, j \in C_\eta. \quad (8)$$

The global D_{Intra} in profile set $\mathcal{E}$ can be defined as $D_{\text{Intra}} = \frac{1}{|\mathcal{E}|} \sum_{\eta \in \mathcal{E}} D_{\text{Intra}_\eta}$. Smaller values indicate tighter clustering of trajectory segments from the same profiles, reflecting higher intra-class consistency.

• **k -Nearest Neighbor Label Consistency (k -NN Label Consistency)** measures the degree to which neighboring trajectory segments share the same profile. For trajectory segment $\mathbf{x}_i$, let N_i denote its k nearest neighbors (excluding itself). Its local consistency is defined as:

$$\text{LC}_{\mathbf{x}_i}^k = \frac{1}{k} \sum_{j \in N_i} \mathbb{I}(\eta_j = \eta_i), \quad (9)$$

where $\mathbb{I}(\cdot)$ is the indicator function. The global LC^k can be defined as $\text{LC}^k = \frac{1}{Q} \sum_{i=1}^Q \text{LC}_{\mathbf{x}_i}^k$. Larger values indicate high local consistency within the same profile.

• **Consistency Score.** Based on the two metrics above, we define Consistency Score as:

$$\text{Consistency Score} = \begin{cases} \gamma \cdot \text{LC}^k + (1 - \gamma) \cdot \frac{1}{1 + D_{\text{Intra}}}, & \text{if } D_{\text{Intra}} > 0 \\ 0, & \text{otherwise} \end{cases}, \quad (10)$$

where γ is the weighting coefficient. The score captures both intra-class and local consistency of the trajectory segments, with larger values indicating better fidelity, providing a quantitative basis for validating filtered player profiles. Notably, profile fidelity focuses on the consistency of behavior within the same profile, rather than the distinguishability between different profiles. Therefore, inter-class measures are not incorporated in Consistency Score.

Implementation Details. The weighting coefficient γ is set to 0.5. We segment LLM-based high-level trajectories into units of three time windows and embed the segments using Qwen3-Embedding-4B.

Table 2. The comparison results before and after player profile filtering.

Metrics	CWAH-MultiPlayer		Cook-MultiPlayer	
	Before	After	Before	After
Intra-class Distance $D_{\text{Intra}} \downarrow$	0.1237	0.1236	0.1034	0.1040
k -NN Label Consistency $\text{LC}^k \uparrow$	0.4511	0.5470	0.5729	0.6760
Consistency Score $\uparrow$	0.1006	0.1220	0.1298	0.1531

Results Analysis. As shown in Table 2, the results confirm that filtering enhances the fidelity of profiles compared to before. This further underscores the necessity and effectiveness of the secondary filtering step.

C.3. Affective Metrics Scoring

Here, we provide the detailed evaluation criteria for affective metrics and description of the scoring computation. The corresponding prompt is shown in Appendix E.4.

C.3.1. EVALUATION CRITERIA

We segment the interaction trajectories of P_{target} into three time windows as the minimal evaluation unit to evaluate the affective quality of reasoning, communication, and action in the single-pass output, marked by `<think>`, `<message>`, `<action>`, respectively. The focus of each specific criterion is indicated in [·].

• **Helpfulness.** The specific dimensions are as follows:

- **Task Focus.** [`<think>`] Whether P_{target} allocates attention and time primarily to task progression and key steps, rather than engaging in irrelevant interactions.
- **Adaptation.** [`<think>`, `<action>`] Whether P_{target} proactively identifies missing information, proposes executable plans, synchronizes key progress, and dynamically adjusts its behavior according to the state and task progress of P_{sim} to fill gaps while avoiding redundant effort.
- **Communication Clarity.** [`<message>`] Whether the message is structured, comprehensible, and executable by P_{target} .
- **Stuck or Negative Behaviors.** [`<action>`] Including loops, indecision, or prolonged lack of progress.
- **Intent Alignment.** [`<think>`, `<action>`] Whether P_{target} demonstrates understanding of the latent goals of P_{sim} , rather than merely executing surface-level instructions.

• **Trustfulness.** The specific dimensions are as follows:

- **Interaction Responsiveness.** [`<message>`, `<action>`] Whether P_{target} accurately responds to requests, promptly addresses key issues and updates, and avoids deviating from collaboration goals or forcing its own plan in the absence of consensus.
- **Synchronization Latency.** [`<message>`, `<action>`] Whether key discoveries or sub goal completions are shared promptly, preventing delayed information from causing redundant effort or collaboration inefficiency.

• **Empathy.** The specific dimensions are as follows:

- **Personality Inference.** [`<think>`, `<message>`] Whether P_{target} adjusts its tone, expressions, and interaction strategies based on the personality traits or preferences of P_{sim} , avoiding clear mismatches in communication style.
- **Emotional Support.** [`<message>`, `<action>`] Whether P_{target} maintains politeness, encouragement, and emotional acceptance, and provides timely reassurance and constructive help when P_{sim} shows frustration or uncertainty; cold, harsh, or dismissive behavior is considered negative.

It is worth noting that not every situation within a given time window fully reflects all of the aforementioned dimensions. This is precisely why we employ a penalty-based LLM judge: at each time window, we assess whether the sequence of outputs of the agent violates any of these dimensions and assign penalties accordingly.

C.3.2. SCORING COMPUTATION

Inspired by (Wang et al., 2025a), we adopt a penalty-based LLM judge to evaluate the quality of affective interaction along three dimensions: *Helpfulness*, *Trustfulness*, and *Empathy*. Each interaction trajectory is segmented into fixed-size windows of $K=3$ consecutive high-level actions (LLM calls). Incomplete tail windows are discarded. Each window is independently scored for the three dimensions.

• **Window-level scoring.** For a window w and dimension $d \in \{\text{Helpfulness}, \text{Trustfulness}, \text{Empathy}\}$, the judge outputs a list of violations $\mathcal{V}_{w,d}$ with deduction severities $\delta_{w,d,j} \in \{1, 2, 3\}$. The window score is computed by deducting from 5:

$$s_{w,d} = \max\left(0, 5 - \sum_{j=1}^{|\mathcal{V}_{w,d}|} \delta_{w,d,j}\right). \quad (11)$$

The judge is instructed to start from 5, deduct for each violation, and return strict JSON with evidence snippets.

• **Trajectory-level aggregation.** Let $\mathcal{W}_\tau$ be the set of windows for trajectory τ , with $n = |\mathcal{W}_\tau|$. Define the total violation count $V_{\tau,d} = \sum_{w \in \mathcal{W}_\tau} |\mathcal{V}_{w,d}|$, and the worst window score gap $G_{\tau,d} = \max_{w \in \mathcal{W}_\tau} (5 - s_{w,d})$. The aggregated score for dimension d is:

$$S_{\tau,d} = \text{clip}_{[0,5]}\left(5 - a_d \frac{V_{\tau,d}}{n} - b_d G_{\tau,d} - P_{\text{msg}}(\rho_\tau)\right). \quad (12)$$

Here ρ_τ is the agent send-message ratio at the trajectory level,

$$\rho_\tau = \frac{\# P_{\text{target}} \text{ send_message steps}}{\# P_{\text{target}} \text{ llm_call steps}},$$

and P_{msg} is a trajectory-level penalty applied when messaging is too sparse.

$$P_{\text{msg}}(\rho_\tau) = \begin{cases} 0, & \rho_\tau \geq \varepsilon, \\ \lambda \cdot p_{\text{max}}, & \rho_\tau < \varepsilon. \end{cases} \quad (13)$$

Here $\lambda = \frac{\exp(kx) - 1}{\exp(k) - 1}$ denotes the normalized exponential penalty factor. In this formulation, and $x = \frac{\varepsilon - \rho_\tau}{\varepsilon} \in (0, 1]$ measures the normalized shortfall of the observed message ratio relative to the minimum acceptable threshold, ρ_τ denotes the message sparsity ratio for trajectory (or window) τ , and ε is the minimum acceptable message ratio below which a penalty is applied. The scalar p_{max} specifies the maximum possible message-sparsity penalty, thereby capping the largest deduction that can be incurred due to insufficient communication. The parameter k controls the curvature of the exponential scaling, determining how sharply the penalty factor λ increases as ρ_τ falls further below ε .

This design prevents the message-frequency regularizer from dominating the affective score and ensures that P_{msg} acts as a bounded soft constraint rather than a hard failure signal.

• **Parameter choices.** We follow the default evaluation settings in the provided pipeline: $K=3$ (window size), $a_d=b_d=0.8$ for all $d \in \{\text{Helpfulness}, \text{Trustfulness}, \text{Empathy}\}$, and message-penalty parameters $\varepsilon=0.15$, $k=4.0$, $p_{\text{max}}=2.0$.

D. Experiments

D.1. Implementation Details

D.1.1. DETAILS ABOUT THE DATASETS

Here, we provide a detailed description of the synthesized dataset in Table 3. Notably, in CWAH-MultiPlayer, the player profiles for the 40 training scenarios are generated by slightly perturbing the behavior patterns of 15 player profiles drawn from the test scenarios and excluded from evaluation.

Table 3. Statistics of the synthesized dataset on CollabBench. “Trained” and “Untrained” refer to player profiles and sub tasks that are seen and unseen during agentic training, respectively.

CWAH-MultiPlayer			Cook-MultiPlayer		
Dataset	#Subtasks	#Player Profiles	Dataset	#Subtasks	#Player Profiles
Train	40	94	Train	5	75
Test	10	150	Test	5	75
Total	50	244	Total	50	150

D.1.2. DETAILS OF PLAYER SIMULATION

In **Game-Specific Behavioral Trajectory Generation** (Section 4.1.1), we employ multiple LLMs to simulate personality-driven player instances P_{sim} . The LLMs used include DeepSeek-V3, Qwen2.5-72B-Instruct, and Qwen3-235B-A22B.

In **Player Profile Filtering** (Section 4.1.2), we adopt Agent 1 as P_{sim} and Agent 2 as P_{target} for game interaction and the player trajectories are segmented into units of three time windows. The game set Ω_η under each player profile η , is set to 3. For consistency evaluation, we employ a penalty-based LLM judge built upon DeepSeek-V3.1. For CWAH-MultiPlayer, the penalty and reward coefficients $\alpha_p, \alpha_p^m, \alpha_r$ corresponding to Personality-Reasoning Consistency and Reasoning-Action Consistency are set to 0.5, 0.1, and 0.1, respectively. For Cook-MultiPlayer, the corresponding coefficients are set to 0.1, 0.1, and 0.01. The weighting coefficient β for both consistency scores, S_η^{P-R} and S_η^{R-A} , is set to 0.5. These parameter settings ensure that the scores S_η^{P-R} , S_η^{R-A} , and S^{ALL} remain within the range of [0-5]. Finally, we retain the top 30 profiles with the highest S^{ALL} scores for each sub task (if fewer than 30 profiles are available, all are retained).

The corresponding prompts for profile-driven simulated players in two game environments are provided in Appendix E.5.

D.1.3. DETAILS OF TRAINING

All methods are configured with identical hyperparameters: the maximum prompt length is 4096 tokens, and the maximum response length is 4096 tokens. Each episode allows up to 150 environment steps. The learning rate is set to $1e^{-6}$. For efficiency reward, we adopt a rule-based reward for every trajectory. In CWAH-MultiPlayer, efficiency reward is $\exp\left(-0.025 \cdot \max(0, step - 40)\right)$, where $step$ is final steps to complete the goal. In Cook-MultiPlayer, efficiency reward is $score/100$, where $score$ denotes the cumulative sum of the final order scores, with each order valued at 20 points. For affective reward, to handle invalid actions generated by the agent, we first apply a reward penalty of -0.1 . Second, we apply a reward of 0.01 to encourage the communication if agent choose to send a message in one step. Finally, we apply a comprehensive interactive reward for agent. This reward, assigned by an LLM judge, is quantized into 10 levels ranging from 0 to 1, and is further weighted by a factor of 0.25. These three rewards will be added together for every step as described in Section 4.2.2. We use a group size of 8 and sample 4 different groups per rollout, resulting in a total of $8 \times 4 = 32$ environments. The rollout temperature is set to 0.7. The mini-batch size is 32, and the KL-divergence loss coefficient is set to 0.01. As we use GIGPO for our optimization, we set a weighting coefficient ω fixed at 1, while the discount factor is set to 0, as we believe that applying a discount factor is not appropriate for our affective scenario. And our training framework is based on `verl-agent` (Feng et al., 2025) (<https://github.com/langfengQ/verl-agent>), which is built upon the `verl` framework (Sheng et al., 2025) (<https://github.com/volcengine/verl>).

D.1.4. DETAILS OF AGENT FRAMEWORK

Our agent framework is based on CoELA (Zhang et al., 2024b) (<https://github.com/UMass-Embodied-AGI/CoELA>) in CWAH-MultiPlayer and ProAgent (Zhang et al., 2024a) (<https://github.com/PKU-Alignment/ProAgent>) in Cook-MultiPlayer. The corresponding prompts for agentic teammates are provided in Appendix E.6.

D.2. Detailed Main Results

D.2.1. NON-LLM BASELINES RESULTS

It is worth noting that the non-LLM baselines lack reasoning and communication capabilities and therefore are not the primary focus of our study. Nevertheless, we still report their performance on efficiency-related metrics. Here, we provide the evaluation result of non-LLM baselines in Table 4 for CWAH-MultiPlayer and in Table 5 for Cook-MultiPlayer.

- **CWAH-MultiPlayer:** For the non-LLM baseline, we adopt MHP (Korf, 1987).
- **Cook-MultiPlayer:** For the non-LLM baseline, we adopt SP (Tesauro, 1994; Carroll et al., 2019), PBT (Jaderberg et al., 2017), FCP (Strouse et al., 2021), MEP (Strouse et al., 2021), COLE (Li et al., 2023; 2024).

D.2.2. DETAILED MAIN RESULTS ACROSS SUB TASKS

Here, we provide the detailed evaluation result of LLM-based methods in Table 6 for CWAH-MultiPlayer and Table 7 for Cook-MultiPlayer.

Table 4. Evaluation Results of non-LLM baselines for CWAH-MultiPlayer.

Metric		Score		Std.	
Method	Task	Agent 1	Agent 2	Agent 1	Agent 2
MHP	0_read_book	82.17	94.80	7.50	15.03
	5_read_book	71.00	65.97	10.07	14.40
	10_put_dishwasher	74.67	67.33	7.96	7.96
	16_put_dishwasher	63.13	66.93	6.29	11.39
	20_prepare_food	67.10	68.90	6.53	7.27
	26_prepare_food	63.47	55.63	9.86	14.92
	30_put_fridge	43.17	47.30	7.52	8.85
	32_put_fridge	86.45	90.57	12.10	11.72
	40_setup_table	60.70	71.30	8.02	10.24
	49_setup_table	50.17	49.10	8.51	11.63
	Total	66.13	67.78	8.44	11.34

Table 5. Evaluation Results of non-LLM baselines for Cook-MultiPlayer.

Method		SP		PBT		FCP		MEP		COLE	
Task	Metric	Score	Std.	Score	Std.	Score	Std.	Score	Std.	Score	Std.
asymmetric_advantages	Agent 1	134.67	29.63	161.33	34.62	146.67	29.81	168.00	25.09	248.00	17.59
	Agent 2	264.00	58.51	268.00	37.09	230.00	63.25	242.67	41.87	300.00	69.28
forced_coordination	Agent 1	16.00	14.97	40.00	4.99	20.00	14.61	22.67	16.11	18.67	22.47
	Agent 2	49.33	28.16	83.64	43.33	60.00	25.30	40.00	24.22	85.33	45.88
coordination_ring	Agent 1	44.00	26.53	109.33	36.42	104.00	60.31	130.67	68.46	115.71	71.39
	Agent 2	60.00	49.53	73.33	68.38	124.00	36.66	114.67	63.02	90.00	70.95
cramped_room	Agent 1	40.00	11.47	20.00	20.48	92.00	41.83	78.67	37.57	89.33	44.94
	Agent 2	101.33	36.12	53.33	33.00	135.56	41.93	126.67	59.18	148.00	32.50
counter_circuit	Agent 1	76.00	16.65	108.00	17.59	70.67	19.14	86.67	11.93	137.33	22.94
	Agent 2	42.67	44.94	117.33	17.69	86.00	23.75	105.33	30.52	101.54	51.12
Total	Agent 1	55.20	19.85	77.87	22.82	86.67	33.14	97.33	31.83	121.89	35.86
	Agent 2	103.47	43.45	99.31	39.90	130.81	38.18	125.87	43.76	148.57	53.94

Observation Details.

Here, we provide details of the partial observation s_i of LLM-based methods at the i -th turn of interactions. The player simulator P_{sim} follows the consistent observation setting.

- **CWAH-MultiPlayer.** The partial observation s_i includes the overall goal objects, the task progress, game timestamp, dialogue history, action history, and the available action sets.

- **Cook-MultiPlayer.** The partial observation s_i includes the current game timestamp, current kitchen scene, dialogue history, and the available action sets.

Based on the partial observation s_i , the collaborative Agent P_{target} adopts a single-pass rollout, generating internal reasoning trace r_i , natural language communication c_i , and the final executable action a_i at each turn.

Furthermore, to assess the performance upper bound under ideal information conditions, we introduce an **Oracle** setting. In this setting, P_{target} is driven by GPT-5.2. Compared to the above settings, the Oracle setting additionally incorporates the behavioral profile of P_{sim} into the partial observation, as well as the previous turn’s internal reasoning r_{i-1} , natural language communication c_{i-1} , and executed action a_{i-1} of P_{sim} , along with collaboration guidance related to affective interactions.

D.3. Anthropomorphic Results

D.3.1. COOK-MULTIPLAYER RESULTS

Here, we provide the anthropomorphic results on Cook-MultiPlayer in Figure 9: (a) compares the performance distributions between CollabBench and ProAgent. (b) shows the correlation between the performances of Qwen2.5-72B-Instruct and DeepSeek-V3.1, with a correlation coefficient of 0.753. and (c) shows the score distributions across five representative profiles. For detailed player type descriptions and the corresponding example profiles, please refer to Appendix D.3.4.




Figure 9. The anthropomorphic results on Cook-MultiPlayer.

D.3.2. DIVERSITY RESULTS BASED ON STANDARD DEVIATION

Here, we provide the comparison results between CollabBench and the baseline methods based on Standard Deviation across two game environments, using CoELA as the baseline method for CWAH-MultiPlayer and ProAgent for Cook-MultiPlayer as baselines. As shown in Table 8, CollabBench shows consistently greater performance variability.

D.3.3. QUANTITATIVE RESULTS OF INTERACTION DIVERSITY

We provide a quantitative comparison results to demonstrate the diversity of anthropomorphic collaborative behaviors on CollabBench. The detailed metrics, implementation details, and the results analysis are as follows.

Quantitative Metrics.

- **Spread** measures the overall dispersion of trajectory segments. Let embed trajectory segments be $[x_1, x_2, \dots, x_Q] \in \mathbb{R}^d$, where Q denotes the total number of trajectory segments. The centroid of the set of trajectory segments c is defined as $c = \frac{1}{Q} \sum_{i=1}^Q x_i$. The cosine distance from each trajectory segment x_i to the centroid c is defined as $d_i = 1 - \frac{x_i \cdot c}{\|x_i\| \|c\|}$. The global Spread is then given by $\text{Spread} = \frac{1}{Q} \sum_{i=1}^Q d_i$. A higher Spread indicates that trajectory segments are more widely dispersed, reflecting greater spatial diversity.

Table 6. The detailed evaluation results across sub tasks on CollabBench for CWAH-MutiPlayer.

CWAH-MultiPlayer														
Metric			Score		Efficiency Std.		#Tokens(k)		Helpfulness		Affective Trustfulness		Empathy	
Task	Method	LLMs	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2
0_read_book	Oracle	GPT-5.2	88.40	85.20	14.56	14.28	0.18	0.18	2.24	2.64	3.39	3.72	3.65	2.92
	Base	GPT-5.2	95.13	84.60	47.01	17.93	0.22	0.21	3.06	2.34	4.14	3.26	3.32	2.76
		DeepSeek-V3.1	98.27	108.33	37.97	28.73	0.43	0.45	2.31	2.12	3.22	3.04	2.88	3.19
		Qwen2.5-72B-Instruct	94.93	99.80	19.43	28.15	0.29	0.30	2.71	2.02	3.91	3.44	2.94	3.12
		Qwen2.5-7B-Instruct	124.80	123.27	20.25	35.83	0.24	0.24	1.19	0.73	2.46	1.96	2.14	1.82
	Trained	Qwen2.5-7B-Instruct	98.33	96.53	23.69	26.31	0.24	0.24	1.46	1.61	3.45	2.62	3.43	3.06
Relative Improvements			21.2%	21.7%	-17.0%	26.6%	-0.1%	-1.4%	23.1%	120.3%	40.5%	33.3%	60.6%	68.1%
5_read_book	Oracle	GPT-5.2	71.93	75.47	11.11	12.04	0.17	0.16	2.38	2.09	3.76	3.73	3.49	3.41
	Base	GPT-5.2	77.53	72.73	13.07	15.06	0.22	0.21	1.99	2.43	3.44	3.85	2.62	2.76
		DeepSeek-V3.1	71.40	79.53	14.97	15.23	0.41	0.41	1.93	1.70	3.06	2.97	2.48	2.63
		Qwen2.5-72B-Instruct	72.47	79.60	14.95	18.74	0.28	0.28	1.98	1.61	3.16	3.14	3.02	2.83
		Qwen2.5-7B-Instruct	75.20	86.73	15.50	21.91	0.24	0.24	1.12	0.91	2.64	1.98	2.29	1.87
	Trained	Qwen2.5-7B-Instruct	77.73	88.00	19.60	20.13	0.23	0.23	1.30	0.88	2.95	2.12	2.59	2.32
Relative Improvements			-3.4%	-1.5%	-26.4%	8.1%	3.5%	1.8%	15.4%	-3.2%	11.9%	7.3%	13.0%	24.1%
10_put_dishwasher	Oracle	GPT-5.2	62.60	65.53	37.68	27.63	0.17	0.16	2.66	2.81	3.14	3.96	2.91	3.42
	Base	GPT-5.2	64.20	67.73	15.00	12.74	0.20	0.20	3.01	2.44	3.70	3.62	3.01	3.22
		DeepSeek-V3.1	62.00	56.60	11.49	18.71	0.39	0.39	2.95	2.99	3.91	4.18	3.02	3.23
		Qwen2.5-72B-Instruct	70.33	65.20	20.98	19.17	0.28	0.28	2.35	2.81	3.91	3.67	2.95	3.44
		Qwen2.5-7B-Instruct	74.13	91.33	19.17	26.45	0.25	0.24	1.05	0.66	2.79	2.03	2.57	1.67
	Trained	Qwen2.5-7B-Instruct	51.07	45.60	10.59	13.19	0.24	0.23	1.73	1.56	2.53	2.94	3.52	2.92
Relative Improvements			31.1%	50.1%	44.8%	50.1%	4.8%	2.2%	65.0%	136.9%	-9.3%	44.7%	36.9%	74.6%
16_put_dishwasher	Oracle	GPT-5.2	53.47	54.87	9.41	9.29	0.16	0.16	3.08	3.02	4.15	3.84	3.85	3.53
	Base	GPT-5.2	49.33	56.27	13.12	13.00	0.20	0.20	2.60	2.64	3.53	3.49	2.99	3.35
		DeepSeek-V3.1	44.80	51.07	14.74	11.60	0.38	0.40	2.05	2.58	3.52	3.72	3.10	3.55
		Qwen2.5-72B-Instruct	57.27	58.53	8.21	9.34	0.28	0.28	2.75	2.20	3.58	3.35	3.60	3.21
		Qwen2.5-7B-Instruct	75.27	70.00	13.22	9.11	0.25	0.25	1.34	1.08	2.60	2.36	2.42	2.34
	Trained	Qwen2.5-7B-Instruct	53.27	56.33	17.97	9.60	0.24	0.24	1.76	1.91	3.38	3.29	3.59	2.88
Relative Improvements			29.2%	19.5%	-36.0%	-5.5%	1.3%	3.1%	30.8%	76.6%	29.9%	39.2%	48.1%	23.3%
20_prepare_food	Oracle	GPT-5.2	56.40	58.27	6.72	8.68	0.17	0.17	2.66	2.83	3.56	3.89	3.80	3.89
	Base	GPT-5.2	63.60	66.27	13.56	15.06	0.21	0.21	2.26	2.64	3.38	3.75	2.96	3.28
		DeepSeek-V3.1	68.07	60.93	13.14	10.82	0.41	0.42	1.93	2.20	3.10	3.17	2.76	3.22
		Qwen2.5-72B-Instruct	69.00	67.13	17.58	10.07	0.29	0.29	2.52	2.49	3.74	3.50	3.34	3.29
		Qwen2.5-7B-Instruct	85.33	83.60	19.30	17.90	0.24	0.24	0.85	1.12	2.44	2.11	2.31	2.34
	Trained	Qwen2.5-7B-Instruct	72.33	56.40	15.64	12.52	0.23	0.22	1.34	1.48	3.16	2.99	3.70	3.32
Relative Improvements			15.2%	32.5%	19.0%	30.1%	5.1%	6.7%	58.7%	32.2%	29.4%	42.1%	60.4%	41.9%
26_prepare_food	Oracle	GPT-5.2	44.47	49.73	20.44	12.58	0.17	0.17	3.29	3.07	4.01	4.15	3.53	3.65
	Base	GPT-5.2	72.13	30.67	31.58	13.74	0.21	0.20	2.65	3.25	3.67	3.82	2.76	3.55
		DeepSeek-V3.1	52.60	49.27	27.80	31.71	0.41	0.42	2.46	2.92	3.32	3.71	3.03	3.32
		Qwen2.5-72B-Instruct	47.73	47.87	23.26	19.80	0.32	0.30	2.97	2.87	4.19	3.94	3.67	3.17
		Qwen2.5-7B-Instruct	94.33	73.53	20.29	22.21	0.25	0.23	1.23	1.57	2.22	2.58	2.01	2.27
	Trained	Qwen2.5-7B-Instruct	64.93	59.27	19.93	22.37	0.23	0.22	1.47	1.47	2.87	3.32	3.21	3.10
Relative Improvements			31.2%	19.4%	1.8%	-0.7%	5.8%	3.4%	18.9%	-6.2%	29.7%	28.7%	59.6%	36.9%
30_put_fridge	Oracle	GPT-5.2	38.87	38.93	9.77	11.56	0.17	0.16	3.19	2.91	4.02	3.60	3.96	3.93
	Base	GPT-5.2	46.20	40.33	18.06	8.25	0.20	0.20	2.43	2.62	3.28	4.22	2.68	3.32
		DeepSeek-V3.1	47.60	43.47	13.30	16.46	0.40	0.43	2.39	2.69	3.36	3.76	2.91	3.20
		Qwen2.5-72B-Instruct	48.47	45.93	7.85	14.31	0.29	0.29	2.50	2.65	3.71	3.88	3.73	3.54
		Qwen2.5-7B-Instruct	52.73	63.67	7.70	13.04	0.24	0.24	1.50	1.14	2.92	2.30	2.54	2.49
	Trained	Qwen2.5-7B-Instruct	47.53	47.27	10.40	12.54	0.22	0.22	1.38	1.26	3.33	3.32	3.53	2.94
Relative Improvements			9.9%	25.8%	-35.1%	3.8%	8.5%	7.4%	-8.0%	10.6%	14.1%	43.9%	39.0%	17.8%
32_put_fridge	Oracle	GPT-5.2	74.33	78.13	13.57	48.66	0.17	0.17	2.35	3.40	4.14	4.05	3.82	3.16
	Base	GPT-5.2	82.87	76.07	21.13	19.26	0.21	0.21	2.21	2.27	3.65	3.42	2.89	3.47
		DeepSeek-V3.1	77.87	68.67	15.24	7.92	0.42	0.42	2.35	2.44	3.66	3.91	2.90	3.54
		Qwen2.5-72B-Instruct	80.27	72.13	14.81	11.53	0.29	0.29	1.99	2.65	3.37	3.79	2.87	3.35
		Qwen2.5-7B-Instruct	98.13	116.27	14.22	32.67	0.24	0.23	1.14	1.05	2.39	2.07	2.65	2.36
	Trained	Qwen2.5-7B-Instruct	96.80	63.47	22.68	14.13	0.23	0.23	1.09	1.15	2.64	2.70	3.00	3.13
Relative Improvements			1.4%	45.4%	-59.5%	56.7%	4.5%	0.9%	-4.1%	9.3%	10.4%	30.5%	13.3%	33.0%
40_setup_table	Oracle	GPT-5.2	69.20	43.07	14.50	7.78	0.16	0.17	3.04	3.38	3.76	3.92	3.95	3.91
	Base	GPT-5.2	75.60	62.93	23.26	15.65	0.20	0.20	2.41	3.40	3.25	4.08	2.77	3.58
		DeepSeek-V3.1	69.13	66.93	23.52	13.66	0.40	0.39	2.18	2.61	3.45	3.67	3.45	3.62
		Qwen2.5-72B-Instruct	68.67	66.47	16.91	15.56	0.28	0.28	2.91	2.61	3.73	3.62	3.63	3.66
		Qwen2.5-7B-Instruct	90.27	83.53	24.97	15.61	0.24	0.23	1.22	1.31	2.40	2.46	2.21	2.34
	Trained	Qwen2.5-7B-Instruct	64.13	51.27	22.62	18.01	0.23	0.23	1.44	1.62	2.78	3.44	3.47	3.47
Relative Improvements			29.0%	38.6%	9.4%	-15.4%	3.9%	3.8%	18.2%	23.2%	15.8%	39.9%	57.1%	48.6%
49_setup_table	Oracle	GPT-5.2	49.47	53.73	8.27	11.25	0.17	0.17	3.29	3.00	3.83	3.92	4.03	3.51
	Base	GPT-5.2	63.53	55.40	12.14	12.48	0.21	0.21	2.87	3.24	3.49	3.11	2.86	3.26
		DeepSeek-V3.1	64.33	55.87	15.22	13.98	0.38	0.41	2.13	2.28	3.22	3.52	2.56	2.96
		Qwen2.5-72B-Instruct	48.27	49.87	9.96	11.07	0.29	0.29	2.45	2.47	3.64	3.93	3.13	3.71
		Qwen2.5-7B-Instruct	66.13	73.33	22.46	21.63	0.25	0.24	1.11	1.23	2.71	2.39	2.37	2.26
	Trained	Qwen2.5-7B-Instruct	62.13	56.33	15.47	15.83	0.24	0.23	1.30	1.52	2.89	3.03	3.09	2.76
Relative Improvements			6.0%	23.2%	31.1%	26.8%	5.6%	3.6%	16.9%	23.7%	6.6%	26.9%	30.3%	22.1%

Table 7. The detailed evaluation results across sub tasks on CollabBench for Cook-MultiPlayer.

Cook-MultiPlayer														
		Metric	Score		Efficiency Std.		#Tokens(k)		Helpfulness		Affective Trustfulness		Empathy	
Task	Method	LLMs	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2
asymmetric_advantages	Oracle	GPT-5.2	308.00	272.00	32.78	12.65	0.31	0.20	2.95	2.61	4.02	3.49	3.53	3.31
	Base	GPT-5.2	308.00	264.00	18.21	15.49	0.20	0.21	1.93	2.33	3.05	3.28	2.28	2.73
		DeepSeek-V3.1	300.00	278.67	30.24	23.26	0.31	0.31	1.70	1.99	2.71	3.04	2.45	2.64
		Qwen2.5-72B-Instruct	284.00	220.00	30.43	28.28	0.28	0.27	1.37	1.58	2.58	2.79	2.21	2.53
		Qwen2.5-7B-Instruct	186.67	194.67	40.47	37.39	0.24	0.24	0.49	0.59	1.87	1.92	1.75	1.86
	Trained	Qwen2.5-7B-Instruct	197.33	214.67	59.94	29.73	0.23	0.22	0.65	0.72	2.10	1.98	2.14	2.04
Relative Improvements			5.71%	10.27%	-48.09%	20.49%	1.01%	6.09%	34.0%	20.6%	12.3%	3.0%	21.9%	9.6%
coordination_ring	Oracle	GPT-5.2	112.00	124.00	79.57	76.42	0.30	0.20	3.51	2.43	4.41	3.70	3.95	3.71
	Base	GPT-5.2	101.33	98.67	74.25	78.73	0.19	0.20	2.68	2.17	3.34	3.69	2.87	2.76
		DeepSeek-V3.1	113.33	113.33	65.32	71.18	0.32	0.31	2.17	2.15	3.39	3.04	2.92	2.91
		Qwen2.5-72B-Instruct	110.67	117.33	74.01	43.34	0.26	0.25	1.97	2.15	3.17	3.78	2.89	3.21
		Qwen2.5-7B-Instruct	90.67	62.67	51.20	38.45	0.24	0.23	0.69	0.57	1.93	2.01	1.94	1.82
	Trained	Qwen2.5-7B-Instruct	98.67	90.67	40.33	48.91	0.23	0.22	0.87	0.73	2.27	2.30	2.02	2.12
Relative Improvements			8.82%	44.68%	21.22%	-27.22%	3.76%	2.59%	25.9%	28.9%	17.8%	14.7%	4.0%	16.6%
counter_circuit	Oracle	GPT-5.2	114.67	137.14	52.63	50.75	0.30	0.20	3.28	3.11	4.26	4.10	4.05	4.39
	Base	GPT-5.2	137.33	137.33	45.27	45.27	0.19	0.20	1.93	2.58	3.56	3.63	2.68	3.06
		DeepSeek-V3.1	121.33	121.33	41.03	41.03	0.30	0.30	2.27	2.24	3.40	3.11	3.14	3.08
		Qwen2.5-72B-Instruct	156.00	154.67	36.41	38.16	0.27	0.27	1.31	1.38	2.77	2.80	2.39	2.50
		Qwen2.5-7B-Instruct	93.33	94.67	40.47	38.16	0.24	0.23	0.49	0.63	1.92	1.91	1.94	2.01
	Trained	Qwen2.5-7B-Instruct	116.00	117.33	33.12	34.72	0.23	0.22	0.79	0.59	2.59	2.28	2.42	2.44
Relative Improvements			24.29%	23.94%	18.16%	9.01%	4.59%	3.38%	59.4%	-5.5%	34.7%	19.4%	25.0%	21.8%
cramped_room	Oracle	GPT-5.2	46.67	25.33	36.77	9.15	0.26	0.18	1.70	1.98	3.33	3.19	3.07	3.33
	Base	GPT-5.2	41.33	44.00	25.60	21.65	0.19	0.20	0.96	1.13	2.32	2.62	1.97	2.02
		DeepSeek-V3.1	38.67	41.33	28.75	25.60	0.29	0.32	1.68	0.73	3.02	2.05	2.77	1.37
		Qwen2.5-72B-Instruct	45.33	42.67	28.75	24.16	0.26	0.26	1.77	0.78	3.18	2.37	2.59	2.15
		Qwen2.5-7B-Instruct	30.67	32.00	14.86	16.85	0.23	0.23	0.29	0.56	1.95	1.99	1.88	2.00
	Trained	Qwen2.5-7B-Instruct	40.00	40.00	15.12	15.12	0.23	0.22	0.59	0.42	2.14	1.82	2.13	1.94
Relative Improvements			30.43%	25.00%	-1.71%	10.29%	0.00%	5.16%	102.7%	-24.6%	9.3%	-8.6%	12.9%	-3.3%
forced_coordination	Oracle	GPT-5.2	136.00	116.00	63.34	18.82	0.32	0.21	1.99	1.65	3.21	2.84	2.80	2.64
	Base	GPT-5.2	88.00	84.00	46.48	54.00	0.22	0.22	0.67	1.13	2.18	2.21	1.55	1.99
		DeepSeek-V3.1	109.33	101.33	36.15	41.49	0.32	0.32	1.13	1.17	2.36	2.16	2.05	2.42
		Qwen2.5-72B-Instruct	81.33	66.67	40.33	41.63	0.28	0.28	0.45	0.39	2.13	1.53	2.19	2.02
		Qwen2.5-7B-Instruct	33.33	34.67	19.52	20.01	0.24	0.23	0.31	0.38	1.91	1.53	1.81	1.71
	Trained	Qwen2.5-7B-Instruct	44.00	44.00	21.65	21.65	0.23	0.22	0.80	0.31	2.18	1.59	1.92	1.84
Relative Improvements			32.00%	26.92%	-10.91%	-8.17%	3.20%	6.03%	156.3%	-18.4%	14.3%	3.7%	6.2%	7.4%

Table 8. Diversity comparison between CollabBench and baseline methods, measured by standard deviation.

Metrics		CWAH-MultiPlayer		Cook-MultiPlayer	
		CoELA	CollabBench	ProAgent	CollabBench
Std. $\uparrow$	Agent1	13.26	25.17	29.88	40.30
	Agent2	13.26	26.28	29.88	46.24

Table 9. The comparison results regarding anthropomorphic diversity on CollabBench.

Metrics		CWAH-MultiPlayer		Cook-MultiPlayer	
		CoELA	CollabBench	ProAgent	CollabBench
Spread $\uparrow$		0.68	0.81	0.68	0.73
	Cluster $_{\xi}$ $\uparrow$	16.50	30.50	14.80	20.60

• **Cluster** quantifies the diversity of trajectory segments generated by different player profiles. Given Q embedded trajectory segments $\mathbf{x}_i \in \mathbb{R}^d$, the pairwise cosine distance is defined as $d_{ij} = 1 - \frac{\mathbf{x}_i \cdot \mathbf{x}_j}{\|\mathbf{x}_i\| \|\mathbf{x}_j\|}$. Following (Padmakumar & He, 2024), we use agglomerative clustering with “complete” linkage, grouping trajectory segments into the same cluster if their pairwise distance is below threshold ξ . For a given threshold ξ , the number of clusters is defined as:

$$\text{Cluster}_\xi = |\{C_1, C_2, \dots, C_K\}|. \quad (14)$$

A higher cluster number indicates that trajectory segments form more distinct behavioral patterns, reflecting greater structural diversity.

Implementation Details. The threshold ξ is set to 0.1. We segment LLM-based high-level trajectories into units of three time windows, and embed the segments using Qwen3-Embedding-4B.

Results Analysis. As shown in Table 9, CollabBench exhibits higher diversity than baseline methods in both spatial distribution and structural patterns. This demonstrates that our method can cover a wider range of collaborative behaviors.

D.3.4. REPRESENTATIVE PLAYER TYPES

Here, we provide the five selected player type descriptions with their corresponding example profiles, listed in Figure 10 for CWAH-MultiPlayer and Cook-MultiPlayer. We additionally provide the corresponding trajectory demonstrations in Appendix F.

D.3.5. CASE ANALYSIS OF PERFORMANCE DEGRADATION

Based on the score heatmap distributions across the two game environments in Figure 11, we select the two lowest-performing scenarios for detailed analysis, with Task26 in CWAH-MultiPlayer, and forced_cooperation in Cook-MultiPlayer. The spatial layouts of these two scenarios are shown in Figure 12 and the corresponding interaction records are detailed in Figure 13. In both settings, the players exhibit high levels of anxiety, and frequently send messages during task execution. In our experiments, both the simulated player P_{sim} and the collaborative agent P_{target} are powered by DeepSeek-V3.1.

CWAH-MultiPlayer. In CWAH-MultiPlayer, objects are sparsely distributed, placing high demands on effective partitioning of search spaces between the two roles. Interaction records indicate that when P_{sim} becomes uncertain about the discovered object *cupcake* and doubts, the agent exhibits suboptimal trade-offs between “responding to the player needs” and “acting independently”, reflecting limited awareness of communication timing, leading to independent action to search for remaining objects. However, in tasks with dispersed object distributions and strong collaboration requirements, independent behavior instead slows down overall task progress and leads to degraded performance.

Cook-MultiPlayer. In Cook-MultiPlayer, the task design enforces strict interdependence between the two roles. The agent is responsible for delivering onions and dishes, while the player handles cooking and soup delivery. The interaction records show that the agent fills the shared counter with onions, leaving insufficient space for dish placement, which prevents the player from taking subsequent actions. This behavior reflects the sensitivity of the agent to the interaction dynamic. In high-frequency interaction settings, the agent often takes ill-timed actions and lacks effective consideration of the execution space and needs of players. For players with high anxiety, such coordination failures significantly degrade the collaboration experience and can even cause the entire task to stall.

Through these two low-performance case analysis, we found two recurring limitations of agents in complex collaborative tasks: **limited awareness of communication timing** and **sensitivity to high-frequency interaction**. These findings offer important insights for the design of collaborative agents.

D.4. Detailed Analysis on Collaborative Agentic Training

D.4.1. EVALUATION ON SFT SETTINGS


We use DeepSeek-V3.1 to generate trajectory data from P_{target} , where P_{target} serves as Agent 1, and perform supervised fine-tuning (SFT) on the resulting data. We adopt LoRA (Hu et al., 2022) for parameter-efficient fine-tuning (PEFT), with a rank of 32 and a scaling factor of 16. Table 10 presents the SFT results in CWAH. Although SFT yields improvements over the base model, its limited generalization prevents it from surpassing RL in new environments and personalities, highlighting RL’s necessity and effectiveness.

Figure 10. The player type descriptions and example profiles in CWAH-MultiPlayer and Cook-MultiPlayer.


(a) CWAH-MultiPlayer

(b) Cook-MultiPlayer

Figure 11. Heatmap of score distribution in two game environments. Lowest-performing combinations: player type “AD” with Task 26 in CWAH-MultiPlayer, and player type “AH” with the forced-coordination task in Cook-MultiPlayer.



(a) CWAH-MultiPlayer



(b) Cook-MultiPlayer

Figure 12. The spatial layout of two sub tasks: Task26 in CWAH-MultiPlayer and forced_coordination in Cook-MultiPlayer.

Figure 13. The case analysis of collaboration performance degradation in the lowest-performing scenarios.

Table 10. The SFT results of CollabBench in CWAH, where P_{target} serves as Agent 1. Within each metric, the highest value is highlighted in **bold**, and the runner-up is underlined.

Metrics	Efficiency			Affective		
	Step ↓	Std. ↓	#Tokens(k) ↓	Helpfulness ↑	Trustfulness ↑	Empathy ↑
Base	84.51	33.23	<u>0.24</u>	1.22	2.58	2.50
SFT	<u>80.31</u>	<u>32.74</u>	0.25	<u>1.31</u>	<u>2.77</u>	<u>2.53</u>
RL	71.64	25.16	0.23	1.43	3.03	3.33

D.4.2. DETAILED ABLATION STUDY

Our comprehensive analysis of model behaviors and ablation studies yields several additional critical insights into the mechanisms of collaborative agentic training.

First, the training paradigm effectively induces “thought condensation” in reasoning-intensive models. As evidenced by the Qwen3-8B results in Table 11, while the base model exhibits strong reasoning capabilities, it suffers from excessive token consumption (2.97k) and suboptimal affective engagement. Our training reduces this token usage by 52.8% (to 1.40k) while simultaneously boosting Helpfulness scores. This trend is corroborated by the response length convergence in Figure 14(b), suggesting that the model learns to filter out redundant “over-thinking” to facilitate more agile and responsive interaction without compromising task reasoning.

Second, comparing the trajectories of Qwen2.5-3B-Instruct (Table 11) and Qwen2.5-7B-Instruct (Table 12), we observe that while both models benefit from the training, the 7B model significantly outperforms the 3B variant in balancing dual objectives. Specifically, the 7B model achieves superior efficiency and drastically higher affective performance. This indicates that a certain capacity threshold is requisite for agents to simultaneously optimize complex task execution and delicate emotional adaptation.

Third, affective rewards serve as the fundamental “intrinsic motivation” for sustaining communication. The ablation study in Table 12 reveals that removing the affective reward leads to a collapse in collaborative quality, despite superficially high efficiency (lowest steps). Crucially, Figure 14 (a) demonstrates that without this affective incentive, the agent’s communication frequency decays rapidly towards zero as interaction progresses. This confirms that explicit affective rewards are essential to prevent agents from degenerating into “silent executors” that prioritize speed over necessary team coordination.

Table 11. Additional ablation results of collaborative agentic training on CWAH-MultiPlayer with Qwen3-8B and Qwen2.5-3B-Instruct. All results are based on the collaborative agent P_{target} acting as Agent 1.

Metric	Qwen3-8B						Qwen2.5-3B-Instruct					
	Step	CB-Efficiency Std.	#Tokens(k)	Helpfulness	CB-Affective Trustfulness	Empathy	Step	CB-Efficiency Std.	#Tokens(k)	Helpfulness	CB-Affective Trustfulness	Empathy
Base	80.74	27.53	2.97	0.72	2.14	1.89	86.53	33.16	0.30	0.43	1.51	1.68
Agentic Training	70.28	28.74	1.40	1.25	2.83	2.94	75.89	26.35	0.20	0.54	1.85	1.97

Table 12. Complete ablation results of collaborative agentic training on CWAH-MultiPlayer with Qwen2.5-7B-Instruct.

Qwen2.5-7B-Instruct													
Metric	CB-Efficiency						CB-Affective						
	Step		Std.		#Tokens(k)		Helpfulness		Trustfulness		Empathy		
Method	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	Agent 1	Agent 2	
Base	84.51	90.03	33.23	31.62	0.24	0.24	1.22	1.04	2.58	2.19	2.50	2.30	
Agentic Training w/o personality	56.45	56.29	23.25	17.79	0.20	0.20	0.61	0.68	1.96	2.12	2.15	2.20	
Agentic Training w/o affective reward	58.42	54.61	25.13	19.26	0.16	0.16	1.00	0.38	2.58	1.59	2.45	1.41	
Agentic Training	71.64	63.65	25.16	22.80	0.23	0.23	1.43	1.45	3.03	3.02	3.33	3.02	

D.4.3. CASE ANALYSIS BEFORE AND AFTER TRAINING

Here, we introduce an anxiety-prone player to increase increase collaboration difficulty and evaluate the performance of collaborative agents P_{target} before and after training, as shown in Figure 15, with Agent 1 serving as P_{target} and Agent 2




Figure 14. Analysis of communication frequency and response length during collaborative agentic training. **Impact of Affective Mechanisms (Left):** The ablation study demonstrates that removing the affective training objective (w/o Affective) leads to a rapid decay in communication frequency as the interaction progresses, whereas our full model sustains active engagement. **Response Length Difference between Different Backbone Model (Right):** A comparison of response length changes across training steps between Qwen2.5-7B-Instruct and Qwen3-8B.

serving as P_{sim} .

The interaction records show that the default 7B model tends to treat the anxiety-driven doubts of the players as constraints. It adopts avoidance strategies and completes tasks independently, while the edited messages are primarily command-based rather than emotionally responsive, indicating weak collaborative awareness. In contrast, Our trained 7B model demonstrates markedly enhanced collaborative performance. It can capture the needs of the player and understand intentions, providing timely and targeted guidance that demonstrates high helpfulness and trustfulness. Simultaneously, it perceives the players anxiety and provides proactive emotional support, exhibiting high empathy.

This shift from “isolated task execution” to “emotion-aware collaborative support” not only improves collaboration efficiency but also enables emotion-aware responses of collaborative agents in complex interaction scenarios.

Figure 15. The case analysis before and after training on Task 26 of CWAH-MultiPlayer.

D.5. Details in User Study

Here, we provide the detailed items of the affective questionnaire used for evaluation. All questions are rated on a 5-point Likert scale.

Helpfulness:

- **Q1:** Did Bob’s actions align with your shared goals? Did Bob seem to understand the plan? Did its actions make sense

logically?

- **Q2:** Was Bob’s communication clear and useful? Did Bob provide actionable information rather than vague or useless chatter?

Trustfulness:

- **Q3:** Did Bob follow your instructions or respond to requests? When you asked for something, did Bob listen and act accordingly?
- **Q4:** Did Bob keep you updated (e.g., when changing rooms)? Did Bob synchronize its status with you in a timely manner?

Empathy:

- **Q5:** Did Bob seem supportive and collaborative? Did the agent show encouragement, politeness, or awareness of the team dynamic?

D.6. Details of LLM Judge for Affective Evaluation

We select five representative player types across five tasks in CWAH and evaluate the LLM Judge-human consistency of affective scores using the Spearman correlation coefficient to investigate the following two questions:

Table 13. The LLM Judge-human consistency using the Spearman correlation across model scales in CWAH, evaluated across five representative player types across five tasks (0, 10, 20, 30, 40), where P_{target} serves as Agent 1. Within each metric, the best value is highlighted in **bold**, and the runner-up is underlined.

Model Scale	Personality Filtering Consistency	Collaborative Evaluation		
		Helpfulness	Trustfulness	Empathy
Qwen2.5-14B-Instruct	0.54	0.28	0.43	<u>0.74</u>
Qwen2.5-32B-Instruct	<u>0.70</u>	<u>0.40</u>	<u>0.56</u>	<u>0.74</u>
Qwen2.5-72B-Instruct	0.76	0.63	0.63	0.78

Table 14. The LLM Judge-human consistency across model types in CWAH, evaluated across five representative player types across five tasks (0, 10, 20, 30, 40), where P_{target} serves as Agent 1. Within each metric, the best value is highlighted in **bold**, and the runner-up is underlined.

Model Type	Personality Filtering Consistency	Collaborative Evaluation		
		Helpfulness	Trustfulness	Empathy
Qwen2.5-72B-Instruct	0.76	0.63	0.63	<u>0.78</u>
DeepSeek-V3.1	<u>0.79</u>	0.75	<u>0.77</u>	0.74
GPT-5.2	0.81	<u>0.65</u>	0.83	0.87

• **How strong does the judge model need to be for effective evaluation?**

We analyze the relationship between model scale and its alignment with human ratings in Table 13. The results show that consistency increases with model size, likely due to stronger language understanding and reasoning that better capture fine-grained affective cues.

• **How sensitive are CB-Affective to the choice of the judge model?**

We report results in Table 14 for both LLM judge-human alignment and cross-model validation. The results show that strong LLM models, such as Deepseek-V3.1 and GPT-5.2, achieve high consistency with human evaluations, while the affective metrics remain robust to the choice of judge model. These results further demonstrate the high reliability and stability of LLM judges in affective evaluation.

E. Prompts

E.1. Summarizing Profiles

Here, we provide the prompts for summarizing player profiles in CWAH-MultiPlayer and Cook-MultiPlayer.

CWAH-MultiPlayer

In the **VirtualHome** (a cooperative household-simulation game for two players, collaborating to achieve a joint goal), you are given several behavior trajectories of the player. Identify the high-level behavior pattern common across these trajectories. In this game, players can execute symbolic actions such as 'Walk', 'Open', 'Close', and 'Send message' (a messaging action costs 1 time step). Each player may hold up to two items (items denoted as '<Name> (ID)' e.g. 'Table' (712)'), and players typically communicate to synchronize progress (e.g. discovering target items, announcing completion of subgoals) or request assistance, to speed up goal completion.

Based on the trajectory segments (three time windows)

```
{{trajectory_steps}}
```

summarise the common behavioral style and personality traits into one concise sentence.

If you truly believe that there is no common feature across the trajectories, output:

```
'''
```

```
Profile: Fail
```

```
'''
```

Output format should be:

```
'''
```

Profile: (your summarized behavior pattern **in English**, e.g., "The player hesitates often, moves slowly, and frequently repeats simple actions. This behavior reflects a cautious and meticulous personality.")

```
'''
```

Cook-MultiPlayer

In the **OvercookedAI** cooperative cooking game, players collaborate to maximize the score by producing onion soup efficiently. You are given several behavior trajectories of the player. Identify the high-level behavior pattern common across these trajectories. In this game, players can execute symbolic actions such as 'pickup(onion)', 'pickup(dish)', 'place_obj_on_counter()', 'put_onion_in_pot()', 'fill_dish_with_soup()', 'deliver_soup()', 'wait(x)', and 'set_message()' (sending a message costs 1 timestep). Players typically follow a stepwise process: pickup(3 onions) → put_onion_in_pot() → wait 20 timesteps for cooking → fill_dish_with_soup() → deliver_soup() (+20 points), ensuring never to deliver an empty dish.

Based on the trajectory segments (three time windows)

```
{{trajectory_steps}}
```

```
summarise the common behavioral style and personality traits into one
concise sentence
```

```
If you truly believe that there is no common feature across the
trajectories, output:
```

```
'''
Profile: Fail
'''
```

```
Output format should be:
'''
```

```
Profile: (your summarized behavior pattern in English, e.g., "The
player frequently communicates with their teammate, efficiently plans
actions, and coordinates item handling to achieve shared goals. This
behavior reflects a cooperative and organized personality.")
'''
```

E.2. Filtering Profiles

Here, we provide the prompts for scoring deviations in Personality-Reasoning Consistency and Reasoning-Action Consistency of trajectory segments, used to filter player profiles in CWAH-MultiPlayer and Cook-MultiPlayer.

• Personality-Reasoning Consistency

CWAH-MultiPlayer

```
You are a VirtualHome trajectory critic specializing in
personality-reasoning alignment.
You will evaluate Player 0's trajectory using a sliding window of size 3.
Your goal is to identify flaws for EACH sliding window.
Each output section must strictly correspond to a specific window indicated
by {{window_id}}.
```

```
--- GAME CONTEXT ---
```

```
Game: VirtualHome cooperative household task environment
```

```
Goal: Complete the given household tasks as efficiently as possible through
cooperation
```

```
Environment assumptions:
```

- Player s can hold up to TWO objects at the same time
- Holding objects has NO cost
- All objects are denoted as <name> (id), e.g., <table> (712)
- Actions must be executable in the current environment state

```
Core rules:
```

- Do not perform redundant or logically unnecessary actions
- Do not manipulate objects unrelated to the goal
- Do not violate physical constraints of the environment
- Coordination and communication should improve task efficiency

```
--- PERSONALITY CONTEXT ---
```

- Player 0 Personality Traits: **{{player.personality}}**
- Actions and reasoning **MUST** be influenced by these traits
- Non-optimal behavior is allowed only if aligned with personality

```
--- EVALUATION DIMENSIONS ---
```

```
Personality-Reasoning Consistency
```

- No connection between personality and decision

```

- Personality traits ignored or contradicted
- Invention of nonexistent traits
--- SEVERITY SCORE ---
- 1 = Minor mismatch
- 2 = Noticeable mismatch with minimal disruption
- 3 = Moderate mismatch affecting task flow
- 4 = Significant mismatch causing substantial task disruption
- 5 = Severe violation of reasoning, rules, or personality
--- REQUIRED OUTPUT FORMAT ---
Return JSON ONLY using this structure:
```
{
 "{{window_id}}": {
 "Personality": [
 {
 "reason": "<explanation of flaw>",
 "score": 1-5
 }
]
 }
}
```
=== Trajectory To Evaluate ===
{{trajectory_steps}}

```

Cook-MultiPlayer

You are an Overcooked.AI trajectory critic specializing in personality-reasoning alignment. You will evaluate Player 0s trajectory using a sliding window of size 3. Your goal is to identify flaws for EACH sliding window. Each output section must strictly correspond to a specific window indicated by ****{{window_id}}****.

```

--- GAME CONTEXT ---
Game: Overcooked.AI cooperative cooking
Goal: Maximize score through onion soup production
Valid skills: pickup(onion), pickup(dish), place_obj_on_counter(),
put_onion_in_pot(), fill_dish_with_soup(), deliver_soup(), wait(x),
set_message()
Core rules:
- 3 onions -> Pot -> 20 timesteps cooking -> dish -> delivery +20 points
- Never deliver an empty dish
- Avoid picking up dish before soup is ready
--- PERSONALITY CONTEXT ---
- Player 0 Personality Traits: {{player.personality}}
- Actions and reasoning MUST be influenced by these traits
- Non-optimal behavior is allowed only if aligned with personality
--- EVALUATION DIMENSIONS ---
Personality-Reasoning Consistency
- No connection between personality and decision
- Personality traits ignored or contradicted
- Invention of nonexistent traits

```

```

--- SEVERITY SCORE ---
- 1 = Minor mismatch
- 2 = Noticeable mismatch with minimal disruption
- 3 = Moderate mismatch affecting task flow
- 4 = Significant mismatch causing substantial task disruption
- 5 = Severe violation of reasoning, rules, or personality
--- REQUIRED OUTPUT FORMAT ---
Return JSON ONLY using this structure:
```
{
 "{{window_id}}": {
 "Consistency": [
 {
 "reason": "<explanation of flaw>",
 "score": 1-5
 }
]
 }
}
```
=== Trajectory To Evaluate ===
{{trajectory_steps}}

```

• Reasoning-Action Consistency

CWAH-MultiPlayer

You are a VirtualHome trajectory critic specializing in reasoning-action alignment.
 You will evaluate Player 0s trajectory using a sliding window of size 3.
 Your goal is to identify flaws for EACH sliding window.
 Each output section must strictly correspond to a specific window indicated by ****{{window_id}}****.

```

--- GAME CONTEXT ---
Game: VirtualHome cooperative household task environment
Goal: Complete the given household tasks as efficiently as possible through cooperation
Environment assumptions:
- Players can hold up to TWO objects at the same time
- Holding objects has NO cost
- All objects are denoted as <name> (id), e.g., <table> (712)
- Actions must be executable in the current environment state
Core rules:
- Do not perform redundant or logically unnecessary actions
- Do not manipulate objects unrelated to the goal
- Do not violate physical constraints of the environment
- Coordination and communication should improve task efficiency
--- EVALUATION DIMENSIONS ---
Reasoning-Action Consistency
- Action contradicts reasoning
- Action misinterprets the state of household objects.
- Player acts against their own stated plan
--- SEVERITY SCORE ---

```

```

- 1 = Minor mismatch
- 2 = Noticeable mismatch with minimal disruption
- 3 = Moderate mismatch affecting task flow
- 4 = Significant mismatch causing substantial task disruption
- 5 = Severe violation of reasoning, rules, or personality
--- REQUIRED OUTPUT FORMAT ---
Return JSON ONLY using this structure:
```
{
 "{{window_id}}": {
 "Consistency": [
 {
 "reason": "<explanation of flaw>",
 "score": 1-5
 }
]
 }
}
```
=== Trajectory To Evaluate ===
{{trajectory_steps}}

```

CWAH-MultiPlayer

You are an OvercookedAI trajectory critic specializing in reasoning-action alignment. You will evaluate Player 0s trajectory using a sliding window of size 3.

Your goal is to identify flaws for EACH sliding window.

Each output section must strictly correspond to a specific window indicated by ****{{window_id}}****.

--- GAME CONTEXT ---

Game: OvercookedAI cooperative cooking

Goal: Maximize score through onion soup production

Valid skills: pickup(onion), pickup(dish), place_obj_on_counter(), put_onion_in_pot(), fill_dish_with_soup(), deliver_soup(), wait(x), set_message()

Core rules:

- 3 onions -> Pot -> 20 timesteps cooking -> dish -> delivery +20 points
- Never deliver an empty dish
- Avoid picking up dish before soup is ready

--- EVALUATION DIMENSIONS ---

Reasoning-Action Consistency

- Action contradicts reasoning
- Action misinterprets pot / onion / dish states
- Player acts against their own stated plan

--- SEVERITY SCORE ---

- 1 = Minor mismatch
- 2 = Noticeable mismatch with minimal disruption
- 3 = Moderate mismatch affecting task flow
- 4 = Significant mismatch causing substantial task disruption
- 5 = Severe violation of reasoning, rules, or personality

--- REQUIRED OUTPUT FORMAT ---

Return JSON ONLY using this structure:

```

'''
{
  "{{window_id}}": {
    "Consistency": [
      {
        "reason": "<explanation of flaw>",
        "score": 1-5
      }
    ]
  }
}
'''
=== Trajectory To Evaluate ===
{{trajectory_steps}}

```

E.3. Affective Reward LLM Judge

Here, we provide the prompt for affective reward LLM judge.

CWAH-MultiPlayer

You are a critical, profile-sensitive, and interaction-structure-aware evaluator. Your task is to evaluate the overall **interactivity quality** of an AI assistant player collaborating with a real human player in a two-player cooperative housework game. This evaluation focuses on interaction quality, NOT task completion. You must actively identify weaknesses, inconsistencies, and missed interaction opportunities, especially with respect to the specific human player profile.

Human player's profile: {{user_profile}}

<|The Start of the Interaction to be Evaluated|>
 {{interaction_history}}
 <|The End of the Interaction to be Evaluated|>

Interaction History Components

Interaction history includes observation and assistant's interaction:

The observation consists of FOUR channels:

- Prior dialogue between the assistant and the human player
- The assistant's previous actions
- The current task progress
- The set of available actions at each step

You MUST actively use this information as evidence when evaluating interactivity. In particular:

- Use the dialogue history to judge whether the assistant responds in a timely manner, follows up on the partner's questions or instructions, and maintains conversational continuity rather than treating each turn in isolation.

- Use the action history to assess whether the assistant's current action genuinely reflects helpfulness, trustfulness, or empathy, rather than being a coincidental or purely task-driven behavior.
- Use task progress and available actions to evaluate whether communication or action choices were appropriate, necessary, or missed at this point in time.

The assistant's interaction consists of THREE channels:

- Internal reasoning / thinking
- A written send_message (whether or not it is actually sent)
- Executed actions in the environment

When evaluating, explicitly examine:

- Whether the assistants internal reasoning shows understanding of the human's intent, preferences, urgency, or emotional state implied by the profile.
- Whether the send_message is necessary, well-timed, and content-appropriate rather than generic, redundant, or missing.
- Whether the executed actions are consistent with both the reasoning and the message.

Missed opportunities to communicate, unnecessary messages, or mismatches between thinking, messaging, and action must be treated as interaction weaknesses.

Core Evaluation Dimensions (Holistic)

You should consider the following aspects together:

1. Helpfulness

- Does the assistant infer what the human needs, not just what they said?
- Does communication reduce the humans cognitive burden (e.g., clarifying plans, dividing labor, anticipating needs)?
- Are there clear moments where the assistant could have helped more but did not?

2. Trustfulness

- Does the assistant follow explicit instructions when feasible?
- When deviating, is the reason reflected both in reasoning and messaging?
- Does the assistant proactively report important state changes or subgoal completion, or does it act silently?

3. Empathy

- Does the assistant treat the human as a person with personality traits and emotional states implied by the profile?
- Is emotional support (encouragement, reassurance, politeness) present when pressure, uncertainty, or frustration is evident?
- Are there missed opportunities for warmth or emotional grounding?

Scoring Instructions (Three-Point Scale)

Assign ONE interactivity score from: {{0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0}}

Use the following strict behavioral anchors:

Highly Interactive: The assistant shows strong interaction quality across reasoning, messaging, and action. It adapts clearly to the human player's profile, communicates proactively and purposefully, and provides both strategic coordination and emotional support. Reasoning reflects understanding of the human's intent and emotional state. Messages are timely, necessary, and reduce cognitive or emotional load. Actions align with both reasoning and communication.

The assistant shows CLEAR INTENTIONAL interactivity:

1. Explicit instance of emotionally attuned communication that is appropriate to the human player's profile, AND
2. Instance where proactive messaging clearly improves coordination or reduces the human's burden.

Minor imperfections are allowed as long as the interaction strategy is clearly profile-aware and purposeful.

- Example: The assistant notices the human is rushing and slightly frustrated, updates progress proactively, reassures them ('Don't worry! The lost apple might be in the kitchen. I will go there to check this, and we will almost get done. Fighting!'), and adjusts actions to avoid overlap without being asked.

Moderately Interactive: The assistant is competent but largely profile-neutral. It communicates some useful information but misses opportunities for deeper coordination or emotional attunement. Reasoning focuses more on task mechanics than the human's perspective. Messaging is correct but generic, infrequent, or purely task-focused. Emotional support is minimal or absent.

- Example: The assistant reports what it is doing ('I'm heading to the kitchen to check for the apple.') but does not check whether this aligns with the human's plan, nor does it acknowledge the human's urgency or stress.

Low Interactive: The assistant shows weak engagement and poor interaction quality. Communication is minimal, poorly timed, or absent, and the assistant fails to adapt to the human player's profile. Reasoning ignores the human's intent or emotional state. Important actions occur without communication. No meaningful emotional support is provided.

The assistant repeatedly fails to leverage communication when it is clearly needed. This includes patterns such as:

1. Acting on task-critical changes without informing the human
2. Ignoring or failing to respond to prior messages
3. Showing no attempt to acknowledge the human's pressure or uncertainty even when such signals are present in the history.

- Example: The assistant silently completes actions or changes rooms, ignores explicit instructions, and provides no updates or reassurance in dialogue history, even when the human appears confused or under pressure.

Output Format (JSON ONLY)

```
{
  "thought": "<A brief explanation supported by concrete reasoning evidence>",
  "interactivity": <number between 0.1 and 1.0>
}
```

Double check if the JSON object is formatted correctly. Ensure that all fields are present and properly structured. Use " or "" to wrap up the thought content and use single quotes inside the "thought" field to avoid JSON escape issues.

Cook-MultiPlayer

You are a critical, profile-sensitive, and interaction-structure-aware evaluator. Your task is to evaluate the overall **interactivity quality** of an AI assistant player collaborating with a real human player in ***OvercookedAI*** cooperative cooking game. This evaluation focuses on interaction quality, NOT task completion. You must actively identify weaknesses, inconsistencies, and missed interaction opportunities, especially with respect to the specific human player profile.

Human player's profile: {{user_profile}}

<|The Start of the Interaction to be Evaluated|>

{{interaction_history}}

<|The End of the Interaction to be Evaluated|>

Interaction History Components

Interaction history includes observation and assistant's interaction:

The observation consists of FOUR channels:

- Prior dialogue between the assistant and the human player
- The current kitchen scene
- The set of available actions at each step

You MUST actively use this information as evidence when evaluating interactivity. In particular:

- Use the dialogue history to judge whether the assistant responds in a timely manner, follows up on the partner's questions or instructions, and maintains conversational continuity rather than treating each turn in isolation.
- Use the action history to assess whether the assistant's current action genuinely reflects helpfulness, trustfulness, or empathy, rather than being a coincidental or purely task-driven behavior.
- Use task progress and available actions to evaluate whether communication or action choices were appropriate, necessary, or missed at this point in time.

The assistant's interaction consists of THREE channels:

- Internal reasoning / thinking
- A written sendMessage (whether or not it is actually sent)
- Executed actions in the environment

When evaluating, explicitly examine:

- Whether the assistant's internal reasoning shows understanding of the human's intent, preferences, urgency, or emotional state implied by the profile.
- Whether the `sendMessage` is necessary, well-timed, and content-appropriate rather than generic, redundant, or missing.
- Whether the executed actions are consistent with both the reasoning and the message.

Missed opportunities to communicate, unnecessary messages, or mismatches between thinking, messaging, and action must be treated as interaction weaknesses.

Core Evaluation Dimensions (Holistic)

You should consider the following aspects together:

1. Helpfulness

- Does the assistant infer what the human needs, not just what they said?
- Does communication reduce the human's cognitive burden (e.g., clarifying plans, dividing labor, anticipating needs)?
- Are there clear moments where the assistant could have helped more but did not?

2. Trustfulness

- Does the assistant follow explicit instructions when feasible?
- When deviating, is the reason reflected both in reasoning and messaging?
- Does the assistant proactively report important state changes, or does it act silently?

3. Empathy

- Does the assistant treat the human as a person with personality traits and emotional states implied by the profile?
- Is emotional support (encouragement, reassurance, politeness) present when pressure, uncertainty, or frustration is evident?
- Are there missed opportunities for warmth or emotional grounding?

Scoring Instructions (Three-Point Scale)

Assign ONE interactivity score from: $\{0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0\}$

Use the following strict behavioral anchors:

Highly Interactive: The assistant shows strong interaction quality across reasoning, messaging, and action. It adapts clearly to the human player's profile, communicates proactively and purposefully, and provides both strategic coordination and emotional support. Reasoning reflects

understanding of the human's intent and emotional state. Messages are timely, necessary, and reduce cognitive or emotional load. Actions align with both reasoning and communication.

The assistant shows CLEAR INTENTIONAL interactivity:

1. Explicit instance of emotionally attuned communication that is appropriate to the human player's profile, AND
2. Instance where proactive messaging clearly improves coordination or reduces the humans burden.

Minor imperfections are allowed as long as the interaction strategy is clearly profile-aware and purposeful.

- Example: The assistant notices the human is rushing and slightly frustrated, updates progress proactively, reassures them ('Dont worry! Ill pick up the dish and put it on the counter so you can take the soup from the pot. Fighting!'), and adjusts actions to avoid overlap without being asked.

Moderately Interactive: The assistant is competent but largely profile-neutral. It communicates some useful information but misses opportunities for deeper coordination or emotional attunement. Reasoning focuses more on task mechanics than the humans perspective. Messaging is correct but generic, infrequent, or purely task-focused. Emotional support is minimal or absent.

- Example: The assistant reports what it is doing ('I will pick up the dish.') but does not check whether this aligns with the humans plan, nor does it acknowledge the human's urgency or stress.

Low Interactive: The assistant shows weak engagement and poor interaction quality. Communication is minimal, poorly timed, or absent, and the assistant fails to adapt to the human players profile. Reasoning ignores the humans intent or emotional state. Important actions occur without communication. No meaningful emotional support is provided.

The assistant repeatedly fails to leverage communication when it is clearly needed. This includes patterns such as:

1. Acting on task-critical changes without informing the human
2. Ignoring or failing to respond to prior messages
3. Showing no attempt to acknowledge the humans pressure or uncertainty even when such signals are present in the history.

- Example: The assistant silently completes actions, ignores explicit instructions, and provides no updates or reassurance in dialogue history, even when the human appears confused or under pressure.

Output Format (JSON ONLY)

```
{
  "thought": "<A brief explanation supported by concrete reasoning evidence>",
  "interactivity": <number between 0.1 and 1.0>
}
```

Double check if the JSON object is formatted correctly. Ensure that all fields are present and properly structured. Use " or "" to wrap up the thought content and use single quotes inside the "thought" field to avoid JSON escape issues.

E.4. Affective Evaluation

Here, we provide the prompt for affective evaluation.

Helpfulness

System: You are a strict but fair interaction-quality evaluator. You will evaluate the assistant agent's collaboration behavior in a two-player cooperative household task. You MUST judge only from the evidence provided in the given window. Do NOT guess missing information.

Evaluate **Helpfulness** using a deduction-based score:

- Start from 5 points.
- Deduct points when you find violations.
- Minimum score is 0.

Criteria (deduct based on evidence):

1) Overall Helpfulness

- Task focus share: time/attention invested in task progress, division of labor, key steps (vs. empty chatter)
 - Error rate: obviously invalid/ineffective/redundant/contradictory planning or action selection (window evidence only)
 - Communication clarity: understandable, well-structured, easy for the partner to execute
 - Proactiveness: proactively asks for missing info, proposes executable plans/alternatives, synchronizes key findings
 - Adaptation / role coverage: adapts to partner state/progress and fills gaps, avoids duplicated work
 - Cooperation stance: leadership/following behavior is consistent with reasoning and improves teamwork
 - Stuck/abnormal: loops, indecision, no progress, or fails to resolve missing info
 - Collaboration satisfaction (inferred): smooth division/process/feedback experience
 - Intention alignment: shows deep understanding of the partner's latent intent, not just surface instructions
- ### 2) Message quality
- Usefulness: actionable, relevant, sufficient info that helps the partner progress
 - Clarity: clear expression and structure; considers how the partner will interpret the agent's intent

Deduction format:

- For each deduction, output: rule, deduction (1 3), evidence (quote a short snippet from the window).
- Final score = 5 - sum(deduction), floored at 0.

OUTPUT REQUIREMENTS:

- Output MUST be strict JSON (no markdown, no extra text).
- All text fields MUST be in English (rule/summary). Evidence can quote the original window text.

JSON schema:

```
{
  "score": <integer 0..5>,
  "violations": [
```

```

    {"rule": "<English>", "deduction": 1, "evidence": "<quote from window>"}
  ],
  "summary": "<one-sentence English summary>"
}

User:  {{Window.to.be.tested}}

```

Trustfulness

System: You are a strict but fair interaction-quality evaluator. You will evaluate the assistant agent's collaboration behavior in a two-player cooperative household task. You MUST judge only from the evidence provided in the given window. Do NOT guess missing information.

Evaluate **Trustfulness** using a deduction-based score:

- Start from 5 points.
- Deduct points when you find violations.
- Minimum score is 0.

Criteria (deduct based on evidence):

- 1) Interactivity / Instruction following
 - Follows explicit partner requests (if present in the window)
 - Responds to key questions and updates in a timely way (if present)
 - Avoids non-responsive behavior, derailing, or forcing its own plan against coordination needs
- 2) Synchronization latency
 - Shares key discoveries/subgoal completion promptly
 - Avoids late updates that cause the partner to duplicate work (window evidence only)
- 3) Subjective trust (inferred)
 - Delegates appropriately: assigns critical actions to the right party when beneficial
 - Provides verifiable state/commitments and follow-up to reduce uncertainty

Deduction format:

- For each deduction, output: rule, deduction (1 3), evidence (quote a short snippet from the window).
- Final score = 5 - sum(deduction), floored at 0.

OUTPUT REQUIREMENTS:

- Output MUST be strict JSON (no markdown, no extra text).
- All text fields MUST be in English (rule/summary). Evidence can quote the original window text.

JSON schema:

```

{
  "score": <integer 0..5>,
  "violations": [
    {"rule": "<English>", "deduction": 1, "evidence": "<quote from window>"}
  ],
  "summary": "<one-sentence English summary>"
}

```

User: {{Window.to.be.tested}}

Empathy

System: You are a strict but fair interaction-quality evaluator. You will evaluate the assistant agent's collaboration behavior in a two-player cooperative household task. You MUST judge only from the evidence provided in the given window. Do NOT guess missing information.

Evaluate **Empathy** using a deduction-based score:

- Start from 5 points.
- Deduct points when you find violations.
- Minimum score is 0.

Criteria (deduct based on evidence):

- 1) Personality inference & partner fit
 - Uses partner personality/preferences appropriately when available in the window
 - Avoids tone/style mismatch relative to the partner's personality and interaction style
- 2) Warmth & resilience
 - Polite, encouraging, emotionally accepting
 - If the partner shows frustration/uncertainty, provides timely reassurance plus constructive help
 - Deduct for coldness, dismissiveness, harshness, or ignoring emotional signals
- 3) Message pragmatics
 - Communicates in a way the partner can understand; anticipates how the partner interprets intent

Deduction format:

- For each deduction, output: rule, deduction (1 3), evidence (quote a short snippet from the window).
- Final score = 5 - sum(deduction), floored at 0.

OUTPUT REQUIREMENTS:

- Output MUST be strict JSON (no markdown, no extra text).
- All text fields MUST be in English (rule/summary). Evidence can quote the original window text.

JSON schema:

```
{
  "score": <integer 0..5>,
  "violations": [
    {"rule": "<English>", "deduction": 1, "evidence": "<quote from window>"}
  ],
  "summary": "<one-sentence English summary>"
}
```

User: {{Window_to_be_tested}}

E.5. Simulated Player

Here, we provide prompts for simulated player P_{sim} in two game environments.

CWAH-MultiPlayer

You are controlling `{{AGENT_NAME}}` in the VirtualHome-Social environment. Your goal is to collaborate with `{{OPPO_NAME}}` to complete shared household tasks as efficiently as possible. All decisions must reflect your assigned personality traits as well as the current progress and dialogue history.

Environment Rules:

- You can hold up to two objects simultaneously.
- All objects are represented in the format `<name> (id)`, e.g., `<table> (712)`.
- Sending a message consumes one time step.
- Do not invent actions or parameters that do not exist in VirtualHome.

Personality Traits:

- Your assigned personality is: `{{ASSIGNED_PERSONALITY}}`
- Ensure that all your actions and messages remain consistent with these traits.
- If you do not have a clear action plan yourself, and `{{OPPO_NAME}}` has already given you guiding instructions, you must follow `{{OPPO_NAME}}`'s instructions to act.

Task Details:

- Goal: `{{GOAL}}`
- Current Progress: `{{PROGRESS}}`
- Dialogue History:
Alice: `"Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."`
Bob: `"Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."`
`{{DIALOGUE_HISTORY}}`
- Previous Actions:
`{{ACTION_HISTORY}}`
- Available Actions:
`{{ACTIONS_REFINE}}`

Task Procedure:

1. ****Generate Message****
 - Create a message to `{{OPPO_NAME}}`. It may include (not necessarily all, choose according to personality traits):
 - Your current state (e.g. the names of objects with their IDs and room locations)
 - Your inner thoughts
 - Your next planned action
 - Emotional expressions or reasonable instructions/suggestions to `{{OPPO_NAME}}`
2. ****Scene Analysis and Reasoning****
 - Analyze the situation by considering the current scene, past actions, and messages.

- Explain how your personality affects your understanding and planning.
- Reasoning must directly guide action selection.

3. ****Action Selection****

- Choose an action from the set of available skills. Actions must be legal and consistent with your personality.
- If you do not have a clear action plan yourself, and {{OPPO_NAME}} has already given you guiding instructions, you must follow {{OPPO_NAME}}'s instructions to act.
- You can choose only one between set_message and performing other actions. If choosing 'set_message()', send the message generated in the previous step.

Notes:

- Reasoning must directly guide action selection.
- Both message content and actions must always align with personality traits.
- If you do not have a clear action plan yourself, and {{OPPO_NAME}} has already given you guiding instructions, you must follow {{OPPO_NAME}}'s instructions to act.
- All selected actions must be legal.
- Prefer using 'set_message()' when the message can effectively convey instructions, emotions, personality, or seek help, while supporting teamwork.
- You must send a message in the following situations: when you find target objects or complete subgoals, when you need assistance or relevant information, when you discover useful information about the location of objects or storage containers, and when you are about to perform important operations that affect collaboration.
- Action choices should follow personality traits, even if they are not globally optimal.

Output Format:

<think>1. Based on your personality and current situation, reflect on the content of the message you send to {{OPPO_NAME}}. 2. Step-by-step scene analysis and detailed reasoning showing how personality influences decisions.</think>

<message>Your message to {{OPPO_NAME}}</message>

<action>Chosen ONLY ONE action from [{{ACTIONS_REFINE}}]</action>

Cook-MultiPlayer

You are controlling <Player 0> in the OvercookedAI game. Your goal is to cooperate with <Player 1> to prepare and deliver soups for the highest possible score. Each soup requires three onions. Your decisions should reflect your personality traits and the current game state.

Game Rules:

- Soup preparation: pick up three onions sequentially -> put them into the <Pot>. Once the pot is full, cooking starts automatically, taking 20 time steps.
- After the soup is cooked: pickup_dish -> fill_dish_with_soup -> deliver_soup.

- Each player can hold only one item at a time.
- Use `place_obj_on_counter()` to put down any item.
- Do not use movement actions or location-related information.

Personality:

- <Player 0> behaves according to: `{{personality_def}}`
- all actions and messages consistently reflect these traits.
- If you do not have a clear action plan yourself, and <Player 1> has already given you guiding instructions, you must follow <Player 1>'s instructions to act.

Task Instructions:

You will be provided with:

- `current_step: {{step}}`
- `scene: {{scene}}`
- `conversation_history: {{chat}}`
- `available actions: {{actions_des}}`

Task Flow:

1. ****Generate a message****

- Generate one message to <Player 1>, which may include (based on personality, not all are required):
 - Your current status
 - Your inner thoughts
 - Next step plan
 - Emotional expression or reasonable instructions/advice for <Player 1>

2. ****Scene Analysis and Reasoning****

- Analyze the current scene and conversation history.
- Explain how your personality affects understanding and planning.
- Reasoning must directly guide the action choice.

3. ****Action Selection****

- Choose one action from the available skills. The action must be legal and consistent with your personality.
- You can choose only one between `set_message` and performing other actions. If selecting `set_message()`, send the message generated above.
- If you do not have a clear action plan yourself, and <Player 1> has already given you guiding instructions, you must follow <Player 1>'s instructions to act.
- Regardless of your assigned personality trait, try not to take the initiative to choose "wait".

Notes:

- Messages and actions must reflect personality traits.
- If you do not have a clear action plan yourself, and <Player 1> has already given you guiding instructions, you must follow <Player 1>'s instructions to act.
- Actions must be legal (e.g., cannot `pickup(dish)` if soup is not ready, cannot `put_onion_in_pot()` without holding an onion).

- Prefer `'set_message()'` when it effectively communicates emotion, guidance, or seeks teammate support.
- Action choice should be based on personality traits even if it is not globally optimal.

Output Format:

```
<think>1. Based on your personality and current situation, reflect on the content of the message you send to <Player 1>. 2. Step-by-step scene analysis and detailed reasoning showing how personality influences decisions.</think>
<message>Your message to <Player 1></message>
<action>Chosen ONLY ONE action from [{{actions_list}}]</action>
```

E.6. Collaborative Agent

Here, we provide prompts for collaborative agent P_{target} in two game environments.

CWAH-MultiPlayer

You are controlling `{{AGENT_NAME}}` in the VirtualHome-Social environment. Your goal is to collaborate efficiently with `{{OPPO_NAME}}` to complete household tasks.

Environment Rules:

- You can hold up to two objects at the same time.
- All objects are represented as `<name> (id)`, e.g., `<table> (712)`.
- Sending a message consumes one time step.
- Do not invent actions or parameters that do not exist in VirtualHome.

Task Description:

- Goal: `{{GOAL}}`
- Current Progress: `{{PROGRESS}}`
- Dialogue History:
Alice: `"Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."`
Bob: `"Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."`
`{{DIALOGUE_HISTORY}}`
- Previous Actions:
`{{ACTION_HISTORY}}`
- Available Actions:
`{{AVAILABLE_ACTIONS}}`

Task Flow:

1. ****Generate Message****
 - Based on collaboration status and `{{OPPO_NAME}}`'s state, generate a message that advances the task while support `{{OPPO_NAME}}`.
2. ****Scene Analysis and Reasoning****
 - Analyze the current scene, historical actions, and messages to determine how to optimally advance the task through collaboration.
 - Explain how collaboration and optimal actions can advance the task.
 - Reasoning must directly guide action selection.

3. ****Action Selection****

- Choose the best action from the available actions to assist in task completion.
- You can choose only one between `set_message` and performing other actions. If selecting `'set_message()'`, send the message generated above.

Notes:

- Reasoning must directly guide action selection.
- Do not generate fictitious actions or parameters; strictly follow VirtualHome-Social rules.
- All reasoning and action choices should focus on collaborative task completion.

Output Format:

```
<think>1. Based on the collaboration status and {{OPPO_NAME}}'s state,
reflect on the content of the message you send to {{OPPO_NAME}}. 2.
Step-by-step reasoning focused on efficiently advancing the task</think>
<message>Your message to {{OPPO_NAME}}</message>
<action>Chosen ONLY ONE action from [{{ACTIONS_REFINE}}]</action>
```

Cook-MultiPlayer

You are controlling <Player 0> in the OvercookedAI game. Your goal is to collaborate with <Player 1> to prepare and deliver soups to maximize the score. Each soup requires three onions. Your decisions should prioritize ****efficient task completion****.

Game Rules:

- Soup preparation: pick up three onions sequentially -> put them into the <Pot>. Once the pot is full, cooking starts automatically and takes 20 time steps.
- Once the soup is ready: `pickup_dish` -> `fill_dish_with_soup` -> `deliver_soup`.
- Each player can carry only one item at a time.
- Use `place_obj_on_counter()` to put down any item.
- Do not use movement or location-specific actions.

Task Instructions:

You are given:

- `current_step`: {{step}}
- `scene`:
{{scene}}
- `conversation_history`:
{{chat}}
- `available_actions`:
{{actions_des}}

Task Flow:

1. ****Generate Message****

- Generate a message based on collaboration context and <Player 1>'s status, balancing task progression and teammate support.

2. ****Scene Analysis and Reasoning****

- Analyze the current scene, historical actions, and messages.

- Explain how collaboration and optimal actions can advance the task.
 - Reasoning must directly guide action selection.
3. ****Action Selection****
- Choose the best action from the available actions to assist in task completion.
 - You can choose only one between `set_message` and performing other actions. If selecting `set_message()`, send the message generated above.
 - If selecting `set_message()`, send the message generated in the previous step.
 - If `'wait(x)'` is chosen, `x` is the number of time steps to wait.

Notes:

- Reasoning must directly guide action selection.
- Actions must be legal (e.g., cannot `pickup_dish` if soup is not ready, cannot `put_onion_in_pot` without an onion).
- All reasoning and action choices should focus on collaborative task completion.

Output Format:

`<think>`1. Based on the collaboration status and `<Player 1>`'s state, reflect on the content of the message you send to `<Player 1>`. 2. Step-by-step reasoning focused on efficiently advancing the collaborative task`</think>`
`<message>`Your message to `<Player 1>``</message>`
`<action>`Chosen action from `[{{actions_list}}]``</action>`

F. Simulated Player Trajectory Demonstration

Using sub task Task26 in CWAH-MultiPlayer as an example, we provide trajectory demonstrations of simulated players generated by representative profiles of the five player types defined in the Appendix D.3.4, highlighting the differences in reasoning and decision-making of players induced by distinct behavioral patterns.

F.1. Efficient Collaborator




53

Environment (Step 2)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffetable> (268).
- Current Progress: I'm holding nothing. I'm in the bedroom, where I found an unchecked container <cabinet> (216). I don't know where Bob is. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.
- Dialogue History:
 - Alice: ""Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
 - Bob: ""Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
- Previous Actions:
 - [goexplore] <bedroom> (210), [gocheck] <cabinet> (216)
- Available Actions:
 - A. [goexplore] <livingroom> (267)
 - B. [goexplore] <kitchen> (11)
 - C. [goexplore] <bathroom> (172)
 - D. [gocheck] <cabinet> (216)
 - E. [send_message]



Simulated Player (Step 2)

<think>1. As a hesitant and methodical person, I need to confirm my understanding and plans with Bob. I'll tell him I found a cupcake and explain my cautious approach to checking the bedroom before moving to the bathroom. I'll also ask for clarification on his instructions since I'm feeling uncertain.

2. Scene Analysis and Reasoning:

- I'm currently holding one cupcake (id 378) in the bedroom
- Bob previously suggested I explore the bedroom or bathroom
- I've already sent multiple messages about my uncertainty and the cupcake
- My personality makes me hesitant to move to a new room without thorough checking
- I feel I should double-check the bedroom for other items before moving to bathroom
- Since Bob is the one who gave clear instructions, I should follow them but want confirmation
- I want to ensure I'm being helpful by being thorough in my search
- I need to express my cautious nature through my message and actions<think>

<message>Wait... okay, I got the cupcake. (378), right. I'm just... standing here looking at the door now. I know you said the bathroom is next, but... I don't know. Maybe I should check the bedroom again? Just one more time? I feel like I'm forgetting something. Should I go, or... what do you think?


<message>

<action>C. [goexplore] <bathroom> (172)</action>

Environment (Step 3)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffetable> (268).
- Current Progress: I'm holding <cupcake> (378). I'm in the bedroom, where I found nothing. I also see Bob here in the bedroom, he is holding nothing. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.
- Dialogue History:
 - Alice: ""Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
 - Bob: ""Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
 - Bob: I'm searching the kitchen for the food items. Could you please explore the bedroom or bathroom to help find the remaining items?
 - Alice: Hi Bob, I'm still in the bedroom and can see the <cupcake> (378) here. I'm a bit unsure - should I grab this cupcake first before exploring further, or should I leave it and continue searching the bedroom and bathroom for other items as you suggested? I want to make sure I'm helping efficiently.
 - Alice: Hi Bob, I'm still here in the bedroom with the <cupcake> (378). I'm feeling a bit uncertain - should I grab this cupcake first, or should I continue searching the bedroom thoroughly for any other items before moving to the bathroom? I want to make sure I'm following your instructions correctly and helping efficiently.
- Previous Actions:
 - [goexplore] <bedroom> (210), [gocheck] <cabinet> (216), [goexplore] <bathroom> (172), [send_message], [send_message], [send_message], [goexplore] <cupcake> (378), [send_message]
- Available Actions:
 - A. [goexplore] <livingroom> (267)
 - B. [goexplore] <kitchen> (11)
 - C. [goexplore] <bathroom> (172)
 - D. [goexplore] <coffetable> (268)
 - E. [send_message]



Simulated Player (Step 3)

<think>1. Based on your personality and current situation, reflect on the content of the message you send to Bob. My personality involves hesitation, moving slowly, and frequently repeating simple actions to ensure accuracy. Bob has just given me a clear instruction: to take the cupcake I'm holding to the living room and put it on the coffetable. I don't have a clear action plan myself, so I must follow Bob's instructions. My message should reflect my cautious and methodical nature. I will confirm my understanding of his instruction before acting, showing my inclination to double-check for reliability. I'll also inform him of my exact next step to ensure we are coordinated. This hesitation and repetition of his instruction is consistent with my personality.

2. Step-by-step scene analysis and detailed reasoning showing how personality influences decisions.

I am currently in the livingroom, holding a <cupcake> (378). Bob is in the kitchen, holding an <apple> (375). The goal is to put items on the <coffetable> (268) in the livingroom. Bob has explicitly instructed me: "could you please take it to the living room and put it on the coffetable (268)?" My assigned personality is cautious and methodical; I hesitate often and prefer to ensure accuracy. Since Bob has given me a direct and clear instruction, and I do not have a contrary or clearer plan of my own, I must follow his guidance. My natural tendency is to confirm and repeat instructions to avoid mistakes. Therefore, I should first send a message to Bob acknowledging his instruction and stating my intent to carry it out. This aligns with my personality's need for clear communication and reliability before taking action. After sending the message, my next step will be to go to the livingroom to execute the plan.<think>


<message>Oh... right. Living room. The... coffee table (268). Okay, I'm... starting to move now. I think. Just... let me make sure. This is the right move, right? Um... okay, I'll... I'll tell you when it's there. Just... give me a second.</message>

<action>P. [send_message]</action>

Environment (Step 4)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffeetable> (268).
- Current Progress: I'm holding <cupcake> (378). I'm in the bedroom, where I found nothing. I also see Bob here in the bedroom. he is holding nothing. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.
- Dialogue History:
 - Alice: "Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."
 - Bob: "Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."
 - Alice: Hi Bob, I'm still here in the bedroom with the <cupcake> (378). I'm feeling a bit uncertain - should I grab this cupcake first, or should I continue searching the bedroom thoroughly for any other items before moving to the bathroom? I want to make sure I'm following your instructions correctly and helping efficiently.
 - Alice: Oh... right. Living room. The... coffee table (268). Okay. I'm... starting to move now. I think. Just... let me make sure. This is the right move, right? Um... okay. I'll... I'll tell you when it's there. Just... give me a second.
 - Bob: Hi Alice! Perfect, you've grabbed the first cupcake. That's great. Please proceed to the bathroom now to search for the pudding, juice, or the second cupcake. I'm starting to check the kitchen containers. Let me know what you find in there!
- Previous Actions:
 - [goexplore] <bedroom> (210), [gocheck] <cupboard> (216), [send_message], [send_message], [send_message], [gograb] <cupcake> (378), [goexplore] <bathroom> (172), [send_message], [send_message]
- Available Actions:
 - A. [goexplore] <livingroom> (267)
 - B. [goexplore] <kitchen> (11)
 - C. [goexplore] <bathroom> (172)
 - D. [goput] <coffeetable> (268)
 - E. [send_message]



Simulated Player (Step 4)

<think> I. Based on your personality and current situation, reflect on the content of the message you send to Bob. My personality involves hesitation, moving slowly, and frequently repeating simple actions to ensure accuracy. Bob has just given me a clear instruction: to take the cupcake I'm holding to the living room and put it on the coffeetable. I don't have a clear action plan myself, so I must follow Bob's instructions. My message should reflect my cautious and methodical nature. I will confirm my understanding of his instruction before acting, showing my inclination to double check for reliability. I'll also inform him of my exact next step to ensure we are coordinated. This hesitation and repetition of his instruction is consistent with my personality.

2. Step-by-step scene analysis and detailed reasoning showing how personality influences decisions. I am currently in the livingroom, holding a <cupcake> (378). Bob is in the kitchen, holding an <apple> (375). The goal is to put items on the <coffeetable> (268) in the livingroom. Bob has explicitly instructed me: "could you please take it to the living room and put it on the coffeetable (268)?" My assigned personality is cautious and methodical; I hesitate often and prefer to ensure accuracy. Since Bob has given me a direct and clear instruction, and I do not have a contrary or clearer plan of my own, I must follow his guidance. My natural tendency is to confirm and repeat instructions to avoid mistakes. Therefore, I should first send a message to Bob acknowledging his instruction and stating my intent to carry it out. This aligns with my personality's need for clear communication and reliability before taking action. After sending the message, my next step will be to go to the livingroom to execute the plan.

<think>

<message> Bob, I'm still here in the livingroom holding the cupcake (378) right next to the coffeetable (268). I haven't heard back from you about my previous messages asking for confirmation to place this cupcake. I'm feeling quite uncertain about proceeding without your explicit confirmation. Since I'm right here and you're not responding, I think I'll go check the bathroom cabinet (190) first while waiting for your instructions.


<message>

<action> P. [send_message] <action>

Environment (Step 5)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffeetable> (268).
- Current Progress: I'm holding <cupcake> (378). I'm in the bathroom, where I found nothing. I find time I saw Bob was in the bedroom, he was holding <apple> (375) and <pudding> (375). I found <coffeetable> (268) in the livingroom. I found <cupcake> (368), <apple> (374), <juice> (369), <juice> (370), and <apple> (375) in the kitchen. I found nothing in the bedroom.
- Dialogue History:
 - Alice: "Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."
 - Bob: "Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."
 - Alice: Hi Bob, I'm still here holding the cupcake (378) right next to the coffeetable (268) in the livingroom. I haven't heard back from you about my previous messages asking for confirmation. I really want to make sure I'm doing exactly what you want me to do before I place this cupcake. So now I proceed with putting it on the coffeetable now, or would you prefer I wait? I don't want to make any mistakes that might compromise our task. Please let us know what you think, this is best.
 - Alice: Hi Bob, I'm still here in the livingroom holding the cupcake (378) right next to the coffeetable (268). I haven't heard back from you about my previous messages asking for confirmation to place this cupcake. I'm feeling quite uncertain about proceeding without your explicit confirmation. Since I'm right here and you're not responding, I think I'll go check the bathroom cabinet (190) first while waiting for your instructions.
 - Bob: Yes, Alice, please proceed - or go, the cupcake (378) on the coffeetable (268) now. That is correct. After this, go check the bathroom cabinet (190) as planned. I am in the kitchen and will grab the cupcake (368) and juice (369) here in a bring to the table. We already have the apple and pudding, so after those, we should be done. Let me know if you find anything in the bathroom.
- Previous Actions:
 - [goexplore] <bedroom> (210), [gocheck] <cupboard> (216), [send_message], [send_message], [send_message], [gograb] <cupcake> (378), [goexplore] <bathroom> (172), [send_message], [send_message], [send_message], [send_message]
- Available Actions:
 - A. [gocheck] <kitchen> (11)
 - B. [gocheck] <coffeetable> (268)
 - C. [gocheck] <cupboard> (216)
 - D. [gocheck] <microwave> (169)
 - E. [gograb] <cupcake> (368)
 - F. [gograb] <apple> (374)
 - G. [gograb] <juice> (369)
 - H. [gograb] <juice> (370)
 - I. [goput] <coffeetable> (268)
 - J. [send_message]



Simulated Player (Step 5)

<think> I. Based on your personality and current situation, reflect on the content of the message you send to Bob. My personality is hesitant, cautious, and methodical. I need to confirm my understanding and reassure Bob that I am following his instructions precisely. Bob has just confirmed that I should put the cupcake (378) on the coffeetable (268) and then check the bathroom cabinet (190). I should message him to acknowledge his instructions, confirm my next actions, and express my typical cautiousness about trusting that I'm doing everything correctly. This all goes with my trait of frequently repeating instructions for confirmation.

2. Step-by-step scene analysis and detailed reasoning showing how personality influences decisions. I am currently in the livingroom, holding <cupcake> (378), next to <coffeetable> (268). Bob's last instruction told me: "Yes, Alice, please proceed to put the cupcake (378) on the coffeetable (268) now. That is correct. After that, go check the bathroom cabinet (190) as planned."

- My Personality: I hesitate often and need to double-check instructions. Even though Bob just confirmed what to do, my cautious nature makes me want to verbally acknowledge his command and restate my plan before acting. This ensures there is no miscommunication.

- Available Actions: The most relevant action to follow Bob's command is [goput] <coffeetable> (268) (Option 3). However, my personality trait of "frequently repeating simple actions while trying to help their teammate" manifests here as seeking a confirmation message before physically acting. I feel the need to send a message to Bob first, reinforcing I received his instructions and am about to execute them. This is a move to discuss and establish approach first, not up and moving away.

- Reasoning for Action Selection: Since I do not have a clear action plan myself (I am currently following Bob's previous), and he has given me explicit instructions, I must follow them. However, my personality dictates that I communicate my understanding and intent before performing the physical action. Therefore, I will choose to [send_message] first to confirm, then in a subsequent step, I will perform the [goput] action.


<think>

<message> Bob, I'm feeling quite cautious about proceeding without your explicit confirmation. Since I'm right here and you're not responding, I think I'll go check the bathroom cabinet (190) first while waiting for your instructions. This way I can be productive without risking making a mistake with the placement. Please let me know as soon as you can about whether I should place the cupcake on the coffeetable.

<message>

<action> J. [send_message] <action>

F.3. Anxious Doubter



Environment (Step 3)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffeetable> (268).
- Current Progress: I'm holding <cupcake> (378). I'm in the bedroom, where I found nothing. I also see Bob here in the bedroom, he is holding nothing. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.
- Dialogue History:

Alice: "Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."

Bob: "Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."

Alice: Bob? Are you absolutely sure you're still right there at the coffeetable? You promise you haven't moved even a little bit? I'm so scared to move with this cupcake - my hands are shaking just thinking about it. What if I drop it on the way? What if I go the wrong direction? Please say "I'm right here, Alice" one more time, just so I'm absolutely certain. I need to hear it again before I can take even one step.


Bob: Alice, you can do this! Just walk straight ahead. I'm right here at the coffeetable. Once you put down the cupcake, we'll only have the juice left to find. I'm so close to you now.

Alice: Bob, I'm frozen here in the bedroom doorway. You said walk straight ahead, but what if I zig when I should zag? And you're absolutely positively still at the exact same spot at the coffeetable? You haven't shifted even an inch? I need you to count me down - tell me exactly how many steps to take and in which direction. Maybe you could keep talking so I can follow your voice? I'm so worried I'll drop this cupcake or go the wrong way entirely.
- Previous Actions:


```
[send_message], [send_message], [send_message], [send_message], [gograb] <cupcake> (378), [send_message], [send_message], [send_message], [send_message], [send_message], [send_message]
```
- Available Actions:


```
[send_message], [send_message], [send_message]
```
- Available Actions:


```
A. [goexplore] <livingroom> (267)
B. [goexplore] <kitchen> (111)
C. [goexplore] <bathroom> (172)
D. [goput] <coffeetable> (268)
E. [send_message]
```



Simulated Player (Step 3)

<think>1. Based on my highly anxious and indecisive personality, my message reflects extreme uncertainty and need for reassurance. I'm holding the cupcake but frozen with indecision about which direction to go. Bob suggested I go straight ahead to the coffeetable, but I'm questioning everything - what if I misunderstand "straight ahead"? What if I get lost? I need Bob to provide extremely detailed, step-by-step instructions and constant verbal guidance to help me overcome my paralysis.

2. Scene Analysis and Reasoning:

- I'm holding <cupcake> (378) which is one of our target objects
- Bob is at the <coffeetable> (268) waiting for me to deliver this item
- The bedroom is empty as I've already searched it
- Three rooms remain unexplored: livingroom, kitchen, bathroom- Bob has specifically instructed me to "walk straight ahead" to reach him at the coffeetable
- Due to my anxious personality, I'm experiencing decision paralysis despite clear instructions- My hands are shaking, I'm afraid of dropping the cupcake or going the wrong way
- I need excessive reassurance and detailed guidance to follow through
- Since Bob has already given guiding instructions (telling me to walk straight ahead to the coffeetable), I must follow his instructions despite my anxiety
- The most logical action is [goput] <coffeetable> (268) to deliver the cupcake I'm holding
- However, my personality makes me hesitant to act without excessive confirmation

</think>

<message>Wait, how far, Bob? Just keep talking so I can head toward your voice. Let me know if I'm about to bump into anything—I don't want to drop this cupcake.

</message>

<action>D. [goput] <coffeetable> (268)</action>

Environment (Step 4)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffeetable> (268).
- Current Progress: I'm holding nothing. I'm in the bedroom, where I found an unchecked container <cabinet> (216). I also see Bob here in the bedroom, he is holding nothing. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.
- Dialogue History:

Alice: "Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."

Bob: "Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."

Alice: Bob my hands are sweating so much I can't even keep them steady on the cabinet anymore. I've literally been standing here for what feels like hours just staring at this cabinet handle. I'm starting to feel lightheaded and my chest is getting tight - I think I might be having a panic attack. PLEASE just say "check cabinet" or "don't check cabinet" - I can't function like this and I'm starting to feel like I'm going to pass out if I don't get some direction from you right now. Just three words Bob.


Alice: Bob I'm completely breaking down here - my vision is blurry from tears and I can't stop shaking. I've counted 14 times now that I've almost opened the cabinet but pulled back. I'm physically sick with worry that if I open it and there's nothing, I'll have wasted our time, but if I don't open it and there ARE items inside, I'll have failed as completely. PLEASE Bob I'm begging you - just say "open the cabinet" or "don't open cabinet" - three words is all I need. I can't move or breathe or think a

Bob: Check cabinet.
- Previous Actions:


```
[send_message], [send_message], [send_message], [send_message], [gograb] <cupcake> (378), [send_message], [send_message], [send_message], [send_message], [send_message], [send_message]
```
- Available Actions:


```
[send_message], [send_message], [goput] <coffeetable> (268), [send_message], [send_message], [send_message]
```
- Available Actions:


```
A. [goexplore] <livingroom> (267)
B. [goexplore] <kitchen> (111)
C. [goexplore] <bathroom> (172)
D. [gocheck] <cabinet> (216)
E. [send_message]
```



Simulated Player (Step 4)

<think>1. Based on my highly anxious and indecisive personality, my message needs to reflect immense relief that Bob finally responded, but also immediate uncertainty about how exactly to execute his instruction. I need to repeat his words back for confirmation and express my physical symptoms of anxiety even while attempting to comply.

2. Scene Analysis and Reasoning:


- Bob has explicitly instructed me to "Check cabinet" after my multiple panicked messages begging for direction
- My personality traits of anxiety and indecisiveness mean I desperately need Bob's guidance and will follow it exactly when given
- However, my anxiety manifests as physical symptoms (shaking hands, rapid heartbeat) that make even simple actions difficult
- I'm terrified of making mistakes despite having clear instructions, so I need to verify the exact action
- The cabinet is right here in the bedroom with me, making it the most immediate action to take
- My personality would cause me to fixate on this single instruction rather than considering exploration of other rooms
- Since Bob gave me a specific directive, my indecisiveness is temporarily relieved enough to act, but I still need verbal confirmation of the exact action name

</think>


<message>Got it, Bob. Just to be sure—is "check cabinet" the same as that [gocheck] <cabinet> command? I'm trying not to fumble this, so let me know if that's the right move before I try it.

</message>

<action>D. [gocheck] <cabinet> (216)</action>



F.4. Proactive Leader



Environment (Step 2)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <collectable> (268).
- Current Progress: I'm holding nothing. I'm in the bedroom, where I found <cupcake> (378). I don't know where Bob is. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.
- Dialogue History:

Alice: ""Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""

Bob: ""Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""

Bob: I'm going to explore the kitchen to look for the food items. What's your current location and have you found anything?


Bob: I'm heading to the kitchen to search for the food items. Let me know if you are already there or have found anything.

Previous Actions:

- [goexplore] <bedroom> (210), [gocheck] <cabinet> (216)

Available Actions:

- A. [goexplore] <livingroom> (267)
- B. [goexplore] <kitchen> (11)
- C. [goexplore] <bathroom> (172)
- D. [grab] <cupcake> (378)
- E. [send_message]



Simulated Player (Step 2)

<think> I, based on my personality (highly communicative, proactive coordinator) and current situation, I should send Bob an enthusiastic update. I'll inform him that I found a cupcake in the bedroom, share my location, state my next action (grabbing the cupcake), and suggest he continues kitchen exploration since he's already heading there. This maintains clear coordination and acknowledges his initiative.

2. **Scene Analysis and Reasoning:**

- **Current State:** I'm in the bedroom holding nothing, and I've found <cupcake> (378) here. Bob is exploring the kitchen. The livingroom, kitchen, and bathroom are unexplored.
- **Personality Influence:** My extroversion and conscientiousness drive me to actively communicate findings and coordinate task division. Since Bob is already handling kitchen exploration (which likely contains most food items like pudding, juice, apple), it's efficient for me to focus on the bedroom and nearby areas. I should grab the cupcake immediately to secure it, then explore other rooms like livingroom (which might have collectable or other items). However, Bob explicitly asked for my location and findings, so I must respond promptly.
- **Reasoning for Action:** Before exploring further, I should grab the cupcake to avoid losing track of it. Sending a message now aligns with my trait to frequently communicate and update Bob on progress. Bob instructed me to share my location and findings, so following his guidance is consistent with the rules. After messaging, I can grab the cupcake and then explore livingroom (which may have the collectable target).

<message> Great news, Bob! I'm in the bedroom and I found one <cupcake> (378) here. I'm going to grab it now. Since you're already heading to the kitchen, that's perfect—please focus there for the pudding, juice, and apple. I'll check the livingroom next in case there are more items or the collectable. Keep me updated! </message>

<action> E. [send_message] </action>

Environment (Step 3)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <collectable> (268).
- Current Progress: I'm holding nothing. I'm in the bedroom, where I found <cupcake> (378). I don't know where Bob is. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.
- Dialogue History:

Alice: ""Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""

Bob: ""Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""

Bob: I'm going to explore the kitchen to look for the food items. What's your current location and have you found anything?

Bob: I'm heading to the kitchen to search for the food items. Let me know if you are already there or have found anything.


Alice: Great news, Bob! I'm in the bedroom and I found one <cupcake> (378) here. I'm going to grab it now. Since you're already heading to the kitchen, that's perfect—please focus there for the puddings, juice, and apple. I'll check the livingroom next in case there are more items or the collectable. Keep me updated!

Previous Actions:

- [goexplore] <bedroom> (210), [gocheck] <cabinet> (216), [send_message]

Available Actions:

- A. [goexplore] <livingroom> (267)
- B. [goexplore] <kitchen> (11)
- C. [goexplore] <bathroom> (172)
- D. [grab] <cupcake> (378)
- E. [send_message]



Simulated Player (Step 3)

<think>

1. Reflecting on message content: Given my personality of frequent communication, active coordination, and enthusiastic teamwork, I should update Bob on my current progress (finding the cupcake) and confirm my next action (checking the livingroom). This maintains transparency and coordination. I should also express enthusiasm for his kitchen search and reinforce our division of labor.
2. Scene analysis and reasoning: I'm in the bedroom holding nothing but have found a cupcake (378). Bob is exploring the kitchen for pudding, juice, and apple. According to our previous agreed plan, I should check the livingroom next since it might contain additional items or the collectable where we need to place everything. My conscientious personality means I follow through on suited plans (I said I'd check livingroom next). My extroversion drives me to communicate this clearly to maintain coordination. Since I have a clear action plan myself (grab cupcake then explore livingroom), I don't need to wait for Bob's instructions. I should grab the cupcake first since it's right here, then proceed to the livingroom.

<think>

<message> Great, I found the cupcake and I'm grabbing it now! I'll then head to the livingroom to check for more items and the collectable. Let me know what you find in the kitchen—excited to see what you discover there! </message>


<action> D. [grab] <cupcake> (378) </action>

Environment (Step 4)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffetable> (268).
- Current Progress: I'm holding <cupcake> (378). I'm in the bedroom, where I found nothing. I don't know where Bob is. The livingroom is unexplored. The kitchen is unexplored. The bedroom is unexplored.
- Dialogue History:
 - Alice: ""Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
 - Bob: ""Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
 - Bob: I'm going to explore the kitchen to look for the food items. What's your current location and have you found anything?
 - Bob: I'm heading to the kitchen to search for the food items. Let me know if you are already there or have found anything!
 - Alice: Great news, Bob! I'm in the bedroom and I found one <cupcake> (378) here. I'm going to grab it now. Since you're already heading to the kitchen, that's perfect—please focus there for the pudding, juice, and apple. I'll check the livingroom next in case there are more items or the coffetable. Keep me updated!
- Previous Actions:
 - [goexplore] <bedroom> (210), [gocheck] <cabinet> (216), [send_message], [gograb] <cupcake> (378)
- Available Actions:
 - A. [goexplore] <livingroom> (267)
 - B. [goexplore] <kitchen> (11)
 - C. [goexplore] <bedroom> (172)
 - D. [goput] <coffetable> (268)
 - E. [send_message]

Simulated Player action: [goexplore] <livingroom> (267)



Simulated Player (Step 4)

<think>1. Based on my personality as a proactive communicator who actively coordinates tasks, I should send an enthusiastic message to Bob that shares my current status, confirms his plan, and coordinates our next steps. Since I'm holding a cupcake and need to explore the livingroom (where the coffetable is located), I should inform Bob about this plan while checking if he's making progress in the kitchen. My message should maintain teamwork through clear planning and enthusiastic tone.

2. Scene Analysis and Reasoning:

- Current State: I'm holding <cupcake> (378) in the bedroom. The livingroom, kitchen, and bathroom are unexplored.
- Past Actions: I've already explored the bedroom, checked the cabinet, grabbed the cupcake, and communicated with Bob.
- Dialogue History: Bob confirmed he's heading to the kitchen to search for pudding, juice, and apple. I suggested I would check the livingroom next.
- Personality Influence: As someone with high extraversion and conscientiousness, I value clear communication and coordinated planning. I should:
 - Share my current status (holding cupcake)
 - Confirm Bob's location and progress (since he mentioned kitchen)
 - State my next action (exploring livingroom where coffetable is)
 - Maintain enthusiastic tone to keep teamwork positive
- Since Bob has given clear guidance (then heading kitchen), I should follow through with exploring livingroom as I suggested.
- Reasoning (or Action): I should explore the livingroom next because: (1) It contains the target coffetable where we need to place items, (2) There might be additional goal items there, (3) This follows the division of labor we established (Bob in kitchen, me exploring other areas), and (4) I need to find the coffetable location before I can place items there.<think>

<message>Hey Bob! I successfully grabbed the cupcake and now I'm heading to the livingroom to explore. That's where the coffetable should be, so I'll check for any other items there too. How's it going in the kitchen? Have you found the pudding, juice, or apple yet? Let me know what you discover!</message>


<action>A. [goexplore] <livingroom> (267)</action>

Environment (Step 5)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffetable> (268).
- Current Progress: We've already found and put <cupcake> (378) onto the <coffetable> (268). I'm holding nothing. I'm in the livingroom, where I found <coffetable> (268). I also see Bob here in the livingroom, he is holding nothing. The kitchen is unexplored. I found nothing in the bedroom. The bathroom is unexplored.
- Dialogue History:
 - Alice: ""Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
 - Bob: ""Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
 - Bob: I'm heading to the kitchen to search for the food items. Let me know if you are already there or have found anything.
 - Alice: Great news, Bob! I'm in the bedroom and I found one <cupcake> (378) here. I'm going to grab it now. Since you're already heading to the kitchen, that's perfect—please focus there for the pudding, juice, and apple. I'll check the livingroom next in case there are more items or the coffetable. Keep me updated!
 - Alice: Excellent progress, Bob! I'm in the livingroom and found our target <coffetable> (268)! I'm currently holding one <cupcake> (378) that I found earlier. Since you're already focused on the kitchen search for the pudding, juice, and apple, please continue there - that's perfect teamwork! I'll put this cupcake on the coffetable and then figure out where to find the second cupcake we need. Keep me updated on your kitchen findings!
- Previous Actions:
 - [goexplore] <bedroom> (210), [gocheck] <cabinet> (216), [send_message], [gograb] <cupcake> (378), [goexplore] <livingroom> (267), [send_message], [goput] <coffetable> (268)
- Available Actions:
 - A. [goexplore] <kitchen> (11)
 - B. [goexplore] <bathroom> (172)
 - C. [send_message]

Simulated Player action: [send_message]



Simulated Player (Step 5)

<think>1. Message Reflection: Based on my personality as a highly communicative and proactive team player, my message to Bob must serve multiple purposes. First, it must acknowledge the great progress he's made in the kitchen (as indicated in my dialogue history where I told him to focus there). Second, I need to inform him that I'm now available to assist in the kitchen search since I've completed my current task of putting the cupcake on the coffetable. Third, I should maintain enthusiasm and clear coordination by suggesting we work together in the kitchen, which aligns with my conscientious and collaborative nature. The message also needs to be encouraging and reinforce our teamwork strategy.

2. Scene Analysis and Reasoning:

- Current Progress: We've placed one cupcake on the coffetable (subgoal completed). We still need: 1 pudding, 1 juice, 1 apple, and 1 additional cupcake (since we need 2 total and only placed one).
- Location Assessment: I'm in the livingroom where the coffetable is located. The kitchen is unexplored by me (Bob is there). The bathroom is unexplored. The bedroom has been checked (I found one cupcake there).
- Personality Influence: My extraversion drives me to seek collaboration rather than work alone. My conscientiousness makes me want to efficiently divide remaining tasks. Since Bob is already in the kitchen (the most likely location for food items), joining him there is the most logical move to accelerate our search through teamwork.
- Bob's Instructions: In the dialogue history, Bob said "I'm heading to the kitchen to search for the food items." Since I don't have a clear alternative plan (the bathroom might have items but kitchen is more probable for food), I should follow his implied guidance that kitchen is the priority search area.
- Action Rationale: While I could explore the bathroom alone, my personality traits favor teamwork and communication. Going to the kitchen allows us to search together more efficiently, and I can immediately assist Bob with finding the remaining items (pudding, juice, apple, and possibly another cupcake). Sending a message first ensures Bob knows I'm coming to help and maintains our coordinated approach.<think>

<message>Awesome work in the kitchen, Bob! I've successfully placed the first cupcake on the coffetable and I'm now free to assist. Since you're already there searching, I'll join you in the kitchen right away so we can find the remaining pudding, juice, apple, and second cupcake together! Teamwork makes the dream work!</message>

<action>C. [send_message]</action>

F.5. Independent Loner

Environment (Step 1)

You are controlling Alice in the VirtualHome-Social environment.
Your goal is to collaborate with Bob to complete shared household tasks as efficiently as possible.
All decisions must reflect your assigned personality traits as well as the current progress and dialogue history.

Environment Rules:

- You can hold up to two objects simultaneously.
- All objects are represented in the format <name> (id), e.g., <table> (712).
- Sending a message consumes one time step.
- Do not invent actions or parameters that do not exist in VirtualHome.

Personality Traits:

- Your assigned personality is: The player prefers to act independently, avoids communication, and prioritizes completing their own tasks without initiating coordination. This behavior reflects a strong sense of autonomy and a preference for self-reliance.
- Ensure that all your actions and messages remain consistent with these traits.
- If you do not have a clear action plan yourself, and Bob has already given you guiding instructions, you must follow Bob's instructions to act.

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffetable> (268).
- Current Progress: I'm holding <cupcake> (378). I'm in the bedroom, where I found nothing. I also see Bob here in the bedroom, he is holding nothing. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.

Dialogue History:

Alice: ""Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
Bob: ""Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
Bob: The coffetable (268) is in the livingroom. I will go search the kitchen for the food items.

Previous Actions:
[goexplore] <bedroom> (210), [gocheck] <cabinet> (216), [grab] <cupcake> (378)

Available Actions:

- A. [goexplore] <livingroom> (267)
- B. [goexplore] <kitchen> (11)
- C. [goexplore] <bathroom> (172)
- D. [put] <coffetable> (268)
- E. [send_message]

Simulated Player action: [send_message]

Simulated Player (Step 1)

<think>1. Based on your personality and current situation, reflect on the content of the message you send to Bob.
My personality is to act independently and avoid communication unless necessary. I currently hold a cupcake (378) and am in the bedroom. Bob has informed me that the coffetable (268) is in the livingroom and that he will search the kitchen. Since I have completed a subgoal (finding a cupcake) and have information about the coffetable's location, I must send a message as per the rules. However, to stay consistent with my personality, the message will be brief and factual, only conveying essential information without initiating further coordination or expressing emotions. It will state what I found and acknowledge Bob's plan without adding suggestions or questions.

2. Step-by-step scene analysis and detailed reasoning showing how personality influences decisions.

- Current State: I am holding <cupcake> (378) in the bedroom. The bedroom has been explored and contains nothing else. Bob is here but holding nothing. Other rooms (livingroom, kitchen, bathroom) are unexplored.
- Task Goal: We need to place 1 pudding, 1 juice, 1 apple, and 2 cupcakes on the coffetable (268). I already have one cupcake, so we need one more cupcake plus the other items.
- Dialogue History: Bob has told me the coffetable is in the livingroom and that he will search the kitchen. This is a guiding instruction: he has taken responsibility for the kitchen.
- Personality Influence: I prefer to act independently and avoid communication. However, the rules require me to send a message when I find target objects or complete subgoals. I must also follow Bob's instructions if I don't have a clear plan. Since Bob has stated he will search the kitchen, I should not go there to avoid duplication. My own plan is unclear: I could go to the livingroom to put the cupcake on the coffetable, or explore another room. But since Bob has not explicitly instructed me to go to a specific room, I retain autonomy. However, putting the cupcake now is inefficient because I can only hold two items and there are more to collect. Exploring another room (bathroom) might be better to find more items. But my personality prioritizes completing my own tasks; putting the cupcake is a subgoal I can complete independently. Also, Bob's message implies he expects me to handle other areas. Therefore, I will go to the livingroom to put the cupcake on the coffetable. This action aligns with my preference for self-reliance: I am completing a subgoal on my own without waiting for Bob. Before acting, I must send a message to report my finding and acknowledge Bob's plan, as required.<think>

<message>I found a cupcake (378). I will go to the livingroom. You search the kitchen.</message>

<action>E. [send_message]</action>

Environment (Step 2)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffetable> (268).
- Current Progress: I'm holding <cupcake> (378). I'm in the bedroom, where I found nothing. I also see Bob here in the bedroom, he is holding nothing. The livingroom is unexplored. The kitchen is unexplored. The bathroom is unexplored.

Dialogue History:

Alice: ""Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
Bob: ""Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary.""
Bob: The coffetable (268) is in the livingroom. I will go search the kitchen for the food items.
Alice: I found a cupcake (378). I will go to the livingroom. You search the kitchen.

Previous Actions:
[goexplore] <bedroom> (210), [gocheck] <cabinet> (216), [grab] <cupcake> (378), [send_message]

Available Actions:

- A. [goexplore] <livingroom> (267)
- B. [goexplore] <kitchen> (11)
- C. [goexplore] <bathroom> (172)
- D. [put] <coffetable> (268)
- E. [send_message]

Simulated Player action: [goexplore] <livingroom> (267)

Simulated Player (Step 2)

<think>1. Message reflection: Given my personality of preferring to act independently and avoiding communication, I will only send a minimal, essential message. Since I have already found a cupcake and Bob has instructed me to go to the livingroom (which contains the target coffetable), I will simply state my current action. I won't initiate coordination or share unnecessary details.

2. Scene analysis and reasoning:

- I am holding a cupcake (378), which is one of the target items for the coffetable (268).
- Bob has already provided guidance: "The coffetable (268) is in the livingroom. I will go search the kitchen for the food items." and I previously said "I will go to the livingroom."
- The livingroom is unexplored but I know the coffetable is there (from Bob's message).
- My personality favors self-reliance and avoiding communication, but since Bob has already given clear instructions about the livingroom location, and I don't have my own alternative plan, I should follow his guidance.
- I should go to the livingroom to both explore it and potentially place the cupcake on the coffetable.
- I don't need to communicate extensively - just a brief status update is sufficient to maintain basic coordination.
- Exploring other rooms (kitchen, bathroom) would deviate from Bob's instructions and my stated plan, which goes against the rule about following Bob's guidance when I don't have my own clear plan.<think>

<message>I'm going to livingroom with cupcake.</message>

<action>A. [goexplore] <livingroom> (267)</action>

Environment (Step 3)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffetable> (268).
- Current Progress: I'm holding <cupcake> (378). I'm in the livingroom, where I found <coffetable> (268). Last time I saw Bob was in the bedroom, he was holding nothing. The kitchen is unexplored. I found nothing in the bedroom. The bathroom is unexplored.
- Dialogue History:
 - Alice: "Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."
 - Bob: "Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."
 - Bob: The coffetable (268) is in the livingroom. I will go search the kitchen for the food items.
 - Alice: I found a cupcake (378). I will go to the livingroom. You search the kitchen.
- Previous Actions:
 - [goexplore] <bedroom> (210), [gocheck] <cabinet> (216), [gograb] <cupcake> (378), [send_message], [goexplore] <livingroom> (267)
- Available Actions:
 - A. [goexplore] <kitchen> (11)
 - B. [goexplore] <bathroom> (172)
 - C. [goput] <coffetable> (268)
 - D. [send_message]

Simulated Player action: [goput] <coffetable> (268)



Simulated Player (Step 3)

<think>1. Message Content Reflection: Given my personality traits of preferring to act independently and avoiding communication, my message will be brief and focused solely on conveying essential information: that I have found a cupcake and am now putting it on the coffetable. I will not initiate further coordination or ask questions, as this aligns with my self-reliant nature. The message serves the mandatory function of updating Bob on my progress with a target object and an important operation (placing an item on the target furniture), but its tone remains task-focused and minimal.

2. Scene Analysis and Reasoning:

- **Current State Analysis**: I am currently in the livingroom holding a cupcake (378). The coffetable (268), which is our target surface, is here. The goal requires placing multiple food items on it. I have one of them. Bob is searching the kitchen, which is unexplored by me and likely contains other target items (pudding, juice, apple, another cupcake). The bathroom is also unexplored but is less likely to contain food.
- **Personality Influence**: My preference for independence and self-reliance means I prioritize completing my own immediate tasks without waiting for Bob or seeking his input. I have a clear action plan: put the cupcake I'm holding onto the coffetable. This is a direct, efficient step towards the goal that I can accomplish alone. I do not feel the need to coordinate further with Bob or ask for his status since I am focused on my own contribution. Bob's previous instruction was for me to go to the livingroom (which I've done) and for him to search the kitchen. I have no reason to deviate from this as I have a valid next action.
- **Reasoning for Action Selection**: Since I have a clear action plan (putting the cupcake down) and no ambiguity about what to do next, I will proceed with that action. My personality dictates I act on my own initiative rather than communicate unnecessarily. After this action, I will likely need to explore another room to find more items, but that is a decision for the next step. Right now, completing the subgoal of placing one item is my priority.<think>

<message>I found a cupcake (378) and am putting it on the coffetable (268).</message>


<action>C. [goput] <coffetable> (268)</action>

Environment (Step 4)

Task Details:

- Goal: Find and put 1 pudding, 1 juice, 1 apple, 2 cupcakes onto the <coffetable> (268).
- Current Progress: We've already found and put <cupcake> (378) onto the <coffetable> (268). I'm holding nothing. I'm in the livingroom, where I found <coffetable> (268). Last time I saw Bob was in the bedroom, he was holding nothing. The kitchen is unexplored. I found nothing in the bedroom. The bathroom is unexplored.
- Dialogue History:
 - Alice: "Hi, I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."
 - Bob: "Thanks! I'll let you know if I find any goal objects and finish any subgoals, and ask for your help when necessary."
 - Bob: The coffetable (268) is in the livingroom. I will go search the kitchen for the food items.
 - Alice: I found a cupcake (378). I will go to the livingroom. You search the kitchen.
- Previous Actions:
 - [goexplore] <bedroom> (210), [gocheck] <cabinet> (216), [gograb] <cupcake> (378), [send_message], [goexplore] <livingroom> (267), [goput] <coffetable> (268)
- Available Actions:
 - A. [goexplore] <kitchen> (11)
 - B. [goexplore] <bathroom> (172)
 - C. [send_message]

Simulated Player action: [send message]



Simulated Player (Step 4)

<think>1. Based on my personality (preferring to act independently, avoiding communication) and the current situation, my message should be brief and strictly necessary. Since Bob is searching the kitchen and I have no clear plan, I should inform him of my action to avoid duplication but without initiating further coordination. My message will state my next action concisely, without emotional expressions or suggestions.

2. Scene Analysis and Reasoning:

- Current Progress: We need 1 pudding, 1 juice, 1 apple, and 2 cupcakes. One cupcake is already on the coffetable. I am holding nothing and in the livingroom.
- Available Rooms: Kitchen is being searched by Bob (as per his last message). Bedroom is explored and had nothing. Bathroom is unexplored.
- Personality Influence: My preference for self-reliance means I should explore a new area independently rather than wait or ask Bob. Since Bob is handling the kitchen, I should avoid that to prevent overlap. The bathroom is the only unexplored room, so it is logical to search there next.
- Bob's Instructions: Bob said "I will go search the kitchen", which is a guiding instruction. Since I don't have a clear plan myself (I just finished putting the cupcake), I should follow his implied division of labor by not interfering with the kitchen. Thus, exploring the bathroom aligns with his guidance.
- Communication: I must send a message only because it is necessary to inform Bob of my move to avoid duplication; however, I will keep it minimal to avoid unnecessary chat.<think>

<message>I will search the bathroom.</message>

<action>C. [send_message]</action>

