



Sun StorageTek 5800 System SDK Reference Manual



Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054
U.S.A.

Part No: 820-4797
June 2008

Copyright 2008 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more U.S. patents or pending patent applications in the U.S. and in other countries.

U.S. Government Rights – Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

This distribution may include materials developed by third parties.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, the Solaris logo, the Java Coffee Cup logo, docs.sun.com, StorageTek Java, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and SunTM Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Products covered by and information contained in this publication are controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical or biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2008 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. Tous droits réservés.

Sun Microsystems, Inc. détient les droits de propriété intellectuelle relatifs à la technologie incorporée dans le produit qui est décrit dans ce document. En particulier, et ce sans limitation, ces droits de propriété intellectuelle peuvent inclure un ou plusieurs brevets américains ou des applications de brevet en attente aux Etats-Unis et dans d'autres pays.

Cette distribution peut comprendre des composants développés par des tierces personnes.

Certains composants de ce produit peuvent être dérivées du logiciel Berkeley BSD, licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays; elle est licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, le logo Solaris, le logo Java Coffee Cup, docs.sun.com, StorageTek Java et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui, en outre, se conforment aux licences écrites de Sun.

Les produits qui font l'objet de cette publication et les informations qu'il contient sont régis par la législation américaine en matière de contrôle des exportations et peuvent être soumis au droit d'autres pays dans le domaine des exportations et importations. Les utilisations finales, ou utilisateurs finaux, pour des armes nucléaires, des missiles, des armes chimiques ou biologiques ou pour le nucléaire maritime, directement ou indirectement, sont strictement interdites. Les exportations ou réexportations vers des pays sous embargo des Etats-Unis, ou vers des entités figurant sur les listes d'exclusion d'exportation américaines, y compris, mais de manière non exclusive, la liste de personnes qui font objet d'un ordre de ne pas participer, d'une façon directe ou indirecte, aux exportations des produits ou des services qui sont régis par la législation américaine en matière de contrôle des exportations et la liste de ressortissants spécifiquement désignés, sont rigoureusement interdites.

LA DOCUMENTATION EST FOURNIE "EN L'ETAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFACON.

Contents

Preface	7
1 Introduction to the Sun StorageTek 5800 System Client SDK	11
Overview of the SDK	11
SDK Terms of Use	12
SDK Components	12
Supported Operating Systems	12
Software Requirements	13
Java API Software Requirements	13
C API Software Requirements	13
Open Edition Software Requirements	13
SDK Installation Instructions	13
5800 System Semantics Overview	14
Data and Metadata	14
Metadata Schema	14
Attributes	14
Namespace	14
5800 System Query Language	15
SDK Application Deployment	15
Java API	15
C API	15
2 Example Applications	17
Example Application Summary	17
Java Example Applications	18
Example Overview	19
Before You Begin	19

Running the Applications	19
Building the Java Example Applications	20
Running a Java Example Application	20
About the Example Application Source Code	20
Example Applications	20
StoreFile	21
CheckIndexed	23
RetrieveData	24
RetrieveMetadata	25
AddMetadata	26
DeleteRecord	28
Query	29
RetrieveSchema	31
GetDate	32
C Example Applications	33
Example Overview	33
Before You Begin	33
Building the C Example Applications	34
Running a C Example Application	34
About the C Example Application Source Code	34
Example Applications	34
StoreFile	35
CheckIndexed	36
RetrieveData	37
RetrieveMetadata	38
AddMetadata	39
DeleteRecord	41
Query	42
RetrieveSchema	44
3 Sun StorageTek 5800 System Open Edition Software	45
Introduction to the Open Edition Software	45
Software Requirements	46
Open Edition Software Startup	46
Open Edition Software Shutdown	46

Schema Modification	46
▼ To Activate a New Schema for the Open Edition Software	46
Open Edition Software Event Log	47
Open Edition Software Configuration Settings	47
 Index	 49

Preface

The *Sun StorageTek 5800 System SDK Reference Manual* is written for programmers and application developers. This document, along with the *Sun StorageTek 5800 SystemClient API Reference Manual*, provides the information that you need in order to develop custom applications for the Sun StorageTek 5800 System.

How This Book Is Organized

- [Chapter 1, “Introduction to the Sun StorageTek 5800 System Client SDK,”](#) provides an introduction to the Sun StorageTek 5800 System client Software Development Kit (SDK) and its components.
- [Chapter 2, “Example Applications,”](#) provides information about the Java and C example applications that are provided with the Sun StorageTek 5800 System SDK.
- [Chapter 3, “Sun StorageTek 5800 System Open Edition Software,”](#) provides information on running test client applications without having to connect to a 5800 system..

Related Books

- *Sun StorageTek 5800 System Regulatory and Safety Compliance Manual*, part number 819–3809
- *Sun StorageTek 5800 System Site Preparation Guide*, part number 820–1635
- *Sun StorageTek 5800 System Administration Guide*, part number 820–4118
- *Sun StorageTek 5800 System Client API Reference Manual*, part number 820–4796
- *Sun StorageTek 5800 System 1.1.1 Release Notes*, part number 820–4120

Related Third-Party Web Site References

Third-party URLs are referenced in this document and provide additional, related information.

Note – Sun is not responsible for the availability of third-party web sites mentioned in this document. Sun does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Sun will not be responsible or liable for any actual or alleged damage or loss caused or alleged to be caused by or in connection with use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

Documentation, Support, and Training

The Sun web site provides information about the following additional resources:

- [Documentation](http://www.sun.com/documentation/) (<http://www.sun.com/documentation/>)
- [Support](http://www.sun.com/support/) (<http://www.sun.com/support/>)
- [Training](http://www.sun.com/training/) (<http://www.sun.com/training/>)

Typographic Conventions

The following table describes the typographic conventions that are used in this book.

TABLE P-1 Typographic Conventions

Typeface	Meaning	Example
AaBbCc123	The names of commands, files, and directories, and onscreen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. <code>machine_name%</code> you have mail.
AaBbCc123	What you type, contrasted with onscreen computer output	<code>machine_name% su</code> Password:
<i>aabbcc123</i>	Placeholder: replace with a real name or value	The command to remove a file is <i>rm filename</i> .

TABLE P-1 Typographic Conventions (Continued)

Typeface	Meaning	Example
<i>AaBbCc123</i>	Book titles, new terms, and terms to be emphasized	Read Chapter 6 in the <i>User's Guide</i> . A <i>cache</i> is a copy that is stored locally. Do <i>not</i> save the file. Note: Some emphasized items appear bold online.

Shell Prompts in Command Examples

The following table shows the default UNIX® system prompt and superuser prompt for the C shell, Bourne shell, and Korn shell.

TABLE P-2 Shell Prompts

Shell	Prompt
C shell	machine_name%
C shell for superuser	machine_name#
Bourne shell and Korn shell	\$
Bourne shell and Korn shell for superuser	#

Sun Welcomes Your Comments

Sun is interested in improving its documentation and welcomes your comments and suggestions. You can submit your comments by clicking the Feedback link on the <http://docs.sun.com> web site.

Please include the title and part number of your document with your feedback:

Sun StorageTek 5800 System SDK Reference Manual, part number 820-4797

Introduction to the Sun StorageTek 5800 System Client SDK

This chapter provides an introduction to the Sun™ StorageTek™ 5800 System client Software Development Kit (SDK) and its components.

The following topics are discussed:

- “Overview of the SDK” on page 11
- “SDK Terms of Use” on page 12
- “SDK Components” on page 12
- “Supported Operating Systems” on page 12
- “Software Requirements” on page 13
- “SDK Installation Instructions” on page 13
- “5800 System Semantics Overview” on page 14
- “5800 System Query Language” on page 15
- “SDK Application Deployment” on page 15

Overview of the SDK

The 5800 system client SDK enables you to work with data and metadata stored on a 5800 system.

This document assumes that you have a basic understanding of how the 5800 system uses data and metadata. For more information, see [“5800 System Semantics Overview” on page 14](#).

The SDK comes with open edition software that enables you to test client applications without having to connect to a 5800 system. For further documentation on the open edition software, see [Chapter 3, “Sun StorageTek 5800 System Open Edition Software.”](#) Also refer to the *Sun StorageTek 5800 System Administration Guide* to better understand the type of server being emulated.

The SDK provides separate Application Programming Interfaces (APIs) for the Java™ and C languages. These APIs enable you to store and retrieve data and to store, retrieve, query, and delete metadata records.

For more information on the Java and C APIs, refer to the *Sun StorageTek 5800 SystemClient API Reference Manual*. Also, see [Chapter 2, “Example Applications.”](#) For known bugs, see the *Sun StorageTek 5800 System Release Notes*.

SDK Terms of Use

The 5800 system client SDK is released to you under the following copyright notice:

“Copyright 2007 Sun Microsystems, Inc. All rights reserved. Use is subject to license terms.”

License terms are contained in the file `StorageTek_5800_SLA&Entitlement&PRN.txt` in the top-level directory of the installation. Licence terms for embedded software are in the file `LICENSE.txt` in the same directory.

SDK Components

The 5800 system client SDK distribution includes a Java distribution (Java examples and Java libraries), a C distribution (C examples and libraries), and the 5800 system open edition software. All parts of the SDK support Solaris, Linux, and Windows environments.

The Java and C example programs serve both as examples of how to program a client application and as generally useful utilities in their own right.

The contents of the .zip archive include:

- `SDK_Overview_README.html`
- `doc/`
- `java/`
- `c/`
- `openedition/`
- `StorageTek_5800_SLA&Entitlement&PRN.txt`
- `LICENSE.txt`

Supported Operating Systems

This release supports the following operating systems:

- Red Hat Enterprise Linux 4 (32 bit)
- Red Hat Enterprise Linux 4 (64 bit)
- Solaris 9 SPARC
- Solaris 10 SPARC
- Solaris 10 x64 and x86

- Windows 2003 Server (32 bit)

Software Requirements

This release requires the following software. For detailed software configuration information, refer to the specific section or chapter in this book.

Java API Software Requirements

The 5800 system Java API requires at minimum the JDK™ 5.0 software.

C API Software Requirements

The 5800 system C API requires the following software:

- All platforms
 - GNU make
 - Perl
- Solaris: Sun Studio
- Linux: gcc
- Windows 2003 server:
 - Microsoft Visual C++ Express Edition 2005
 - Microsoft Windows SDK
 - Cygwin (See <http://www.cygwin.com>)

Open Edition Software Requirements

The 5800 system open edition software requires at minimum the JDK™ 5.0 software.

SDK Installation Instructions

The 5800 system SDK is compressed in a file with a name similar to `StorageTek5800_SDK_1_1-20.zip`, where `1_1-20` refers to the version (`1_1`) and build number (`20`). This `.zip` file expands into a directory `StorageTek5800_SDK_1_1-20`, which contains the entire SDK.

5800 System Semantics Overview

This section provides an overview of 5800 system semantics.

Data and Metadata

The 5800 system stores two types of data: *arbitrary object data* and *structured metadata records*. Every metadata record is associated with exactly one data object. Every data object has at least one metadata record. A unique object identifier (OID) is returned when a metadata record is stored. The OID can later be used to retrieve the metadata record or its object data. In addition, metadata records can be retrieved by a query:

OID \leftrightarrow Metadata Record \rightarrow Object Data

The two types of metadata are *system metadata* and *user metadata*. The names and types of system metadata are predefined and cannot be overridden by the user.

Metadata Schema

A user metadata record consists of a set of attributes. The set of possible attributes is defined by the schema. Only one schema exists for each 5800 system. For information on configuring a schema, see “Configuring Metadata and File System Views” in *Sun StorageTek 5800 System Administration Guide*.

The 5800 system open edition software loads its schema from an XML file. The `metadata_merge_config` utility can be used to extend the default schema, appending the new entries to the original schema, which is then read by the open edition software. For additional information, see [Chapter 2, “Example Applications,”](#) and [Chapter 3, “Sun StorageTek 5800 System Open Edition Software.”](#)

Attributes

For information on the valid data types that you can use when specifying attributes in a schema, see “Configuring Metadata and File System Views” in *Sun StorageTek 5800 System Administration Guide*.

Namespace

A namespace is a container that holds a set of typed attribute names. Attribute names must be unique within a given namespace. Defining a namespace is a way to organize and group together a set of related attribute names for a given application. For more information, see “Configuring Metadata and File System Views” in *Sun StorageTek 5800 System Administration Guide*.

5800 System Query Language

The 5800 system Java and C APIs both have a `Query` method that passes a query string to the 5800 system. Queries are presented to the name-value metadata cache.

For more information on the 5800 system query language, see Chapter 4, “Sun StorageTek 5800 System Query Language,” in *Sun StorageTek 5800 SystemClient API Reference Manual*.

SDK Application Deployment

Java API

You must deploy `honeycomb-client.jar` with any application using the Java API. If you are using the SDK example applications, you must also deploy `honeycomb-sdk.jar`.

C API

The files in the `lib` directory must be deployed with any application using the C API. Different `lib` directories exist for different operating systems. You must use the correct `lib` directory for the OS under which the application is deployed. The `LD_LIBRARY_PATH` environment variable must be set accordingly for Unix systems. In the Windows environment, you must update the `PATH` environment variable.

Example Applications

This chapter provides information about the Java and C example applications that are provided with the 5800 system SDK.

The following topics are discussed:

- “Example Application Summary” on page 17
- “Java Example Applications” on page 18
- “C Example Applications” on page 33

Example Application Summary

Table 2–1 summarizes the Java and C example applications provided with the 5800 system SDK. All code examples are command-line applications.

For detailed information about the Java example applications, see “Java Example Applications” on page 18.

For detailed information about the C example applications, see “C Example Applications” on page 33.

TABLE 2–1 5800 system Client SDK Example Applications

Application	Java Version	C Version
StoreFile – Enables you to specify a file from the command line to store on a 5800 system server as data. You can also specify metadata to include with the file.	“StoreFile” on page 21	“StoreFile” on page 35

TABLE 2-1 5800 system Client SDK Example Applications (Continued)

Application	Java Version	C Version
CheckIndexed – Checks if the metadata for an object is present in the query engine, and inserts it if not.	“CheckIndexed” on page 23	“CheckIndexed” on page 36
RetrieveData – Enables you to retrieve data from the 5800 system server by Object ID. The data object is sent to standard output or to a file specified on the command line.	“RetrieveData” on page 24	“RetrieveData” on page 37
RetrieveMetadata – Enables you to retrieve a metadata record from the 5800 system server associated with the supplied OID. The metadata record is printed to standard output.	“RetrieveMetadata” on page 25	“RetrieveMetadata” on page 38
AddMetadata – Enables you to specify name-value pairs from the command line to store on a 5800 system server as a metadata record.	“AddMetadata” on page 26	“AddMetadata” on page 39
DeleteRecord – Deletes a record from the 5800 system server for an OID supplied on the command line.	“DeleteRecord” on page 28	“DeleteRecord” on page 41
Query – Queries a 5800 system server for specified metadata. The query string is provided on the command line. Query can print out the results as a list of name-value pairs or as a list of OIDs. You can specify the maximum number of results returned.	“Query” on page 29	“Query” on page 42
RetrieveSchema – Retrieves the schema from a 5800 system server, printing it to standard output.	“RetrieveSchema” on page 31	“RetrieveSchema” on page 44
GetDate – Gets the date.	“GetDate” on page 32	N/A

Java Example Applications

This section provides detailed information about the Java example applications provided with the 5800 system client SDK.

Example Overview

Included with the 5800 system SDK are several command-line example applications that demonstrate the Java API. The example applications are located in the SDK in the `java/examples` directory. These example applications come complete with a build script.

Before You Begin

Make sure you configure your software environment before using the Java example applications.

- In Microsoft Windows 2003:

Add `C:\Program Files\Java\jdk_version\bin` to the PATH environment variable where *jdk_version* is the version, for example, `jdk5.0`.

To edit the windows PATH environment variable:

1. Click the Start button.
2. Right-click My Computer and select properties to launch System Properties.
3. Click the Advanced tab.
4. Click Environment Variables.
5. Under System Variables, scroll down and click Path.
6. Click Edit to launch Edit System Variable.
7. Add the Java path name to the PATH environment variable. Make certain each path name is separated by a semicolon (;).
8. Click OK to close each window.

Also see [“Software Requirements” on page 13](#).

Running the Applications

UNIX (`.sh`) and Windows (`.bat`) scripts for running the example applications are provided in the `java/scripts/` directory. These scripts must be run from the `java/scripts/` directory. The scripts illustrate the CLASSPATH environment variable required. The `.jar` files are in the `java/lib/` directory.

Note – The usage messages printed by the applications omit the CLASSPATH environment variable for the sake of readability. If you are running the example application without using the provided scripts, then you must set the CLASSPATH environment variable manually.

Building the Java Example Applications

To build the Java example applications, go to the `java/examples/` directory and execute the `master-build.sh` script for Solaris and Linux environments or the `master-build.bat` script for Windows environments. These scripts build the examples and put them in the `honeycomb-sdk.jar` archive located in the `java/lib` directory.

Running a Java Example Application

Once you have built the Java example applications, go to the `java/scripts` directory and execute the `.sh` scripts for Solaris and Linux environments or `.bat` scripts for Windows environments:

Syntax: *script_name arguments*

See the scripts for details of how the applications are run.

About the Example Application Source Code

The Java example applications are all simple applications that follow the same basic structure. First, `CommandLine.parse` is called to parse the argument list. Next, the appropriate method in the `NameValueObjectArchive` class is called to communicate with the 5800 system server. Finally, output is delivered back to either standard output, a file, or both. Refer to the comments in the sample code for further details.

Example Applications

The following sections describe the Java example applications that are included with the 5800 system client SDK:

- “StoreFile” on page 21
- “CheckIndexed” on page 23
- “RetrieveData” on page 24
- “RetrieveMetadata” on page 25
- “AddMetadata” on page 26
- “DeleteRecord” on page 28
- “Query” on page 29
- “RetrieveSchema” on page 31
- “GetDate” on page 32

StoreFile

Stores a file and associated metadata to a 5800 system server.

Synopsis

```
java StoreFile <IP | HOST> <FILE> [OPTIONS]
```

Description

Stores a file and its associated metadata record. If no `-m` options are specified, a metadata record without user content is generated. The OID of the metadata record is printed to `stdout`.

Note – StoreFile interprets the time in metadata arguments as local time zone unless the T..Z format indicating UTC is used. For example, 1952-10-27T00:30:29.999Z.

Options

```
-m <name>=<value>
```

Any number of `-m` options can be specified. Each `-m` option specifies a single (name, value) pair.

`<name>` should be specified in the format `<namespace>.<attribute>`. Use double quotes if `<value>` is a string containing spaces.

```
-h
```

Print this message.

Examples

```
java StoreFile 10.152.0.12 myFile
java StoreFile server myFile.jpg \
    -m filesystem.mimetype="image/jpeg"
java StoreFile server myFile \
    -m system.test.type_char="do re mi"
java StoreFile server myFile \
    -m system.test.type_string="fa so la"
java StoreFile server myFile \
    -m system.test.type_long=123
java StoreFile server myFile \
    -m system.test.type_double=1.23
java StoreFile server myFile \
    -m system.test.type_binary=0789abcdef
java StoreFile server myFile \
    -m system.test.type_date=2010-10-20
```

```
java StoreFile server myFile \  
    -m system.test.type_time=23:30:29  
java StoreFile server myFile \  
    -m system.test.type_timestamp="2010-10-20 23:30:29.999"  
java StoreFile server myFile \  
    -m name1=value1 -m name2="value 2"
```

Source Code

```
java/examples/StoreFile.java
```

CheckIndexed

Ensure an object can be queried. Checks if the metadata for an object is present in the query engine, and inserts the metadata if it is not present.

Synopsis

```
java CheckIndexed <IP | HOST> <OID> [OPTIONS]
```

Description

Check with the 5800 systemserver to determine if the specified OID has become queryable. If not, attempt to make it queryable.

A short message about the supplied OID is printed to stdout:

```
Object OID was already queryable.  
Object OID not yet queryable.  
Object OID has now been made queryable.
```

Options

-h

Print this message.

Examples

```
java CheckIndexed server \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000  
java CheckIndexed 10.152.0.12 \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000
```

Source Code

```
java/examples/CheckIndex.java
```

RetrieveData

Retrieves data from a 5800 system server.

Synopsis

```
java RetrieveData <IP | HOST> <OID> [FILE] [OPTIONS]
```

Description

Retrieves data from the 5800 system. The OID specifies what data to retrieve. Data is written to FILE, if specified, otherwise to stdout.

Options

-h

Print this message.

Examples

```
java RetrieveData archivehost \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \  
    /archive/log.1  
java RetrieveData 10.152.0.12 \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \  
    /archive/log.2
```

Source Code

```
java/examples/RetrieveData.java
```


RetrieveMetadata

Retrieves metadata from the 5800 system. The OID specifies what data to retrieve.

Note – By default, RetrieveMetadata displays the time according to the configuration of the client machine, including its time zone.

Synopsis

```
java RetrieveMetadata <IP | HOST> <OID> [OPTIONS]
```

Description

Retrieves a data record and metadata from the 5800 system server. The metadata record identified by the supplied OID is printed to stdout.

Options

-h

Print this message.

Examples

```
java RetrieveMetadata 10.152.0.12 \  
0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000
```

Source Code

```
java/examples/RetrieveMetadata.java
```

AddMetadata

Adds a metadata record to an already stored object.

Synopsis

```
java AddMetadata <IP | HOST> <OID> [OPTIONS]
```

Description

Adds a new metadata record to an existing data object.

Options

```
-m <name>=<value>
```

Any number of `-m` options can be specified. Each option specifies a single (name, value) pair.

`<name>` should be specified in the format `<namespace>.<attribute>`. Use double quotes if `<value>` is a string containing spaces.

```
-h
```

Print this message.

Examples

```
java AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \
    -m filesystem.mimetype="image/jpeg"
java AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \
    -m system.test.type_char="do re mi"
java AddMetadata server
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \
    -m system.test.type_string="fa so la"
java AddMetadata server
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \
    -m system.test.type_long=123
java AddMetadata server
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \
    -m system.test.type_double=1.23
java AddMetadata
    server 0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \
    -m system.test.type_date=1952-10-27
java AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \
    -m system.test.type_time=23:30:29
```

```
java AddMetadata server \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \  
    -m system.test.type_timestamp="1952-10-27 23:30:29.999"  
java AddMetadata server \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000@ \  
    -m name1=value1 -m name2="value 2"
```

Source Code

```
java/examples/AddMetadata.java
```

DeleteRecord

Deletes the Sun 5800 system metadata record associated with an OID.

Synopsis

```
java DeleteRecord <IP | Host> <OID> [OPTIONS]
```

Description

Deletes the record with the specified OID. If this record is the only record pointing to the data, the data will also be deleted.

Options

-v

Print deleted OID to stdout.

-h

Print this message.

Examples

```
java DeleteRecord server \  
0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000
```

Source Code

```
java/examples/DeleteRecord.java
```

Query

Queries a 5800 system server for metadata records that match the query string passed on the command line.

Note – Query requires the T..Z UTC format. For example, 1952-10-27T00:30:29.999Z.

Synopsis

```
java Query <IP | HOST> <QUERY> [OPTIONS]
```

Description

Queries for metadata records. QUERY is of the form:

```
<name1>=<value1>' AND <name2>=<value2>' OR ...
```

See the examples below for formatting of various types of values. The OID and any specified fields of metadata records that match the query are printed to `stdout`.

<name> should be specified in the format <namespace>.<attribute>.

Note that names that are keywords need to be enclosed in escaped double quotes (for example, with the bash shell, use `"\"<name>\"=<value>"`). Refer to the list of keywords in Chapter 4, “Sun StorageTek 5800 System Query Language,” in *Sun StorageTek 5800 SystemClient API Reference Manual*.

Options

```
-s <FIELD>
```

Specifies a field to be retrieved, much like an SQL `select` clause. To retrieve multiple fields, repeat this option. By default, the results are returned as a list of OIDs.

```
-n <number of results>
```

The maximum number of metadata records or OIDs that will be returned. The default is 1000.

```
-h
```

Print this message.

Examples

In the following examples, “first” is a keyword.

```
java Query server "book.author='King'"
java Query server "\"first\"='a'"
java Query 10.152.0.12 "mp3.artist='The Beatles' AND mp3.album='Abbey Road'"
java Query 10.152.0.12 "mp3.artist='The Beatles'" -s mp3.album -s mp3.title
java Query 10.152.0.12 system.test.type_char="do re mi"
java Query 10.152.0.12 system.test.type_string="fa so la"
java Query 10.152.0.12 system.test.type_long=123
java Query 10.152.0.12 system.test.type_double=1.23
java Query 10.152.0.12 system.test.type_binary="x'0789abcdef'"
java Query 10.152.0.12 system.test.type_date="2010-10-20"
java Query 10.152.0.12 system.test.type_time="23:30:29"
java Query 10.152.0.12 system.test.type_timestamp="{timestamp'2010-10-20T23:30:29.123Z'}"
```

Source Code

java/examples/Query.java

RetrieveSchema

Returns the schema defined on a 5800 system server to standard output.

Synopsis

```
java RetrieveSchema [OPTIONS] <IP | HOST>
```

Description

Retrieves the metadata schema from a 5800 system server, printing it to stdout.

Options

-h

Print this message.

Examples

```
java RetrieveSchema archivehost
```

Source Code

```
java/examples/RetrieveSchema.java
```

GetDate

Gets the date.

Synopsis

```
java GetDate <IP | HOST> [OPTIONS]
```

Description

Gets the current date used to compute time setting and checking during store and delete operations.

Options

-h

Print this message.

Examples

```
java GetDate server
```

Source Code

```
java/examples/GetDate.java
```


C Example Applications

This section provides detailed information on the C example applications provided with the 5800 system client SDK.

Example Overview

Included with the 5800 system SDK are several command-line example applications that demonstrate the use of the C API. The example applications are located in the SDK under `c/examples`. Appropriate libraries are supplied for Solaris SPARC, Solaris x86, Red Hat Linux, and Windows.

Before You Begin

Make sure you configure your software environment before using the C example applications.

- In Solaris and Linux, set the `LD_LIBRARY_PATH` environment variable to *SDK directory name/c/OS/lib* where *SDK directory name* is the root directory of the unzipped 5800 system SDK archive and *OS* is either Solaris or Linux. For example:

```
StorageTek500_SDK_1_1-20/c/Solaris/lib
```

- In Microsoft Windows 2003:

The example programs will run if they are run as installed in the default build directory. However, if you have moved them elsewhere, the location of the library files (DLLs) must be added to the `PATH` environment variable as follows:

```
C:\StorageTek500_SDK_1_1_82\c\Win32\lib
```

To edit the windows `PATH` environment variable:

1. Click the Start button.
2. Right-click My Computer and select properties to launch System Properties.
3. Click the Advanced tab.
4. Click Environment Variables.
5. Under System Variables, scroll down and click Path.
6. Click Edit to launch Edit System Variable.
7. Add the full path name of the SDK `lib` directory to the `PATH` environment variable. Make certain each path name is separated by a semicolon (;).
8. Click OK to close each window.

Also see “[Software Requirements](#)” on page 13.

Building the C Example Applications

To build the C example applications, go to the `c/examples` directory and run `make`. This will build the example applications and put them in the `c/examples/OS/build` directory.

Each C example application can be built separately by running `make program_name`.

Running a C Example Application

Once you have built the C example applications, go to the `c/examples/<OS>/build` directory and execute the binary file with the appropriate command line. The examples depend on `libhoneycomb.so`.

About the C Example Application Source Code

First, the function `parseCommandLine` is called to parse the command line and store the information in a `struct` called `CommandLine`. Next, any files that contain data to be sent to the 5800 system server are opened. The appropriate 5800 system C API is then called. Finally, output is delivered back to either standard output, a file, or both. Refer to the comments in the sample code for further details.

Example Applications

The following C example applications are included with the 5800 system client SDK:

- [“StoreFile” on page 35](#)
- [“CheckIndexed” on page 36](#)
- [“RetrieveData” on page 37](#)
- [“RetrieveMetadata” on page 38](#)
- [“AddMetadata” on page 39](#)
- [“DeleteRecord” on page 41](#)
- [“Query” on page 42](#)
- [“RetrieveSchema” on page 44](#)

StoreFile

Stores a file and associated metadata on a 5800 system server.

Synopsis

```
StoreFile <IP | HOST> <FILE> [OPTIONS]
```

Description

Stores a file and its associated metadata record. If no `-m` options are specified, a metadata record without user content is generated. The OID of the metadata record is printed to `stdout`.

Options

`-m <name>=<value>`

Any number of `-m` options can be specified. Each option specifies a single (name, value) pair.

`<name>` should be specified in the format `<namespace>.<attribute>`. Use double quotes if `<value>` is a string containing spaces.

`-h`

Print this message.

Examples

```
StoreFile server /var/log/messages
StoreFile server ~/journal
StoreFile server myfile.jpg -m filesystem.mimetype="image/jpeg"
StoreFile 10.152.0.12 myfile -m system.test.type_char="do re mi"
StoreFile 10.152.0.12 myfile -m system.test.type_string="fa so la"
StoreFile 10.152.0.12 myfile -m system.test.type_long=123
StoreFile 10.152.0.12 myfile -m system.test.type_double=1.23
StoreFile 10.152.0.12 myfile -m system.test.type_binary=0789abcdef
StoreFile 10.152.0.12 myfile -m system.test.type_date=2010-10-20
StoreFile 10.152.0.12 myfile -m system.test.type_time=23:30:29
StoreFile 10.152.0.12 myfile \
    -m system.test.type_timestamp="2010-10-20T23:30:29.999"
StoreFile 10.152.0.12 myfile -m name1=value1 -m name2="value 2"
```

Source Code

`c/examples/StoreFile.c`

CheckIndexed

Ensure an object is queryable. Checks if the metadata for an object is present in the query engine, and inserts the metadata if it is not present.

Synopsis

```
CheckIndexed <IP | HOST> <OID> [OPTIONS]
```

Description

Check with the 5800 systemserver to determine if the specified OID has become queryable. If not, attempt to make it queryable.

A short message about the supplied OID is printed to stdout:

```
Object OID was already queryable.  
Object OID not yet queryable.  
Object OID has now been made queryable.
```

Options

```
-h
```

Print this message.

Examples

```
CheckIndexed archivehost \  
0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000  
CheckIndexed 10.152.0.12 \  
0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000
```

Source Code

```
c/examples/CheckIndexed.c
```

RetrieveData

Retrieves a data object from a 5800 system server.

Synopsis

```
RetrieveData <IP | HOST> <OID> <FILE> [OPTIONS]
```

Description

Retrieves data from the 5800 system. The OID specifies what data to retrieve. Data is written to FILE, if specified, otherwise to stdout.

Options

-h

Print this message.

Examples

```
RetrieveData storagetek \  
0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \  
/archive/log.1
```

Source Code

```
c/examples/RetrieveData.c
```

RetrieveMetadata

Retrieves a metadata record from a specified 5800 system server.

Synopsis

```
RetrieveMetadata <IP | HOST> <OID> [OPTIONS]
```

Description

Retrieves metadata from the 5800 system. The OID specifies what data to retrieve. Metadata is printed to stdout.

Options

-h

Print this message.

Examples

```
RetrieveMetadata archivehost \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000  
RetrieveMetadata 10.152.0.12 \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000
```

Source Code

```
c/examples/RetrieveMetadata.c
```

AddMetadata

Adds a metadata record to an already stored object.

Synopsis

```
AddMetadata <IP | HOST> <OID> [OPTIONS]
```

Description

Adds a new metadata record to an existing data object.

Options

```
-m <name>=<value>
```

Any number of -m options can be specified. Each option specifies a single (name, value) pair.

<name> should be specified in the format <namespace>.<attribute>. Use double quotes if <value> is a string containing spaces.

```
-h
```

Print this message.

Examples

```
AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \
    -m filesystem.mimetype="image/jpeg"
AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \
    -m system.test.type_char="do re mi"
AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \
    -m system.test.type_string="fa so la"
AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \
    -m system.test.type_long=123
AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \
    -m system.test.type_double=1.23
AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \
    -m system.test.type_date=1992-10-27
AddMetadata server \
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \
    -m system.test.type_time=23:30:29
```

```
AddMetadata server \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \  
    -m system.test.type_timestamp="1992-10-27T23:30:29"  
AddMetadata server \  
    0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000 \  
    -m name1=value1 -m name2="value 2"
```

Source Code

c/examples/AddMetadata.c

DeleteRecord

Deletes a record associated with an OID.

Synopsis

```
DeleteRecord <IP | HOST> <OID> [OPTIONS]
```

Description

Deletes a record associated with an OID. The OID specifies which record to delete. The record consists of all metadata associated with the OID, or the data if it is a data OID. The OID itself becomes inaccessible. If this OID is the last OID associated with the data, the data is also deleted.

Options

-v

Print deleted OID to stdout.

-h

Print this message.

Examples

```
DeleteRecord server 0200004f75ee01094cc13e11dbbad000e08159832d000024d40200000000
```

Source Code

```
c/examples/DeleteRecord.c
```

Query

Queries a 5800 system server for metadata records that match the query string passed on the command line.

Note – Query requires the T..Z UTC format. For example, 1952-10-27T00:30:29.999Z.

Synopsis

```
Query <IP | HOST> <QUERY> [OPTIONS]
```

Description

Queries for metadata records. QUERY is of the form:

```
<name1>=<value1>' AND <name2>=<value2>' OR ...
```

See the examples below for formatting of various types of values. The OID and any specified fields of metadata records that match the query are printed to stdout.

<name> should be specified in the format <namespace>.<attribute>.

Note that names that are keywords need to be enclosed in escaped double quotes (for example, with the bash shell, use "\"<name>\"='<value>"). Refer to the list of keywords in Chapter 4, “Sun StorageTek 5800 System Query Language,” in *Sun StorageTek 5800 SystemClient API Reference Manual*.

Options

-s <FIELD>

Print out results as metadata name-value records. Use as many -s switches as needed to define all fields that will be printed to stdout.

-n <number of results>

The maximum number of metadata records or OIDs that will be returned. The default is 1000.

-h

Print this message.

Examples

In the following examples, “first” is a keyword.

```
Query archivehost "book.author='King'"
Query archivehost "\"first\"='a'"
Query archivehost system.test.type_char="do re mi"
Query archivehost system.test.type_string="fa so la"
Query archivehost system.test.type_long=123
Query archivehost system.test.type_double=1.23
Query archivehost system.test.type_binary="x'0789abcdef'"
Query archivehost system.test.type_date="2010-10-20"
Query archivehost system.test.type_time="22:10:29"
Query archivehost system.test.type_timestamp="{timestamp'2010-10-20T23:30:29.123Z'}"
Query 10.152.0.12 "mp3.artist='The Beatles' AND mp3.album='Abbey Road'"
Query 10.152.0.12 "mp3.artist='The Beatles'" -s mp3.album -s mp3.title
Query 10.152.0.12 "system.test.type_timestamp={timestamp '1952-10-27T08:30:29.999Z'}"
```

Source Code

c/examples/Query.c

RetrieveSchema

Prints metadata attributes to stdout.

Synopsis

```
RetrieveSchema <IP | HOST> [OPTIONS]
```

Description

Retrieves the schema from a 5800 system server, printing it to stdout.

Options

```
-h
```

Print this message.

Examples

```
RetrieveSchema archivehost
```

Source Code

```
c/examples/RetrieveSchema.c
```

Sun StorageTek 5800 System Open Edition Software

This chapter provides information on running the 5800 system open edition software.

Note – For the 1.1.1 release, the name of the 5800 system emulator was changed to the 5800 system open edition software.

The following topics are discussed:

- “Introduction to the Open Edition Software” on page 45
- “Software Requirements” on page 46
- “Open Edition Software Startup” on page 46
- “Open Edition Software Shutdown” on page 46
- “Schema Modification” on page 46
- “Open Edition Software Event Log” on page 47
- “Open Edition Software Configuration Settings” on page 47

Introduction to the Open Edition Software

The 5800 system open edition software mimics the behavior of a 5800 system server. This feature enables you to test software being developed for a 5800 system without having to access a 5800 system server. The open edition software stores all data and metadata on the local hard drive. This data is by default stored in the `openedition/var` directory.

Software Requirements

The 5800 system open edition software requires at minimum the JDK 1.5 software.

Open Edition Software Startup

The 5800 system open edition software can run on Solaris, Linux, or Windows environments. To start the open edition software, go to the `openedition/bin` directory and execute the `start.sh` file for Solaris and Linux environments or the `start.bat` file for the Windows environment. The open edition software listens on port 8080 of the machine you start it on.

See [“Open Edition Software Configuration Settings” on page 47](#) for directions on changing the port number.

Open Edition Software Shutdown

Connect to port 8080 of the machine running the 5800 system open edition software with your web browser (`http://localhost:8080` if you are on your local system). Click on `HttpContext` [`/admin`], then [Click here to shutdown the open edition software](#).

Schema Modification

To add a custom schema to the 5800 system, create an XML file detailing your custom schema. Refer to the XML files in the `config` directory for examples of a custom schema. Also, see *“Configuring Metadata and File System View”* in *Sun StorageTek 5800 System Administration Guide*.

Once your XML schema file is complete, stop the open edition software and run the `metadata_merge_config.sh` script (`metadata_merge_config.bat` on Windows) located in the `bin` directory. This script takes one command-line argument, which is the full path to your XML schema file. The open edition software should be stopped while updating the schema.

▼ To Activate a New Schema for the Open Edition Software

- 1 **Shut down the open edition software if it is currently running.**
See [“Open Edition Software Shutdown” on page 46](#) for details.
- 2 **Run the `metadata_merge_config` program to activate the new schema.**

3 Restart the open edition software.

See “Open Edition Software Startup” on page 46 for details.

Open Edition Software Event Log

The open edition software event log is automatically stored under `/openedition/logs/emulator.log`. The event log contains all the transactions that the open edition software has processed, as well as startup and shutdown information. This log can be very helpful in debugging your 5800 system client applications.

Open Edition Software Configuration Settings

You can configure the open edition software through the open edition software configuration file located at `/openedition/config/emulator.config`. Table 3–1 provides the settings you can change.

TABLE 3–1 Open Edition Software Configuration File Settings

Settings	Description
<code>honeycomb.cell.capacity.megs = size</code>	<i>size</i> is the amount of available storage (in Mbytes) for the open edition software. The default is 500 Mbytes. Note that the actual capacity is 80% of the value provided, which enables the healing of a missing disk in the 5800 system (healing is not implemented in the open edition software).
<code>honeycomb.protocol.port = port_number</code>	<i>port_number</i> is the port the open edition software will listen on.

For further information on the configuration file, refer to the *Sun StorageTek 5800 Administrator's Guide*.

Index

A

AddMetadata, 18
 C, 39-40
 Java, 26-27
applications
 C API, deployment, 15
 examples, C, 33-44
 examples, Java, 19
 examples, summary, 17-18
 Java API, deployment, 15
attributes, 14

C

C example applications, *See* example applications, C
C library directory, 15
CheckIndexed
 C, 36
 Java, 23
configuration file, open edition software, 47

D

data types, 14
DeleteRecord, 18
 C, 41
 Java, 28

E

emulator, *see* open edition software, 45
event log, 47
example applications

C

AddMetadata, 39-40
building, 34
CheckIndexed, 36
DeleteRecord, 41
overview, 33
Query, 42-43
RetrieveData, 37
RetrieveMetadata, 38
RetrieveSchema, 44
running, 34
software requirements, 13
source code, 34
StoreFile, 35

Java

AddMetadata, 26-27
building, 20
CheckIndexed, 23
DeleteRecord, 28
GetDate, 32
overview, 19
Query, 29-30
RetrieveData, 24
RetrieveMetadata, 25
RetrieveSchema, 31
running, 20
software requirements, 13
source code, 20

example applications, Java (*Continued*)
 StoreFile, 21-22

G

GetDate, 18
 Java, 32

I

installation instructions, 13

J

Java example applications, 19

M

metadata schema, 14

N

namespace, definition of, 14

O

open edition software
 configuration file, 47
 event log, 47
 introduction, 45
 reconfiguring port, 47
 requirements, 13, 46
 schema modification, 46-47
 setting storage size, 47
 shutdown, 46
 startup, 46
operating systems supported, 12-13

P

PATH environment, changing for Windows, 19

Q

Query, 18
 C, 42-43
 Java, 29-30
query language, 15

R

RetrieveData, 18
 C, 37
 Java, 24
RetrieveMetadata, 18
 C, 38
 Java, 25
RetrieveSchema, 18
 C, 44
 Java, 31

S

schema
 activation, 46-47
 modification, 46-47
SDK
 application deployment, 15
 components, 12
 example applications, 17-18
 installation instructions, 13
 open edition software, 45
 overview, 11-12
 software requirements, 13
 system requirements, 12-13
 terms of use, 12
semantics, 14
 attributes, 14
 data and metadata, 14
 metadata schema, 14
 namespace, 14

- software requirements, 13
- source code
 - C, summary, 33
 - Java, summary, 20
- StoreFile, 17, 18
 - C, 35
 - Java, 21-22
- system requirements, 12-13

W

- Windows PATH environment variable, changing, 19

