

BUG BOUNTY FIELD GUIDE

Criminal IP Target-Based Recon

Tag & Filter System, Real-World Dorks &
Automation for Bug Bounty Hunters and
Penetration Testers

- Threat Intelligence Search
- 2025 Edition

Table of Contents

1. Introduction to Criminal IP

2. Criminal IP Query Syntax

2.1 Basic Syntax & Rules

2.2 Logical Operators

2.3 Common Query Mistakes

3. Core Search Filters & Tags

3.1 Filter Fields Reference

3.2 Tag Categories

3.3 SSL & Certificate Filters

4. Bug Bounty Dorks by Category

4.1 Admin Panels & DevOps

4.2 Databases & Data Stores

4.3 VPN & Remote Access

4.4 Cloud & Container Exposure

4.5 IoT & Industrial Systems

5. Targeting Specific Organizations

6. Criminal IP API & Automation

7. Criminal IP vs Other Search Engines

8. Integration & Workflow

9. Best Practices & Legal

1. Introduction to Criminal IP

Criminal IP is a South Korean-developed cyber threat intelligence (CTI) search engine created by AI SPERA in 2017. It indexes over **4.2 billion IP addresses** worldwide, combining internet asset scanning with AI-powered threat analysis, risk scoring, and malicious infrastructure detection. For bug bounty hunters, it is a powerful passive reconnaissance platform that goes beyond simple service discovery to assess the security posture of exposed assets. 🌐

What sets Criminal IP apart is its native **threat intelligence context** — each IP gets a risk score, VPN/proxy detection, phishing classification, and tag-based categorization. This means you can not only find exposed services but also assess their security posture at a glance. It excels at detecting abandoned infrastructure, temporary dev servers, and misconfigured cloud assets that traditional scanners miss. 🎯

Why Criminal IP Matters for Bug Bounty

4.2B+ IPs Indexed: Massive coverage across IPv4 space. **IP Risk Scoring:** Instant threat assessment for any host. **Tag-Based Search:** Pre-classified asset categories (C2, IoT, DevOps, VPN). **AI Analysis:** Automatic phishing, malware, and VPN detection. **Image Search:** Visual reconnaissance of web interfaces. **Exploit Search:** Built-in vulnerability database lookup. **Free Tier Available:** 50 free search credits for new users.

Core Search Tools

Table 1 Criminal IP Search Tools

Tool	Purpose	Use Case
Asset Search	IP/service scanning data	Find exposed services, banners, ports
Domain Search	Domain-based intelligence	Domain reputation, WHOIS, DNS records
Exploit Search	Vulnerability database	CVE lookup, exploit PoC discovery
Image Search	Visual asset discovery	Identify web UIs by screenshots
Statistics	10-day trend graphs	Track maliciousness over time
Element Analysis	Aggregated asset analytics	Country/service/ASN breakdowns
Maps	Geographic visualization	Global asset distribution
Banner Explorer	Category-based banner search	Crypto, ICS, IoT, gaming servers

Account Tiers

Table 2 Criminal IP Pricing Plans

Plan	Cost	API Access	Credits
Free	Free	Limited	50 initial credits
Personal	\$49/mo	Basic	3,000 credits/mo
Professional	\$199/mo	Full	15,000 credits/mo
Enterprise	Custom	Full + SIEM	Unlimited

Free Tier Strategy

New users get **50 free search credits** upon registration. Use them strategically — run targeted queries with combined filters rather than broad scans. Asset Search consumes 1 credit per query. Domain Search and Exploit Search have separate credit pools.

2. Criminal IP Query Syntax

Criminal IP uses a field-based query syntax combining **filters** (structured fields) and **tags** (pre-classified asset labels). Understanding the syntax rules is critical — even minor mistakes can return empty results. 📝✏️

2.1 Basic Syntax & Rules

SYNTAX

Table 3 Basic Syntax Rules

Pattern	Description	Example
field:value	Exact field match	port:443
field:"multi word"	Quoted multi-word value	tag:"SSL VPN"
tag:value	Pre-classified asset tag	tag:C2

Critical Syntax Rules

- **Case-insensitive:** tag:c2 , tag:C2 , and tag:Cobalt Strike all work
- **Country codes only:** Use ISO 3166-1 alpha-2 codes (US, KR, DE) — NOT full names
- **Quotes for multi-word:** tag:"SSL VPN" is required — tag:SSL VPN breaks
- **No spaces around colon:** Write port:80 not port : 80
- **Field names are fixed:** Only documented fields work — typos return no results

Common Syntax Mistakes

Wrong: country:United States (use country:US). **Wrong:** ssl:expired (use ssl_expired:true). **Wrong:** tag:SSL VPN (use tag:"SSL VPN"). **Wrong:** tag:C2 AND port:80 OR port:443 (AND has higher precedence — see below).

2.2 Logical Operators

LOGIC

Table 4 Logical Operators

Operator	Description	Example	Result
AND	Both conditions (higher precedence)	tag:C2 AND port:80	C2 on port 80 only
OR	Either condition (lower precedence)	tag:C2 AND port:80 OR port:443	Evaluates as (C2 AND 80) OR ANY 443
space	Implicit AND between filters	tag:IoT ssl_expired:true	IoT with expired SSL

AND Precedence Warning

In Criminal IP, **AND has higher precedence than OR**. This is the opposite of many programming languages. tag:C2 AND port:80 OR port:443 is evaluated as (tag:C2 AND port:80) OR port:443 — meaning ALL port 443 results are returned, not just C2 ones. For precision, split queries or use explicit grouping.

2.3 Common Query Mistakes

AVOID THESE

Table 5 Query Mistakes & Fixes

Mistake	Wrong Query	Correct Query
Full country name	country:United States	country:US
Unsupported field	SSL ssl:expired	ssl_expired:true
Unquoted multi-word tag	tag:SSL VPN	tag:"SSL VPN"
AND/OR precedence trap	tag:C2 AND port:80 OR port:443	Split: tag:C2 AND port:80 + tag:C2 AND port:443
Case sensitivity worry	tag:COBALT STRIKE	tag:"cobalt strike" (case-insensitive OK)
Space around colon	port : 80	port:80

3. Core Search Filters & Tags

3.1 Filter Fields Reference

FILTERS

Table 6 Core Filter Fields

Filter	Description	Example
tag	Pre-classified asset category	tag:C2
port	Open port number	port:9200
ssl_expired	Expired SSL cert (true/false)	ssl_expired:true

cloud_provider	Cloud hosting provider	cloud_provider:AWS
hostname	Hostname pattern	hostname:ec2
as_name	Autonomous System name	as_name:Amazon
country	ISO 3166-1 alpha-2 code	country:US
title	HTML page title	title:"Login Page"
ssl_issuer_organization	SSL cert issuer org	ssl_issuer_organization:"Let's Encrypt"
ip	IPv4 address	ip:8.8.8.8

3.2 Tag Categories

TAGS

Criminal IP auto-tags assets with pre-defined labels. These tags are the most powerful feature for bug bounty hunters — they instantly classify infrastructure type without needing complex banner analysis.

Table 7 Key Tags for Bug Bounty

Tag	Description	Bug Bounty Value
C2	Command & Control servers	Threat intel context for target
Cobalt Strike	Cobalt Strike team servers	Identify compromised infrastructure
DevOps	CI/CD platforms (Jenkins, GitLab)	Source code leaks, RCE
IoT	Internet of Things devices	Default creds, firmware vulns
Docker	Docker daemon/API exposed	Container escape, RCE
"SSL VPN"	SSL VPN endpoints	VPN bypass, auth bypass
Compromised	Known compromised systems	Post-compromise indicators
Database	Exposed database services	Data leak, unauthorized access

RDP	Remote Desktop Protocol	Brute-force, BlueKeep
Phishing	Known phishing sites	Brand impersonation reports

3.3 SSL & Certificate Filters

SSL

Table 8 SSL & Certificate Filters

Filter	Description	Bug Bounty Use
<code>ssl_expired:true</code>	Expired certificates	Find abandoned/neglected infra
<code>ssl_expired:false</code>	Valid SSL certificates	Filter to active maintained assets
<code>ssl_issuer_organization:"Let's Encrypt"</code>	Free SSL certs	Temporary/test infrastructure
<code>ssl_issuer_organization:"DigiCert"</code>	Enterprise SSL certs	Production-grade assets
<code>ssl_subject_common_name:*</code>	SSL CN field	Domain correlation

The `ssl_expired:true` Trick

Combining `ssl_expired:true` with tags is one of Criminal IP's most powerful techniques. Expired SSL certificates indicate **abandoned, neglected, or temporary infrastructure** — exactly the kind of shadow IT that bug bounty hunters love to find. These systems are often unmaintained and vulnerable.

4. Bug Bounty Dorks by Category

These Criminal IP queries are crafted for real-world bug bounty hunting. Every dork targets a specific exposure type with the exact tag/filter combination. 🎯

4.1 Admin Panels & DevOps

HIGH-IMPACT

ADMIN Exposed DevOps Platforms (Jenkins, GitLab)

Publicly accessible CI/CD platforms that may leak source code, API keys, or allow pipeline compromise.

```
tag:DevOps AND port:80
```

ADMIN DevOps with Expired SSL (Abandoned)

Abandoned DevOps tools are often unmaintained and running vulnerable versions.

```
tag:DevOps AND ssl_expired:true
```

ADMIN Elastic Beanstalk Environments

AWS Elastic Beanstalk may expose debugging or testing apps unintentionally.

```
title:"Elastic Beanstalk" AND port:80
```

ADMIN Login Pages on Target ASN

Find all login panels within a target's Autonomous System.

```
title:"Login" AND as_name:"TargetASN"
```

ADMIN Admin Consoles in Cloud

Admin panels hosted on cloud providers with weak or missing auth.

```
(title:"Admin" OR title:"Dashboard") AND cloud_provider:AWS
```

ADMIN Jenkins via Title Search

Target Jenkins CI/CD servers by HTML title and port.

```
title:"Dashboard [Jenkins]" AND port:8080
```

4.2 Databases & Data Stores

SENSITIVE DATA

DATABASE Tagged Database Services

Criminal IP auto-tags exposed databases — MongoDB, Elasticsearch, MySQL, Redis.

```
tag:Database AND country:US
```

DATABASE Databases with Expired SSL

Abandoned databases are goldmines — often left with default credentials and no patches.

```
tag:Database AND ssl_expired:true
```

DATABASE Elasticsearch Port 9200

Elasticsearch without authentication exposes all indexed data.

```
port:9200 AND title:"Elasticsearch"
```

DATABASE MongoDB Port 27017

MongoDB on default port without auth = full database access.

```
port:27017 AND country:US
```

DATABASE Redis Port 6379

Unauthenticated Redis allows data theft and config rewrite for RCE.

```
port:6379 AND ssl_expired:true
```

DATABASE MySQL on Unusual Ports

MySQL running on non-standard ports may indicate dev/test databases.

```
port:3306 AND ccloud_provider:AWS
```

4.3 VPN & Remote Access

REMOTE ACCESS

VPN SSL VPN Endpoints

SSL VPNs are common entry points for attackers — check for auth bypass and known CVEs.

```
tag:"SSL VPN"
```

VPN Neglected SSL VPNs

Expired SSL certs on VPNs indicate abandoned or mismanaged remote access infrastructure.

```
tag:"SSL VPN" AND ssl_expired:true
```

VPN SSL VPN by Cloud Provider

VPNs hosted on cloud — may be temporary or shadow IT deployments.

```
tag:"SSL VPN" AND cloud_provider:Azure
```

REMOTE RDP Exposed (Port 3389)

Exposed RDP is a major risk — BlueKeep, brute-force, and lateral movement.

```
tag:RDP AND country:US
```

REMOTE RDP on Cloud Instances

Cloud-hosted RDP with weak security groups — common misconfiguration.

```
tag:RDP AND cloud_provider:AWS
```

VPN OpenVPN / WireGuard Signs

VPN services exposed without proper hardening or outdated configs.

```
port:1194 OR port:51820
```

4.4 Cloud & Container Exposure

CLOUD INFRA

CLOUD Exposed Docker API

Docker daemon on ports 2375/2376 without auth = container escape and host RCE.

```
tag:Docker AND (port:2375 OR port:2376)
```

CLOUD Docker in Cloud

Cloud-hosted Docker instances may have weak network ACLs.

```
tag:Docker AND cloud_provider:AWS
```

CLOUD AWS-Hosted Services

All exposed services on AWS for a target ASN or country.

```
cloud_provider:AWS AND as_name:"Amazon"
```

CLOUD GCP-Hosted Services

Google Cloud Platform exposed assets for target enumeration.

```
cloud_provider:Google AND port:443
```

CLOUD Azure-Hosted Services

Microsoft Azure exposed services — often include dev/test environments.

```
cloud_provider:Azure AND ssl_expired:true
```

CLOUD Kubernetes API Port 6443

Exposed Kubernetes API server allows cluster enumeration and potential takeover.

```
port:6443 AND cloud_provider:AWS
```

4.5 IoT & Industrial Systems

IOT / ICS

IOT IoT Devices with Expired SSL

IoT devices often lack proper cert management — indicates poor security posture.

```
tag:IoT AND ssl_expired:true
```

IOT CCTV / DVR Systems

IP cameras and DVRs with default credentials or no auth.

```
tag:IoT AND (port:554 OR port:8554)
```

IOT Industrial Control Systems

ICS/SCADA protocols exposed — critical infrastructure risk.

```
port:502 OR port:44818 OR port:102
```

IOT Webcams Without Auth

Unprotected webcams — privacy breach and physical security risk.

```
tag:IoT AND title:webcam AND port:80
```

IOT Network Printers

Exposed printer admin panels — often have default passwords and leak documents.

```
tag:IoT AND (title:"HP" OR title:"Printer" OR title:"Lexmark")
```

IOT Router Admin Panels

Router admin interfaces with known default credentials and CVEs.

```
tag:IoT AND title:"Router" AND ssl_expired:true
```

5. Targeting Specific Organizations

Criminal IP provides multiple ways to narrow reconnaissance to a specific target organization. Using ASN names, cloud providers, hostnames, and SSL issuer fields creates surgical precision.



Organization Enumeration Strategy

STEP-BY-STEP TARGETING

```
# Step 1: Find by Autonomous System name
as_name:"Target Company"

# Step 2: Filter by country
as_name:"Amazon" AND country:US

# Step 3: Find specific services on target ASN
as_name:"TargetASN" AND (tag:DevOps OR tag:Database)

# Step 4: Cloud-only assets for target
as_name:"TargetASN" AND cloud_provider:AWS

# Step 5: Find abandoned/expired assets
as_name:"TargetASN" AND ssl_expired:true

# Step 6: Hostname-based discovery
hostname:ec2 AND as_name:"Amazon"

# Step 7: SSL issuer correlation
ssl_issuer_organization:"Let's Encrypt" AND as_name:"TargetASN"
```

SSL Issuer Intelligence

SSL Issuer Tells a Story

The `ssl_issuer_organization` filter reveals infrastructure maturity. "Let's Encrypt" = often temporary/dev. "DigiCert" or "GlobalSign" = production enterprise. Combining issuer + tag finds shadow IT — dev tools using free certs on enterprise networks.

RECON Let's Encrypt + DevOps (Shadow IT)

DevOps tools using free certs on enterprise ASNs — likely unauthorized deployments.

```
tag:DevOps AND ssl_issuer_organization:"Let's Encrypt" AND as_name:"TargetASN"
```

RECON Expired Enterprise Certs

Expired DigiCert certs indicate abandoned production-grade infrastructure.

```
ssl_issuer_organization:"DigiCert" AND ssl_expired:true AND as_name:"TargetASN"
```

RECON Cloud Provider Mapping

Map target's cloud footprint across AWS, Azure, and GCP.

```
as_name:"TargetASN" AND (cloud_provider:AWS OR cloud_provider:Azure OR
cloud_provider:Google)
```

Hostname Pattern Discovery

HOSTNAME RECON

```
# EC2 instances for a target
hostname:ec2 AND as_name:"TargetASN"

# Vultr / DigitalOcean droplets
hostname:vultr AND country:US

# Heroku-hosted apps
hostname:heroku AND ssl_issuer_organization:"DigiCert"

# Find dev/staging hostnames
hostname:dev OR hostname:staging OR hostname:test
```

6. Criminal IP API & Automation

Criminal IP provides a REST API for all search tools. Automation lets you scale reconnaissance across multiple targets and integrate findings into your bug bounty pipeline. 🤖

API Authentication

API SETUP


```
# API Key from: https://www.criminalip.io/mypage/information
API_KEY="your_api_key"
BASE_URL="https://api.criminalip.io/v1"

# Endpoints:
# /asset/search      - Asset Search
# /domain/search    - Domain Search
# /exploit/search    - Exploit Search
# /image/search      - Image Search
# /ip/data           - IP Summary Data
```

Python API Script

PYTHON: TARGETED ASSET SEARCH

```
import requests

API_KEY = "YOUR_API_KEY"
HEADERS = {"x-api-key": API_KEY}

def asset_search(query, offset=0):
    url = "https://api.criminalip.io/v1/asset/search"
    params = {
        "query": query,
        "offset": offset,
        "scan_type": "device"
    }
    resp = requests.get(url, headers=HEADERS, params=params, timeout=30)
    return resp.json()

# Search for DevOps on target ASN
query = 'tag:DevOps AND as_name:"TargetASN"'
data = asset_search(query)

for item in data.get("data", {}).get("result", []):
    ip = item.get("ip_address")
    ports = [p.get("open_port_no") for p in item.get("port_info", [])]
    tags = item.get("tag", [])
    print(f"{ip} | Ports: {ports} | Tags: {tags}")
```

PYTHON: IP RISK ASSESSMENT

```
import requests

API_KEY = "YOUR_API_KEY"
HEADERS = {"x-api-key": API_KEY}

def ip_data(ip):
    url = f"https://api.criminalip.io/v1/ip/data"
    params = {"ip": ip}
    resp = requests.get(url, headers=HEADERS, params=params, timeout=30)
    return resp.json()

# Assess risk of discovered IPs
target_ips = ["203.0.113.42", "203.0.113.43"]
for ip in target_ips:
    data = ip_data(ip)
    score = data.get("data", {}).get("ip_score", "N/A")
    is_vpn = data.get("data", {}).get("is_vpn", False)
    print(f"{ip} | Risk Score: {score} | VPN: {is_vpn}")
```

cURL One-Liners

CLI WORKFLOWS

```
# Basic asset search
curl -s "https://api.criminalip.io/v1/asset/search?query=tag%3ADevOps&offset=0" \
  -H "x-api-key: YOUR_API_KEY" | jq .

# Extract IPs for nmap scanning
curl -s "https://api.criminalip.io/v1/asset/search?query=port%3A9200&offset=0" \
  -H "x-api-key: YOUR_API_KEY" | jq -r '.data.result[].ip_address' | tee
elastic_ips.txt

# Domain reputation check
curl -s "https://api.criminalip.io/v1/domain/search?query=target.com" \
  -H "x-api-key: YOUR_API_KEY" | jq '.data'

# IP summary with risk score
curl -s "https://api.criminalip.io/v1/ip/data?ip=8.8.8.8" \
  -H "x-api-key: YOUR_API_KEY" | jq '.data.ip_score,.data.is_vpn,.data.is_proxy'
```

7. Criminal IP vs Other Search Engines

Each platform has unique strengths. Criminal IP's threat intelligence context sets it apart from pure asset scanners. 

Table 9 Platform Comparison

Dimension	Criminal IP	Shodan	Censys	Netlas
Founded	2017 (AI SPERA)	2009	2015	2022
Indexed IPs	4.2 billion+	~1 billion	~51 million	~344M HTTP
IP Risk Scoring	Native AI scoring	No	No	No
VPN/Proxy Detection	Native	Shodan Members	No	No
Phishing Detection	Native AI	No	No	No
Tag System	Pre-classified tags	No	No	Tag categories
Image Search	Yes (screenshots)	Membership only	No	No
Exploit Search	Built-in	Membership only	No	No
Free API	50 credits	100/mo	250/mo	Limited
Cheapest Paid	\$49/mo	\$49/mo	\$69/mo	\$49/mo

When to Use Criminal IP

Table 10 Use Case Selection

Task	Why Criminal IP
Assessing IP risk/reputation	Native AI risk score + VPN/proxy detection
Finding abandoned infrastructure	ssl_expired:true + tag combination is unique
Threat context for findings	Tag-based classification (C2, Compromised)
Visual reconnaissance	Built-in Image Search with screenshots
Exploit verification	Built-in Exploit Search for CVE lookup
Phishing detection	AI-powered phishing site classification
General asset discovery	4.2B+ IPs, competitive coverage

The Threat Context Advantage

When you find an exposed Jenkins instance on Shodan, you just know it exists. On Criminal IP, you also see its **IP risk score**, whether it's on a **VPN/proxy**, if it's **tagged as compromised**, and its **SSL status**. This context helps prioritize which findings to investigate first and adds weight to your bug bounty reports.

8. Integration & Workflow

Criminal IP integrates into the bug bounty pipeline as both a primary discovery tool and a threat intelligence validator. [🔗](#)

Criminal IP + httpx + Nuclei Pipeline

FULL RECON CHAIN

```
# Phase 1: Criminal IP asset discovery for target ASN
curl -s "https://api.criminalip.io/v1/asset/search?query=as_name%3ATargetASN" \
  -H "x-api-key: KEY" | jq -r '.data.result[].ip_address' | sort -u | tee cip_ips.txt

# Phase 2: Check risk scores for prioritization
for ip in $(head -50 cip_ips.txt); do
  curl -s "https://api.criminalip.io/v1/ip/data?ip=${ip}" \
    -H "x-api-key: KEY" | jq -r '"\(.data.ip_address) | Score: \(.data.ip_score) | VPN: \(.data.is_vpn)"'
done | tee risk_assessment.txt

# Phase 3: Port scan interesting IPs
nmap -iL cip_ips.txt -p 80,443,8080,8443,9200,27017,2375 --open -oG nmap_results.txt

# Phase 4: HTTP probing with metadata
cat cip_ips.txt | httpx -title -status-code -tech-detect -o live_http.txt

# Phase 5: CVE validation with Nuclei
cat live_http.txt | nuclei -t cves/ -severity critical,high -o nuclei_cip.txt
```

Image Search for Visual Recon

IMAGE SEARCH WORKFLOW

```
# Use Criminal IP Image Search to visually identify admin panels
# Query: title:"Login" AND country:US
# Browse screenshots to quickly spot interesting interfaces
# without sending any requests to the target

# Via API:
curl -s "https://api.criminalip.io/v1/image/search?query=title%3ALogin" \
  -H "x-api-key: KEY" | jq -r '.data.result[].ip_address,.data.result[].img_url'
```

Continuous Monitoring

MONITOR SCRIPT

```
#!/usr/bin/env python3
# cip_monitor.py - Daily Criminal IP asset monitor

import requests, json, datetime

API_KEY = "YOUR_API_KEY"
HEADERS = {"x-api-key": API_KEY}
TARGET_ASN = "TargetASN"
STATE_FILE = "cip_state.json"

def search_assets(query):
    url = "https://api.criminalip.io/v1/asset/search"
    params = {"query": query, "offset": 0}
    resp = requests.get(url, headers=HEADERS, params=params, timeout=30)
    return resp.json()

# Load known state
try:
    with open(STATE_FILE) as f:
        known = set(json.load(f))
except:
    known = set()

# Query current assets
query = f'as_name:"{TARGET_ASN}"'
data = search_assets(query)

current = set()
for item in data.get("data", {}).get("result", []):
    current.add(item.get("ip_address"))

# Find new IPs
new = current - known
if new:
    print(f"[{datetime.datetime.now()}] NEW ASSETS: {len(new)}")
    for ip in new:
        # Get risk score
        r = requests.get(f"https://api.criminalip.io/v1/ip/data?ip={ip}",
                        headers=HEADERS, timeout=10).json()
        score = r.get("data", {}).get("ip_score", "N/A")
        print(f" - {ip} (Risk: {score})")

# Save state
with open(STATE_FILE, 'w') as f:
    json.dump(list(current), f)
```

9. Best Practices & Legal

Validation Checklist

Table 11 Before Reporting

Step	Action	Why
1	Confirm ownership via ASN name or hostname	Shared hosting creates false positives
2	Check IP risk score — high risk may mean compromised	Compromised hosts need different handling
3	Verify exposure is in program scope	Out-of-scope reports waste time
4	Validate exploitability manually	Confirmed findings get higher payouts
5	Document Criminal IP query and risk context	Shows methodology + threat intel
6	Include screenshot from Image Search if available	Visual proof strengthens report

Report Template

Criminal IP Finding Report Template

Title: [P1] Exposed Docker API on Target Infrastructure (Risk Score: 87/100)

Description: Using Criminal IP passive reconnaissance, I discovered an exposed Docker daemon API belonging to [Target Company].

Criminal IP Query: tag:Docker AND as_name:"TargetASN" AND port:2375

Asset: 203.0.113.42:2375 | Criminal IP Risk Score: 87/100 | VPN: false

Impact: Exposed Docker API allows unauthenticated container listing, creation, and execution. An attacker can spawn privileged containers escaping to the host OS, achieving full remote code execution.

Remediation: Enable TLS authentication for Docker daemon. Restrict port 2375 to internal network only. Use firewall rules to block external access. Consider Docker Swarm with proper TLS certs.

Legal & Ethical Reminders

Do not exploit without authorization. Criminal IP is passive reconnaissance, but accessing discovered systems without permission violates CFAA, Computer Misuse Act, and similar laws.

Only report to programs where you have explicit written scope. Never modify data, create accounts, or execute commands on target systems. Follow responsible disclosure timelines.

Report Criminal IP vulnerabilities to report_security@aispera.com.

Recommended Resources

- **Criminal IP** — criminalip.io (Official platform)
- **Criminal IP API Docs** — docs.criminalip.io
- **Filters Reference** — criminalip.io/resources/filters
- **Tags Reference** — criminalip.io/resources/tags
- **Dorks Cheat Sheet** — criminalip.io/knowledge-hub/blog/28629
- **ExploitDB** — exploit-db.com
- **Nuclei Templates** — github.com/projectdiscovery/nuclei-templates