



# Seleniumworks

Wednesday, 28 August 2013

## Page Scroll using Selenium WebDriver

### Scroll Down:

```
import org.openqa.selenium.JavascriptExecutor;
WebDriver driver = new FirefoxDriver();
JavascriptExecutor jse = (JavascriptExecutor)driver;
jse.executeScript("scroll(0, 250)"); //y value '250' can be altered
```

### Scroll up:

```
JavascriptExecutor jse = (JavascriptExecutor)driver;
jse.executeScript("scroll(250, 0)"); //x value '250' can be altered
```

### Scroll bottom of the Page:

```
JavascriptExecutor jse = (JavascriptExecutor)driver;
jse.executeScript("window.scrollTo(0,Math.max(document.documentElement.scrollHeight,document.body.scrollHeight,document.documentElement.clientHeight));");
```

(or)

```
Actions actions = new Actions(driver);
actions.keyDown(Keys.CONTROL).sendKeys(Keys.END).perform();
```

### Full scroll to bottom in slow motion:

#### Selenium Essentials | Prashanth Sams



#### Blog Archive

- ▶ 2016 (2)
- ▶ 2014 (30)
- ▼ 2013 (68)
  - ▶ December (5)
  - ▶ November (2)
  - ▶ October (16)
  - ▶ September (18)
  - ▼ August (4)
    - Selenium & Locators

```

for (int second = 0;; second++) {
    if(second >=60){
        break;
    }
    ((JavascriptExecutor) driver).executeScript("window.scrollTo(0,400)", ""); //y value '400' can be
    altered
    Thread.sleep(3000);
}
(or)
JavascriptExecutor jse = (JavascriptExecutor)driver;
for (int second = 0;; second++) {
    if(second >=60){
        break;
    }
    jse.executeScript("window.scrollTo(0,800)", ""); //y value '800' can be altered
    Thread.sleep(3000);
}

```

## Scroll automatically to your WebElement:

```

Point hoverItem =driver.findElement(By.xpath("Value")).getLocation();
((JavascriptExecutor)driver).executeScript("return window.title;");
Thread.sleep(6000);
((JavascriptExecutor)driver).executeScript("window.scrollTo(0,(hoverItem.getY()+"));
// Adjust your page view by making changes right over here (hoverItem.getY()-400)
(or)
((JavascriptExecutor)driver).executeScript("arguments[0].scrollIntoView();",
driver.findElement(By.xpath("Value"))));
(or)
WebElement element = driver.findElement(By.xpath("Value"));
Coordinates coordinate = ((Locatable)element).getCoordinates();
coordinate.onPage();
coordinate.inViewPort();

```

Posted by Prashanth sams at 01:43



+6 Recommend this on Google

## How to store Left & Top (Location) | Width & Heigh...

### Page Scroll using Selenium WebDriver

#### Selenium Basics & Tips

- ▶ July (2)
- ▶ June (2)
- ▶ May (3)
- ▶ March (3)
- ▶ February (7)
- ▶ January (6)
- ▶ 2012 (3)

## Popular Posts

- 1 *Page Scroll using Selenium WebDriver*
- 2 *XSLT- Generate Interactive reports on TestNG+ANT*
- 3 *Appium Native iOS App Testing | WebDriver*
- 4 *How to set proxies with Username and Password in FirefoxDriver*
- 5 *Headless Browser Testing using PhantomJS - GhostDriver | WebDriver*

## About Me