Considerations for ID3

Relevant Readings: Section 3.7 in Mitchell

CS495 - Machine Learning, Fall 2009

► One way deal with overfitting is to prune the tree produced by ID3

- ► One way deal with overfitting is to prune the tree produced by ID3
- ► To *prune* a node:

- One way deal with overfitting is to prune the tree produced by ID3
- ▶ To prune a node:
 - Remove the subtree rooted at that node

- One way deal with overfitting is to prune the tree produced by ID3
- ► To *prune* a node:
 - Remove the subtree rooted at that node
 - Replacing it with a leaf node that takes the majoriy vote of training instances associated with it

- One way deal with overfitting is to prune the tree produced by ID3
- ► To *prune* a node:
 - Remove the subtree rooted at that node
 - Replacing it with a leaf node that takes the majoriy vote of training instances associated with it

► First, grow the tree completely (as in ID3)

- First, grow the tree completely (as in ID3)
- ► Then, keep pruning the node which causes the most improvement on the tuning set when pruned

- First, grow the tree completely (as in ID3)
- ► Then, keep pruning the node which causes the most improvement on the tuning set when pruned
- ▶ If any possible further pruning causes accuracy on tuning set to decrease, stop.

- First, grow the tree completely (as in ID3)
- ► Then, keep pruning the node which causes the most improvement on the tuning set when pruned
- ▶ If any possible further pruning causes accuracy on tuning set to decrease, stop.

First, grow the tree completely (as in ID3)

- First, grow the tree completely (as in ID3)
- ▶ Then for some large number of trials:

- First, grow the tree completely (as in ID3)
- ▶ Then for some large number of trials:
 - Make a copy of the original tree

- First, grow the tree completely (as in ID3)
- ▶ Then for some large number of trials:
 - Make a copy of the original tree
 - Choose a random number of nodes to prune

- First, grow the tree completely (as in ID3)
- ▶ Then for some large number of trials:
 - Make a copy of the original tree
 - Choose a random number of nodes to prune
 - Prune that many number of nodes, uniformly at random

- ► First, grow the tree completely (as in ID3)
- ▶ Then for some large number of trials:
 - Make a copy of the original tree
 - ► Choose a random number of nodes to prune
 - Prune that many number of nodes, uniformly at random
 - If this gets the best accuracy so far on the tuning set, remember it

- ► First, grow the tree completely (as in ID3)
- ▶ Then for some large number of trials:
 - Make a copy of the original tree
 - Choose a random number of nodes to prune
 - Prune that many number of nodes, uniformly at random
 - If this gets the best accuracy so far on the tuning set, remember it
- Return the best tree found (as measured on the tuning set)

- ► First, grow the tree completely (as in ID3)
- ▶ Then for some large number of trials:
 - Make a copy of the original tree
 - Choose a random number of nodes to prune
 - Prune that many number of nodes, uniformly at random
 - If this gets the best accuracy so far on the tuning set, remember it
- Return the best tree found (as measured on the tuning set)

▶ How do we deal with continuous attributes?

- ▶ How do we deal with continuous attributes?
- One easy way:

- ▶ How do we deal with continuous attributes?
- One easy way:
 - Split the attribute by the mean or the median

- ▶ How do we deal with continuous attributes?
- One easy way:
 - Split the attribute by the mean or the median
- A better way:

- ▶ How do we deal with continuous attributes?
- One easy way:
 - Split the attribute by the mean or the median
- A better way:
 - Sort the instances by the attribute we are trying out

- ▶ How do we deal with continuous attributes?
- One easy way:
 - Split the attribute by the mean or the median
- A better way:
 - Sort the instances by the attribute we are trying out
 - ► Try out every midpoint between these consecutive values, and take the best (in terms of information gain)

- ▶ How do we deal with continuous attributes?
- One easy way:
 - Split the attribute by the mean or the median
- A better way:
 - Sort the instances by the attribute we are trying out
 - ► Try out every midpoint between these consecutive values, and take the best (in terms of information gain)

Example

▶ Do a complete example of ID3 with continuous features

Example

▶ Do a complete example of ID3 with continuous features