



अर्किओन
INTERNATIONAL INSTITUTE
OF MEDICAL SCIENCE &
TECHNOLOGY COUNCIL

INTERNSHIP REPORT

on

IoT and Embedded Systems

Submitted by: Cohort– 04 (IoT & Embedded Systems)

Name	USN
Krithi	4DM22EC025
Vijetha	4DM22EC049
Sachidananda M M	1JB22EC096
Hadiya Khan	1AT22EC030
Harsha Vardhan S	1EE22EC019
C Pavitra	1EE22EC009
Ramitha R	1EE22EC048
Palaparthi Krishna Vamsi	1EE22EC038
S.Vidyashree	1MJ22EC124
Ananya Chandrashekar	1EE22EC004
Abhinav P	1EE22EC001
Charan B S	4VM23EC403
Durga Prasad S	1MV22EC049
Nagaraju M	4VM22EC032
Sachin Murchavar	4VM22EC045

ABSTRACT

This internship provided comprehensive exposure to Embedded Systems, Internet of Things (IoT), and PCB design, enabling the application of theoretical knowledge to practical engineering problems. The primary objective was to develop a strong understanding of hardware-software integration through hands-on experience in circuit design, embedded programming, and real-time system development.

A significant part of the internship was dedicated to PCB design using KiCad, where detailed knowledge of schematic creation, component selection based on electrical specifications, footprint assignment, routing strategies, ground plane design, and generation of fabrication files was acquired. Circuit designs were analyzed and validated through simulation to ensure proper functionality and optimized performance before implementation.

To strengthen fundamental concepts, hardware-oriented systems were designed and simulated. A password-based door lock system was developed at the simulation level using a microcontroller and keypad interface to understand secure access control mechanisms. A reverse polarity protection circuit was also simulated to study protection techniques and ensure safe operation under incorrect power conditions.

The primary focus of the internship was the development of an IoT-based Cold Chain Monitoring System with hardware implementation. The system is designed to continuously monitor temperature and environmental parameters of sensitive products such as vaccines and medicines. Sensor data is acquired and processed using a microcontroller and can be transmitted to a monitoring platform for real-time monitoring and analysis. This enables early detection of abnormal conditions and helps maintain the integrity of temperature-sensitive products.

Overall, the internship emphasized PCB design using KiCad, embedded system development, sensor interfacing, and real-time IoT-based monitoring. It significantly enhanced technical skills, problem-solving ability, and the understanding of developing reliable and efficient engineering solutions.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE NO.
	ABSTRACT	i
	TABLE OF CONTENTS	ii-v
	LIST OF FIGURES	vi-vii
1	COMPANY PROFILE	1-5
1.1	OVERVIEW OF THE ORGANIZATION	1
1.2	VISION AND OBJECTIVES	2
1.3	NATURE OF OPERATIONS	2-3
1.4	KEY MILESTONES AND ACHIEVEMENTS	3-4
1.5	ORGANIZATIONAL STRUCTURE	4
1.6	SERVICES OFFERED	4-5
2	INTERNSHIP DOMAIN OVERVIEW	6-10
2.1	FUNCTIONAL OVERVIEW OF IoT & EMBEDDED SYSTEMS	6-7
2.2	SYSTEM DEVELOPMENT METHODOLOGY	7-8
2.3	SYSTEM TESTING AND VALIDATION	8
2.4	TEAM STRUCTURE AND ROLES	9
2.5	ROLES AND RESPONSIBILITIES OF INDIVIDUALS	9-10
3	WORK CARRIED OUT DURING INTERNSHIP	11-26
3.1	PCB DESIGN AND DEVELOPMENT USING KICAD	11-13
3.1.1	INTRODUCTION	11
3.1.2	PCB DESIGN WORKFLOW	11-13
3.2	DC TO DC CONVERTER	13-16

3.2.1	INTRODUCTION	13
3.2.2	CIRCUIT DESCRIPTION	14
3.2.3	WORKING PRINCIPLE	15
3.2.4	PCB DESIGN CONSIDERATION	15-16
3.2.5	RESULT	16
3.3	LDR BASED LIGHT DETECTION CIRCUIT	16–18
3.3.1	INTRODUCTION	16
3.3.2	COMPONENTS USED	17
3.3.3	CIRCUIT DESCRIPTION	17
3.3.4	WORKING PRINCIPLE	17
3.3.5	PCB DESIGN CONSIDERATION	18
3.3.6	APPLICATION	18
3.3.7	RESULT	18
3.4	AUTOMOTIVE TURN SIGNAL & HAZARD LIGHT CONTROL SYSTEM	18–20
3.4.1	INTRODUCTION	19
3.4.2	COMPONENTS USED	19
3.4.3	CIRCUIT DESCRIPTION	19-20
3.4.4	WORKING PRINCIPLE	20
3.4.5	PCB DESIGN CONSIDERATION	20
3.4.6	RESULT	20
3.5	BATTERY REVERSE POLARITY PROTECTION CIRCUIT	21–22
3.5.1	INTRODUCTION	21
3.5.2	COMPONENTS USED	21
3.5.3	WORKING PRINCIPLE	21-22

3.5.4	PCB DESIGN CONSIDERATION	22
3.5.5	RESULT	22
3.6	PASSWORD BASED DOOR LOCK SYSTEM	22–24
3.6.1	INTRODUCTION	22
3.6.2	COMPONENTS USED	23
3.6.3	CIRCUIT DESCRIPTION	23
3.6.4	WORKING PRINCIPLE	23-24
3.6.5	RESULT	24
3.7	ULTRASONIC DISTANCE MEASUREMENT SYSTEM	24–26
3.7.1	INTRODUCTION	25
3.7.2	COMPONENTS USED	25
3.7.3	CIRCUIT DESCRIPTION	25
3.7.4	WORKING PRINCIPLE	25
3.7.5	RESULT	26
4	MAJOR PROJECT	27–49
4.1	INTRODUCTION	27–28
4.2	OBJECTIVE	28
4.3	PROBLEM STATEMENT	29
4.4	LITERATURE REVIEW	29–30
4.5	METHODOLOGY	30–31
4.6	SYSTEM ARCHITECTURE	31–32
4.7	HARDWARE AND SOFTWARE USED	32–41
4.7.1	ESP32	32–33
4.7.2	DHT22 SENSOR	34
4.7.3	MAGNETIC REED SENSOR	34

4.7.4	LCD DISPLAY	35
4.7.5	LED INDICATOR	35
4.7.6	BUZZER	36
4.7.7	RELAY MODULE	36
4.7.8	PELTIER MODULE WITH COOLING FAN	37
4.7.9	SIM900A GSM MODULE	37–38
4.7.10	LM2596 BUCK CONVERTER	38
4.7.11	BREADBOARD AND JUMPER WIRES	38–39
4.7.12	ARDUINO IDE	39
4.7.13	ANDROID STUDIO	39–40
4.7.14	MOBILE APPLICATION	40–41
4.7.15	WEB DASHBOARD	41–42
4.8	WORKING MODEL	42–43
4.9	RESULT	44–47
4.9.1	INTRODUCTION	44
4.9.2	LCD DISPLAY RESULT	44
4.9.3	MOBILE APPLICATION RESULT	45
4.9.4	WEBSITE DASHBOARD RESULT	45
4.9.5	GSM ALERT RESULT	46
4.9.6	PERFORMANCE ANALYSIS	46–47
4.10	ADVANTAGES	47
4.11	DISADVANTAGES	47–48
4.12	FUTUE SCOPE	48
5	CONCLUSION	49
	REFERENCES	50

LIST OF FIGURES

SL NO	NAME OF FIGURE	FIG NO	PAGE NO.
1	PCB Design	3.1	11
2	DC–DC Converter (Circuit)	3.2.1	13
3	DC–DC Converter (Layout)	3.2.2	14
4	DC–DC Converter (Gerber File)	3.2.3	15
5	LDR Based Light Detection Circuit	3.3.1	16
6	Automotive Turn Signal & Hazard System	3.4.1	18
7	Reverse Polarity Protection Circuit	3.5	21
8	Password Based Door Lock System	3.6	23
9	Ultrasonic Distance Measurement System	3.7	24
10	Block Diagram	4.5	31
11	System Architecture	4.6	32
12	ESP32	4.7.1	33
13	DHT22 Sensor	4.7.2	34
14	Magnetic Reed Sensor	4.7.3	34
15	LCD Display	4.7.4	35
16	LED Indicator	4.7.5	35
17	Buzzer	4.7.6	36
18	Relay Module	4.7.7	36
19	Peltier Module with Cooling Fan	4.7.8	37
20	GSM Module	4.7.9	37
21	LM2596 Buck Converter	4.7.10	38
22	Breadboard and Jumper Wires	4.7.11	38

23	Arduino IDE	4.7.12	39
24	Android Studio	4.7.13	39
25	Mobile Application	4.7.14	40
26	Web Dashboard	4.7.15	41
27	Working Model	4.8	42
28	Result Overview	4.9	44
29	LCD Display Result	4.9.1	44
30	Mobile Application Result	4.9.2	45
31	Website Dashboard Result	4.9.3	45
32	GSM Alert Result	4.9.4	46

CHAPTER 1

COMPANY PROFILE

1.1 OVERVIEW OF THE ORGANIZATION



The internship program titled “*The Diamond Beneath Your Feet*” is an initiative aimed at aligning academic knowledge with industry expectations through practical learning. It is organized by the International Institute of Medical Science and Technology Council in association with Visvesvaraya Technological University. The program is built on the objective of preparing students to become competent professionals who can perform effectively in real-world environments. It was introduced under the guidance of Dr. Sreedhar Saraswathy, who emphasizes the idea that students possess untapped potential that can be developed through structured training and exposure. IIMSTC functions as a multidisciplinary institution dedicated to education, research, and skill enhancement, and it operates in accordance with recognized regulatory frameworks in India. With recognition from government bodies and a growing international presence across regions such as South Africa, the Netherlands, and Mozambique, the organization provides learners with opportunities to gain broader perspectives and adapt to global professional standards.

1.2 VISION AND OBJECTIVES

The vision of the “*The Diamond Beneath Your Feet*” internship program is to transform students into competent, industry-ready professionals by integrating academic knowledge with practical experience. Conducted by the International Institute of Medical Science and Technology Council in collaboration with Visvesvaraya Technological University, the program aims to foster technical expertise, professional skills, and ethical values. It strives to prepare students to adapt to evolving industry demands and contribute effectively in a global professional environment.

The primary objective of the internship program is to develop students into competent professionals equipped with both technical expertise and essential soft skills. The program aims to achieve the following:

- To transform theoretical knowledge into practical application through experiential learning
- To develop analytical thinking and problem-solving abilities
- To enhance interdisciplinary skills across domains such as IoT, Artificial Intelligence, and Data Science
- To improve communication skills, leadership qualities, and professional ethics
- To prepare students for global career opportunities
- To encourage innovation and creativity in solving real-world problems
- To promote research-oriented thinking and evidence-based decision-making
- To build industry-relevant skills aligned with current technological advancements

1.3 NATURE OF OPERATIONS

The International Institute of Medical Science and Technology Council operates through a structured and well-defined framework aimed at delivering high-quality training and internship programs. Its key operational areas are outlined as follows:

1. Academic and Training Operations

- Conducting domain-specific training programs in areas such as IoT, Embedded Systems, Artificial Intelligence, Data Science, and Full Stack Development
- Organizing workshops, live sessions, and practical laboratory exercises
- Providing mentorship and guidance through experienced faculty and industry professionals

2. Research and Development

- Promoting innovation through project-based and experiential learning
- Supporting interdisciplinary research initiatives
- Facilitating real-world problem-solving through IFSPD-based projects

3. Global Collaboration

- Collaborating with international organizations for knowledge sharing and academic exchange
- Providing opportunities for global exposure and training
- Ensuring alignment with international standards and quality benchmarks

4. Digital Platform Integration

- Utilizing the PORT platform for maintaining digital portfolios and tracking student progress
- Leveraging the Tie-OPP platform for career development, skill assessment, and placement support

5. Internship Delivery Model

- Following a structured internship framework divided into two phases:
 - **Phase 1:** Skill development and execution of mini-projects
 - **Phase 2:** Implementation of industry-level projects
- Ensuring systematic learning, continuous monitoring, and performance evaluation throughout the program

1.4 KEY MILESTONES AND ACHIEVEMENTS

The International Institute of Medical Science and Technology Council and its internship programs have achieved several important milestones that reflect their growth and contribution to skill development and industry-oriented education. Some of the key achievements are as follows:

- Establishment of IIMSTC as a recognized multidisciplinary institution focused on education, research, and capacity building
- Collaboration with Visvesvaraya Technological University for delivering industry-aligned internship programs
- Recognition under various government bodies such as MSME and NITI Aayog
- Expansion of operations to international locations, including regions in Europe and Africa
- Adoption of quality benchmarks aligned with global and United Nations-oriented frameworks
- Development and implementation of digital platforms such as PORT and Tie-OPP for portfolio management and career support

- Successful execution of structured internship models across multiple technical domains

These milestones highlight the organization's continuous efforts toward enhancing educational quality, promoting innovation, and preparing students for professional excellence.

1.5 ORGANIZATIONAL STRUCTURE

The organizational structure of the International Institute of Medical Science and Technology Council is designed to ensure efficient functioning and effective delivery of training and internship programs. It comprises several key divisions, each responsible for specific roles and responsibilities.

- **Management Team:** Responsible for strategic planning, decision-making, and overall leadership of the organization
- **Academic Division:** Handles curriculum design, training modules, and student evaluation processes
- **Technical Division:** Focuses on domain-specific training such as IoT, Artificial Intelligence, and software development
- **Research Division:** Supports innovation, research activities, and project development
- **Global Collaboration Team:** Manages international partnerships and collaborative programs
- **Training and Mentorship Team:** Provides guidance, supervision, and hands-on training to students
- **Digital Platform Team:** Maintains and manages platforms such as PORT and Tie-OPP

This structured organizational framework ensures effective coordination among different departments, thereby enhancing the overall efficiency and quality of the internship program.

1.6 SERVICES OFFERED

The International Institute of Medical Science and Technology Council provides a wide range of services aimed at enhancing student skills and ensuring industry readiness. The major services offered are as follows:

1. Training Services

- Domain-specific technical training in areas such as IoT, Artificial Intelligence, Data Science, and Embedded Systems
- Soft skills and communication skill development programs
- Industry-oriented workshops, seminars, and interactive sessions

2. Internship Programs

- Structured internship programs involving real-time projects
- Practical exposure to industry-level implementation
- Continuous evaluation, monitoring, and mentorship

3. Research and Development Services

- Support for innovative and project-based learning initiatives
- Guidance for interdisciplinary research activities
- Problem-solving through IFSPD-based methodologies

4. Career Development Services

- Resume building and interview preparation support
- Placement assistance through the Tie-OPP platform
- Development of digital portfolios using the PORT platform

5. Global Exposure

- Opportunities for participation in international training programs
- Collaboration with global institutions and organizations
- Exposure to international standards, practices, and work environments

CHAPTER 2

INTERNHSIP DOMAIN OVERVIEW

2.1 FUNCTIONAL OVERVIEW OF IoT & EMBEDDED SYSTEMS

The IoT and Embedded Systems domain focuses on the development of smart and connected solutions by combining hardware components with software systems. It enables real-time data collection, processing, and communication, which are essential for modern automation and intelligent applications.

The major functional areas of this domain include:

1. Embedded Hardware Development

This area deals with designing and programming microcontroller-based systems such as Arduino, ESP8266, and ESP32. These systems are developed to perform dedicated tasks efficiently with minimal manual intervention, while ensuring reliability and optimized resource usage.

2. Connected System Implementation

This function involves creating systems where devices can communicate over the internet. It includes integrating sensors and actuators with controllers, enabling data transmission to cloud platforms, and supporting remote access and control.

3. Data Acquisition through Sensors

Various sensing devices such as temperature, humidity, infrared, ultrasonic, and motion sensors are used to gather environmental data. This data is then processed for monitoring, analysis, and automation purposes.

4. Network Communication Mechanisms

This area focuses on enabling communication between devices using protocols such as Wi-Fi, Bluetooth, MQTT, and HTTP, ensuring efficient and reliable data transfer across the system.

5. Smart Automation Applications

The domain supports the development of intelligent systems such as home automation, industrial monitoring, and environmental tracking solutions. These applications improve efficiency, reduce human effort, and enable smarter decision-making.

2.2 SYSTEM DEVELOPMENT METHODOLOGY

The IoT and Embedded Systems domain follows a structured and systematic approach for the development of projects, ensuring efficient design, implementation, and deployment of solutions.

The key stages involved in this methodology are as follows:

1. Problem Definition and Requirement Analysis

This stage involves identifying real-world problems and clearly defining the system requirements. It helps in understanding the objectives and expected outcomes of the project.

2. System Planning and Design

In this phase, the overall system architecture is designed, including:

- Selection of appropriate sensors and microcontrollers
- Choice of communication methods
- Determination of power requirements

3. Hardware Setup and Implementation

This step includes assembling the hardware components such as sensors, resistors, and microcontrollers to form a functional circuit.

4. Embedded Software Development

Programs are developed using platforms such as Arduino IDE to control hardware components and ensure proper system functionality.

5. IoT Integration and Connectivity

The system is integrated with IoT platforms to enable data transmission, storage, and real-time monitoring through cloud-based services.

6. Testing and Troubleshooting

Both hardware and software components are tested thoroughly to identify errors and ensure reliable system performance.

7. Deployment and Real-Time Application

The final system is implemented in real-world scenarios to perform the intended operations effectively.

2.3 SYSTEM TESTING AND VALIDATION

Testing and validation are critical processes in the IoT and Embedded Systems domain to ensure the reliability, accuracy, and proper functioning of developed systems.

The testing process is carried out at multiple levels, as outlined below:

1. Hardware Verification

- Inspecting circuit connections and overall hardware setup
- Ensuring stable and adequate power supply to all components
- Validating the accuracy and consistency of sensor outputs

2. Software Verification

- Identifying and resolving errors in the program code
- Verifying the correctness of logic and control flow
- Testing input-output operations for proper system response

3. IoT Communication Testing

- Confirming successful data transmission to cloud platforms
- Monitoring real-time data updates and system responsiveness
- Evaluating network reliability and connectivity performance

4. Integrated System Testing

- Testing the complete system after hardware and software integration
- Ensuring proper coordination between all system components
- Verifying overall system performance under real-time conditions

2.4 TEAM STRUCTURE AND ROLES:

The IoT and Embedded Systems domain follows a structured team-based approach to ensure efficient execution of projects and smooth coordination among members. The responsibilities are distributed across different roles as follows:

- **Project Lead / Mentor:** Provides overall guidance, supervises project progress, and ensures that objectives are achieved effectively
- **Hardware Team:** Responsible for circuit design, component selection, and physical implementation of the system
- **Software Team:** Develops and manages the program code required for system operation and control
- **IoT Integration Team:** Handles cloud connectivity, data transmission, and communication between devices and servers
- **Testing and Quality Team:** Conducts system testing, identifies issues, and ensures proper debugging and performance validation

This structured distribution of roles helps in maintaining an organized workflow and enhances collaboration throughout the project development process.

2.5 ROLES AND RESPONSIBILITIES OF INDIVIDUALS

The IoT and Embedded Systems domain involves multiple roles that work collaboratively to design, develop, and implement smart systems. Each role contributes specific expertise to ensure efficient project execution and successful outcomes.

1. IoT Engineers

- Design connected systems that enable communication between devices and cloud platforms
- Configure data flow and ensure reliable transmission across networks
- Oversee integration of hardware with cloud-based services

2. Embedded Systems Engineers

- Develop firmware for microcontroller-based systems
- Configure and manage interaction between sensors and controllers
- Ensure real-time performance and efficient resource utilization

3. Hardware Engineers

- Plan and construct electronic circuits required for the system
- Select appropriate components and ensure safe electrical operation
- Troubleshoot hardware-related issues during development

4. Software Developers

- Create application logic to control system behavior
- Test and refine code to improve functionality and performance
- Enable smooth coordination between software modules and hardware units

5. Interns

- Participate in different phases of system development
- Assist in basic programming, testing, and hardware interfacing
- Contribute to documentation and reporting
- Gain practical exposure to real-world IoT implementation

CHAPTER 3

WORK CARRIED OUT DURING INTERNSHIP

3.1 PCB DESIGN AND DEVELOPMENT USING KICAD




Fig 3.1 PCB Design

3.1.1 INTRODUCTION

Printed Circuit Board (PCB) design is a fundamental process in modern electronics, enabling the transformation of circuit schematics into functional physical systems. A PCB mechanically supports and electrically connects electronic components through conductive pathways etched on an insulating substrate.

During the internship, practical exposure to PCB design was gained using KiCad software. The work involved end-to-end design activities including schematic capture, component selection, footprint assignment, layout design, routing, and preparation of manufacturing files. This hands-on experience provided a clear understanding of both theoretical concepts and real-world implementation challenges in PCB development.

3.1.2 PCB DESIGN WORKFLOW

The PCB design process carried out during the internship is summarized below:

1. Schematic Design

- Circuit diagrams were created using KiCad schematic editor
- Electronic components such as resistors, capacitors, integrated circuits, and connectors were added
- Logical electrical connections were defined to represent the intended circuit functionality

2. Component Selection

- Components were selected based on technical requirements such as:
 - Voltage and current ratings
 - Power dissipation capacity
 - Availability and cost
 - Package type and size
- Preference was given to standard and industry-reliable components

3. Footprint Assignment

- Appropriate footprints were assigned to each component
- Ensured compatibility between schematic symbols and physical packages
- Verified dimensions based on datasheets for accurate board assembly

4. PCB Layout Design

- Components were arranged on the board considering:
 - Signal flow and logical grouping
 - Minimum track lengths
 - Adequate spacing between components
 - Thermal considerations for heat-generating elements

5. Routing

- Electrical connections were established using copper tracks
- Separate attention was given to signal routing and power routing
- Wider tracks were used for high-current paths to avoid overheating
- Efforts were made to reduce noise and interference

6. Ground Plane Design

- A ground plane was implemented to provide a low-resistance return path

- Helped in minimizing electrical noise and improving signal stability
- Enhanced overall electromagnetic compatibility of the design

7. Design Rule Check (DRC)

- The design was verified using DRC tools to ensure:
 - No short circuits or open connections
 - Proper clearance and spacing between tracks
 - Compliance with manufacturing constraints

8. Gerber File Generation

- Final PCB design files were exported in Gerber format
- These files are essential for PCB fabrication and manufacturing processes

3.2 DC TO DC CONVERTER




FIGURE 3.2.1: Schematic Design of DC to DC Converter





Figure 3.2.2: Layout and 3D Model of the DC-to-DC Converter



Layers Manager	
Layers	Items
1	SC-B_Cu.gbr (Copper, L2)
2	SC-B_Mask.gbr (Soldermask, Bot)
3	SC-B_Paste.gbr (Paste, Bot)
4	SC-B_Silkscreen.gbr (Legend, Bot)
5	SC-Edge_Cuts.gbr (Profile, NP)
6	SC-F_Cu.gbr (Copper, L1)
7	SC-F_Mask.gbr (Soldermask, Top)
8	SC-F_Paste.gbr (Paste, Top)
9	SC-F_Silkscreen.gbr (Legend, Top)
10	SC-NPTH-drl.gbr (NonPlated,1,2,NPTH,Drill)
11	SC-PTH-drl.gbr (Plated,1,2,PTH,Drill)

Figure 3.2.3: Gerber File Generation for DC-to-DC Converter

3.2.1 INTRODUCTION

A DC-to-DC converter is an electronic circuit used to convert a direct current (DC) voltage from one level to another. In this project, a **buck converter (step-down converter)** is designed to reduce a higher input voltage to a regulated output of approximately **8V with a current rating of up to 2A**. Such converters are widely used in embedded systems and power management applications due to their high efficiency.

3.2.2 CIRCUIT DESCRIPTION

The designed circuit consists of the following main sections:

- **Input Stage:**
Includes the input connector (J1), MOSFET (Q1), diode (D1), and a π (pi) filter formed by L1, C1, and C2. This stage helps in reducing input noise and stabilizing the supply.
- **Switching Regulator IC:**
The AP1534 switching regulator IC is used as the main control element. It regulates the switching operation required for voltage conversion.
- **Inductor (L2):**
Acts as an energy storage element during the switching process.
- **Diode (CR1):**
Provides a conduction path for current when the switching element is in the OFF state.
- **Output Capacitors (C3, C4, C5, C6):**
These capacitors filter the output and reduce voltage ripple, ensuring a smooth DC output.
- **Feedback Network (RA1, RB1):**
Determines and maintains the desired output voltage by providing feedback to the regulator IC.

3.2.3 WORKING PRINCIPLE

The operation of the buck converter is based on high-frequency switching:

- When the internal switch of the regulator IC turns **ON**, current flows through the inductor, and energy is stored in its magnetic field.
- When the switch turns **OFF**, the inductor releases the stored energy, supplying current to the load.
- The diode ensures continuous current flow during the OFF period.
- Output capacitors smooth the voltage, reducing ripple and maintaining a stable output.

3.2.4 PCB DESIGN CONSIDERATION

During PCB design, the following important factors were considered:

- Adequate trace width was maintained for high-current paths to prevent overheating
- A continuous ground plane was used to minimize electrical noise and improve stability

- Components were placed close together to reduce parasitic effects and improve efficiency
- Thermal management techniques were applied to handle heat dissipation effectively

3.2.5 RESULT

The designed DC-DC buck converter successfully steps down the input voltage and provides a stable and regulated output of approximately **8V/2A**. The circuit demonstrates reliable performance and is suitable for powering embedded systems and low-power electronic devices.

3.3 LDR BASED LIGHT DETECTION CIRCUIT




Fig 3.3.1- LDR based light detection circuit

3.3.1 INTRODUCTION

A Light Dependent Resistor (LDR) is a passive electronic component whose resistance varies with the intensity of light falling on it. It is commonly used in light-sensing applications. In this project, an LDR-based circuit is designed to automatically control an LED based on ambient light conditions, enabling efficient energy usage.

3.3.2 COMPONENTS USED

The main components used in the circuit include:

- LDR sensor
- Resistors (R1, R3)
- NPN Transistor (BC817)
- Light Emitting Diode (LED)
- DC power supply

3.3.3 CIRCUIT DESCRIPTION

- The LDR and resistor (R1) form a voltage divider circuit.
- The output voltage from this divider is connected to the base of the transistor.
- The transistor (BC817) functions as an electronic switch to control the LED.
- Resistor R3 is used to limit the current flowing through the LED and protect it from damage.

3.3.4 WORKING PRINCIPLE

The circuit operates based on changes in light intensity:

- **In bright light conditions:**

The resistance of the LDR decreases, resulting in a lower voltage at the transistor base. This keeps the transistor in the OFF state, and the LED remains OFF.

- **In dark conditions:**

The resistance of the LDR increases, causing a higher voltage at the transistor base. This turns the transistor ON, allowing current to flow and the LED to glow.

3.3.5 PCB DESIGN CONSIDERATION

- A compact PCB layout was designed to reduce size and improve efficiency
- Short and direct routing was used to maintain signal stability
- Proper grounding techniques were applied to minimize noise
- Component placement was optimized for easy assembly and testing

3.3.6 APPLICATION

- Automatic street lighting systems
- Smart home lighting control
- Energy-saving lighting solutions
- Light-sensitive switching circuits

3.3.6 RESULT

The designed LDR-based circuit successfully detects ambient light levels and automatically controls the LED. It operates reliably and demonstrates an effective method for energy-efficient lighting control.

3.4 AUTOMOTIVE TURN SIGNAL & HAZARD LIGHT CONTROL SYSTEM




Fig 3.4.1- Automotive Turn Signal & Hazard Light Control System

3.4.1 INTRODUCTION

This project presents a microcontroller-based automotive lighting control system designed to manage turn indicators and hazard lights in a vehicle. The system processes input signals such as left turn, right turn, hazard switch, and ignition status, and accordingly controls the output lights. It ensures reliable and efficient operation under automotive conditions, including protection against voltage fluctuations and electrical noise.

3.4.2 COMPONENTS USED

- N32G031F1QAT7 Microcontroller
- VND9016AJTR High-Side Driver IC
- LM317 Voltage Regulator
- MOSFET (for reverse polarity protection)
- Inductor and capacitors (for filtering)
- Resistors and diodes (including Zener and TVS diodes)
- Connectors for input and output signals

3.4.3 CIRCUIT DESCRIPTION

The circuit is divided into the following functional blocks:

1. Input Section

- Receives signals such as **turn left**, **turn right**, **hazard**, and **ignition**
- Includes protection components like resistors, diodes, and Zener diodes to safeguard the microcontroller

2. Power Supply Section

- A MOSFET is used for reverse polarity protection
- Filters (inductor and capacitors) reduce noise and voltage fluctuations
- The LM317 Voltage Regulator provides a stable **+5V supply** for the microcontroller

3. Control Section

- The N32G031F1QAT7 Microcontroller processes all input signals
- Generates control signals for indicator blinking and hazard operation

4. Driver Section

- The VND9016AJTR High-Side Driver IC drives the output loads
- Capable of handling high current required for automotive lamps

5. Output Section

- Controls **Left Output** and **Right Output** for vehicle indicators
- Includes capacitors for noise suppression

3.4.4 WORKING PRINCIPLE

- The system continuously monitors input signals such as turn and hazard switches
- Based on the input:
 - **Left signal active** → **Left indicator blinks**
 - **Right signal active** → **Right indicator blinks**
 - **Hazard signal active** → **Both indicators blink simultaneously**
- The microcontroller generates timing signals for blinking
- These signals are sent to the driver IC, which controls the high-current output loads
- Protection circuits ensure safe operation under varying voltage conditions

3.4.5 PCB DESIGN CONSIDERATION

- High-current paths were designed with wider traces
- Ground plane was used to reduce electrical noise
- Proper separation between control and power sections was maintained
- Input protection components were placed close to connectors
- Thermal considerations were applied for driver IC and power components

3.4.6 RESULT

The designed system successfully controls vehicle indicator and hazard lights based on input conditions. It provides stable, reliable, and efficient performance with proper protection and power management, making it suitable for real-world automotive applications.

3.5 BATTERY REVERSE POLARITY PROTECTION CIRCUIT





Fig 3.5- Battery Reverse Polarity Protection Circuit

3.5.1 INTRODUCTION

Reverse polarity protection is an essential technique used in electronic circuits to prevent damage when the power supply is connected incorrectly. This circuit uses a **MOSFET-based approach**, which offers higher efficiency and lower power loss compared to traditional diode-based protection.

3.5.2 COMPONENTS USED

- P-channel MOSFET (Q1)
- LED (D1) – used as an indicator
- Resistor (R1 – 100kΩ) – gate pull-down resistor
- Resistor (R2 – 1kΩ) – current limiting resistor for LED
- DC Power Supply (9V Battery)

3.5.3 WORKING PRINCIPLE

1. Correct Polarity Condition

- When the battery is connected correctly:
 - The gate-source voltage (V_{gs}) becomes negative.
 - This turns the **P-channel MOSFET ON**.
 - Current flows from source to drain.

- The **LED glows**, indicating normal operation.

2. Reverse Polarity Condition

- When the battery is connected in reverse:
 - The gate-source voltage condition is not satisfied.
 - The MOSFET remains **OFF**.
 - No current flows through the circuit.
 - The **LED remains OFF**, protecting the circuit from damage.

3.5.4 PCB DESIGN CONSIDERATION

- Short and wide traces were used for power paths to handle current safely
- Proper grounding ensured stable operation
- MOSFET placed close to input for effective protection
- Compact layout maintained for efficiency

3.5.5 RESULT

The designed circuit successfully protects the system from reverse polarity conditions. Under correct polarity, the circuit operates normally and the LED glows, while under reverse connection, the MOSFET blocks current, ensuring safe operation.

3.6 PASSWORD BASED DOOR LOCK SYSTEM

3.6.1 INTRODUCTION

A password-based door lock system is an electronic security solution that allows access only when a correct password is entered. This system uses a microcontroller to verify user input and control a locking mechanism. It enhances security and eliminates the need for physical keys.




Fig 3.6 Password Based Door Lock System

3.6.2 COMPONENTS USED

- Arduino Uno microcontroller
- 4×4 Matrix Keypad
- Servo Motor (for door lock mechanism)
- 16×2 LCD Display
- Buzzer
- Connecting wires and power supply

3.6.3 CIRCUIT DESCRIPTION

- The **keypad** is connected to the digital pins of the Arduino to accept user input.
- The **LCD display** is interfaced to show messages such as “ENTER PASSWORD”.
- The **servo motor** is connected to a PWM pin and acts as the locking mechanism.
- The **buzzer** is connected to provide audio feedback during correct or incorrect password entry.
- The Arduino acts as the central controller, processing all inputs and controlling outputs.

3.6.4 WORKING PRINCIPLE

- The system prompts the user to enter a password through the keypad.
- When keys are pressed, the input is sent to the Arduino for verification.

- The entered password is compared with a predefined password stored in the program.

Correct Password:

- Arduino sends a signal to the servo motor
- Servo rotates to unlock the door
- LCD displays access granted message
- Buzzer may give a short beep

Incorrect Password:

- Access is denied
- LCD displays error message
- Buzzer alerts with a warning sound

3.6.5 RESULT

The system successfully allows access only when the correct password is entered. It provides a simple and reliable electronic locking mechanism suitable for basic security applications.

3.7 ULTRASONIC DISTANCE MEASUREMENT SYSTEM




Fig 3.7- Ultrasonic Distance Measurement System

3.7.1 INTRODUCTION

This project is designed to measure distance using an ultrasonic sensor and display the measured value on a 16×2 LCD. The system uses the HC-SR04 Ultrasonic Sensor to detect the distance of an object by transmitting ultrasonic waves and calculating the time taken for the echo to return. Such systems are widely used in automation, robotics, and obstacle detection applications.

3.7.2 COMPONENTS USED

- Arduino Uno microcontroller
- HC-SR04 Ultrasonic Sensor
- 16×2 LCD Display
- Potentiometer (for LCD contrast adjustment)
- Breadboard and connecting wires
- Power supply

3.7.3 CIRCUIT DESCRIPTION

- The ultrasonic sensor consists of two main pins:
 - **Trigger (Trig):** Connected to an Arduino output pin
 - **Echo:** Connected to an Arduino input pin
- The LCD is interfaced with the Arduino to display the measured distance.
- A potentiometer is connected to the LCD to control and adjust the display contrast.
- The Arduino acts as the central processing unit, handling signal generation, measurement, and display.

3.7.4 WORKING PRINCIPLE

- The Arduino sends a short trigger pulse (usually 10 microseconds) to the ultrasonic sensor.
- The sensor emits ultrasonic waves into the surrounding environment.
- When these waves hit an object, they are reflected back to the sensor.
- The echo pin outputs a pulse corresponding to the time taken for the wave to return.
- The Arduino measures this time duration and calculates the distance of the object.

3.7.5 RESULT

The system successfully measures distance and displays accurate readings on the LCD. It provides a reliable and low-cost solution for real-time distance sensing applications.

CHAPTER 4

MAJOR PROJECT

IoT-Driven Cold Chain System for Real-Time Monitoring and Predictive Failure Prevention

4.1 INTRODUCTION

Cold chain systems are essential for maintaining the quality and safety of temperature - sensitive products like vaccines, biologics, and perishable foods. According to the World Health Organization, vaccines need to be stored within a temperature range of 2°C to 8°C to preserve their effectiveness. If these temperature limits are not maintained, the potency of the vaccines can be compromised, which may result in reduced efficacy and pose public health risks.

Ensuring this temperature range during storage and transport is particularly challenging in areas with limited infrastructure. Research indicates that common causes of cold chain failures include equipment breakdowns, power outages, and the absence of continuous monitoring. Conventional cold storage systems often depend on manual checks, which can delay the detection of temperature fluctuations and increase the risk of spoilage.

To overcome these issues, recent advancements in the Internet of Things (IoT) have made it possible to develop intelligent monitoring systems that offer real-time data collection and remote supervision. IoT-based solutions use sensors, microcontrollers, and cloud services to continuously monitor environmental factors such as temperature and humidity. These technologies enhance visibility, maintain compliance with safety regulations, and reduce reliance on manual inspections.

The proposed IoT-based cold chain system leverages an ESP32 microcontroller combined with sensors like the DHT22 to monitor conditions continuously. Data is transmitted to cloud platforms for visualization and analysis, while instant alerts are sent through GSM communication when irregularities occur.

In addition to real-time monitoring, the system utilizes data logging and analytical methods to support predictive maintenance by identifying early signs of potential failures. This forward-

looking strategy helps prevent temperature deviations before they happen, minimizing product loss and increasing system reliability.

The goal of this project is to create an affordable and scalable cold chain monitoring solution suitable for practical deployment. By integrating IoT technology with automated control features, the system improves operational efficiency, safeguards product quality, and contributes to the development of smarter logistics and healthcare infrastructure.

4.2 OBJECTIVE

The main goal of this project is to develop an IoT-based Cold Chain System that guarantees secure storage and transportation of temperature-sensitive products by enabling real-time monitoring and predictive failure detection. The detailed objectives include:

1. To design an efficient cold storage monitoring system The system will maintain the optimal storage environment (2°C to 8°C for vaccines, in line with WHO recommendations) by integrating sensors and control components to ensure stable operation.
2. To implement real-time monitoring using sensors Temperature and humidity sensors (such as DHT22) will be used to collect real-time environmental data inside the storage unit. This eliminates reliance on manual checking and ensures continuous supervision.
3. To develop an automated control mechanism A microcontroller-based system (ESP32) will process sensor data and automatically trigger actions such as activating cooling systems, alarms, or relays when parameters exceed safe thresholds.
4. To enable instant alert and notification system The system will use GSM or internet-based communication to send real-time alerts (SMS/notifications) to users when abnormal conditions such as temperature rise or door opening are detected.
5. To integrate cloud-based data logging and visualization The system will store data on cloud platforms, enabling remote monitoring through dashboards. This improves traceability, record-keeping, and compliance with safety standards.

4.3 PROBLEM STATEMENT

Conventional cold chain systems depend largely on manual checks and periodic monitoring, making them unreliable and prone to human error. Without continuous tracking, temperature variations caused by equipment faults, power interruptions, or improper handling may go unnoticed, leading to deviations from the required storage conditions for different products. For instance, vaccines must be maintained within a strict temperature range of 2°C to 8°C as specified by the World Health Organization, while other perishable goods require different controlled environments. Fluctuations in temperature and humidity, along with frequent door openings, can compromise the quality and safety of sensitive products such as vaccines and food items. While some modern solutions provide basic monitoring capabilities, they often lack real-time alert mechanisms and fail to respond promptly to abnormal conditions. Furthermore, these systems rarely utilize collected data for predictive analysis, resulting in a reactive approach where issues are detected only after damage has occurred. This leads to increased spoilage, economic losses, and potential health risks, highlighting the need for an intelligent, automated, and IoT-enabled cold chain system that ensures continuous monitoring, timely intervention, and improved reliability.

4.4 LITERATURE REVIEW

[1] The study titled “Enhancing Food Safety in the Cold Chain Through Internet of Things and Artificial Intelligence” by Wagner Augusto Müller et al. in the Journal of Food Science (2026) analyzes the impact of temperature variations on food quality and shelf life. The authors emphasize the role of IoT sensors in continuous monitoring and AI algorithms in predicting quality degradation. The system enables data-driven decision-making by identifying patterns in storage conditions. However, the study highlights limitations such as high computational requirements, increased system complexity, and limited real-world implementation. These challenges indicate the need for simpler, cost-effective solutions that can be deployed in practical environments.

[2] The paper “Development of Disposable Paper-Based Smart Visual Labels with Thermochromic Materials for Cold Chain Temperature Monitoring” by Qiwen Chen et al. in ScienceDirect (2025) presents a low-cost monitoring approach using thermochromic materials that change color when temperature thresholds are exceeded. This method provides a simple and intuitive way to detect temperature breaches without requiring electronic components. However, the system is limited by its single-use nature and lack of real-time monitoring capabilities. It also

does not provide alerts or remote access, making it unsuitable for continuous cold chain tracking.

[3] The research “Predicting ‘Broken Chain’ Risks in Food and Pharmaceutical Cold Chains Based on Multi-Modal Data Fusion and Machine Learning” by Gang Ping (2025) proposes advanced predictive models using IoT data combined with machine learning techniques such as LSTM and Transformer networks. The approach enables early detection of temperature deviations and potential failures. While the model demonstrates high prediction accuracy, it depends heavily on large datasets and computational resources. Additionally, challenges in real-time implementation and system scalability limit its practical applicability.

[4] The paper “Development of an IoT-Based Smart Cold Storage with Inventory Monitoring System” by Suganya Agappan et al. (2024) discusses integrating environmental monitoring with inventory management systems. The proposed system improves efficiency by tracking both storage conditions and stock levels simultaneously. It highlights the benefits of combining IoT-based sensing with supply chain management. However, the study lacks detailed implementation of automated control mechanisms and requires further validation under real-world conditions.

[5] The study “IoT-Based Integrated Sensing and Logging Solution for Cold Chain Management” (IEEE Xplore, 2025) presents a comprehensive framework for monitoring temperature-sensitive goods using IoT sensors and cloud-based storage. The system ensures continuous data logging and enhances traceability across the supply chain. It supports compliance with safety regulations by maintaining accurate historical records. However, challenges such as sensor calibration issues, data synchronization delays, and infrastructure costs affect system reliability and scalability.

4.5 METHODOLOGY

The proposed system operates by continuously collecting environmental data such as temperature, humidity, and door status using sensors integrated within the storage unit. The sensed data is processed by the ESP32 microcontroller and compared with predefined threshold values (for example, 2°C to 8°C for vaccines as specified by the World Health Organization). If any deviation from the safe range is detected, the system automatically triggers control actions such as activating cooling mechanisms through relays, generating buzzer alerts, and sending notifications via GSM or internet-based services. The processed data is simultaneously transmitted to a cloud platform (Firebase) using Wi-Fi, where it is stored and visualized through a web or mobile dashboard. This enables users to monitor system conditions in real time and take necessary

actions remotely. The system is tested under different conditions to ensure accurate sensing, timely alert generation, and reliable performance.




Fig 4.5 Block Diagram

4.6 SYSTEM ARCHITECTURE

The system architecture of the IoT-Driven Cold Chain System is designed to continuously monitor environmental conditions, maintain optimal storage temperature, provide real-time alerts, and enable remote monitoring through cloud integration.

- **Sensing Layer** : This layer includes sensors such as the DHT22 for temperature and humidity measurement and a magnetic reed switch module for detecting door status. These sensors continuously collect environmental data from the storage unit.
- **Processing Layer** : The ESP32 microcontroller acts as the central processing unit. It reads sensor data, performs basic processing, and converts it into a structured format suitable for transmission.
- **Decision Layer** : The system compares the processed data with predefined threshold values (for example, 2°C– 8°C for vaccines as specified by the World Health Organization). Any deviation from the safe range is identified as an abnormal condition.

- **Communication Layer** : The ESP32 transmits data to the cloud using Wi-Fi. Additionally, a GSM module is used to send SMS alerts during critical conditions when immediate attention is required.
- **Cloud Layer(Firebase)** : Firebase is used as the cloud database to store both real-time and historical sensor data. It ensures reliable data storage, synchronization, and remote accessibility.
- **Application & Dashboard Layer** : The system includes a web-based dashboard (developed using the NxtWave platform) and a mobile application interface. These platforms provide real-time visualization of parameters such as temperature, humidity, door status, and system alerts, enabling users to monitor system performance remotely.




Fig.4.6 System Architecture

4.7 HARDWARE AND SOFTWARE USED

4.7.1 ESP32

The ESP32 serves as the central processing unit of the system. It acquires sensor data, performs preliminary processing, and transmits the data to the cloud platform via Wi-Fi.

Features of ESP32:

- 1. Built-in Wi-Fi Connectivity:** The ESP32 supports 2.4 GHz Wi-Fi, allowing it to easily connect to local networks and send real-time data to mobile apps, cloud servers, or IoT platforms.




Fig.4.7.1 ESP32

2. Bluetooth and BLE Support: In addition to Wi-Fi, the module supports Bluetooth Classic and Bluetooth Low Energy (BLE), providing multiple options for communication and device pairing.

3. Dual-Core Processor: The ESP32 operates with a dual-core Tensilica LX6 CPU, providing fast performance and enabling simultaneous handling of sensor data, network tasks, and control signals.

4. Low Power Consumption: Designed with multiple sleep modes, the ESP32 is energy-efficient and suitable for solarpowered systems like this dryer.

5. Rich Peripheral Support: It includes GPIO pins, ADC, DAC, SPI, I2C, UART, PWM, and capacitive touch sensors, making it extremely flexible for hardware interfacing. **6. Enhanced Security Features:** Supports encrypted communication, secure boot, and flash encryption, ensuring safe data transmission.

Working Principle:

- The ESP32 receives humidity and temperature readings from the Arduino Uno.
- It processes and formats the data for wireless transmission.
- Using its Wi-Fi module, it connects to the user's local network.
- It sends real-time environmental data (temperature/humidity) to the mobile application.
- Farmers can remotely monitor drying conditions through the app from any location.
- This makes the system smart, user-friendly, and efficient.
- Smart agriculture and Home automation.
- IoT-based monitoring systems and Wireless sensor networks

4.7.2 DHT22 SENSOR

The DHT22 sensor is employed for accurate measurement of ambient temperature and relative humidity within the cold storage environment. It provides digital output, facilitating easy interfacing with the microcontroller.



Fig.4.7.2 DHT22 Sensor

The DHT22 uses a capacitive humidity sensing element and an NTC thermistor to measure environmental conditions. Changes in humidity affect the capacitance, while temperature variations change the resistance of the thermistor. An internal IC processes these changes and converts them into calibrated digital signals, which are transmitted to the ESP32 for further processing, monitoring, and control.

4.7.3 MAGNETIC REED SENSOR:




Fig.4.7.3 Magnetic Reed Sensor

The magnetic reed sensor is utilized to detect the open or closed state of the storage door. This enables monitoring of access frequency, which directly impacts temperature stability. The sensor is interfaced with the ESP32, which reads its status in real time. Whenever the door is opened, the ESP32 can trigger alerts, activate a buzzer, or log the event to the cloud platform. This feature enhances safety, improves monitoring accuracy, and supports preventive action in the cold chain system.

4.7.4 LCD DISPLAY:



Fig.4.7.4 LCD Display

An LCD (Liquid Crystal Display) is an electronic display module widely used in embedded systems, automation, and IoT projects. It is preferred for its low power consumption, clear visibility, and ability to display alphanumeric characters and custom symbols. The most commonly used type in microcontroller-based projects is the 16x2 LCD, meaning it can display 16 characters per line across 2 lines.

4.7.5 LED INDICATOR:



Fig.4.7.5 LED Indicator

An LED (Light Emitting Diode) emits light when current flows through it in the forward direction. The ESP32 controls the LED by sending HIGH or LOW signals to the connected GPIO pins. When the output pin is HIGH, current flows and the LED glows; when LOW, the LED remains off. Based on sensor data from the system, the microcontroller activates specific LEDs to indicate different environmental conditions, enabling real-time visual monitoring.

4.7.6 BUZZER:



Fig.4.7.6 Buzzer

An LCD (Liquid Crystal Display) is an electronic display module widely used in embedded systems, automation, and IoT projects. It is preferred for its low power consumption, clear visibility, and ability to display alphanumeric characters and custom symbols. The most commonly used type in microcontroller-based projects is the 16x2 LCD, meaning it can display 16 characters per line across 2 lines

4.7.7 RELAY MODULE:



Fig.4.7.7 Relay Module

A relay module works as an electrically operated switch. When the ESP32 sends a signal to the relay input, it energizes an internal coil, creating a magnetic field that moves a mechanical contact. This action either opens or closes the circuit connected to the external device. In a cold storage system, the relay is activated when temperature or humidity exceeds set limits, allowing the microcontroller to turn ON or OFF devices like compressors or fans automatically, maintaining optimal storage conditions.

4.7.8 PELTIER MODULE WITH COOLING FAN AND HEAT SINK:




Fig.4.7.8 Peltier Module with cooling fan and heat sink

The Peltier module operates based on the thermoelectric effect, specifically the Peltier effect. When direct current passes through the module, heat is absorbed on one side (creating a cooling effect) and released on the opposite side (creating a heating effect). The cold side is placed inside the storage chamber, while the hot side is connected to a heat sink and fan to dissipate heat. The ESP32 controls the module based on temperature readings, turning it ON or OFF to maintain the desired cooling conditions.

4.7.9 SIM900A GSM MODULE:



Fig.4.7.9 GSM Module

The SIM900A GSM module operates by connecting to a cellular network using a SIM card. It communicates with the ESP32 through serial communication (UART). When the microcontroller detects abnormal conditions from sensors, it sends commands to the GSM module to

transmitSMS alerts to predefined phone numbers. The module converts these commands into signals that are sent over the mobile network, ensuring real-time remote notification and system awareness.

4.7.10 LM2596 BUCK CONVERTER:



Fig.4.7.10 LM2596 Buck Converter

The LM2596 operates based on the principle of a switching regulator. It rapidly switches the input voltage ON and OFF using an internal transistor, controlling the energy transferred to the output through an inductor, diode, and capacitor. By adjusting the duty cycle of the switching signal, the converter regulates the output voltage to a lower, stable level. This stepped-down voltage is then supplied to components like the ESP32, ensuring efficient and safe operation of the overall system.

4.7.11 BREADBOARD AND JUMPER WIRES:



Fig.4.7.11 Breadboard and Jumper Wires

A breadboard consists of a grid of holes internally connected by metal strips. When components and wires are inserted into these holes, electrical connections are established through these conductive paths. The central area is typically used for placing components, while the side rails are used for power supply distribution. This arrangement allows the ESP32 and other components to be interconnected easily, enabling quick testing and modification of the circuit without permanent soldering.

4.7.12 ARDUINO IDE:



Fig.4.7.12 Arduino IDE

The Arduino IDE works by translating the user-written program into a format that the microcontroller can understand. Once the code is compiled, it is uploaded to the ESP32 through a communication interface. The microcontroller then executes the instructions continuously in loop, reading sensor inputs, processing data, and controlling connected devices accordingly. The serial monitor helps in observing outputs and diagnosing errors during execution.

4.7.13 ANDROID STUDIO:




Fig.4.7.13 Arduino Studio

Android Studio functions by allowing developers to write application code and design user interfaces within a single platform. The code is compiled into an Android application package (APK), which can be installed on mobile devices. The application communicates with the system through defined protocols or cloud services, receives data, and updates the interface accordingly. This enables users to monitor system conditions and receive notifications in real time

4.7.14 MOBILE APPLICATION:




Fig.4.7.14 Mobile Application

The cold chain monitoring mobile application is developed to display real-time temperature and humidity values from the storage unit, enabling users to monitor environmental conditions remotely. The application communicates with the ESP32-based system through IoT integration and receives continuous sensor data for live tracking. When the user launches the application, a dashboard interface is displayed showing system parameters and connection status. The user can initiate communication with the system through a connection option provided in the app. Once the connection is successfully established, the ESP32 begins transmitting real-time data, including temperature and humidity readings, to the application. The received data is updated dynamically

on the dashboard, allowing users to continuously observe storage conditions. In case of abnormal variations beyond the defined threshold limits, the system triggers alerts, ensuring timely action to prevent damage to temperature-sensitive products.

4.7.15 WEB DASHBOARD:




Fig.4.7.15 Web Dashboard

The dashboard displays key parameters such as temperature (in °C), humidity (in %), and the operational status of the cooling system. It presents real-time data received from the ESP32 in a clear and organized format, allowing users to easily understand whether the storage environment is maintained within the required threshold range of 2°C to 8°C. The data is updated dynamically as new readings are transmitted, ensuring accurate and continuous monitoring. With its simple and user-friendly design, the dashboard can be accessed from any location, enabling users to track system behavior effectively and stay informed about changes in storage conditions.

4.8 WORKING MODEL




Fig.4.8 Working Model of IoT Driven Cold Chain System

1. System Initialization: The operation of the system begins with the initialization phase, where power is supplied to the ESP32 microcontroller and all connected components. These include sensors, LCD display, GSM module, and output devices. After initialization, the ESP32 establishes a Wi-Fi connection for communication with the mobile application. Simultaneously, the GSM module is configured to enable SMS-based alert notifications.

2. Data Acquisition (Sensing Layer): The sensing layer consists of a DHT22 sensor and a magnetic reed switch module. The DHT22 sensor continuously measures temperature and humidity inside the cold storage unit, while the reed switch module detects the door status (open or closed). These sensors provide real-time environmental data to the ESP32 microcontroller.

3. Data Processing and Decision Making: The ESP32 microcontroller processes the received sensor data and compares the temperature values with predefined threshold limits, typically maintained within the range of 2°C to 8°C. Based on this comparison, the system classifies the operating condition as normal, warning, or critical. This decision-making process forms the core logic of the system.

4. Local Monitoring Using LCD Display: For on-site monitoring, the processed data is displayed on an LCD screen. The display shows real-time values of temperature, humidity, and door status. This ensures that users can monitor system conditions locally even without internet connectivity.

5. Remote Monitoring Through Mobile Application: The ESP32 transmits real-time data to a mobile application via Wi-Fi. The application provides a user interface for monitoring system parameters, including temperature, humidity, and door status. It also displays graphical trends and system status indicators, enabling effective remote supervision.

6. Alert and Notification System: When abnormal conditions are detected, such as temperature exceeding the safe range or the door remaining open, the system activates the alert mechanism. Local alerts include buzzer activation and LED indication. Additionally, the GSM module sends SMS notifications to the user, ensuring reliable alerts even in the absence of internet connectivity.

7. Cooling System Operation: To maintain the required temperature conditions, the system includes an automated cooling mechanism. When the temperature rises above the threshold value, the ESP32 activates a relay or MOSFET driver to power the Peltier module and cooling fan. The cooling system reduces the temperature and restores it to the acceptable range. Once the temperature stabilizes, the system automatically deactivates the cooling components.

8. Continuous Monitoring and Control: The system operates continuously in a loop where sensing, data processing, decision-making, communication, and control actions are performed repeatedly. This closed-loop operation ensures real-time monitoring, quick response to environmental changes, and efficient maintenance of optimal cold chain condition.

4.9 RESULT

4.9.1 INTRODUCTION

The IoT-based Cold Chain Monitoring System was tested under different operating conditions to evaluate its performance, accuracy, and reliability. The results obtained from LCD display, GSM alerts, mobile application, and website dashboard are discussed in the following subsections.

4.9.2 LCD DISPLAY RESULT




Fig.4.9.2 LCD Display Result

The LCD display provided real-time monitoring of temperature, humidity, and door status. The values were updated continuously without delay, ensuring reliable local monitoring. The display clearly indicated normal, warning, and critical conditions based on threshold limits.

4.9.3 MOBILE APPLICATION RESULT

The mobile application successfully displayed real-time data received from the ESP32 via Wi-Fi. It provided live temperature and humidity values, door status, and graphical trends. Warning and critical alerts were generated accurately. The application enabled remote monitoring and ensured quick response to abnormal conditions.



Fig.4.9.3 Mobile Application Result

4.9.4 WEBSITE DASHBOARD RESULT




Fig.4.9.4 Website Dashboard Result

The website dashboard displayed real-time data updates similar to the mobile application. It provided a centralized interface for monitoring system parameters and historical trends. The dashboard ensured continuous visibility of system performance and enhanced data accessibility.

4.9.5 GSM ALERT RESULTS



Fig.4.9.5 GSM Alert Result

The GSM module successfully transmitted SMS alerts during abnormal conditions such as temperature exceeding limits or door opening. The alerts were received instantly on the registered mobile number. This ensured reliable communication even in the absence of internet connectivity.

4.9.6 PERFORMANCE ANALYSIS

The system demonstrated accurate sensing, fast response time, and reliable communication. The integration of LCD, mobile application, website dashboard, and GSM module ensured efficient monitoring and control. Overall, the system maintained temperature within the required range and responded effectively to all tested conditions.

- 1. Accurate Monitoring of Storage Conditions:** The DHT22 sensor continuously measured temperature and humidity inside the cold storage unit with good accuracy. This ensured that the environmental conditions remained within the required range for storing temperature-sensitive products.
- 2. Successful Real-Time Display and Remote Monitoring:** The system displayed live temperature and humidity values on both the LCD and mobile application. The ESP32 transmitted data efficiently, allowing users to monitor storage conditions remotely without being physically present..
- 3. Automated Temperature Control Mechanism:** The cooling system, controlled through the relay and Peltier module, responded automatically to changes in temperature. This helped maintain stable internal conditions and reduced dependency on manual intervention.
- 4. Effective Humidity Management:** The system continuously tracked humidity levels and responded when values exceeded safe limits. This prevented issues such as moisture buildup, condensation, and potential spoilage of stored products.

5. Reliable Alert and Notification System: The buzzer and GSM module worked effectively to alert users during abnormal conditions. Immediate notifications enabled quick corrective action, improving the safety and reliability of the system.

6. Continuous Real-Time Data Monitoring: The mobile application consistently displayed updated temperature and humidity readings received from the ESP32. This ensured uninterrupted monitoring and allowed users to track system performance at all times.

4.10 ADVANTAGES:

- **Real-Time Monitoring:**– The system continuously tracks temperature and humidity, ensuring that storage conditions are always visible and under control.
- **Improved Product Safety:**– By maintaining optimal environmental conditions, the system helps preserve the quality of temperature-sensitive products such as vaccines and perishable goods.
- **Automated Control:**– The integration of sensors with relay and cooling modules allows automatic regulation of temperature, reducing the need for manual intervention.
- **Instant Alert System:**– The buzzer and GSM module provide immediate notifications when conditions exceed safe limits, enabling quick response to prevent damage or spoilage.
- **Remote Accessibility:**– Users can monitor system parameters through a mobile application, allowing supervision from any location without physical presence.
- **Reliable Communication:**– The system supports both IoT-based monitoring and GSM alerts, ensuring communication even in limited internet conditions.
- **Low Power Consumption:**– Efficient components like ESP32 and optimized modules ensure reduced energy usage, supporting continuous operation.

4.11 DISADVANTAGES:

- **Initial Setup Cost** – The integration of sensors, communication modules, and control systems increases the initial investment compared to basic storage methods.
- **System Complexity:**– Integration of multiple hardware and software components increases system complexity and requires proper configuration

- **Maintenance Requirement:**– Sensors and electronic modules require periodic calibration and maintenance to ensure accurate performance.

4.1 FUTURE SCOPE:

- 1. Location-Aware Cold Chain Tracking:** Integration of a GPS module to monitor the real-time location of storage units during transportation, improving traceability and logistics management.
- 2. Predictive Failure Detection:** Application of Artificial Intelligence and Machine Learning techniques to analyze sensor trends and predict potential failures before they occur.
- 3. Multi-Parameter Monitoring:** Addition of advanced sensors to track parameters such as air quality, gas leakage, and pressure for comprehensive environmental monitoring.
- 4. Scalability for Industrial Applications:** Expansion of the system to support large-scale cold chain networks with multiple interconnected storage units.
- 5. Security Enhancement:** Incorporation of authentication mechanisms and data encryption to ensure secure communication and prevent unauthorized access.

CHAPTER 5

CONCLUSION

This internship served as an important step in transforming academic knowledge into practical skills within the domains of embedded systems and IoT. It provided hands-on experience in designing, developing, and testing real-world electronic systems, which significantly improved both technical understanding and confidence.

During the course of the internship, multiple circuit-based and microcontroller-driven projects were explored, allowing a deeper understanding of hardware components, sensor integration, and system behavior. Working on these projects helped in developing a systematic approach to problem-solving, from initial design to final testing and validation.

The development of the IoT-based cold chain monitoring system was a key learning experience. It demonstrated how modern technologies can be applied to solve real-life problems by enabling continuous monitoring, automated control, and remote access to critical data. This project highlighted the importance of reliability, efficiency, and real-time response in smart systems.

In addition, exposure to PCB design and tools like KiCad enhanced practical knowledge of circuit layout and design considerations. The internship also contributed to improving analytical thinking, adaptability, and the ability to work with interdisciplinary technologies.

Overall, the experience was highly beneficial in building a strong foundation for future work in embedded systems and IoT. It has prepared me to take on more advanced challenges and contribute effectively to technology-driven solutions in real-world applications.

REFERENCES

- [1] Cil, A. Y., Abdurahman, D., & Cil, I. (2022). Internet of Things enabled real-time cold chain monitoring in a container port. *Journal of Shipping and Trade*, 7(1), 1–18.
- [2] Sarkar, S., Akshatha, K. S., Saurabh, A., & Samanvitha, B. (2022). IoT enabled cold supply chain monitoring system. *Proceedings of the IEEE Global Conference for Advancement in Technology (GCAT)*.
- [3] Alshdadi, A., Kamel, S., Alsolami, E., Lytras, M. D., & Boubaker, S. (2024). An IoT smart system for cold supply chain storage and transportation management. *Engineering, Technology & Applied Science Research*, 14(2), 13167–13172.
- [4] Torres-Sánchez, R. (2024). Monitoring perishable commodities using cellular IoT: An intelligent real-time conditions tracker design. *Applied Sciences*, 14(23), 11050.
- [5] Baghel, L. K., Raina, R., Kumar, S., & Catarinucci, L. (2024). IoT-based integrated sensing and logging solution for cold chain monitoring applications. *IEEE Journal of Radio Frequency Identification*.
- [6] Shanmugam, M., Gomathi, R. D., Sathesh, S., & Poovizhi, S. (2024). Intelligent cold chain security using ESP32 and temperature sensors. *Journal of Environmental Nanotechnology*, 13(1), 17–25.