

COMP6080

Web Front-End Programming

Javascript (General)

Map, Reduce, Filter

Map, Reduce, Filter

- **Map**: creates a new list with the results of calling a provided function on every element in the given list
- **Reduce**: executes a **reducer** function (that you provide) on each member of the array resulting in a single output value
- **Filter**: creates a new array with all elements that pass the test implemented by the provided function

Map

Map: creates a new array with the results of calling a provided function on every element in the calling array

map.js

```
1  const items = [1, 2, 3];
2
3  const makeSquare = (i) => {
4    return {
5      item: i,
6      square: i*i,
7    };
8  };
9
10 const itemsAndSquares = items.map(makeSquare);
11
12 console.log(itemsAndSquares);
```

Reduce

Reduce: executes a **reducer** function (that you provide) on each member of the array resulting in a single output value

reduce.js

```
1  const items = [1, 2, 3];
2
3  const getSum = (total, num) => {
4    return total + num;
5  };
6
7  const totalItems = items.reduce(getSum, 0);
8
9  console.log(totalItems);
```

Filter

Filter: creates a new array with all elements that pass the test implemented by the provided function

filter.py

```
1 const items = [1, 2, 3];
2
3 const onlyEven = (i) => {
4   if (i % 2 == 0) return true;
5   return false;
6 };
7
8 const evenItems = items.filter(onlyEven);
9
10 console.log(evenItems);
```

Combined

allthree.py

```
1 from functools import reduce
2
3 if __name__ == '__main__':
4     marks = [ 39, 43.2, 48.6, 24, 33.6 ] # Marks out of 60
5     normalised_marks = map(lambda m: 100*m/60, marks)
6     passing_marks = list(filter(lambda m: m >= 50, normalised_marks))
7     total = reduce(lambda a, b: a + b, passing_marks)
8     average = total/len(passing_marks)
9     print(average)
```