

GeeksforGeeks

A computer science portal for geeks

Practice

IDE

Q&A

GeeksQuiz

Given only a pointer to a node to be deleted in a singly linked list, how do you delete it?

A **simple solution** is to traverse the linked list until you find the node you want to delete. But this solution requires pointer to the head node which contradicts the problem statement.

Fast solution is to copy the data from the next node to the node to be deleted and delete the next node. Something like following.

```
struct node *temp = node_ptr->next;
node_ptr->data = temp->data;
node_ptr->next = temp->next;
free(temp);
```

Program:

```
#include<stdio.h>
#include<assert.h>
#include<stdlib.h>

/* Link list node */
struct node
{
    int data;
    struct node* next;
};

/* Given a reference (pointer to pointer) to the head
of a list and an int, push a new node on the front
of the list. */
void push(struct node** head_ref, int new_data)
{
    /* allocate node */
    struct node* new_node =
        (struct node*) malloc(sizeof(struct node));

    /* put in the data */
    new_node->data = new_data;
```

```

/* link the old list off the new node */
new_node->next = (*head_ref);

/* move the head to point to the new node */
(*head_ref)    = new_node;
}

void printList(struct node *head)
{
    struct node *temp = head;
    while(temp != NULL)
    {
        printf("%d  ", temp->data);
        temp = temp->next;
    }
}

void deleteNode(struct node *node_ptr)
{
    struct node *temp = node_ptr->next;
    node_ptr->data    = temp->data;
    node_ptr->next    = temp->next;
    free(temp);
}

/* Driver program to test above function*/
int main()
{
    /* Start with the empty list */
    struct node* head = NULL;

    /* Use push() to construct below list
    1->12->1->4->1  */
    push(&head, 1);
    push(&head, 4);
    push(&head, 1);
    push(&head, 12);
    push(&head, 1);

    printf("\n Before deleting \n");
    printList(head);

    /* I m deleting the head itself.
    You can check for more cases */
    deleteNode(head);

    printf("\n After deleting \n");
    printList(head);
    getchar();
}

```

This solution doesn't work if the node to be deleted is the last node of the list. To make this solution work we can mark the end node as a dummy node. But the programs/functions that are using this function should also be modified.

Try this problem for doubly linked list.



41 Comments Category: [Linked Lists](#)

Related Posts:

- [Merge two sorted linked lists such that merged list is in reverse order](#)
- [Compare two strings represented as linked lists](#)
- [Rearrange a given linked list in-place.](#)
- [Sort a linked list that is sorted alternating ascending and descending orders?](#)
- [Select a Random Node from a Singly Linked List](#)
- [Merge Sort for Doubly Linked List](#)
- [Point to next higher value node in a linked list with an arbitrary pointer](#)
- [Swap nodes in a linked list without swapping data](#)

([Login](#) to Rate and Mark)

2

Average Difficulty : **2/5.0**
Based on 4 vote(s)

☐
☐

Add to TODO List

Mark as DONE

[Like](#) [Share](#) One person likes this. Be the first of your friends.

Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.

@geeksforgeeks, Some rights reserved

[Contact Us!](#)

[About Us!](#)

[Advertise with us!](#)