

GeeksforGeeks

A computer science portal for geeks

Practice

IDE

Q&A

GeeksQuiz

Given a linked list of line segments, remove middle points

Given a linked list of co-ordinates where adjacent points either form a vertical line or a horizontal line. Delete points from the linked list which are in the middle of a horizontal or vertical line.

Examples:

Input: (0,10)->(1,10)->(5,10)->(7,10)

|
(7,5)->(20,5)->(40,5)

Output: Linked List should be changed to following

(0,10)->(7,10)

|
(7,5)->(40,5)

The given linked list represents a horizontal line from (0,10) to (7, 10) followed by a vertical line from (7, 10) to (7, 5), followed by a horizontal line from (7, 5) to (40, 5).

Input: (2,3)->(4,3)->(6,3)->(10,3)->(12,3)

Output: Linked List should be changed to following

(2,3)->(12,3)

There is only one vertical line, so all middle points are removed.

Source: [Microsoft Interview Experience](#)

We strongly recommend to minimize the browser and try this yourself first.

The idea is to keep track of current node, next node and next-next node. While the next node is same as next-next node, keep deleting the next node. In this complete procedure we need to keep an eye on shifting of pointers and checking for NULL values.

Following are C/C++ and Java implementations of above idea.

C/C++

```
// C program to remove intermediate points in a linked list
// that represents horizontal and vertical line segments
```

```
#include <stdio.h>
#include <stdlib.h>

// Node has 3 fields including x, y coordinates and a pointer
// to next node
struct node
{
    int x, y;
    struct node *next;
};

/* Function to insert a node at the beginning */
void push(struct node ** head_ref, int x,int y)
{
    struct node* new_node =
        (struct node*) malloc(sizeof(struct node));
    new_node->x = x;
    new_node->y = y;
    new_node->next = (*head_ref);
    (*head_ref) = new_node;
}

/* Utility function to print a singly linked list */
void printList(struct node *head)
{
    struct node *temp = head;
    while (temp != NULL)
    {
        printf("(%d,%d)-> ", temp->x,temp->y);
        temp = temp->next;
    }
    printf("\n");
}

// Utility function to remove Next from linked list
// and link nodes after it to head
void deleteNode(struct node *head, struct node *Next)
{
    head->next = Next->next;
    Next->next = NULL;
    free(Next);
}

// This function deletes middle nodes in a sequence of
// horizontal and vertical line segments represented by
// linked list.
struct node* deleteMiddle(struct node *head)
{
    // If only one node or no node...Return back
```

```
if (head==NULL || head->next ==NULL || head->next->next==NULL)
    return head;
```

```
struct node* Next = head->next;
struct node *NextNext = Next->next ;
```

```
// Check if this is a vertical line or horizontal line
if (head->x == Next->x)
{
    // Find middle nodes with same x value, and delete them
    while (NextNext !=NULL && Next->x==NextNext->x)
    {
        deleteNode(head, Next);

        // Update Next and NextNext for next iteration
        Next = NextNext;
        NextNext = NextNext->next;
    }
}
else if (head->y==Next->y) // If horizontal line
{
    // Find middle nodes with same y value, and delete them
    while (NextNext !=NULL && Next->y==NextNext->y)
    {
        deleteNode(head, Next);

        // Update Next and NextNext for next iteration
        Next = NextNext;
        NextNext = NextNext->next;
    }
}
else // Adjacent points must have either same x or same y
{
    puts("Given linked list is not valid");
    return NULL;
}
```

```
// Recur for next segment
deleteMiddle(head->next);
```

```
return head;
```

```
}
```

```
// Driver program to tsst above functions
```

```
int main()
```

```
{
```

```
    struct node *head = NULL;
```

```
    push(&head, 40,5);
```

```
    push(&head, 20,5);
```

```

push(&head, 10,5);
push(&head, 10,8);
push(&head, 10,10);
push(&head, 3,10);
push(&head, 1,10);
push(&head, 0,10);
printf("Given Linked List: \n");
printList(head);

if (deleteMiddle(head) != NULL);
{
    printf("Modified Linked List: \n");
    printList(head);
}
return 0;
}

```

Java

```

// Java program to remove middle points in a linked list of
// line segments,
class LinkedList
{
    Node head; // head of list

    /* Linked list Node*/
    class Node
    {
        int x,y;
        Node next;
        Node(int x, int y)
        {
            this.x = x;
            this.y = y;
            next = null;
        }
    }

    // This function deletes middle nodes in a sequence of
    // horizontal and vertical line segments represented
    // by linked list.
    Node deleteMiddle()
    {
        // If only one node or no node...Return back
        if (head == null || head.next == null ||
            head.next.next == null)
            return head;

        Node Next = head.next;
    }
}

```

```
Node NextNext = Next.next;

// check if this is vertical or horizontal line
if (head.x == Next.x)
{
    // Find middle nodes with same value as x and
    // delete them.
    while (NextNext != null && Next.x == NextNext.x)
    {
        head.next = Next.next;
        Next.next = null;

        // Update NextNext for the next iteration
        Next = NextNext;
        NextNext = NextNext.next;
    }
}

// if horizontal
else if (head.y == Next.y)
{
    // find middle nodes with same value as y and
    // delete them
    while (NextNext != null && Next.y == NextNext.y)
    {
        head.next = Next.next;
        Next.next = null;

        // Update NextNext for the next iteration
        Next = NextNext;
        NextNext = NextNext.next;
    }
}

// Adjacent points should have same x or same y
else
{
    System.out.println("Given list is not valid");
    return null;
}

// recur for other segment

// temporarily store the head and move head forward.
Node temp = head;
head = head.next;

// call deleteMiddle() for next segment
this.deleteMiddle();
```

```
// restore head
head = temp;

// return the head
return head;
}

/* Given a reference (pointer to pointer) to the head
of a list and an int, push a new node on the front
of the list. */
void push(int x, int y)
{
    /* 1 & 2: Allocate the Node &
        Put in the data*/
    Node new_node = new Node(x,y);

    /* 3. Make next of new Node as head */
    new_node.next = head;

    /* 4. Move the head to point to new Node */
    head = new_node;
}

void printList()
{
    Node temp = head;
    while (temp != null)
    {
        System.out.print("(" + temp.x + ", " + temp.y + ")->");
        temp = temp.next;
    }
    System.out.println();
}

/* Driver program to test above functions */
public static void main(String args[])
{
    LinkedList llist = new LinkedList();

    llist.push(40,5);
    llist.push(20,5);
    llist.push(10,5);
    llist.push(10,8);
    llist.push(10,10);
    llist.push(3,10);
    llist.push(1,10);
    llist.push(0,10);
}
```

```

System.out.println("Given list");
l1list.printList();

if (l1list.deleteMiddle() != null)
{
    System.out.println("Modified Linked List is");
    l1list.printList();
}
}
} /* This code is contributed by Rajat Mishra */

```

Python

```

# Python program to remove middle points in a linked list of
# line segments,
class LinkedList(object):
    def __init__(self):
        self.head = None

# Linked list Node
class Node(object):
    def __init__(self, x, y):
        self.x = x
        self.y = y
        self.next = None

# This function deletes middle nodes in a sequence of
# horizontal and vertical line segments represented
# by linked list.
def deleteMiddle(self):
    # If only one node or no node...Return back
    if self.head == None or self.head.next == None or self.head.next.next == None:
        return self.head
    Next = self.head.next
    NextNext = Next.next
    # check if this is vertical or horizontal line
    if self.head.x == Next.x:
        # Find middle nodes with same value as x and
        # delete them.
        while NextNext != None and Next.x == NextNext.x:
            self.head.next = Next.next
            Next.next = None
            # Update NextNext for the next iteration
            Next = NextNext
            NextNext = NextNext.next
    elif self.head.y == Next.y:
        # find middle nodes with same value as y and
        # delete them

```

```

        while NextNext != None and Next.y == NextNext.y:
            self.head.next = Next.next
            Next.next = None
            # Update NextNext for the next iteration
            Next = NextNext
            NextNext = NextNext.next
    else:
        # Adjacent points should have same x or same y
        print "Given list is not valid"
        return None
    # recur for other segment
    # temporarily store the head and move head forward.
    temp = self.head
    self.head = self.head.next
    # call deleteMiddle() for next segment
    self.deleteMiddle()
    # restore head
    self.head = temp
    # return the head
    return self.head

# Given a reference (pointer to pointer) to the head
# of a list and an int, push a new node on the front
# of the list.
def push(self, x, y):
    # 1 & 2: Allocate the Node &
    # Put in the data
    new_node = self.Node(x, y)
    # 3. Make next of new Node as head
    new_node.next = self.head
    # 4. Move the head to point to new Node
    self.head = new_node

def printList(self):
    temp = self.head
    while temp != None:
        print "(" + str(temp.x) + "," + str(temp.y) + ")->",
        temp = temp.next
    print ''

# Driver program
l1list = LinkedList()
l1list.push(40,5)
l1list.push(20,5)
l1list.push(10,5)
l1list.push(10,8)
l1list.push(10,10)
l1list.push(3,10)
l1list.push(1,10)
l1list.push(0,10)

```



```
print "Given list"
l1list.printList()

if l1list.deleteMiddle() != None:
    print "Modified Linked List is"
    l1list.printList()

# This code is contributed by BHAVYA JAIN
```

Output:

```
Given Linked List:
(0,10)-> (1,10)-> (3,10)-> (10,10)-> (10,8)-> (10,5)-> (20,5)-> (40,5)->
Modified Linked List:
(0,10)-> (10,10)-> (10,5)-> (40,5)->
```

Time Complexity of the above solution is $O(n)$ where n is number of nodes in given linked list.

Exercise:

The above code is recursive, write an iterative code for the same problem.

This article is contributed by Sanket Jain. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



The advertisement features a background image of a person wearing glasses and a light-colored shirt, pointing at a computer monitor. The monitor displays a blue screen with white text. Overlaid on the image is the text 'Learn to Program in Python' in large white font. Below this, it says 'Python for Data Science' and 'A free online course from Microsoft'. At the bottom left is the EdX logo with the website 'www.edx.org'. At the bottom right is a green button with the text 'Enroll Now'.

46 Comments Category: [Linked Lists](#)

Related Posts:

- [Merge two sorted linked lists such that merged list is in reverse order](#)

- Compare two strings represented as linked lists
- Rearrange a given linked list in-place.
- Sort a linked list that is sorted alternating ascending and descending orders?
- Select a Random Node from a Singly Linked List
- Merge Sort for Doubly Linked List
- Point to next higher value node in a linked list with an arbitrary pointer
- Swap nodes in a linked list without swapping data

(Login to Rate and Mark)

3

Average Difficulty : **3/5.0**
Based on **2** vote(s)

☐

Add to TODO List

☐

Mark as DONE

Like Share 14 people like this.

Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.

@geeksforgeeks, Some rights reserved

[Contact Us!](#)

[About Us!](#)

[Advertise with us!](#)