

# GeeksforGeeks

A computer science portal for geeks

Practice

IDE

Q&A

GeeksQuiz

## Find a triplet from three linked lists with sum equal to a given number

Given three linked lists, say a, b and c, find one node from each list such that the sum of the values of the nodes is equal to a given number.

For example, if the three linked lists are 12->6->29, 23->5->8 and 90->20->59, and the given number is 101, the output should be triplet "6 5 90".

In the following solutions, size of all three linked lists is assumed same for simplicity of analysis. The following solutions work for linked lists of different sizes also.

A simple method to solve this problem is to run three nested loops. The outermost loop picks an element from list a, the middle loop picks an element from b and the innermost loop picks from c. The innermost loop also checks whether the sum of values of current nodes of a, b and c is equal to given number. The time complexity of this method will be  $O(n^3)$ .

Sorting can be used to reduce the time complexity to  $O(n^2)$ . Following are the detailed steps.

- 1) Sort list b in ascending order, and list c in descending order.
- 2) After the b and c are sorted, one by one pick an element from list a and find the pair by traversing both b and c. See isSumSorted() in the following code. The idea is similar to Quadratic algorithm of [3 sum problem](#).

Following code implements step 2 only. The solution can be easily modified for unsorted lists by adding the merge sort code discussed [here](#).

### C/C++

```
// C/C++ program to find a triplet from three linked lists with
// sum equal to a given number
#include<stdio.h>
#include<stdlib.h>

/* Link list node */
struct node
{
    int data;
    struct node* next;
};
```

```

/* A utility function to insert a node at the beginning of a
linked list*/
void push (struct node** head_ref, int new_data)
{
    /* allocate node */
    struct node* new_node =
        (struct node*) malloc(sizeof(struct node));

    /* put in the data */
    new_node->data = new_data;

    /* link the old list off the new node */
    new_node->next = (*head_ref);

    /* move the head to point to the new node */
    (*head_ref) = new_node;
}

/* A function to check if there are three elements in a, b
and c whose sum is equal to givenNumber. The function
assumes that the list b is sorted in ascending order
and c is sorted in descending order. */
bool isSumSorted(struct node *headA, struct node *headB,
                struct node *headC, int givenNumber)
{
    struct node *a = headA;

    // Traverse through all nodes of a
    while (a != NULL)
    {
        struct node *b = headB;
        struct node *c = headC;

        // For every node of list a, prick two nodes
        // from lists b and c
        while (b != NULL && c != NULL)
        {
            // If this a triplet with given sum, print
            // it and return true
            int sum = a->data + b->data + c->data;
            if (sum == givenNumber)
            {
                printf ("Triplet Found: %d %d %d ", a->data,
                    b->data, c->data);

                return true;
            }

            // If sum of this triplet is smaller, look for
            // greater values in b
            else if (sum < givenNumber)
                b = b->next;
            else // If sum is greater, look for smaller values in c
                c = c->next;
        }
        a = a->next; // Move ahead in list a
    }

    printf ("No such triplet");
    return false;
}

/* Drier program to test above function*/
int main()
{

```

```

/* Start with the empty list */
struct node* headA = NULL;
struct node* headB = NULL;
struct node* headC = NULL;

/*create a linked list 'a' 10->15->5->20 */
push (&headA, 20);
push (&headA, 4);
push (&headA, 15);
push (&headA, 10);

/*create a sorted linked list 'b' 2->4->9->10 */
push (&headB, 10);
push (&headB, 9);
push (&headB, 4);
push (&headB, 2);

/*create another sorted linked list 'c' 8->4->2->1 */
push (&headC, 1);
push (&headC, 2);
push (&headC, 4);
push (&headC, 8);

int givenNumber = 25;

isSumSorted (headA, headB, headC, givenNumber);

return 0;
}

```

[Run on IDE](#)

## Java

```

// Java program to find a triplet from three linked lists with
// sum equal to a given number
class LinkedList
{
    Node head; // head of list

    /* Linked list Node*/
    class Node
    {
        int data;
        Node next;
        Node(int d) {data = d; next = null; }
    }

    /* A function to check if there are three elements in a, b
    and c whose sum is equal to givenNumber. The function
    assumes that the list b is sorted in ascending order and
    c is sorted in descending order. */
    boolean isSumSorted(LinkedList la, LinkedList lb, LinkedList lc,
                        int givenNumber)
    {
        Node a = la.head;

        // Traverse all nodes of la
        while (a != null)
        {
            Node b = lb.head;
            Node c = lc.head;

```

```

    // for every node in la pick 2 nodes from lb and lc
    while (b != null && c!=null)
    {
        int sum = a.data + b.data + c.data;
        if (sum == givenNumber)
        {
            System.out.println("Triplet found " + a.data +
                               " " + b.data + " " + c.data);
            return true;
        }

        // If sum is smaller then look for greater value of b
        else if (sum < givenNumber)
            b = b.next;

        else
            c = c.next;
        a = a.next;
    }
    System.out.println("No Triplet found");
    return false;
}

/* Given a reference (pointer to pointer) to the head
   of a list and an int, push a new node on the front
   of the list. */
void push(int new_data)
{
    /* 1 & 2: Allocate the Node &
       Put in the data*/
    Node new_node = new Node(new_data);

    /* 3. Make next of new Node as head */
    new_node.next = head;

    /* 4. Move the head to point to new Node */
    head = new_node;
}

/* Drier program to test above functions */
public static void main(String args[])
{
    LinkedList llist1 = new LinkedList();
    LinkedList llist2 = new LinkedList();
    LinkedList llist3 = new LinkedList();

    /* Create Linked List llist1 100->15->5->20 */
    llist1.push(20);
    llist1.push(5);
    llist1.push(15);
    llist1.push(100);

    /*create a sorted linked list 'b' 2->4->9->10 */
    llist2.push(10);
    llist2.push(9);
    llist2.push(4);
    llist2.push(2);

    /*create another sorted linked list 'c' 8->4->2->1 */
    llist3.push(1);
    llist3.push(2);
    llist3.push(4);

```

```
l1list3.push(8);

int givenNumber = 25;
l1list1.isSumSorted(l1list1,l1list2,l1list3,givenNumber);
}
} /* This code is contributed by Rajat Mishra */
```

[Run on IDE](#)

Output:

Triplet Found: 15 2 8

Time complexity: The linked lists b and c can be sorted in  $O(n \log n)$  time using Merge Sort (See [this](#)). The step 2 takes  $O(n^2)$  time. So the overall time complexity is  $O(n \log n) + O(n \log n) + O(n^2) = O(n^2)$ .

In this approach, the linked lists b and c are sorted first, so their original order will be lost. If we want to retain the original order of b and c, we can create copy of b and c.

This article is compiled by **Abhinav Priyadarshi** and reviewed by GeeksforGeeks team. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



[42 Comments](#) Category: [Linked Lists](#)

## Related Posts:

- [Merge two sorted linked lists such that merged list is in reverse order](#)
- [Compare two strings represented as linked lists](#)

- [Rearrange a given linked list in-place.](#)
- [Sort a linked list that is sorted alternating ascending and descending orders?](#)
- [Select a Random Node from a Singly Linked List](#)
- [Merge Sort for Doubly Linked List](#)
- [Point to next higher value node in a linked list with an arbitrary pointer](#)
- [Swap nodes in a linked list without swapping data](#)

([Login](#) to Rate and Mark)

2

Average Difficulty : **2/5.0**  
Based on **2** vote(s)

☐

Add to TODO List

☐

Mark as DONE

[Like](#) [Share](#) 5 people like this.

Writing code in comment? Please use [code.geeksforgeeks.org](http://code.geeksforgeeks.org), generate link and share the link here.

@geeksforgeeks, [Some rights reserved](#)

[Contact Us!](#)

[About Us!](#)

[Advertise with us!](#)