

Find the Number Occurring Odd Number of Times

Given an array of positive integers. All numbers occur even number of times except one number which occurs odd number of times. Find the number in $O(n)$ time & constant space.

Example:

I/P = [1, 2, 3, 2, 3, 1, 3]

O/P = 3

A **Simple Solution** is to run two nested loops. The outer loop picks all elements one by one and inner loop counts number of occurrences of the element picked by outer loop. Time complexity of this solution is $O(n^2)$.

A **Better Solution** is to use Hashing. Use array elements as key and their counts as value. Create an empty hash table. One by one traverse the given array elements and store counts. Time complexity of this solution is $O(n)$. But it requires extra space for hashing.

The **Best Solution** is to do bitwise XOR of all the elements. XOR of all elements gives us odd occurring element. Please note that XOR of two elements is 0 if both elements are same and XOR of a number x with 0 is x .

Below are implementations of this best approach.

Program:

C/C++

```
#include <stdio.h>

int getOddOccurrence(int ar[], int ar_size)
{
    int i;
    int res = 0;
    for (i=0; i < ar_size; i++)
        res = res ^ ar[i];

    return res;
}
```

```
/* Diver function to test above function */
int main()
{
    int ar[] = {2, 3, 5, 4, 5, 2, 4, 3, 5, 2, 4, 4, 2};
    int n = sizeof(ar)/sizeof(ar[0]);
    printf("%d", getOddOccurrence(ar, n));
    return 0;
}
```

Python

```
# Python program to find the element occurring odd number of times

def getOddOccurrence(arr):

    # Initialize result
    res = 0

    # Traverse the array
    for element in arr:
        # XOR with the result
        res = res ^ element

    return res

# Test array
arr = [ 2, 3, 5, 4, 5, 2, 4, 3, 5, 2, 4, 4, 2]

print "%d" % getOddOccurrence(arr)
```

Output:

5

Time Complexity: $O(n)$

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Querying with Transact-SQL

[Enroll now](#)

Self-Paced

124 Comments Category: [Arrays](#) [Bit Magic](#) Tags: [Bit Magic](#)

Related Posts:

- [Longest Span with same Sum in two Binary arrays](#)
- [Count Inversions of size three in a give array](#)
- [Find the subarray with least average](#)
- [Count triplets with sum smaller than a given value](#)
- [Find zeroes to be flipped so that number of consecutive 1's is maximized](#)
- [Reorder an array according to given indexes](#)
- [Find maximum value of \$\text{Sum}\(i * \text{arr}\[i\]\)\$ with only rotations on given array allowed](#)
- [Find maximum average subarray of k length](#)

([Login](#) to Rate and Mark)

1.5

Average Difficulty : **1.5/5.0**
Based on **19** vote(s)

☐

Add to TODO List

☐

Mark as DONE

Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.

@geeksforgeeks, [Some rights reserved](#)

[Contact Us!](#)[About Us!](#)[Advertise with us!](#)