

## Practice questions for Linked List and Recursion

Assume the structure of a Linked List node is as follows.

```
struct node
{
    int data;
    struct node *next;
};
```

[Run on IDE](#)

Explain the functionality of following C functions.

### 1. What does the following function do for a given Linked List?

```
void fun1(struct node* head)
{
    if(head == NULL)
        return;

    fun1(head->next);
    printf("%d ", head->data);
}
```

[Run on IDE](#)

fun1() prints the given Linked List in reverse manner. For Linked List 1->2->3->4->5, fun1() prints 5->4->3->2->1.

### 2. What does the following function do for a given Linked List ?

```
void fun2(struct node* head)
{
    if(head == NULL)
        return;
    printf("%d ", head->data);

    if(head->next != NULL )
        fun2(head->next->next);
    printf("%d ", head->data);
}
```

fun2() prints alternate nodes of the given Linked List, first from head to end, and then from end to head. If Linked List has even number of nodes, then fun2() skips the last node. For Linked List 1->2->3->4->5, fun2() prints 1 3 5 5 3 1. For Linked List 1->2->3->4->5->6, fun2() prints 1 3 5 5 3 1.

Below is a complete running program to test above functions.

```
#include<stdio.h>
#include<stdlib.h>

/* A linked list node */
struct node
{
    int data;
    struct node *next;
};

/* Prints a linked list in reverse manner */
void fun1(struct node* head)
{
    if(head == NULL)
        return;

    fun1(head->next);
    printf("%d ", head->data);
}

/* prints alternate nodes of a Linked List, first
   from head to end, and then from end to head. */
void fun2(struct node* start)
{
    if(start == NULL)
        return;
    printf("%d ", start->data);

    if(start->next != NULL )
        fun2(start->next->next);
    printf("%d ", start->data);
}

/* UTILITY FUNCTIONS TO TEST fun1() and fun2() */
/* Given a reference (pointer to pointer) to the head
   of a list and an int, push a new node on the front
   of the list. */
void push(struct node** head_ref, int new_data)
{
    /* allocate node */
    struct node* new_node =
        (struct node*) malloc(sizeof(struct node));

    /* put in the data */
    new_node->data = new_data;

    /* link the old list off the new node */
    new_node->next = (*head_ref);

    /* move the head to point to the new node */
    (*head_ref) = new_node;
}
```

```
/* Drier program to test above functions */
int main()
{
    /* Start with the empty list */
    struct node* head = NULL;

    /* Using push() to construct below list
       1->2->3->4->5 */
    push(&head, 5);
    push(&head, 4);
    push(&head, 3);
    push(&head, 2);
    push(&head, 1);

    printf("\n Output of fun1() for list 1->2->3->4->5 \n");
    fun1(head);

    printf("\n Output of fun2() for list 1->2->3->4->5 \n");
    fun2(head);

    getchar();
    return 0;
}
```

[Run on IDE](#)

Please write comments if you find any of the answers/explanations incorrect, or you want to share more information about the topics discussed above.



# Replace Your Backend

Save Time & Build Your App  
Faster. Start Building For  
Free!



55 Comments Category: [Linked Lists](#) Tags: [Recursion](#)

## Related Posts:

- [Merge two sorted linked lists such that merged list is in reverse order](#)
- [Compare two strings represented as linked lists](#)
- [Rearrange a given linked list in-place.](#)
- [Sort a linked list that is sorted alternating ascending and descending orders?](#)

- [Select a Random Node from a Singly Linked List](#)
- [Merge Sort for Doubly Linked List](#)
- [Point to next higher value node in a linked list with an arbitrary pointer](#)
- [Swap nodes in a linked list without swapping data](#)

([Login](#) to Rate and Mark)

1

Average Difficulty : **1/5.0**  
Based on **5** vote(s)

☐

Add to TODO List

☐

Mark as DONE

[Like](#) [Share](#) 7 people like this.

Writing code in comment? Please use [code.geeksforgeeks.org](http://code.geeksforgeeks.org), generate link and share the link here.

@geeksforgeeks, [Some rights reserved](#)

[Contact Us!](#)

[About Us!](#)

[Advertise with us!](#)