

GeeksforGeeks


A computer science portal for geeks

Placements Practice GATE CS IDE Q&A
GeeksQuiz

Print nodes at k distance from root

Given a root of a tree, and an integer k. Print all the nodes which are at k distance from root.

For example, in the below tree, 4, 5 & 8 are at distance 2 from root.



The problem can be solved using recursion. Thanks to [eldho](#) for suggesting the solution.

C

```
#include <stdio.h>
#include <stdlib.h>

/* A binary tree node has data, pointer to left child
and a pointer to right child */
struct node
{
    int data;
    struct node* left;
    struct node* right;
};

void printKDistant(node *root , int k)
{
    if(root == NULL)
        return;
    if( k == 0 )
    {
        printf( "%d ", root->data );
        return ;
    }
    else
    {
        printKDistant( root->left, k-1 ) ;
        printKDistant( root->right, k-1 ) ;
    }
}
```

```

}

/* Helper function that allocates a new node with the
   given data and NULL left and right pointers. */
struct node* newNode(int data)
{
    struct node* node = (struct node*)
                        malloc(sizeof(struct node));
    node->data = data;
    node->left = NULL;
    node->right = NULL;

    return(node);
}

/* Driver program to test above functions*/
int main()
{
    /* Constructed binary tree is
        1
       / \
      2   3
     / \ /
    4  5 8
    */
    struct node *root = newNode(1);
    root->left = newNode(2);
    root->right = newNode(3);
    root->left->left = newNode(4);
    root->left->right = newNode(5);
    root->right->left = newNode(8);

    printKDistant(root, 2);

    getchar();
    return 0;
}

```

Run on IDE

Java

```

// Java program to print nodes at k distance from root

// A binary tree node
class Node {
    int data;
    Node left, right;

    Node(int item) {
        data = item;
        left = right = null;
    }
}

class BinaryTree {
    static Node root;

    void printKDistant(Node node, int k) {

```

```
if (node == null) {
    return;
}
if (k == 0) {
    System.out.print(node.data + " ");
    return;
} else {
    printKDistant(node.left, k - 1);
    printKDistant(node.right, k - 1);
}

}

public static void main(String args[]) {
    BinaryTree tree = new BinaryTree();
    tree.root = new Node(1);
    tree.root.left = new Node(2);
    tree.root.right = new Node(3);
    tree.root.left.left = new Node(4);
    tree.root.left.right = new Node(5);
    tree.root.right.left = new Node(8);

    tree.printKDistant(root, 2);
}

// This code has been contributed by Mayank Jaiswal
```

[Run on IDE](#)

The above program prints 4, 5 and 8.

Time Complexity: $O(n)$ where n is number of nodes in the given binary tree.

Please write comments if you find the above code/algorithm incorrect, or find better ways to solve the same problem.



67 Comments Category: Trees

Related Posts:

- [Check if removing an edge can divide a Binary Tree in two halves](#)
- [Check sum of Covered and Uncovered nodes of Binary Tree](#)
- [Lowest Common Ancestor in a Binary Tree | Set 2 \(Using Parent Pointer\)](#)
- [Construct a Binary Search Tree from given postorder](#)
- [BFS vs DFS for Binary Tree](#)
- [Maximum difference between node and its ancestor in Binary Tree](#)
- [Inorder Non-threaded Binary Tree Traversal without Recursion or Stack](#)
- [Check if leaf traversal of two Binary Trees is same?](#)

([Login](#) to Rate and Mark)

1.3

Average Difficulty : **1.3/5.0**
Based on **21** vote(s)

☐

Add to TODO List

☐

Mark as DONE

[Like](#) [Share](#) One person likes this.

Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.

[@geeksforgeeks](#), [Some rights reserved](#)

[Contact Us!](#)

[About Us!](#)

[Advertise with us!](#)