

GeeksforGeeks

A computer science portal for geeks

Practice

IDE

Q&A

GeeksQuiz

Construction of Longest Monotonically Increasing Subsequence (N log N)

In my previous post, I have explained about longest [monotonically increasing sub-sequence](#) (LIS) problem in detail. However, the post only covered code related to querying size of LIS, but not the construction of LIS. I left it as an exercise. If you have solved, cheers. If not, you are not alone, here is code.

If you have not read my previous post, read [here](#). Note that the below code prints LIS in reverse order. We can modify print order using a stack (explicit or system stack). I am leaving explanation as an exercise (easy).

```
#include <iostream>
#include <string.h>
#include <stdio.h>
using namespace std;

// Binary search
int GetCeilIndex(int A[], int T[], int l, int r, int key) {
    int m;

    while( r - l > 1 ) {
        m = l + (r - l)/2;
        if( A[T[m]] >= key )
            r = m;
        else
            l = m;
    }

    return r;
}

int LongestIncreasingSubsequence(int A[], int size) {
    // Add boundary case, when array size is zero
    // Depend on smart pointers

    int *tailIndices = new int[size];
    int *prevIndices = new int[size];
    int len;

    memset(tailIndices, 0, sizeof(tailIndices[0])*size);
    memset(prevIndices, 0xFF, sizeof(prevIndices[0])*size);

    tailIndices[0] = 0;
    prevIndices[0] = -1;
    len = 1; // it will always point to empty location
    for( int i = 1; i < size; i++ ) {
        if( A[i] < A[tailIndices[0]] ) {
```

```

    // new smallest value
    tailIndices[0] = i;
} else if( A[i] > A[tailIndices[len-1]] ) {
    // A[i] wants to extend largest subsequence
    prevIndices[i] = tailIndices[len-1];
    tailIndices[len++] = i;
} else {
    // A[i] wants to be a potential candidate of future subsequence
    // It will replace ceil value in tailIndices
    int pos = GetCeilIndex(A, tailIndices, -1, len-1, A[i]);

    prevIndices[i] = tailIndices[pos-1];
    tailIndices[pos] = i;
}
}
cout << "LIS of given input" << endl;
for( int i = tailIndices[len-1]; i >= 0; i = prevIndices[i] )
    cout << A[i] << " ";
cout << endl;

delete[] tailIndices;
delete[] prevIndices;

return len;
}

int main() {
    int A[] = { 2, 5, 3, 7, 11, 8, 10, 13, 6 };
    int size = sizeof(A)/sizeof(A[0]);

    printf("LIS size %d\n", LongestIncreasingSubsequence(A, size));

    return 0;
}

```

[Run on IDE](#)

Exercises:

1. You know **Kadane's** algorithm to find **maximum sum sub-array**. Modify Kadane's algorithm to trace starting and ending location of maximum sum sub-array.
2. Modify **Kadane's** algorithm to find maximum sum sub-array in a circular array. Refer GFG forum for many comments on the question.
3. Given two integers A and B as input. Find number of Fibonacci numbers existing in between these two numbers (including A and B). For example, A = 3 and B = 18, there are 4 Fibonacci numbers in between {3, 5, 8, 13}. Do it in O(log K) time, where K is max(A, B). What is your observation?

— **Venki**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



AMCAT Test for Freshers

Engineering Job in 1000+
Companies. 3 Lakh Interview Calls
Each Month

myamcat.com/Fresher-Engg-Jobs



39 Comments Category: [Arrays](#)

About Venki

Software Engineer

[View all posts by Venki](#) →

Related Posts:

- [Longest Span with same Sum in two Binary arrays](#)
- [Count Inversions of size three in a give array](#)
- [Find the subarray with least average](#)
- [Count triplets with sum smaller than a given value](#)
- [Find zeroes to be flipped so that number of consecutive 1's is maximized](#)
- [Reorder an array according to given indexes](#)
- [Find maximum value of Sum\(i*arr\[i\]\) with only rotations on given array allowed](#)
- [Find maximum average subarray of k length](#)

([Login](#) to Rate and Mark)

4

Average Difficulty : **4/5.0**
Based on **2** vote(s)

☐

Add to TODO List

☐

Mark as DONE

Like Share 2 people like this. Be the first of your friends.

Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.

@geeksforgeeks, Some rights reserved

[Contact Us!](#)

[About Us!](#)

[Advertise with us!](#)