GeeksforGeeks

A computer science portal for geeks

Practice

IDE	Q&A	GeeksQuiz	

A Product Array Puzzle

Given an array arr[] of n integers, construct a Product Array prod[] (of same size) such that prod[i] is equal to the product of all the elements of arr[] except arr[i]. Solve it without division operator and in O(n).

Example:

```
arr[] = {10, 3, 5, 6, 2}
prod[] = {180, 600, 360, 300, 900}
```

Algorithm:

- 1) Construct a temporary array left[] such that left[i] contains product of all elements on left of arr[i] excluding arr[i].
- 2) Construct another temporary array right[] such that right[i] contains product of all elements on on right of arr[i] excluding arr[i].
- To get prod[], multiply left[] and right[].

Implementation:

```
#include<stdio.h>
#include<stdlib.h>
/* Function to print product array for a given array
arr[] of size n */
void productArray(int arr[], int n)
 /* Allocate memory for temporary arrays left[] and right[] */
 int *left = (int *)malloc(sizeof(int)*n);
 int *right = (int *)malloc(sizeof(int)*n);
 /* Allocate memory for the product array */
 int *prod = (int *)malloc(sizeof(int)*n);
 int i, j;
  /* Left most element of left array is always 1 */
 left[0] = 1;
  /* Rightmost most element of right array is always 1 */
 right[n-1] = 1;
  /* Construct the left array */
 for(i = 1; i < n; i++)
    left[i] = arr[i-1]*left[i-1];
```

```
/* Construct the right array */
  for(j = n-2; j >= 0; j--)
    right[j] = arr[j+1]*right[j+1];
  /* Construct the product array using
    left[] and right[] */
  for (i=0; i<n; i++)
    prod[i] = left[i] * right[i];
  /* print the constructed prod array */
 for (i=0; i<n; i++)
    printf("%d ", prod[i]);</pre>
  return;
/* Driver program to test above functions */
int main()
  int arr[] = {10, 3, 5, 6, 2};
  int n = sizeof(arr)/sizeof(arr[0]);
  printf("The product array is: \n");
  productArray(arr, n);
  getchar();
                                                                                    Run on IDE
Time Complexity: O(n)
Space Complexity: O(n)
Auxiliary Space: O(n)
The above method can be optimized to work in space complexity O(1). Thanks to Dileep for suggesting
the below solution.
void productArray(int arr[], int n)
  int i, temp = 1;
  /* Allocate memory for the product array */
  int *prod = (int *)malloc(sizeof(int)*n);
  /* Initialize the product array as 1 */
  memset(prod, 1, n);
  /* In this loop, temp variable contains product of
    elements on left side excluding arr[i] */
  for(i=0; i<n; i++)</pre>
    prod[i] = temp;
    temp *= arr[i];
  }
  /* Initialize temp to 1 for product on right side */
  temp = 1;
  /* In this loop, temp variable contains product of
    elements on right side excluding arr[i] */
  for(i= n-1; i>=0; i--)
  {
    prod[i] *= temp;
```

```
temp *= arr[i];
}

/* print the constructed prod array */
for (i=0; i<n; i++)
    printf("%d ", prod[i]);

return;
}</pre>
```

Run on IDE

Time Complexity: O(n)
Space Complexity: O(n)
Auxiliary Space: O(1)

Please write comments if you find the above code/algorithm incorrect, or find better ways to solve the same problem.



Querying with Transact-SQL



Enroll now

Self-Paced

91 Comments Category: Arrays

Related Posts:

- Longest Span with same Sum in two Binary arrays
- · Count Inversions of size three in a give array
- · Find the subarray with least average
- Count triplets with sum smaller than a given value
- Find zeroes to be flipped so that number of consecutive 1's is maximized
- Reorder an array according to given indexes
- Find maximum value of Sum(i*arr[i]) with only rotations on given array allowed
- · Find maximum average subarray of k length

(Login to Rate and Mark) 2.5 Average Difficulty: 2.5/5.0 Based on 10 vote(s)		d to TODO Li rk as DONE	st			
Like Share 12 people like this. Be the first of your friends. Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.						
@geeksforgeeks, Some rights reserved	Contact Us!	About Us!	Advertise with us!			