

GeeksforGeeks

A computer science portal for geeks

Practice

IDE

Q&A

GeeksQuiz

Linked List vs Array

Difficulty Level: Rookie

Both Arrays and [Linked List](#) can be used to store linear data of similar types, but they both have some advantages and disadvantages over each other.

Following are the points in favour of Linked Lists.

(1) The size of the arrays is fixed: So we must know the upper limit on the number of elements in advance. Also, generally, the allocated memory is equal to the upper limit irrespective of the usage, and in practical uses, upper limit is rarely reached.

(2) Inserting a new element in an array of elements is expensive, because room has to be created for the new elements and to create room existing elements have to be shifted.

For example, suppose we maintain a sorted list of IDs in an array `id[]`.

`id[] = [1000, 1010, 1050, 2000, 2040,]`.

And if we want to insert a new ID 1005, then to maintain the sorted order, we have to move all the elements after 1000 (excluding 1000).

Deletion is also expensive with arrays unless some special techniques are used. For example, to delete 1010 in `id[]`, everything after 1010 has to be moved.

So Linked list provides following two advantages over arrays

- 1) Dynamic size
- 2) Ease of insertion/deletion

Linked lists have following drawbacks:

- 1) Random access is not allowed. We have to access elements sequentially starting from the first node. So we cannot do binary search with linked lists.
- 2) Extra memory space for a pointer is required with each element of the list.
- 3) Arrays have better cache locality that can make a pretty big difference in performance.

Please also see [this](#) thread.

References:

<http://cslibrary.stanford.edu/103/LinkedListBasics.pdf>

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

HDFC Life
Click2ProtectPlus



A new year, a new plan
and a new start

56 Comments Category: [Arrays](#) [Linked Lists](#)

Related Posts:

- [Longest Span with same Sum in two Binary arrays](#)
- [Count Inversions of size three in a give array](#)
- [Find the subarray with least average](#)
- [Count triplets with sum smaller than a given value](#)
- [Find zeroes to be flipped so that number of consecutive 1's is maximized](#)
- [Reorder an array according to given indexes](#)
- [Find maximum value of Sum\(i*arr\[i\]\) with only rotations on given array allowed](#)
- [Find maximum average subarray of k length](#)

([Login](#) to Rate and Mark)

1

Average Difficulty : **1/5.0**
Based on **11** vote(s)

☐

Add to TODO List

☐

Mark as DONE

[Like](#) [Share](#) 23 people like this. Be the first of your friends.

Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.

