


Inline Functions in C++

- **Definition** : If a function is **inline**, the **compiler places a copy of the code** of that function at **each point** where the function is **called** at **compile time**.
- Any change to an inline function could require the function to be recompiled because compiler would need to replace all the code once again otherwise it will continue with old functionality.
- **Syntax:**

```
inline return-type function-name(parameters){  
    // function code  
}
```



Code: 1

```
#include<iostream>
using namespace std;

inline int add(int a, int b)
{
    return (a+b);
}

int main()
{
    for(int i=0;i<100;i++)
    {
        cout<<"Additon of 4 & 5is:"<<add(4,5)<<endl;
    }
    return 0;
}
```

Code 2:

```
#include<iostream>
using namespace std;

inline void display(string str)
{
    cout<< str << endl;
}

int main()
{
    for(int i=0;i<100;i++)
    {
        display("Hello 100 times"); // cout<< str << endl;
    }
    return 0;
}
```

Default Parameters in C++

Default Parameters in Functions

- A default argument is a value provided in function declaration that is automatically assigned by the compiler if caller of the function doesn't provide a value for the argument with default value.
- Allows a function to be called without providing one or more trailing arguments.

```
int sum(int x, int y, int z=0, int w=0)
{
    return (x + y + z + w);
}
```

```
#include<iostream>
using namespace std;
```

```
int sum(int a, int b, int c=0, int d=5)
{
    return(a+b+c+d);
}
```

```
int main()
{
    cout<<"Sum of 1,2,3,4 is:"<<sum(1,2,3,4);
    cout<<"Sum of 1,2 is:"<<sum(1,2);
    return 0;
}
```