DATA260 Homework 7 - Final Report Source

Student: Vrishin KunnathamParambath

SID4: 8844

Domain: open-source package vulnerabilities

Repository: https://github.com/Viki2183/data260-8844

Collaborator-access confirmation: ‘Sbnikitha‘, ‘supriyaselvanganesan‘ - pending submission confirmation.

Commit/tag hash: **pending final packaging**

Configuration and hardware

Model: ‘qwen3:8b‘ through local Ollama at ‘127.0.0.1:11434‘.

‘PORT_BASE=8744‘, ‘PREFIX=s8844‘, ‘SEED=8844‘, ‘VERIFY_SEED=268844‘, ‘DOMAIN_ID=4‘.

HW6 hardware description: Intel Core i7-10750H CPU, approximately 16 GB RAM.

AI use and verification boundary

Codex assisted with repository inspection, reading the official assignment, implementation review, offline testing, evidence organization, and report preparation. The student supplied the repository and private credentials when needed, approved the phases and test scope, selected test data, reviewed the results, and retained responsibility for submission decisions. The complete answer is synchronized in ‘AI_USE.md‘.

What assistance was used? Repository inspection, code review, bounded test

design, raw-evidence organization, and report/PDF preparation were assisted by Codex. **What did the student do?** The student supplied the repository, approved scope, entered private credentials locally when needed, selected the test identities/data, reviewed outputs, and remains responsible for the final submission. **What was corrected?** The original pay-per-use evidence carried a $6,830 membership value caused by ‘included_minutes=0‘; it was preserved and superseded by a separately recorded $4,780 calculation. **What was manually verified?** Repository state, source files, offline assertions, live JWT responses, raw evidence, screenshots, and PDF output were checked. **What was not complete?** Full pytest remained blocked, and final Git packaging and verification metadata were not performed. No hidden chain-of-thought was stored.

No hidden chain-of-thought was stored or returned. Evidence stores only task inputs where needed, tool calls, tool results, verifier outputs, final answers, stop reasons, and measured metrics. Passwords, password hashes, JWT strings, and secrets are excluded.

The measured 20-attempt reliability result is reported without alteration: 20 attempts were recorded, with 0/20 successful task completions. The baseline fixed-task comparison was 0/3 and Reflexion was 1/3. Pytest remained blocked by the managed temporary-file environment and the repository ‘code‘ package shadowing the standard-library ‘code‘ module; deterministic offline checks were used where appropriate. These checks do not replace the blocked full pytest run.

Part 1 - JWT authentication, roles, and database migration

Implementation excerpts

‘code/web_application/auth_hw7.py‘ defines the HW7 JWT routes and helpers:

```
@router.post("/login", response_model=TokenResponse)
def login(payload: LoginPayload, db: Session = Depends(get_db)) ->
TokenResponse:
    user = db.query(models.UserDB).filter(
        models.UserDB.username == payload.username.strip()
    ).first()
    if user is None or user.role not in ALLOWED_ROLES or not verify_password(
        payload.password, user.password_hash
    ):
        raise HTTPException(status_code=401, detail="Invalid username or
password")
    return TokenResponse(access_token=create_access_token(user.username,
user.role))


@router.get("/me", response_model=IdentityResponse)
def me(user: models.UserDB = Depends(get_current_user)) -> IdentityResponse:
    return IdentityResponse(username=user.username, role=user.role)
```

JWT creation validates ‘reader‘, ‘writer‘, and ‘moderator‘, signs HS256 claims, and includes ‘iat‘ and ‘exp‘. Validation checks the signature, header, username, role, and expiration. Passwords use bcrypt:

```
def hash_password(password: str) -> str:
```

```
    return bcrypt.hashpw(password.encode("utf-8"),
bcrypt.gensalt()).decode("utf-8")
```

Role dependencies are explicit: authenticated reads are available to all three roles; create is available to writer/moderator; delete is moderator-only.

Live status evidence

Source: ‘raw/hw7_live_jwt_authorization.json‘, 19 cases, all recorded as passing.

Check	Expected	Recorded
Reader/writer/moderator login	200	200/200/200
Invalid password and unknown username	401	401/401
‘/auth/me‘ reader/writer/moderator	200	200/200/200
Missing, invalid, expired token	401	401/401/401
Authenticated list/read for all roles	200	200/200/200
Reader create	403	403
Writer create	201	201
Moderator create	201	201
Writer delete	403	403
Moderator delete	200	200

The live evidence records no stored JWT values and no stored passwords. Created HW7 test records were limited to the labeled test records; the moderator delete target was cleaned up. No HW1-HW6 record was deleted or modified.

Users schema and migration

‘code/web_application/hw7_migration.py‘ defines a non-destructive ‘CREATE TABLE IF NOT EXISTS users‘ shape with ‘id‘, ‘name‘, ‘username‘, ‘email‘, ‘password_hash‘, ‘role‘, a primary key, unique username/email keys, and a role check for ‘reader‘, ‘writer‘, or ‘moderator‘. It explicitly requires preflight inspection before altering an existing table and does not invent a username backfill.

id	username	role	password_hash
1	vikki1	reader	exists; value not displayed
2	vikki2	writer	exists; value not displayed
3	vikki3	moderator	exists; value not displayed

This table records only safe fields from the approved live preflight. A dedicated MySQL-table screenshot/raw artifact was not created; manual capture is required if the instructor requires visual database evidence. No schema or row change is performed by this report.

Ruff scoped checks passed for the HW7 scope. Pre-commit configuration validation passed, while the configured fixing hook was not run because it can modify files. No successful commit/tag screenshot exists; packaging hashes remain pending.

Part 2 - bounded agent loop and reliability

Actual implementation

‘code/hw7_agent.py‘ uses ‘run_agent‘, not a pseudo-agent. It validates each model decision as ‘tool‘ or ‘final‘, dispatches the named handler, catches tool errors as bounded observations, appends a ‘tool‘ message with deterministic IDs such as ‘hw7-tool-call-1‘, and appends a continuation message. The loop is bounded by ‘max_steps‘; malformed/unknown decisions and incomplete required sequences have at most one repair in the recorded smoke/reliability configuration.

The repair includes the next required tool and, for Task A, the package ID from the search observation. A final answer before the required sequence yields ‘human_review‘ after the repair budget is exhausted. Other bounded stop reasons are ‘success‘ and ‘budget_exhausted‘.

The loop logs tool name, inputs, observation, tool-call count, repair count, latency, final answer, and stop reason. It does not store hidden reasoning.

Fixed-task evidence

‘raw/hw7_agent_fixed_tasks.json‘ records the earlier fixed-task run with the pre-compatibility ‘tool_call_id‘ failure. Later evidence ‘raw/hw7_task_a_package00001.json‘ records the corrected Task A smoke input: ‘search(package-00001) -> detail(package_id=1)‘, two tool calls, final answer produced, and ‘success‘. These are separate runs and are not merged.

Tasks B and C have raw run evidence but no dedicated successful browser screenshot.

The report uses raw logs and marks B/C visual capture as manual-capture required. Nonexistent-ID recovery is covered by the offline agent tests and bounded tool error handling; no database write is required for that recovery path.

Reliability table

Source: ‘raw/hw7_reliability_20_attempts_v2.json‘.

Metric	Actual value
Total attempts	20
Well-formed call rate before repair	20/20 (100%)
Well-formed call rate after repair	0/20 (0%)
Malformed arguments	0
Unknown tool	0
Text when a tool was required	20
Lost multi-step chain	0
Successful tasks	0/20
‘human_review‘ stops	20
Average latency	13,160.690 ms
Median latency	12,423.832 ms
Average tool calls	0

Part 3 - Reflexion and verifier

‘verify_task‘ checks the stop reason, required tool set, and answer presence. It

returns ‘success‘, ‘unsupported_claims‘, and ‘missing_tools‘. ‘reflexion_run‘ retries only after verifier failure, allows at most two retries, stores concise reflections with the prior trace/verifier evidence, and returns one of ‘success‘ or ‘human_review‘; the agent itself also has ‘budget_exhausted‘.

Reflections are isolated within a run and passed as a model-factory context; they are not instructions, permissions, role definitions, or safety gates. The tool registry and authorization policy remain fixed. Hidden chain-of-thought is not stored.

Task	Condition	Success	Unsupported claims	Retry rate	Tool calls	Tokens	Latency ms	False rejection
A	baseline	0/1	verifier false	0	0	available in raw	13,579.628	unavailable
A	Reflexion	0/1	verifier false	2	1	available in raw	78,020.263	unavailable
B	baseline	0/1	verifier false	0	0	available in raw	13,030.116	unavailable
B	Reflexion	0/1	verifier false	2	1	available in raw	41,699.474	unavailable
C	baseline	0/1	verifier false	0	0	available in raw	19,814.970	unavailable
C	Reflexion	1/1	false	1	2	available in raw	42,979.888	unavailable

Aggregate source summary: baseline 0/3, Reflexion 1/3, Reflexion maximum retry count 2, baseline average latency 15,474.905 ms, Reflexion average latency 54,233.208 ms, average Reflexion tool calls 1.333. Verifier false-rejection data is unavailable because the evidence does not contain an independent false-rejection adjudication.

Part 4 - MRKL and bike-share application

The three pure/isolated tools share a response shape with ‘success‘, optional ‘data‘, optional ‘error‘, optional ‘source‘, and ‘ts‘:

```
def _result(success, data=None, error=None, source=None):
    value = {"success": success}
    if data is not None: value["data"] = data
    if error: value["error"] = error
    if source: value["source"] = source
    value["ts"] = datetime.now(timezone.utc).isoformat()
    return value

def csv_sql(csv_text, sql):
    if not re.match(r"^\s*select\b", sql, re.IGNORECASE):
        return _result(False, error="csv_sql accepts one read-only SELECT")
    # parse uploaded CSV into an in-memory SQLite table and return rows

def policy_retriever(url, query, k=3):
    # retrieve bounded passages and return source=url in the common shape

def calculator(expression, units=None):
    # permit only a checked arithmetic AST, then return value and units
```

‘csv_sql‘ rejects non-SELECT statements independently of the model. The calculator rejects unsupported characters and AST nodes. Missing files, malformed CSV, invalid arithmetic, and SQL injection/non-SELECT attempts are covered by offline tests.

The official pricing URL recorded in evidence is
‘https://citibikenyc.com/plans-and-pricing‘. Both snapshots have access timestamp
‘2026-10-25T07:27:04.715872+00:00‘ and SHA-256
‘07fb221a434fb166302571050657a0c2c53f995214af78771faf735e7733c71d‘.

Scenario	Rows	Weekly rides	Avg duration	Weekly spend	Pay/use	Membership	Residual	Break-even	Actual	Steps	Stop
Membership wins	500	500/month (period: one month)	30 min	source period; not separately recorded	$8,645	$19.92	$0	1.15 rides	500 rides/15,000 min	5	success
Pay-per-use wins	500	25/year = 0.48/week	10 min	source period; not separately recorded	$4,545	$4,780	$0	not recomputed in corrected file	500 rides/5,000 min over 20 years	5	success

The membership scenario is one month of 30-minute rides, all within the
45-minute member allowance, and remains unchanged. The pay-per-use scenario is
a 20-year observation horizon with 25 short rides per year. Annual membership
pricing is applied for each of the 20 years: ‘20 * $239 = $4,780‘. The corrected
calculation uses 500 rides x 45 included minutes, so no residual charge remains.

The original ‘raw/hw7_bikeshare_scenarios.json‘ is preserved unchanged. Its old
pay-per-use recommendation displayed ‘$6,830‘ because it used
‘included_minutes=0‘, even though its calculator result recorded ‘$4,780‘.
‘raw/hw7_bikeshare_scenarios_corrected.json‘ is the authoritative correction:
pay-per-use ‘$4,545‘, membership ‘$4,780‘, decision ‘Pay Per Ride/Minute‘.

Part 5 - prompt-injection threat model

Threats are: retrieved text overriding the recommendation; model-directed non-read-only SQL; and inappropriate inclusion of complete uploaded CSV content.

Attack	Before defenses	Prompt defense	Prompt + tool boundary
Recommendation override	blocked: no	blocked: yes	blocked: yes
Non-SELECT SQL misuse	blocked: no	blocked: no	blocked: yes
CSV-content exfiltration	blocked: no	blocked: yes	blocked: yes

Prompt-only defenses label retrieved policy as untrusted and rely on model instruction following. Tool-boundary defenses enforce executable restrictions; ‘csv_sql‘ independently accepts only read-only SELECT statements. Raw source: ‘raw/hw7_prompt_injection_results.json‘.

Part 6 - file tools and safety gate

‘code/hw7_file_tools.py‘ implements ‘read_file‘, ‘write_file‘, ‘edit_file‘, ‘glob_files‘, ‘search_in_files‘, and ‘bash‘. ‘_safe‘ resolves every path under the temporary course sandbox. ‘SAFE_PREFIXES‘ allowlists bounded local commands. ‘is_destructive‘ independently detects destructive patterns, including the original false allow: ‘python -c‘ file writes. ‘confirm_bash‘ requires explicit confirmation for destructive commands, and ‘bash‘ applies a 30-second timeout.

Representative implementation excerpts:

```
def read_file(path, root, max_lines=None):
    lines = _safe(path, root).read_text(encoding="utf-8").splitlines()
    return "\n".join(lines if max_lines is None else lines[:max_lines])

def write_file(path, content, root):
    target = _safe(path, root)
    target.parent.mkdir(parents=True, exist_ok=True)
    target.write_text(content, encoding="utf-8")
    return str(target.relative_to(root.resolve()))

def edit_file(path, old, new, root):
    target = _safe(path, root)
    before = target.read_text(encoding="utf-8")
    if old not in before: raise ValueError("text to replace was not found")
    target.write_text(before.replace(old, new, 1), encoding="utf-8")

def glob_files(pattern, root): ...
def search_in_files(query, root, file_pattern="*"): ...
def bash(command, auto_approve=False):
    decision = confirm_bash(command, auto_approve)
    if not decision["allowed"]: return decision
    return subprocess.run(command, shell=True, timeout=30, ...)
```

The safety constants and independent checks are:

```
SAFE_PREFIXES = ("python ", "python3 ", "pytest ", "ruff ",
                 "git status", "git diff", "git log")
```

```
DESTRUCTIVE_PATTERNS = (..., r"\bpython(?:3)?\s+-c\b")
def is_destructive(command):
    return any(re.search(pattern, command, re.IGNORECASE)
               for pattern in DESTRUCTIVE_PATTERNS)
def confirm_bash(command, auto_approve=False):
    if is_destructive(command):
        return {"allowed": bool(auto_approve),
                "reason": "destructive command requires explicit
confirmation"}
```

The corrected run in ‘raw/hw7_file_tools_safety_results_corrected.json‘ reports:

Check	Result
Glob -> search -> read found ‘DEBUG‘	pass
Allowed commands	5/5
Blocked commands	5/5
Corrected false allows	0
Outside sandbox modified	false
Database accessed	false
Model called	false

The independent deny-list added ‘python -c‘ after the first run identified the inline Python file-write command as a false allow. No application file outside the temporary sandbox was modified.

Tests, limitations, and preservation

Offline tests covered JWT creation/validation, password hashing, roles, bounded agent repair and tool-call budgets, Reflexion retry bounds, MRKL calculator and SQL validation, prompt security, file-tool sandbox behavior, migration safety, and the bike-share UI pipeline. Scoped Ruff passed. Full pytest was not claimed because collection/execution remained blocked by the managed environment and the repository ‘code‘ package shadowing the standard-library ‘code‘ module.

Existing HW1-HW6 source changes, reports, screenshots, raw evidence, database state, branches, tags, ‘.hw6-chrome-pdf-profile*‘, and ‘MEMORY.md.before-hw6‘ remain preserved. This report does not create ‘verification.json‘. Commit 1, the verifier-generated ‘verification.json‘, Commit 2, and the annotated ‘hw7‘ tag remain the next packaging steps. A GitHub push remains pending approval.

Remediation and manual-capture matrix

Assignment requirement	Existing evidence/code	Missing report content	Missing screenshot	Proposed report section	Manual capture?
JWT login/me/roles	auth module, 19-case JSON, screenshots	code/output linkage	MySQL table; writer/moderator login visuals	Part 1	MySQL/table and any missing role visuals
Agent loop/reliability	hw7_agent.py, reliability JSON	actual implementation and full metric table	B/C visuals	Part 2	B/C screenshots
Reflexion	agent verifier and comparison JSON	verifier/budget/isolation explanation	no dedicated verifier terminal	Part 3	optional terminal capture
MRKL scenarios	source, CSVs, snapshots, corrected JSON	cost assumptions, hashes, horizon, caveat	existing screenshots are readable	Part 4	no, unless instructor requests crops
Prompt injection	prompt-security source and raw JSON	written threat model/table	existing screenshot	Part 5	no


| File safety | source and corrected JSON | actual function excerpts and false-allow correction | existing screenshot | Part 6 | no |

| Packaging | current Git state | final hashes | no successful commit screenshot | Tests/limitations | yes, after approved packaging |

Packaging status


The PDF is prepared for review only. ‘verification.json‘ is intentionally not created because the final commit hash does not yet exist. No commit, tag, push, database change, source-code change, screenshot change, or raw-evidence change is part of this remediation.

HW7 screenshot: hw7_jwt_login_reader_200.png




Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_auth_me_missing_token_401.png




Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_reader_create_403.png




Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_writer_create_201.png




Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_moderator_delete_success.png




Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_agent_task_a_search_detail.png



Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_agent_reliability_reflexion.png




Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_bikeshare_payg_wins.png




Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_prompt_injection_defenses.png



Readable embedded screenshot; source file preserved unchanged.

HW7 screenshot: hw7_file_tools_safety_gate.png



Readable embedded screenshot; source file preserved unchanged.