DATA260 Homework 8

> **Student:** Vrishin KunnathamParambath
>
> **SID4:** 8844
>
> **Repository:** https://github.com/Viki2183/data260-8844
>
> **Branch:** `hw6-development`
>
> **Historical HW7:** tag `hw7`, commit `238163e119dd9fc83c945f287e109d6e2d024fec`
>
> **HW8 artifact commit:** `bda1110c82293aac22d16951f35cff5b368f825a`; final tag: `hw8`
>
> **Collaborator access:** `Sbnikitha` and `supriyaselvanganesan`

0. Configuration

Item	Value
Assigned domain	Open-source package vulnerabilities
`PORT_BASE`	`8744` = `8000 + (8844 mod 900)`
`PREFIX`	`s8844`
`SEED` / `VERIFY_SEED`	`8844` / `268844`
`DOMAIN_ID`	`4` = `8844 mod 8`
Kafka	`apache/kafka:3.9.2`, isolated project `data260-hw8`
Listeners	Docker: `hw08-kafka:9092`; host: `localhost:29092`
Runtime	Windows host, Docker Desktop, Linux x86_64 containers, 12 CPUs, WSL2
Model/database	Configured model `qwen3:8b` and database `s8844_rel`; measured HW8 agent behavior was deterministic and did not use Ollama or MySQL.

1. Kafka entity request/response

Architecture and schema

The host client and isolated FastAPI service publish canonical requests to `s8844_entity_requests`. The entity worker validates the vulnerability-report payload, stores entities in a worker-local Python dictionary, generates UUIDs for CREATE_ENTITY, and publishes responses to `s8844_entity_responses`. The client waits only for the matching `correlation_id` and does not automatically retry.

Envelope field	Request/response use
`message_type`	`entity_request` or `entity_response`
`correlation_id`	Preserved unchanged from request to response
`reply_to`	`s8844_entity_responses` on requests
`operation`	`CREATE_ENTITY`, `GET_ENTITY`, or an intentional invalid operation
`data`	Vulnerability-report fields or returned entity/error data
`entity_id`	Generated UUID for CREATE; lookup ID for GET
`attempt`, `timestamp`, `metadata`	Bounded processing metadata and observable timestamps

Validation requires non-empty package name, vulnerability ID, submitter email, and description; valid email syntax; a 26-character minimum description; one of Critical/High/Medium/Low severity; `termsAccepted=true`; and a non-negative integer version count.

Measured live result

`homework_demo.py` ran against the captured FastAPI service at `http://127.0.0.1:8744`. CREATE correlation was `hw8-8844-live2-create-001`; GET correlation was `hw8-8844-live2-get-001`; generated UUID was `4e9d8b15-a4de-415c-82f0-e5f67123d12d`. The entity contained package `requests`, vulnerability `CVE-2026-0001`, severity `High`, submitter `student@example.com`, two affected versions, accepted terms, and the recorded description. Validation failure, unknown entity, and unknown operation responses each echoed their correlation ID.


The captured service log contains `FastAPI server started at http://127.0.0.1:8744` and `Consumer is ready and listening on s8844_entity_requests`. The Docker snapshot shows Kafka, the entity worker, and the FastAPI service. Topic commands show the exact request/response names.

Evidence: `raw/part1_homework_demo_live2.jsonl`, `raw/part1_service_logs.log`, `raw/part1_docker_ps.txt`, `raw/part1_topic_commands.log`.

Student: Vrishin KunnathamParambath | SID4: 8844



Student: Vrishin KunnathamParambath | SID4: 8844



Student: Vrishin KunnathamParambath | SID4: 8844

```
Student: Vrishin KunnathamParambath | SID4: 8844

> captured live FastAPI/entity-worker flow
hw08-entity-worker-1  | Consumer is ready and listening on s8844_entity_requests
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-create-001", "event": "entity_request_received", "offset": 4, "operation": "CREATE_ENT...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-create-001", "event": "entity_response_published", "offset": 1, "operation": "CREATE_E...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-create-001", "event": "entity_source_offset_committed", "offset": 4, "partition": 0, "...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-get-001", "event": "entity_request_received", "offset": 1, "operation": "GET_ENTITY", ...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-get-001", "event": "entity_response_published", "offset": 4, "operation": "GET_ENTITY"...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-get-001", "event": "entity_source_offset_committed", "offset": 1, "partition": 1, "top...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-validation-error-001", "event": "entity_request_received", "offset": 5, "operation": "...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-validation-error-001", "event": "entity_response_published", "offset": 5, "operation":...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-validation-error-001", "event": "entity_source_offset_committed", "offset": 5, "partit...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-missing-001", "event": "entity_request_received", "offset": 6, "operation": "GET_ENTIT...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-missing-001", "event": "entity_response_published", "offset": 6, "operation": "GET_ENT...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-missing-001", "event": "entity_source_offset_committed", "offset": 6, "partition": 0, ...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-unknown-operation-001", "event": "entity_request_received", "offset": 2, "operation": ...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-unknown-operation-001", "event": "entity_response_published", "offset": 2, "operation"...
hw08-entity-worker-1  | {"correlation_id": "hw8-8844-live2-unknown-operation-001", "event": "entity_source_offset_committed", "offset": 2, "parti...
hw08-api-1            | FastAPI server started at http://127.0.0.1:8744
hw08-api-1            | {"correlation_id": "hw8-8844-live2-create-001", "event": "api_request_published", "operation": "CREATE_ENTITY", "request"...
```

2. Planner, Writer, and Reviewer pipeline

Process	Input	Output
Planner	`s8844_inbox`	`s8844_tasks`
Writer	`s8844_tasks`	`s8844_drafts`
Reviewer	`s8844_drafts`	`s8844_final`

The corrected live run published one input with correlation ID `hw8-8844-agent-live2-001`. It was observed at `s8844_inbox` p0/o0, `s8844_tasks` p1/o0, `s8844_drafts` p1/o0, and `s8844_final` p1/o0. The final JSON message contained `status=approved` and an answer. The complete stage log shows each process receiving, publishing, and committing.

Kafka helped coordinate the agents by providing durable topic boundaries, consumer-group assignment, explicit offsets, and independent restart/failure domains. Each process can be observed and scaled separately, while the correlation ID connects the journey without a shared in-process call stack.


Topic verification recorded `s8844_inbox`, `s8844_tasks` with exactly two partitions, `s8844_drafts`, and `s8844_final`. No Ollama, MySQL, or JMeter call was made.

Student: Vrishin KunnathamParambath | SID4: 8844

```
Student: Vrishin KunnathamParambath | SID4: 8844

> captured live Planner/Writer/Reviewer flow
hw08-planner-1  | {"event_type": "consumer_ready", "process": "planner", "input_topic": "s8844_inbox", "group_id": "s8844-planner"}
hw08-planner-1  | {"event_type": "message_received", "process": "planner", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_inbox", ...
hw08-planner-1  | {"event_type": "output_published", "process": "planner", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_inbox", ...
hw08-planner-1  | {"event_type": "offset_committed", "process": "planner", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_inbox", ...
hw08-writer-2-1  | {"event_type": "consumer_ready", "process": "writer", "input_topic": "s8844_tasks", "group_id": "s8844-writer"}
hw08-writer-2-1  | {"event_type": "message_received", "process": "writer", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_tasks", ...
hw08-writer-2-1  | {"event_type": "output_published", "process": "writer", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_tasks", ...
hw08-writer-2-1  | {"event_type": "offset_committed", "process": "writer", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_tasks", ...
hw08-writer-1-1  | {"event_type": "consumer_ready", "process": "writer", "input_topic": "s8844_tasks", "group_id": "s8844-writer"}
hw08-reviewer-1  | {"event_type": "consumer_ready", "process": "reviewer", "input_topic": "s8844_drafts", "group_id": "s8844-reviewer"}
hw08-reviewer-1  | {"event_type": "message_received", "process": "reviewer", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_drafts...
hw08-reviewer-1  | {"event_type": "output_published", "process": "reviewer", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_drafts...
hw08-reviewer-1  | {"event_type": "offset_committed", "process": "reviewer", "correlation_id": "hw8-8844-agent-live2-001", "topic": "s8844_drafts...
```

Student: Vrishin KunnathamParambath | SID4: 8844



3. Failure handling and idempotency

Measured behavior

Experiment	Measured result
Duplicate delivery	Intentional replay returned the same UUID; duplicate flag was true; derived entity-store count stayed 0 -> 1 -> 1.
Consumer death	Writer 1 crashed before commit; the same p0/o0 was redelivered to Writer 2, which published and committed. Writer 1 restart readiness was logged. No exit code is claimed for the corrected run because it was not captured before recreation.
Poison/DLT	Attempts 1-3 were bounded; DLT publication to `s8844_dead_letter` preceded source commit; a later valid message reached `s8844_drafts` with `blocked_by_poison=false`.

Required implementation excerpts


```
def idempotency_key(message):
    data = message.get("data")
    data_entity_id = data.get("entity_id") if isinstance(data, Mapping) else None
    return (str(message.get("message_type", "")),
            str(message.get("correlation_id", "")),
            str(message.get("operation", "")),
            str(message.get("entity_id") or data_entity_id or ""))
```

```
await producer.send_and_wait(response_topic, serialize_message(response))
await consumer.commit()  # commit only after successful output
```


```
failures = poison_attempt_records(message, error_type=error_type, max_attempts=3)
dead_letter = dead_letter_message(message, error_type=error_type, ...)
await producer.send_and_wait("s8844_dead_letter", serialize_message(dead_letter))
await consumer.commit()
```

```
# ordering harness
key = "entity-268844" if keyed else None
await producer.send_and_wait("s8844_tasks", value, key=key)
```

Student: Vrishin KunnathamParambath | SID4: 8844



Student: Vrishin KunnathamParambath | SID4: 8844



Before/after comparison boundary

No historical before-fix run was captured for duplicate, consumer death, or poison handling. The table therefore does not invent measured before values; it records the actual measured after behavior and identifies the evidence boundary.

Case	Before-fix evidence	After HW8 mechanism	Evidence
Duplicate delivery	No historical before-fix run captured.	Cached response, same UUID, unchanged count.	`part3_duplicate_delivery.jsonl`
Consumer death	No historical before-fix run captured.	Crash before commit, Kafka redelivery, output then commit.	`part3_consumer_death_live2.jsonl` plus logs
Poison message	No historical before-fix run captured.	Three bounded attempts, DLT publication, source commit, later valid output.	`part3_poison_dead_letter_live2.jsonl`
Ordering	In-process graph has no Kafka partition measurement.	Unkeyed and entity-keyed 20-message runs measured per-partition order.	Four ordering JSONL/CSV files

4. Deterministic ordering experiment


`VERIFY_SEED=268844`, exactly 20 related messages per run, two partitions, and two Writers in group `s8844-writer` were used. Unkeyed messages used no key. Keyed messages used `entity-268844`. No retry or resend

occurred.


Run	Measured result	Interpretation
Unkeyed	20/20; partitions 0 and 1; both Writers. By offset: p0 [0,3,4,6,7,9,10,11,12,15,17,18,19]; p1 [1,2,5,8,13,14,16].	Each partition preserved its measured sequence; no global ordering claim.
Entity-keyed	20/20; all p0; Writer 1; sequence and offsets both 0 through 19.	One deterministic key colocated related messages in one partition.

Kafka guarantees ordering within a partition, not global ordering across partitions.

Student: Vrishin KunnathamParambath | SID4: 8844



Student: Vrishin KunnathamParambath | SID4: 8844



5. HW2 in-process graph versus Kafka

Required item	Result
Benefit 1 - independent scaling	Planner, Writer, and Reviewer are separate consumers and can scale or restart independently through Kafka groups.
Benefit 2 - decoupled failure	A Writer crash before commit does not lose the task; Kafka redelivers it to a surviving Writer and topic boundaries isolate stages.
Responsibility 1 - idempotency and DLT	The application must handle duplicate delivery, bound poison attempts, publish the DLT, and commit only after output/DLT success.
Responsibility 2 - ordering and operations	The application must choose keys, understand partition-local ordering, manage listeners/topics/groups, and verify readiness and cleanup.


6. Verification and evidence index

`verification.json` records homework number, SID4, the HW8 artifact commit hash, model/configuration, PORT_BASE, PREFIX, DOMAIN_ID, SEED, VERIFY_SEED, named checks, and pass/fail values. The final `hw8` tag is created on the packaging metadata commit.


Requirement	Evidence
Entity/API	`part1_homework_demo_live2.jsonl`, service logs, Docker snapshot, topic commands
Agent journey	`part2_agent_demo_live2.jsonl`, full pipeline logs, topic commands
Duplicate delivery	`part3_duplicate_delivery.jsonl`

Consumer death	`part3_consumer_death_live2.jsonl`, writer and restart logs
Poison/DLT	`part3_poison_dead_letter_live2.jsonl`, writer/topic logs
Ordering	Four ordering JSONL/CSV files
Offline verification	`python -m unittest test_hw08_offline -v` and `verification.json`

Student: Vrishin KunnathamParambath | SID4: 8844



Student: Vrishin KunnathamParambath | SID4: 8844



7. AI-use disclosure

1. Use: I used AI/Codex for inspection, implementation support, tests, controlled local Kafka commands, evidence organization, screenshots, and report/PDF preparation. I selected data and scope, reviewed results, and made final decisions.

2. Incorrect output/verification: The first hand-built PDF opened blank. I independently verified rendering, the `%PDF-` header, searchable text, raw evidence, logs, tests, and links.

3. Detection: The blank PDF contradicted the expected report content. Comparing poison logs also showed that the later-valid check needed an explicit run.

4. Correction: Chrome headless rendering replaced the blank output; the FastAPI/demo, full stage logs, post-DLT check, and normalized consumer-death evidence were added; the verifier now checks the corrected evidence paths.

No hidden chain-of-thought, credentials, JWTs, hashes, API keys, tokens, or `.env` values are included. Historical before-fix runs were not captured and are not presented as measured data.

Full disclosure: `reports/hw08/AI_USE.md`. Verification source: `code/verify_hw08.py`.