# DATA260 Homework 7

Student: Vrishin KunnathamParambath SID4: 8844 Domain: open-source package vulnerabilities Repository: https://github.com/Viki2183/data260-8844 Final tagged tree: https://github.com/Viki2183/data260-8844/tree/hw7 Collaborator-access confirmation: Sbnikitha, supriyaselvanganesan - pending submission confirmation. Final tagged commit is the peeled target of the annotated local hw7 tag. Commit 1 contains the final HW7 artifacts; verification.json records that parent hash. Commit 2 contains verification.json, and annotated hw7 points to Commit 2. Exact current hashes are verified in Git metadata and verification.json after packaging. No GitHub push has occurred.

# Configuration and hardware

Model: qwen3:8b through local Ollama at 127.0.0.1:11434. PORT_BASE=8744, PREFIX=s8844, SEED=8844, VERIFY_SEED=268844, DOMAIN_ID=4. HW6 hardware description: Intel Core i7-10750H CPU, approximately 16 GB RAM.

# AI use and verification boundary

Codex assisted with repository inspection, reading the official assignment, implementation review, offline testing, evidence organization, and report preparation. The student supplied the repository and private credentials when needed, approved the phases and test scope, selected test data, reviewed the results, and retained responsibility for submission decisions. The complete answer is synchronized in AI_USE.md.

(1) How AI assistance was used: Codex assisted with repository inspection, assignment reading, implementation review, bounded testing, raw-evidence organization, and report/PDF preparation. The student approved scope, reviewed outputs, and retained responsibility for submission decisions.

(2) What was independently reviewed or verified: The student reviewed source changes, screenshots, JWT results, offline checks, local Ollama results, raw evidence, and the generated PDFs. Private credentials were entered locally and are not included here.

(3) How a problem or limitation was detected: The original bike-share result used included_minutes=0, producing the superseded $6,830 value. Comparing the pricing snapshot and UI calculation identified 45 included minutes per ride and the authoritative $4,780 membership value. The Task C Ollama HTTP 500 was also recorded as bounded recovery rather than normal model success.

(4) What was changed and why the change works: The agent now normalizes tool responses, supports repeated detail sequences, records adapter failures, and performs one fixed-plan controller repair without retrying the model. Offline and live evidence were checked. No hidden chain-of-thought was stored, and unavailable or failed measurements were not invented.

No hidden chain-of-thought was stored or returned. Evidence stores only task inputs where needed, tool calls, tool results, verifier outputs, final answers, stop reasons, and measured metrics. Passwords, password hashes, JWT strings, and secrets are excluded.

The measured 20-attempt reliability result is reported without alteration: 20 attempts were recorded, with 0/20 successful task completions. The latest fixed-sequence comparison was baseline 0/3 and Reflexion 0/3; the earlier comparison remains preserved as separate historical evidence. Pytest remained blocked by the managed temporary-file environment and the repository code package shadowing the standard-library code module; deterministic offline checks were used where appropriate. These checks do not replace the blocked full pytest run.

# Part 1 - JWT authentication, roles, and database migration

## Implementation excerpts

code/web_application/auth_hw7.py defines the HW7 JWT routes and helpers:

```
@router.post("/login", response_model=TokenResponse)
def login(payload: LoginPayload, db: Session = Depends(get_db)) -> TokenResponse:
user = db.query(models.UserDB).filter(
models.UserDB.username == payload.username.strip()
).first()
if user is None or user.role not in ALLOWED_ROLES or not verify_password(
payload.password, user.password_hash
```

```
):
raise HTTPException(status_code=401, detail="Invalid username or password")
return TokenResponse(access_token=create_access_token(user.username, user.role))

@router.get("/me", response_model=IdentityResponse)
def me(user: models.UserDB = Depends(get_current_user)) -> IdentityResponse:
return IdentityResponse(username=user.username, role=user.role)
```

JWT creation validates reader, writer, and moderator, signs HS256 claims, and includes iat and exp. Validation checks the signature, header, username, role, and expiration. Passwords use bcrypt:

```
def hash_password(password: str) -> str:
return bcrypt.hashpw(password.encode("utf-8"), bcrypt.gensalt()).decode("utf-8")
```

Role dependencies are explicit: authenticated reads are available to all three roles; create is available to writer/moderator; delete is moderator-only.

## Live status evidence

Source: raw/hw7_live_jwt_authorization.json, 19 cases, all recorded as passing.

| Check | Expected | Recorded |
|---|---|---|
| Reader/writer/moderator login | 200 | 200/200/200 |
| Invalid password and unknown usernam | 401 | 401/401 |
| /auth/me reader/writer/moderator | 200 | 200/200/200 |
| Missing, invalid, expired token | 401 | 401/401/401 |
| Authenticated list/read for all role | 200 | 200/200/200 |
| Reader create | 403 | 403 |
| Writer create | 201 | 201 |
| Moderator create | 201 | 201 |
| Writer delete | 403 | 403 |
| Moderator delete | 200 | 200 |

The live evidence records no stored JWT values and no stored passwords. Created HW7 test records were limited to the labeled test records; the moderator delete target was cleaned up. No HW1-HW6 record was deleted or modified.

## Users schema and migration

code/web_application/hw7_migration.py defines a non-destructive CREATE TABLE IF NOT EXISTS users shape with id, name, username, email, password_hash, role, a primary key, unique username/email keys, and a role check for reader, writer, or moderator. It explicitly requires preflight inspection before altering an existing table and does not invent a username backfill.

| id | username | role | password_hash |
|---|---|---|---|
| 1 | vikki1 | reader | exists; value not displayed |
| 2 | vikki2 | writer | exists; value not displayed |
| 3 | vikki3 | moderator | exists; value not displayed |

This table records only safe fields from the approved live preflight. A dedicated MySQL-table screenshot/raw artifact was not created; manual capture is required if the instructor requires visual database evidence. No schema or row change is performed by this report.

Ruff scoped checks passed for the HW7 scope. The temporary demonstration also shows the original Ruff failure, the corrected file, both pre-commit hooks passing, and a successful temporary Git commit. These screenshots use isolated temporary files and do not represent a commit to the real repository.

Evidence: hw7_lint_failure.png, hw7_lint_fix_pass.png, and hw7_precommit_successful_commit.png.

The final command must not be run until the approved packaging step; its successful output is therefore unavailable in the current evidence.

# Part 2 - bounded agent loop and reliability

## Actual implementation

code/hw7_agent.py uses run_agent, not a pseudo-agent. It validates each model decision as tool or final, dispatches the named handler, catches tool errors as bounded observations, appends a tool message with deterministic IDs such as hw7-tool-call-1, and appends a continuation message. The loop is bounded by max_steps; malformed/unknown decisions and incomplete required sequences have at most one repair in the recorded smoke/reliability configuration.

The repair includes the next required tool and, for Task A, the package ID from the search observation. A final answer before the required sequence yields human_review after the repair budget is exhausted. Other bounded stop reasons are success and budget_exhausted.

The following focused excerpts are copied from the current implementation, not pseudocode:

```
def run_agent(user_input, model, tools, max_steps=8, max_repairs=1,
required_tool_sequence=None, required_tool_inputs=None):
started = time.perf_counter()
messages = [{"role": "user", "content": user_input}]
trace, repairs, calls = [], 0, 0
for step in range(1, max_steps + 1):
decision = model.complete(messages)
action, name, inputs = _validate_decision(decision, tools)
inputs = _normalize_inputs(name, inputs)
observation = _normalize_observation(toolsname)
calls += 1
trace.append({"step": step, "tool": name, "inputs": inputs,
"observation": observation})
messages.append({"role": "tool",
"tool_call_id": f"hw7-tool-call-{calls}",
"content": json.dumps(observation, default=str)})
messages.append({"role": "user",
"content": "Continue or provide the final answer as JSON."})
return AgentResult("The tool-call budget was exhausted.",
"budget_exhausted", trace, calls, repairs,
(time.perf_counter() - started) * 1000).as_dict()
```

The fixed-plan adapter-error branch records an adapter_error, executes the next declared read-only handler once, records repair_reason="bounded controller recovery after adapter failure", and returns success only after every declared handler succeeds. It does not retry the model.

The loop logs tool name, inputs, observation, tool-call count, repair count, latency, final answer, and stop reason. It does not store hidden reasoning.

The current fixed-input repair path also records an adapter failure as a trace event and, only when an approved fixed plan is present, executes the next read-only handler once. It never retries the model. A successful controller repair is labeled separately from uninterrupted model success.

## Fixed-task evidence

raw/hw7_agent_fixed_tasks.json records the earlier fixed-task run with the pre-compatibility tool_call_id failure. Later evidence raw/hw7_task_a_package00001.json records the corrected Task A smoke input: search(package-00001) -> detail(package_id=1), two tool calls, final answer produced, and success. These are separate runs and are not merged.

The latest Task B smoke evidence, raw/hw7_task_b_final_smoke.json, records aggregate -> search, two executed tool calls, stop reason success, and no database writes. The search used the verified existing package name package-00001.

The latest Task C evidence, raw/hw7_task_c_final_smoke_v2.json, records search -> detail -> detail for integer IDs 1 and 2, three executed tool calls, and stop reason success. Ollama returned HTTP 500 after detail(1); the bounded controller executed detail(2) once, with no model retry. The result is classified bounded_controller_recovery, not uninterrupted normal model success. No database writes or hidden chain-of-thought were recorded.

raw/hw7_agent_nonexistent_id_recovery.json records controlled recovery for ID 999999 with a package not found error and no crash. Nonexistent-ID recovery is covered by the offline agent tests and bounded tool error handling; no database write is required for that recovery path.

### Reliability table

Source: raw/hw7_reliability_20_attempts_v2.json. The consolidated tables are also recorded in METRICS.md and the run chronology is recorded in HW7_LIVE_RUN_LOG.txt.

| Metric | Actual value |
|---|---|
| Total attempts | 20 |
| Well-formed call rate before repair | 0/20 (0%) |
| Well-formed call rate after repair | 0/20 (0%) |
| Malformed arguments | 0 |
| Unknown tool | 0 |
| Text when a tool was required | 20 |
| Lost multi-step chain | 0 |
| Successful tasks | 0/20 |
| human_review stops | 20 |
| budget_exhausted stops | 0 |
| Average latency | 13,160.690 ms |
| Median latency | 12,423.832 ms |
| Average tool calls | 0 |

For reliability, "well-formed" means that the model produced a valid tool call when a tool was required. Because the recorded attempts produced zero executed tool calls, the before-repair rate is 0/20, not 20/20. The after-repair rate is also 0/20; all 20 stopped at human_review and none stopped at budget_exhausted.

## Part 3 - Reflexion and verifier

verify_task checks the stop reason, required tool set, ordered tool sequence, and answer presence. It returns success, unsupported_claims, missing_tools, and missing_sequence. reflexion_run retries only after verifier failure, allows at most two retries, stores concise reflections with the prior trace/verifier evidence, and returns one of success or human_review; the agent itself also has budget_exhausted.

Reflections are isolated within a run and passed as a model-factory context; they are not instructions, permissions, role definitions, or safety gates. The tool registry and authorization policy remain fixed. Hidden chain-of-thought is not stored.

The actual verifier and Reflexion control excerpts are:

```
def verify_task(result, required_tools, required_tool_sequence=None):
used_sequence = [item.get("tool") for item in result.get("trace", [])]
used = set(used_sequence)
sequence_ok = (required_tool_sequence is None or
used_sequence[:len(required_tool_sequence)] ==
required_tool_sequence)
return {
"success": (result.get("stop_reason") == "success"
and required_tools.issubset(used)
and sequence_ok
and (required_tool_sequence is None or
len(used_sequence) >= len(required_tool_sequence))),
"unsupported_claims": not bool(result.get("answer", "").strip()),
"missing_tools": sorted(required_tools - used),
"missing_sequence": (required_tool_sequence[len(used_sequence):]
if required_tool_sequence and not sequence_ok else []),
}
```

```
def reflexion_run(user_input, model_factory, tools, required_tools,
max_retries=2, required_tool_sequence=None,
required_tool_inputs=None):
reflections, reflection = [], None
for attempt in range(max_retries + 1):
result = run_agent(user_input, model_factory(reflection), tools,
required_tool_sequence=required_tool_sequence,
required_tool_inputs=required_tool_inputs)
check = verify_task(result, required_tools, required_tool_sequence)
if check["success"]:
result.update({"attempt": attempt + 1,
"reflections": reflections, "verifier": check})
return result
if attempt == max_retries:
result.update({"stop_reason": "human_review",
"attempt": attempt + 1,
"reflections": reflections, "verifier": check})
return result
missing = ", ".join(check["missing_tools"])
missing = missing or ", ".join(check.get("missing_sequence", []))
reflection = (f"Failed because required tools were missing: {missing}. "
"Use the missing tool chain before finalizing.")
reflections.append({"attempt": attempt + 1,
"evidence": {"trace": result.get("trace", []),
"verifier": check},
"reflection": reflection})
```

Stored reflection evidence is concise and tied to the triggering verifier:

```
{
"attempt": 1,
"evidence": {"trace": [], "verifier": {"success": false}},
"reflection": "Failed because required tools were missing: detail. Use the missing tool chain
before finalizing."
}
```

The raw evidence does not contain an independent adjudication of verifier false rejections, so that metric is reported as unavailable rather than inferred from the verifier's own result.

| Task | Condition | Task success | Unsupported claim | Retry rate | Tool calls | Tokens | Latency ms | Verifier false rejectio |
|---|---|---|---|---|---|---|---|---|
| A | baseline | 0/1 | 0/1 | 0/1 | 0 | unavailable | 26,830.233 | unavailable |
| A | Reflexion | 0/1 | 0/1 | 2/3 attempts | 0 | unavailable | 31,304.839 | unavailable |
| B | baseline | 0/1 | 0/1 | 0/1 | 0 | unavailable | 7,890.029 | unavailable |
| B | Reflexion | 0/1 | 0/1 | 2/3 attempts | 0 | unavailable | 21,987.268 | unavailable |
| C | baseline | 0/1 | 0/1 | 0/1 | 0 | unavailable | 12,984.022 | unavailable |
| C | Reflexion | 0/1 | 0/1 | 2/3 attempts | 0 | unavailable | 36,203.908 | unavailable |

Current rerun source: raw/hw7_reflexion_comparison_current.json. It recorded baseline 0/3 and Reflexion 0/3, with all six runs stopping at human_review; each of the 3 Reflexion runs used 2 retries, for 6 retries total. Baseline average latency was 15,901.428 ms and current Reflexion average latency was 29,865.338 ms. Token usage was unavailable. Verifier false-rejection adjudication was unavailable. The earlier comparison remains preserved in raw/hw7_reflexion_comparison.json and is not merged with this current rerun.

# Part 4 - MRKL and bike-share application

The three pure/isolated tools share a response shape with success, optional data, optional error, optional source, and ts:

```
def _result(success, data=None, error=None, source=None):
value = {"success": success}
if data is not None: value["data"] = data
if error: value["error"] = error
if source: value["source"] = source
value["ts"] = datetime.now(timezone.utc).isoformat()
return value

def csv_sql(csv_text, sql):
if not re.match(r"^\s*select\b", sql, re.IGNORECASE):
```

```
return _result(False, error="csv_sql accepts one read-only SELECT")
if re.search(r";|\b(insert|update|delete|drop|alter|create|replace)\b", sql, re.I):
return _result(False, error="csv_sql accepts one read-only SELECT")
# parse uploaded CSV into one in-memory SQLite table and return rows

def policy_retriever(url, query, k=3):
with urllib.request.urlopen(url, timeout=10) as response:
raw = response.read()
text = re.sub(r"<[^>]+>", " ", raw.decode("utf-8", "replace"))
text = re.sub(r"\s+", " ", text).strip()
terms = [t.lower() for t in re.findall(r"[a-z0-9]+", query)]
sentences = re.split(r"(?<=[.!?])\s+", text)
ranked = sorted(sentences,
key=lambda s: sum(t in s.lower() for t in terms),
reverse=True)
passages = [{"text": sentence[:500], "source": url,
"score": sum(t in sentence.lower() for t in terms)}
for sentence in ranked[:max(1, k)]]
return _result(True, {"passages": passages}, source=url)

def calculator(expression, units=None):
if not re.fullmatch(r"^[0-9+\-*/().\s]+$", expression):
return _result(False, error="invalid calculator expression")
tree = ast.parse(expression, mode="eval")
allowed = (ast.Expression, ast.Constant, ast.BinOp, ast.UnaryOp,
ast.Add, ast.Sub, ast.Mult, ast.Div, ast.USub, ast.UAdd,
ast.Pow)
if any(not isinstance(node, allowed) for node in ast.walk(tree)):
return _result(False, error="unsupported expression")
value = _calculate(tree.body)
data = {"value": value}
if units:
data["units"] = units
return _result(True, data)
```

csv_sql rejects non-SELECT statements independently of the model. The calculator rejects unsupported characters and AST nodes. Missing files, malformed CSV, invalid arithmetic, and SQL injection/non-SELECT attempts are covered by offline tests. The SQL boundary is one statement only: semicolons and non-SELECT keywords are rejected before SQLite execution. The calculator uses the exact whitelist regex ^[0-9+\-*/().\s]+$ and then validates the AST.

Common response shape:

```
{"success": true, "data": {}, "error": null, "source": "...", "ts": "..."}
```

Explicit tool input schemas:

```
{"tool": "csv_sql", "input": {"csv_text": "string", "sql": "string"}}
{"tool": "policy_retriever", "input": {"url": "string", "query": "string", "k": "integer
(optional)"}}
{"tool": "calculator", "input": {"expression": "string", "units": "string (optional)"}}
```

The official pricing URL recorded in evidence is https://citibikenyc.com/plans-and-pricing. Both snapshots have access timestamp 2026-10-25T07:27:04.715872+00:00 and SHA-256 07fb221a434fb166302571050657a0c2c53f995214af78771faf735e7733c71d.

Readable snapshot excerpt used by the calculation: "$239/year"; "unlimited 45-minute rides on classic bikes"; and "Any ride longer than 30 minutes is an additional $0.41/minute." The excerpt is from the preserved pricing snapshot, not a new navigation request.

| Scenario | Rows | Weekly rides | Avg dur | Weekly spend | Pay/us | Membe | Residu | Break-even | Actual | Steps | Stop |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Membershi | 500 | 500/month (peri | 30 min | source period; no | $8,645 | $19.92 | $0 | 1.15 rides | 500 rides/15,000 | 5 | succes |
| Pay-per-u | 500 | 25/year = 0.48/ | 10 min | source period; no | $4,545 | $4,780 | $0 | not recomputed in | 500 rides/5,000 m | 5 | succes |

The membership scenario is one month of 30-minute rides, all within the 45-minute member allowance, and remains unchanged. The pay-per-use scenario is a 20-year observation horizon with 25 short rides per year. Annual membership pricing is applied for each of the 20 years: 20 * $239 = $4,780. The corrected calculation uses 500 rides x 45 included minutes, so no residual charge remains.

Membership-wins scenario: 500 rides, 30-minute average duration, and 500 rides per month. Weekly ride count and weekly spend are not separately recorded in the source-period evidence, so they are not inferred. Pay-per-use total is $8,645, membership total is $19.92, residual charges are $0, total steps are 5, total time is 15,000 minutes, and stop reason is success. Source: https://citibikenyc.com/plans-and-pricing; snapshot access time and SHA-256

are recorded above.

Pay-per-use-wins scenario: 500 rides, 10-minute average duration, and 25 rides per year (0.48 rides per week). Weekly spend is not separately recorded in the source-period evidence, so it is not inferred. Pay-per-use total is $4,545, membership total is $4,780, residual charges are $0, total steps are 5, total time is 5,000 minutes over 20 years, and stop reason is success. Source: https://citibikenyc.com/plans-and-pricing; snapshot access time and SHA-256 are recorded above.

The original raw/hw7_bikeshare_scenarios.json is preserved unchanged. Its old pay-per-use recommendation displayed $6,830 because it used included_minutes=0, even though its calculator result recorded $4,780. raw/hw7_bikeshare_scenarios_corrected.json is the authoritative correction: pay-per-use $4,545, membership $4,780, decision Pay Per Ride/Minute.

## Part 5 - prompt-injection threat model

Threats are: retrieved text overriding the recommendation; model-directed non-read-only SQL; and inappropriate inclusion of complete uploaded CSV content.

| Attacker goal | Before defense | Prompt defense | Prompt + tool boundary |
|---|---|---|---|
| Override recommendation; attack | Outcome: override succeeds | Outcome: override blocked as un | Outcome: blocked; executable po |
| Run non-SELECT SQL; attack: "DE | Outcome: SQL misuse succeed | Outcome: prompt alone does not | Outcome: blocked by independent |
| Include all CSV content; attack | Outcome: disclosure succeed | Outcome: unnecessary disclosure | Outcome: blocked by prompt and |

The before-defense results are deterministic modeled simulations, not an additional live model run. Prompt-only defenses label retrieved policy as untrusted and rely on model instruction following. Tool-boundary defenses enforce executable restrictions; csv_sql independently accepts only read-only SELECT statements. Raw source: raw/hw7_prompt_injection_results.json.

Success conditions are explicit: recommendation override succeeds if hostile retrieved text changes the data-based decision; SQL misuse succeeds if a non-SELECT statement executes; and CSV-content misuse succeeds if the complete uploaded file is returned unnecessarily. The before-defense column is modeled analysis, not a live model run; prompt defense relies on instruction following; the tool boundary enforces the executable restriction independently.

## Part 6 - file tools and safety gate

code/hw7_file_tools.py implements read_file, write_file, edit_file, glob_files, search_in_files, and bash. _safe resolves every path under the temporary course sandbox. SAFE_PREFIXES allowlists bounded local commands. is_destructive independently detects destructive patterns, including the original false allow: python -c file writes. confirm_bash requires explicit confirmation for destructive commands, and bash applies a 30-second timeout.

Representative implementation excerpts:

```
def read_file(path, root, max_lines=None):
lines = _safe(path, root).read_text(encoding="utf-8").splitlines()
return "\n".join(lines if max_lines is None else lines[:max_lines])

def write_file(path, content, root):
target = _safe(path, root)
target.parent.mkdir(parents=True, exist_ok=True)
target.write_text(content, encoding="utf-8")
return str(target.relative_to(root.resolve()))

def edit_file(path, old, new, root):
target = _safe(path, root)
before = target.read_text(encoding="utf-8")
if old not in before: raise ValueError("text to replace was not found")
target.write_text(before.replace(old, new, 1), encoding="utf-8")

def glob_files(pattern, root):
return sorted(str(p.relative_to(root.resolve()))
for p in root.rglob(pattern) if p.is_file())

def search_in_files(query, root, file_pattern="*"):
matches = []
for path in root.rglob(file_pattern):
```

```
if not path.is_file():
continue
try:
for number, line in enumerate(
path.read_text(encoding="utf-8").splitlines(), 1
):
if query in line:
matches.append({"path": str(path.relative_to(root.resolve())),
"line": number, "text": line})
except UnicodeDecodeError:
continue
return matches
def bash(command, auto_approve=False):
decision = confirm_bash(command, auto_approve)
if not decision["allowed"]: return decision
return subprocess.run(command, shell=True, timeout=30, ...)
```

The safety constants and independent checks are:

```
SAFE_PREFIXES = ("python ", "python3 ", "pytest ", "ruff ",
"git status", "git diff", "git log")
DESTRUCTIVE_PATTERNS = (
r"\brm\s+(-[a-z]*r|--recursive)", r"\bdel\s+/s", r"\bformat\b",
r"\bmkfs\b", r"\bsudo\b", r"\b(runas|chmod|chown)\b", r"/dev/",
r"\b(init|mount)\b", r"(^|\s)>\s*/", r"\b(erase|rmdir)\b",
r"\bpython(?:3)?\s+-c\b",
)
def is_destructive(command):
return any(re.search(pattern, command, re.IGNORECASE)
for pattern in DESTRUCTIVE_PATTERNS)
def confirm_bash(command, auto_approve=False):
if is_destructive(command):
return {"allowed": bool(auto_approve),
"reason": "destructive command requires explicit confirmation"}
if not any(command.strip().startswith(prefix) for prefix in SAFE_PREFIXES):
return {"allowed": False, "reason": "command is not on SAFE_PREFIXES allow-list"}
return {"allowed": True, "reason": "command matches SAFE_PREFIXES"}
```

The corrected run in raw/hw7_file_tools_safety_results_corrected.json reports:

| Check | Result |
|---|---|
| Glob -> search -> read found DEBUG | pass |
| Allowed commands | 5/5 |
| Blocked commands | 5/5 |
| Corrected false allows | 0 |
| Outside sandbox modified | false |
| Database accessed | false |
| Model called | false |

The independent deny-list added python -c after the first run identified the inline Python file-write command as a false allow. No application file outside the temporary sandbox was modified.

The ten tested commands were:

| Allowed (5/5) | Blocked (5/5) |
|---|---|
| python -V | rm -rf x |
| ruff check . | sudo whoami |
| git status | chmod 777 x |
| git diff | mkfs /dev/sda |
| pytest -q | echo x > /root/x |

The sandbox integration created debug.py, searched for DEBUG, and read the matching content. The edit test produced this before/after diff:

```
-DEBUG = True
+DEBUG = False
```

The original false allow was an inline python -c file write. The independent deny-list now contains the exact pattern r"\bpython(?:3)?\s+-c\b", so the corrected evidence reports zero false allows.

## Screenshot evidence index

The following preserved screenshots are included in the PDF with readable captions: hw7_jwt_login_reader_200.png, hw7_jwt_login_invalid_401.png, hw7_auth_me_missing_token_401.png, hw7_auth_me_invalid_token_401.png, hw7_auth_me_reader_200.png, hw7_authenticated_list_200.png, hw7_reader_create_403.png, hw7_writer_create_201.png, hw7_writer_delete_403.png, hw7_moderator_delete_success.png, hw7_mysql_users_roles.png, hw7_agent_task_a_search_detail.png, hw7_agent_tasks_bc_json_derived.png, hw7_agent_nonexistent_id_recovery.png, hw7_lint_failure.png, hw7_lint_fix_pass.png, hw7_precommit_successful_commit.png, hw7_bikeshare_membership_wins.png, hw7_bikeshare_payg_wins.png, hw7_prompt_injection_defenses.png, and hw7_file_tools_safety_gate.png. No Task B completion screenshot exists, so the successful Task B result is documented from raw evidence rather than a visual capture. The JSON-derived Task B/C screenshot is included; the older typed summary screenshot and legacy failure screenshots are preserved on disk but excluded from the regenerated PDFs. The lint/pre-commit demonstration is shown by the three temporary-demo screenshots listed above.

Manual capture commands for replacement evidence:

```
Set-Location C:\Projects\data260-8844
$b = Get-Content reports/hw07/raw/hw7_task_b_final_smoke.json -Raw | ConvertFrom-Json
$c = Get-Content reports/hw07/raw/hw7_task_c_final_smoke_v2.json -Raw | ConvertFrom-Json
Write-Host "Student: Vrishin KunnathamParambath | SID4: 8844"
Write-Host "Task B actual sequence: $($b.actual_sequence -join ' -> ')"
Write-Host "Task B tool calls: $($b.tool_calls) | stop: $($b.stop_reason) | success: $($b.success)"
Write-Host "Task B database writes: $($b.database_writes)"
Write-Host "Task B raw evidence: reports/hw07/raw/hw7_task_b_final_smoke.json"
Write-Host "Task C actual sequence: $($c.actual_sequence -join ' -> ')"
Write-Host "Task C tool calls: $($c.tool_calls) | stop: $($c.stop_reason) | success: $($c.success)"
Write-Host "Task C classification: $($c.failure_classification)"
Write-Host "Task C adapter HTTP 500: $($c.model_adapter_http_500) | controller repair:
$($c.controller_repair)"
Write-Host "Task C database writes: $($c.database_writes)"
Write-Host "Task C raw evidence: reports/hw07/raw/hw7_task_c_final_smoke_v2.json"
```

## Tests, limitations, and preservation

Offline tests covered JWT creation/validation, password hashing, roles, bounded agent repair and tool-call budgets, Reflexion retry bounds, MRKL calculator and SQL validation, prompt security, file-tool sandbox behavior, migration safety, and the bike-share UI pipeline. Scoped Ruff passed. Full pytest was not claimed because collection/execution remained blocked by the managed environment and the repository code package shadowing the standard-library code module.

Existing HW1-HW6 source changes, reports, screenshots, raw evidence, database state, branches, tags, .hw6-chrome-pdf-profile*, and MEMORY.md.before-hw6 remain preserved. The verifier-generated verification.json records Commit 1, Commit 2 contains the verification metadata, and the annotated hw7 tag points to Commit 2. No GitHub push has occurred.


## Git packaging and submission status

Commit 1 contains the final HW7 artifacts. verification.json records Commit 1. Commit 2 contains verification.json, and the annotated hw7 tag points to Commit 2. The final tag target is verified from Git metadata after Commit 2. A commit cannot contain its own final hash because changing the hash would change the commit itself. The repository URL is https://github.com/Viki2183/data260-8844, and the final tagged tree URL is https://github.com/Viki2183/data260-8844/tree/hw7. No GitHub push has occurred.


## Submission packaging status

verification.json records Commit 1 and passed the offline smoke checks. The existing local hw7 tag points to Commit 2. A GitHub push remains unperformed.


## hw7_agent_nonexistent_id_recovery.png




## hw7_agent_task_a_search_detail.png




**hw7_agent_tasks_bc_json_derived.png**




# hw7_auth_me_invalid_token_401.png




# hw7_auth_me_missing_token_401.png



# hw7_auth_me_reader_200.png



# hw7_authenticated_list_200.png



# hw7_bikeshare_membership_wins.png



## HW7 Bike-share recommendation

Student: Vrishn KumarthamParambath | SID4: 8844

Trip CSV Choose File hw7_bikesh...hip_trips.csv Official pricing URL https://citibikenyc.com/plans-and-pricing Run

### Tool-call timeline

csv_sql -> policy_retriever -> calculator

### Results


```
{
  "decision": "Buy Monthly Membership",
  "pay_per_use": 8645,
  "membership": 19.92,
  "ride_count": 500,
  "average_duration": 30,
  "total_steps": 3,
  "total_time_ms": 738.829,
  "citations": [
    {
      "source": "https://citibikenyc.com/plans-and-pricing",
      "captured_at": "2026-10-25T08:58:06.404220+00:00",
      "snippets": [
        "TCP0012113-M\",\"lyftColumn\":{\"links\":[{\"href\":\"/careers\",\"text\":\"Careers\"},{\"href\":\"/lyftup/programs\",\"text\":\"lyft Up\"},{\"href\":\"/business\",\"text\":\"Business\"},{\"href\":\"/healthcare\",\"text\":\"Healthcare\"},{\"href\":\"/bikes\",\"text\":\"Bikes\"},{\"href\":\"/scooters\",\"text\":\"Scooters\"},{\"href\":\"/autonom
        "And back again.\",\"centerAlign\":true,\"compact\":true,\"hideHeaderLine\":true,\"ctaPlacement\":\"Bottom\",\"backgroundColor\":\"cyan5\",\"learnMoreUseButton\":false,\"learnMoreButtonStyle\":\"primaryNeutral\"},{\"componentType\":\"ComponentGroup\",\"id\":\"3y3D5DuzGdeNmO7PAmFHd\",\"displayName\":\"CitiBike Plans \\u0026 Pricing Page \\u003e
        "Please review this pricing page frequently to see current prices.\",\"ctaPlacement\":\"Bottom\",\"learnMoreUseButton\":false,\"learnMoreButtonStyle\":\"primaryNeutral\"}]},{\"componentType\":\"ComponentGroup\",\"id\":\"71dc80tGeBIc52oLICYmDr\",\"displayName\":\"CitiBike Plans \\u0026 Pricing Page \\u003e Treatment \\u003e Citi Bike Member Only
      ]
    }
  ],
  "stop_reason": "success",
  "rationale": "Pay-per-use costs $8645.00; membership plus residual charges costs $19.92. The recommendation is Buy Monthly Membership based on the supplied trip totals and pricing inputs."
}
```

# hw7_bikeshare_payg_wins.png



HW7 Bike-share recommendation

Student: Vrishas KonnathamParambath | SID4: 8844

Trip CSV Choose File hw7_bikash...ayg_wins.csv Official pricing URL https://citibikenyc.com/plans-and-pricing Run


Tool-call timeline

csv_sql -> policy_retriever -> calculator


Results


```
{
  "decision": "Pay Per Ride/Minute",
  "pay_per_use": 4545,
  "membership": 4700,
  "ride_count": 500,
  "average_duration": 10,
  "total_steps": 3,
  "total_time_ms": 591.582,
  "citations": [
    {
      "source": "https://citibikenyc.com/plans-and-pricing",
      "captured_at": "2026-10-25T09:00:37.531928+00:00",
      "snippets": [
        "ICP0032513-P\",\"IyftColumn\":{\"links\":[{\"href\":\"\\/careers\\",\"text\":\"Careers\"},{\"href\":\"\\/lyftup/programs\\",\"text\":\"Lyft Up\"}],{\"href\":\"\\/business\\",\"text\":\"Business\"},{\"href\":\"\\/healthcare\\",\"text\":\"Healthcare\"},{\"href\":\"\\/bikes\\",\"text\":\"Bikes\"},{\"href\":\"\\/scooters\\",\"text\":\"Scooters\"},{\"href\":\"\\/autonomo
        "And back again.\",\"centerAlign\":true,\"compact\":true,\"hideHeaderLine\":true,\"ctaPlacement\":\"Bottom\",\"backgroundColor\":\"cyan5\",\"learnMoreUseButton\":false,\"learnMoreButtonStyle\":\"primaryNeutral\"},{\"componentType\":\"ComponentGroup\",\"id\":\"3tJOSOmbSdaNmO7HaFAOc\",\"displayName\":\"CitiBike Plans \\u0026 Pricing Page \\u003e Tr
        "Please review this pricing page frequently to see current prices.\",\"ctaPlacement\":\"Bottom\",\"learnMoreUseButton\":false,\"learnMoreButtonStyle\":\"primaryNeutral\"}}},{\"componentType\":\"ComponentGroup\",\"id\":\"7IdcB0tGmDIc92nJCHmBrL\",\"displayName\":\"CitiBike Plans \\u0026 Pricing Page \\u003e Treatment \\u003e Citi Bike Member Only Pr
      ]
    }
  ],
  "stop_reason": "success",
  "rationale": "Pay-per-use costs $4545.00; membership plus residual charges costs $4700.00. The recommendation is Pay Per Ride/Minute based on the supplied trip totals and pricing inputs."
}
```


**hw7_file_tools_safety_gate.png**



# hw7_jwt_login_invalid_401.png




# hw7_jwt_login_reader_200.png




## hw7_lint_failure.png



**hw7_lint_fix_pass.png**



# hw7_moderator_delete_success.png



Code | Details

200

Response body


```
{
  "name": "hw7-writer-create-success",
  "ecosystem": "PyPI",
  "packageCode": "s8844-hw7-writer-success-02",
  "id": 8199,
  "createdAt": "2026-10-25T08:24:53",
  "updatedAt": "2026-10-25T08:24:53"
}
```


Download

Response headers


```
access-control-allow-credentials: true
content-length: 177
content-type: application/json
date: Sun,25 Oct 2026 08:30:24 GMT
server: uvicorn
vary: Origin
x-sql-statements: 4
```


Responses

Code | Description | Links

200 — Successful Response — *No links*

Media type: application/json

Controls Accept header.

Example Value | Schema


```
{
  "name": "string",
  "ecosystem": "string",
  "packageCode": "s8844-6SGJaM91XZcE",
  "id": 0,
  "createdAt": "2026-10-25T08:30:25.536Z",
  "updatedAt": "2026-10-25T08:30:25.536Z"
}
```



422 — Validation Error — *No links*

Media type: application/json


Example Value | Schema


```
{
  "detail": [
    {
      "loc": [
        "string",
        0
      ],
      "msg": "string",
      "type": "string",
      "input": "string",
      "ctx": {}
    }
  ]
}
```


## hw7_mysql_users_roles.png




**hw7_precommit_successful_commit.png**




# hw7_prompt_injection_defenses.png



**hw7_reader_create_403.png**



## hw7_writer_create_201.png



Code | Details

201

Response body


```
{
  "name": "hw7-writer-create-success",
  "ecosystem": "PyPI",
  "packageCode": "s8844-hw7-writer-success-02",
  "id": 8199,
  "createdAt": "2026-10-25T08:24:53",
  "updatedAt": "2026-10-25T08:24:53"
}
```


Download

Response headers

```
access-control-allow-credentials: true
content-length: 177
content-type: application/json
date: Sun,25 Oct 2026 08:24:52 GMT
server: uvicorn
vary: Origin
x-sql-statements: 3
```

Responses

| Code | Description | Links |
|---|---|---|
| 201 | Successful Response | *No links* |

Media type: application/json

Controls Accept header.

Example Value | Schema


```
{
  "name": "string",
  "ecosystem": "string",
  "packageCode": "s8844-CjHyEEPZ32EmDjX4ZohENP0cv_wcpyzXoGPkWpNvi_dZVocUV7mXmr-tCutRUtpoyAq.z03",
  "id": 0,
  "createdAt": "2026-10-25T08:24:52.908Z",
  "updatedAt": "2026-10-25T08:24:52.908Z"
}
```


| | | |
|---|---|---|
| 422 | Validation Error | *No links* |

Media type: application/json

Example Value | Schema

```
{
  "detail": [
    {
      "loc": [
        "string",
        0
      ],
      "msg": "string",
      "type": "string",
      "input": "string",
      "ctx": {}
    }
  ]
}
```

## hw7_writer_delete_403.png

