

Last review: march 2019

## **KIT ADDITIVEINFINITY 2.COMP**

## **DESCRIPTION OF THE PRODUCT**

USE: Bi-component epoxy structure, used with 3 components on INFINITY, 00,

PREMIUM or FINE. With this product you get the maximum performance of

the system.

FEATURES: Use in the last layer of all Inifnity systems.

Very indicated for wet areas and public areas.

## **APPLICATION INSTRUCTIONS**

PREPARING THE MIX: Mix comp.a (240 ml.) with the comp.b (120 ml.).

Mix the mixture KIT (a+b) with water corresponding to each system. 1 l. of water for Infinity and Infinity Premium or 1,2 l. of water for Infinity

"00" and Infinity Premium Fine

Mix all the content with 5 k. of Infinity, 00, Premium or Fine

APPLICATION CONDITIONS: Ambient temperature: > 5 ° C

R.H.: max. 80%

CLEANING: Water

## TECHNICAL DATA

DENSITY: 1,07 Kg./l.

POT LIFE: 1 Hour ready to use as repair or joining material

2 Hours mixed with Infinity, 00, Premium or Fine

APPEARANCE: White liquid

VOC CONTENT: Max. 140 gr./l. (Limit value EU: 140 gr./l. 2010)

PACKAGING: 360 ml. A+B ( 240 ml. comp.A + 120 ml. comp.B )

STORAGE STABILITY: 24 month keep away from frost.

info@h2ocoatings.com www.h2ocoatings.com