



Last review: April 2017

## INFINITY FIX

### DESCRIPTION OF THE PRODUCT

USE:	Adhesion primer based micro-quartz. Good grip on top of tile porous surfaces or ceramic surfaces.
FEATURES:	All surfaces
SYSTEM:	Apply one coat of Infinity Fix with roller or brush. On porous surfaces it is possible to dilute it 30% with water.

### APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be clean, dry, degreased and free of dust.
APPLICATION CONDITIONS :	Ambient temperature: 20°C - 30°C R.H.: max. 80%
APPLICATION MEANS:	Roller or brush
DILUTION :	Ready to use
CLEANING OF TOOLS:	Water
CONSUMPTION :	5 m <sup>2</sup> /Kg
PARTICULARITIES:	Mixing the material before using. Preferably with low speed electronic mixer.

### TECHNICAL DATA

FINISH:	Mat
COLORS :	colourless
WEIGHT CONTENT:	70 % on weight
VOC CONTENT :	VOC free
DENSITY:	1,47 KG / L
FLASH POINT:	No flammable
DRYING TIME:	min. 6 h.
PACKING:	5 Kg
STORAGE STABILITY :	12 months, keep away from frost

[info@h2ocoatings.com](mailto:info@h2ocoatings.com)

[www.h2ocoatings.com](http://www.h2ocoatings.com)

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it.