

Devices In Consideration

AD-CELLPACKBM-SL

What it comes with:

Boards

- 2x EVAL-ADBMS6830BMSW 16-Channel Battery Cell Monitor (can be purchased separately)
- 1x EVAL-ADBMS2950-BASIC Battery Pack Monitor (can be purchased separately)
- 1x EVAL-ADBMS6822 Dual isoSPI Adapter (can be purchased separately)
- 1x EVAL-SDP-CK1Z (SDP-K1) Controller Board (can be purchased separately)
- 2x DC2472A Battery Cell Emulator (can be purchased separately)
- 1x MAX32625PICO Programming Adapter with 10-pin SWD cable (can be purchased separately)

Cables and Other Accessories

- 2x Cell Connector Block (18-cell connector)
- 3x DuraClik isoSPI Twisted Pair Cables
- 3x USB Type A to Micro-B Cable
- 3x Alligator Clip / Test Lead

What it does:

- Accurate voltage and current measurement
- Highly scalable and ease of integration
- Robust isoSPI capability implementable in daisy chain high count
- Inclusive passive balancing with individual pulse-width modulation
- Isolated power supply between microcontroller and battery monitoring devices
- High voltage and current supply measurement
- Fast overcurrent (OC) measurement
- Redundancy measurement
- Modular BMS Solution
- Ready to use Broadmarket BMS GUI for Evaluation

Isolation:

Analog Devices (more common in UART-style isolation)