MP-68 / API testing Login

Login with valid credentials

Priority	Severity	Behavior	Type
High	Critical	Positive	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `POST http://localhost:3001/login` endpoint is available.
- Valid credentials are known: Username: `manager` Password: `Hotel2024!`

Postconditions

A valid authentication token is available for further authorized requests.

Steps to reproduce

#	Step	Action	Expected Result
1	Set a `POST` request to `/login` .		
2	Set `Content-Type` to `application/json` .		
3	Enter valid username and password in the request body.	Username: `manager` Password: `Hotel2024!`	
4	Send the request.		• Response status is `200 OK` . • Response body contains a `token` . • Token is returned as a string.

MP-69 / API testing Login

Login with correct username and incorrect password

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `http://localhost:3001/login` endpoint is available.
- Valid username is known.

Postconditions

- No authenticated session is created.
- No valid authentication token is generated for the failed login attempt.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login`.	Username: `manager` Password: `WrongPassword`	• Response status is `401 Unauthorized`. • Response body contains: `"reason": "Bad credentials"` • No authentication token is returned.

MP-70 / API testing Login

Login with incorrect username and correct password

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `http://localhost:3001/login` endpoint is available.
- Valid password is known.

Postconditions

- No authenticated session is created.
- No valid authentication token is generated for the failed login attempt.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login`.	Username: `wronguser` Password: `Hotel2024!`	• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned.

MP-71 / API testing Login

Login with incorrect username and incorrect password

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `http://localhost:3001/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login`.	Username: `wronguser` Password: `wrongpassword`	• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned.

MP-72 / API testing Login

Login with empty username

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `http://localhost:3001/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login` .	• Username: • Password: `Hotel2024!`	• Response status is `401 Unauthorized` . • Response body contains `Bad credentials` . • No token is returned.

MP-73 / API testing Login

Login with empty password

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `http://localhost:3001/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login` .	Username: `manager` Password:	• Response status is `401 Unauthorized` . • Response body contains `Bad credentials` . • No token is returned.

MP-74 / API testing Login

Login without username field

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	• Send a `POST` request to `/login`. • Provide only the password in the request body.	Password: `Hotel 2024!`	• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned.

MP-75 / API testing Login

Login without password field

Priority	Severity	Behavior	Type
High	Major	Negative	Functional

Layer	Is Flaky	Is Muted	Automation
API	No	No	Manual

Status	Milestone
Actual	-

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	• Send a `POST` request to `/login`. • Provide only the username `manager`.	Username: `manager`	• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned.

MP-76 / API testing Login

Login with empty request body

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	• Send a `POST` request to `/login`. • Set the request body to an empty JSON object.		• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned.

MP-77 / API testing Login

Login with partial password

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login` .	Username: `manager` Password: `Hotel2024`	• Response status is `401 Unauthorized` . • Response body contains `Bad credentials` . • No token is returned. • The API must require the complete password.

MP-78 / API testing Login

Login with username in incorrect case

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login` .	Username: `Manager` Password: `Hotel2024!`	• Response status is `401 Unauthorized` . • Response body contains `Bad credentials` . • No token is returned. • Username comparison is case-sensitive.

MP-79 / API testing Login

Login with password in incorrect case

Priority	Severity	Behavior	Type
High	Major	Negative	Functional

Layer	Is Flaky	Is Muted	Automation
API	No	No	Manual

Status	Milestone
Actual	-

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login`.	Username: `manager` Password: `hotel2024!`	• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned. • Password comparison is case-sensitive.

MP-80 / API testing Login

Login with additional character in password

Priority	Severity	Behavior	Type
High	Major	Negative	Functional

Layer	Is Flaky	Is Muted	Automation
API	No	No	Manual

Status	Milestone
Actual	-

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login`.	Username: `manager` Password: `Hotel2024!!`	• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned. • The password must match exactly.

MP-81 / API testing Login

Login with leading space in password

Priority	Severity	Behavior	Type
High	Major	Negative	Functional
Layer	**Is Flaky**	**Is Muted**	**Automation**
API	No	No	Manual
Status	**Milestone**		
Actual	-		

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login`.	Username: `manager` Password: `Hotel2024!`	• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned. • Leading spaces must not be ignored.

MP-82 / API testing Login

Login with trailing space in password

Priority	Severity	Behavior	Type
High	Major	Negative	Functional

Layer	Is Flaky	Is Muted	Automation
API	No	No	Manual

Status	Milestone
Actual	-

Preconditions

- API is running.
- `/login` endpoint is available.

Postconditions

No authenticated session is created.

Steps to reproduce

#	Step	Action	Expected Result
1	Send a `POST` request to `/login`.	Username: `manager` Password: `Hotel2024!`	• Response status is `401 Unauthorized`. • Response body contains `Bad credentials`. • No token is returned. • Trailing spaces must not be ignored.