

**Boost Your Testing Skills:
The Ultimate
TestNG Cheatsheet
You Can't Miss!**



Basic Annotations

@Test:

Marks a method as a test method.

@BeforeSuite:

Runs before all tests in the suite.

@AfterSuite:

Runs after all tests in the suite.

@BeforeTest:

Runs before any test method in the <test> tag.



@AfterTest:

Runs after all test methods in the <test> tag.

@BeforeClass:

Runs before the first method in the current class.

@AfterClass:

Runs after all the methods in the current class.

@BeforeMethod:

Runs before each test method.



@AfterMethod:

Runs after each test method.

@BeforeGroups:

Runs before the first test method in specified groups.

@AfterGroups:

Runs after all test methods in specified groups.



Test Configuration

TestNG XML File:

```
<!DOCTYPE suite SYSTEM
"https://testng.org/testng-1.0.dtd">
<suite name="Suite">
  <test name="Test">
    <classes>
      <class name="com.example.TestClass"/>
    </classes>
  </test>
</suite>
```



Assertions:

Assert.assertEquals(actual, expected):

Verifies that two values are equal.

Assert.assertNotEquals(actual, expected):

Verifies that two values are not equal.

Assert.assertTrue(condition):

Verifies that a condition is true.

Assert.assertFalse(condition):

Verifies that a condition is false.



Assert.assertNull(object):

Verifies that an object is null.

Assert.assertNotNull(object):

Verifies that an object is not null.



Parameters

TestNG XML File:

```
<parameter name="parameterName"value="parameterValue"/>
```

Java Code:

```
@Test  
@Parameters("parameterName")  
public void testMethod(String parameterName) {  
    // Use parameter  
}
```



Data Providers

Defining a Data Provider:

```
@DataProvider(name = "dataProvider")
public Object[][] dataProviderMethod() {
    return new Object[][] { { "data1" }, { "data2" } };
}
```

Using a Data Provider:

```
@Test(dataProvider = "dataProvider")
public void testMethod(String data) {
    // Use data
}
```



Groups

Grouping Tests:

```
@Test(groups = { "group1", "group2" })  
public void testMethod() {  
    // Test code  
}
```

Including/Excluding Groups in XML:

```
<groups>  
  <run>  
    <include name="group1"/>  
    <exclude name="group2"/>  
  </run>  
</groups>
```



Dependencies

Test Dependency:

```
@Test(dependsOnMethods = { "methodName" })  
public void testMethod() {  
    // Test code  
}
```

Group Dependency:

```
@Test(dependsOnGroups = { "groupName" })  
public void testMethod() {  
    // Test code  
}
```



Timeout

Test Method Timeout:

```
@Test(timeOut = 1000) // Timeout in milliseconds  
public void testMethod() {  
    // Test code  
}
```



Parallel Execution

XML Configuration:

```
<suite name="Suite" parallel="methods" thread-  
count="5">  
  <test name="Test">  
    <classes>  
      <class name="com.example.TestClass"/>  
    </classes>  
  </test>  
</suite>
```



Listeners

Implementing a Listener:

```
public class MyListener implements ITestListener
{
    @Override
    public void onTestStart(ITestResult result) {
        // Code to execute before each test
    }
    // Implement other methods as needed
}
```



Using a Listener:

```
<listeners>
```

```
  <listener class-  
name="com.example.MyListener"/>  
</listeners>
```



Was This Helpful?



www.qaharvest.com