

Types of Queues

- Circular Queue
- Priority Queue
- **deQueue (Double Ended Queue)**

Why need for dequeue?

- The point is that you need "fast access" to insert/deletes at both ends of the line, hence a deque. One example where deque can be used is the A-Steal job scheduling algorithm.
...
- To execute the next thread, the processor gets the first element from the deque (using the "remove first element" deque operation).

Deque

Definition

- A **deque** is a list in which elements can be inserted or deleted at either end.

Main features

- It is also known as a **head-tail linked list** because elements can be added to or removed from the front (head) or back (tail).
- no element can be added and deleted from the **middle**

Implementation

- A **deque** can be implemented either using a **circular array or a circular doubly linked list.**


Deque

Key points to remember

- The elements in a deque stretch from **LEFT** end to the **RIGHT** and since it is circular, **Dequeue[N-1]** is followed by **Dequeue[0]**.
- **Two pointers** are maintained, **LEFT and RIGHT** which point to **either end of the deque**.
- This differs from the queue abstract data type or **First-In-First-Out List (FIFO)**, where elements can only be **added to one end** and **removed from the other end** like a line in front of supermarket.
- Algorithm **INSERT-AT-FRONT** and **DELETE-FROM-REAR** are new and special in DeQueue and other are same as circular queue.

Main operations of dequeue

- **delete_fr_beg() (or) delete_fr_left()**: Deletes an item from front of Dequeue.
- **delete_fr_rear() (or) delete_fr_right()**: Deletes an item from rear or end of Dequeue.
- **insert_at_beg() (or) insert_at_left()**: inserts an item at the front of Dequeue.
- **insert_at_end() (or) insert_at_right()**: inserts an item at the rear or end of Dequeue.




Deque

- There are two variants of a double-ended queue:


□ ***Input restricted deque***: In this dequeue insertions can be done only at one of the ends while deletions can be done from both the ends.

□ ***Output restricted deque***: In this dequeue deletions can be done only at one of the ends while insertions can be done on both the ends.


Output restricted dequeue



Input restricted dequeue



The elements in a deque extend from the LEFT end to the RIGHT end and since it is circular, in a deque of N elements, Nth element of deque is followed by the first element of the deque.



Applications of Queues

- Queues are widely used as **waiting lists** for a single shared resource like **printer, disk, CPU**.
- Queues are used to **transfer data asynchronously** e.g., **pipes, file IO, sockets**.
- Queues are used as **buffers** on **MP3 players and portable CD players, iPod playlist**.
- Queues are used in **Playlist** for **jukebox** to **add songs to the end, play from the front of the list**.
- Queues are used in **OS** for **handling interrupts**. When programming a **real-time system** that can be **interrupted**, for ex, **by a mouse click**, it is necessary to **process the interrupts immediately** before proceeding with the current job. If the **interrupts have to be handled in the order of arrival**, then a FIFO queue is the appropriate data structure