

Food Delivery Time Prediction

Ananya Garg, Mohmmad Ayaan,
Swara Parekh, Vikranth Udandaraao


Group 10
ML-end sem project



INDRAPRASTHA INSTITUTE *of*
INFORMATION TECHNOLOGY
DELHI



Motivation



Running a food delivery service requires ensuring timely and quality deliveries despite challenges like traffic and bad weather.

To tackle this, we are developing a Food Delivery Time Prediction System using machine learning. Our goal is to accurately predict delivery times by analyzing historical delivery data, current traffic conditions, and real-time weather trends.

1. **DergiPark - Comparative Analysis of ML models**

The research paper titled "A Comparative Analysis of Machine Learning Models for Time Prediction in Food Delivery Operations" highlights that ensemble models like Gradient Boosting outperform others in predicting delivery times, using metrics such as MAE and RMSE. Key factors include traffic volume and order quantity.

2. **DergiPark - Application of Random Forest Algorithm**

The study uses features like time of day, restaurant info, and traffic conditions to predict food delivery time, with Random Forest (500 trees) achieving ~95% accuracy. Cross-validation, Bootstrap methods, and metrics like confusion matrices confirm the model's high accuracy and reliability.

Dataset Description



- **Initial Rows:** 41,368 (after cleaning and preprocessing)
- **Preprocessing Steps:**
 - Removed "**conditions**" prefix from *Weather Conditions*.
 - Standardized columns into appropriate formats: strings, integers, and floats.
 - Converted *Order Date* to **datetime** format.
 - Extracted time from *Time Ordered* and *Time Order Picked*.
 - Dropped rows with **null values** for consistency.

Key Features Impacting Delivery Times Using Random Forest Analysis

- Traffic Density
- Multiple Deliveries
- Delivery Person's Rating
- Delivery Person's Age
- Festival Season

Dataset Description



The dataset used is publicly available on Kaggle.


The columns of the dataset are:

ID	Order_Date
Delivery_person_ID	Time_Orderd
Delivery_person_Age	Time_Order_picked
Delivery_person_Ratings	Weatherconditions
Restaurant_latitude	Road_traffic_density
Restaurant_longitude	Vehicle_condition
Delivery_location_latitude	Type_of_order
Delivery_location_longitude	Type_of_vehicle
Festival, City	Multiple_deliveries
Time_taken(min)	

Dataset Description – EDA



Correlation Heatmap of Numeric Features



- The **heatmap** visualizes relationships between various **numeric features**.

- **Red:** Positive Correlations
- **Blue:** Negative Correlations


Key Observations:

- **Delivery Location Latitude & Restaurant Latitude**
 - Strong **positive correlation: 0.94**
 - Indicates that delivery and restaurant locations tend to align closely in latitude.
- **Delivery Person Ratings & Time Taken (minutes)**
 - Moderate **negative correlation: -0.36**
 - Suggests that **higher ratings** are associated with **shorter delivery times**.

Dataset Description – EDA



UMAP Projection of Numeric Features




UMAP (Uniform Manifold Approximation and Projection) visualizes the projection of numeric features in the dataset into a **2D space**.

- Each point represents a **data sample**.

Key Observations:

- **Clusters:**
 - Distinct clusters indicate that deliveries with **similar characteristics** (e.g., traffic density, delivery person ratings, time taken) tend to group together.
 - These clusters may represent deliveries with **comparable time predictions** or **delivery conditions**.

Dataset Description – EDA



- **Delivery Location Latitude** and **Restaurant Latitude** exhibit a clear **linear trend**.
 - This suggests a **strong geographical alignment** between delivery and restaurant locations, indicating that deliveries typically occur within close proximity to the restaurant's latitude.

Data Preprocessing – Feature Selection



Performed feature selection using **SelectKBest** with **F-regression**, which ranked features by their **linear correlation** with the target. Numerical features were used directly, while categorical features were **one-hot encoded**, and their scores aggregated to reflect group importance.

The k best features achieved are:



Road_traffic_density
Festival
multiple_deliveries
Delivery_person_Ratings
Delivery_person_Age

City
Weatherconditions
Vehicle_condition
Type_of_vehicle

Approach:

- **Data Preprocessing:**
 - Handled missing values and standardized the data to ensure consistency and comparability.
 - Performed feature selection using statistical feature selection.
- **Modeling:**
 - Utilized **Ensemble Learning** techniques:
 - **Bagging, Random Forest, XGBoost, LightGBM, K-Cross Validation, and SVM.**
 - Chosen for their ability to handle **structured data** and capture **nonlinear relationships** effectively.
- **Train-Test Split:**
 - Data split into **80% training** and **20% test** sets to evaluate model performance.
- **Evaluation Metrics:**
 - **Mean Squared Error (RMSE)** and **R2 Score** were used to assess model performance.

Results And Analysis



Results, Analysis And Conclusion



R² Scores:

- **LightGBM** and **XGBoost** models have the highest R² scores, indicating better predictive performance with a strong ability to explain the variance in the data.
- **Elastic Net Regularization** shows the lowest R² score, suggesting it struggled to capture the relationships between features and delivery time.

MSE (Mean Squared Error):

- The **LightGBM** and **XGBoost** models have the lowest MSE, meaning they produced the most accurate predictions with minimal error.
- **Elastic Net Regularization** exhibits the highest MSE, indicating it performed poorly compared to the other models.

Conclusion:

- **LightGBM** and **Random Forest** are the top-performing models in terms of both R² and MSE, making them ideal choices for predicting food delivery times in this dataset.
- **Elastic Net Regularization** consistently underperforms across both metrics, showing its limitations for this task.

Completed:

- **Data Cleaning & Preprocessing:** Handled missing values, standardized data.
- **Data Analysis:** Performed exploratory data analysis and pattern visualization.
- **Modeling & Evaluation:** Applied ML models and assessed performance using appropriate metrics.
- **Model Refinement:** Enhanced model performance by testing various feature combinations and using k means feature selection.
- **Reporting:** Drafted and finalized the project report, summarizing model performance, key findings, and detailed conclusions.
- **Presentation Preparation:** Created visualizations and completed the final project presentation.

Individual team members' contributions



- **Vikranth Udandaraao:** Literature review, Data Collection, EDA, visualization of dataset, model analysis and results.
- **Swara Parekh:** Literature review, Data Collection, EDA, visualization of dataset, model analysis and results.
- **Mohmmad Ayaan:** Literature review, Data Collection, EDA, visualization of dataset, model analysis and results.
- **Ananya Garg:** Literature review, Data Collection, EDA, visualization of dataset, model analysis and results.

References



- [1] Comparative Analysis of ML Models for Food Delivery Prediction. Available at: <https://dergipark.org.tr/en/pub/aita/issue/84471/1459560>
- [2] Application of Random Forest Algorithm in Food Delivery Time Prediction. Available at: <https://dergipark.org.tr/en/pub/forecasting/issue/60291/842180>
- [3] Gaurav Malik. Food Delivery Dataset. Available at: <https://www.kaggle.com/datasets/gauravmalik26/food-delivery-dataset/data>
- [4] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., Duchesnay, E. Scikit-learn: Machine Learning in Python. Journal of Machine Learning Research, 12, pp. 2825-2830, 2011. Available at: <https://scikit-learn.org>
- [5] Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., and Liu, T. Y. LightGBM: A Highly Efficient Gradient Boosting Decision Tree. Advances in Neural Information Processing Systems 30 (NIPS 2017). Available at: <https://lightgbm.readthedocs.io>
- [6] Chen, T. and Guestrin, C. XGBoost: A Scalable Tree Boosting System. Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, 2016. Available at: <https://xgboost.readthedocs.io>

Thank You