REPLACE LDO WITH BUCK CONVERTER

5V - 3.3V Buck Converter

Designed for 3.3V - 5V input

Route for 1A in

Inductor: SDR0403-1R0ML
1uH, 20%, 33mOhm DCR (max)
3.8A (rms), 5.5A (sat), 3.2mm tall

Route for 3A out



Maximum output power = 6.6W
Expected efficiency at 1A = 94.3%

Current Calculations

Green LED voltage drop: 2.2V
- I = (3.3-2.2V)/120 = 10.83mA

Title Power			UW Robotics 200 University Avenue Waterloo Ontario Canada N2L 3G6
Size: Letter	Drawn By: Qinyang Bao, Nicole Rosario		
Date: 6/4/2020	Sheet of		
File: C:\Users\badpr\altium_porjects\MarsRover2020-PCB\Projects\Safety\Rev2\SH1 - POWER.SchDoc			

Power Connector



Programming Connector



I2C Current Sensors



CAN Daisy Chain Connectors



Motor Voltage



Battery Voltage



Title: Connectors		UW Robotics 200 University Avenue Waterloo Ontario Canada N2L 3G6
Size: Letter	Drawn By: Qinyang Bao, Nicole Rosario	
Date: 6/4/2020	Sheet of	
File: C:\Users\badpr\altium_porjects\MarsRover2020-PCB\Projects\Safety\Rev2\SH2 - CONNECTORS.SchDoc		

OffSheet



Title Safety - Opamps		UW Robotics 200 University Avenue Waterloo Ontario Canada N2L 3G6
Size: Letter	Drawn By: Qinyang Bao, Kyle Hong	
Date: 6/4/2020	Sheet of	
File: C:\Users\badpr\altium_porjects\MarsRover2020-PCB\Projects\Safety\Rev2\SH3 - OPAMPS.SchDoc		

Characteristic impedance of cable= Zo = 100 Ohms
Cable: https://www.digikey.ca/product-detail/en/general-cable-carol-brand/C0601A-41-10/C0601AG-50-ND/7313814
Calculations & Theory: http://www.ti.com/lit/an/snla031/snla031.pdf pg3
Terminating resistance = Zo =100Ohm = Rc = Rb
Bias resistors for FAILSAFE BIAS = Rd = Ra
Vfsb = Vcc(Rc//Rb / (Rc//Rb + Rd + Ra))
Parallel terminating resistance = 100//100 = 50Ohms, Vcc = 3.3V, Vfsb= 0.2V (for FAILSAFE bias)
Therefore, Ra = Rd = (50*3.3/0.2 - 50)/2 = 387.5 Ohms
Recalculating total terminating resistance: 100// (387.5*2) = 88.6 Ohms
88.6 is more than 10% diff from Zo, therefore recalculate Rc using Zo = Rc//(Ra+Rd)=100
Rc = Zo*(Ra+Rd)/(Ra+Rd-Zo)= 114.8Ohms
Using 1% tolerance: Rc = 115 Ohms Ra=Rd=392Ohms
Check:
Rc//(Ra+Rd)=100.3=Zo
Fsb = Vcc(Rc//Rb / (Rc//Rb + Rd + Ra))= 3.3(115//100 / (115//100 + 2*392)) = 0.21V

Differential I2C Bus Buffer



Termination resistor(s) should only be used on Safety board and last current sensor in the chain of current sensors (ie the first and last node).

Title Safety - Differential I2C		UW Robotics 200 University Avenue Waterloo Ontario Canada N2L 3G6
Size: Letter	Drawn By: Ayesha Ebrahim	
Date: 6/4/2020	Sheet of	
File: C:\Users\badpr\altium_porjects\MarsRover2020-PCB\Projects\Safety\Rev2\SH4 - DIFFERENTIAL I2C.SchD		

STM32F446RET6



Title MCU			UW Robotics 200 University Avenue Waterloo Ontario Canada N2L 3G6
Size: Letter	Drawn By: Qinyang Bao, Nicole Rosario		
Date: 6/4/2020	Sheet of		
File: C:\Users\badpr\altium_porjects\MarsRover2020-PCB\Projects\Safety\Rev2\SH5 - MICROCONTROLLER.SchDoc			

CAN Transceivers



Title CAN		UW Robotics 200 University Avenue Waterloo Ontario Canada N2L 3G6
Size: Letter	Drawn By: Qinyang Bao, Nicole Rosario	
Date: 6/4/2020	Sheet of	
File: C:\Users\badpr\altium_porjects\MarsRover2020-PCB\Projects\Safety\Rev2\SH6 - CAN.SchDoc		

Board Stack Report