


DFM REPORT | quotes@bacircuits.com or 855-811-1975

Name	qcw71leo.zip	ld.	39767 - QED OK
Report Generated on	Feb 1, 2020 5:14:34 AM	Customer	InstantDFM
Board Id			

Top View Top View C2 SQL ALERT SQL SQL R12 R1 R3 SDA R10 TR4 TSCL R8 TR7 T 3V3 R11 TR6 T GND A0 A1	Single PCB View - Original
R1 R3 R2 R12 R12 R12 R10 R84 SCL R8 R10 R7 GND RND	Top View
1.5748 inch	R1 R3 R2 R12 R12 R12 R12 R10 I R4 I SCL R8 I R7 I R6 I GND A0 A1



Summary - General - Original	
PCB Size	1.5748 inch x 1.5748 inch
PCB Thickness	62.00 mil
Customer Panel Size	
Copper Layers	2
Solder Mask	Both
Solder Mask Color	Red
Legend	Both
Legend Color	White
Peeloff Mask	None
Carbon Mask	None
Edge Connectors	No

Surface Finish	unknown
Max. Aspect Ratio on PTH	5.2
Number of Nets	13
Electrical Test	Single Sided
Drilled SMD Pads	No
SMD Pads Top	45
SMD Pads Bottom	0
BGA Pads Top	0
BGA Pads Bottom	0
Drill Hole Density	53 Holes/inch ²

Summary - Copper Layer Minima - Original											
Layer Type	Copper Width	Critical Copper Width	Trace Width	Critical Trace Width	Copper to Copper Clr.	Trace to Trace	Same Net Clr.	Ring	Plated	Copper to NPTH Clr.	Copper to Outline Clr.
	mil	mil	mil	mil	mil	mil	mil	mil	mil	mil	mil
Outer	1.09	7.00	7.00	7.00	5.99	6.00	2.14	6.00	⁹ 11.99	¹⁰ 25.68	19.94

The information of strives to make it

Integr8tor v2019.07-190709 Page1



BayArea DFM REPORT | quotes@bacircuits.com or 855-811-1975

Name	qcw71leo.zip	ld.	39767 - QED OK
Report Generated on	Feb 1, 2020 5:14:34 AM	Customer	InstantDFM
Board Id			


Summary - Sequences - Original											
Туре	Sequences	Tools	Min. End Dia.	Max. End Dia.	Holes	Moves	Min. Ring on Outer	Min. Ring on Inner	Min. Hole to Copper Clr.		
			mil	mil			mil	mil	mil		
PTH	1	4	12.00	140.00	128	0	6.00		11.99		
NPTH	1	1	118.11	118.11	4	0	>32.00		25.68		
Total	2	5	12.00	140.00	132	0	6.00		11.99		

Integr8tor v2019.07-190709



DFM REPORT | quotes@bacircuits.com or 855-811-1975

Name	qcw71leo.zip	ld.	39767 - QED OK
Report Generated on	Feb 1, 2020 5:14:35 AM	Customer	InstantDFM
Board Id			



Trace to Trace

Outer Layers

6.00 mil



Copper to Copper Clr.

Outer Layers


5.99 mil


Integr8tor v2019.07-190709 Page3





DFM REPORT | quotes@bacircuits.com or 855-811-1975


Name	qcw71leo.zip	ld.	39767 - QED OK
Report Generated on	Feb 1, 2020 5:14:35 AM	Customer	InstantDFM
Board Id			














Integr8tor v2019.07-190709 Page4



Bayarea DFM REPORT | quotes@bacircuits.com or 855-811-1975

Name	qcw71leo.zip	ld.	39767 - QED OK
Report Generated on	Feb 1, 2020 5:14:35 AM	Customer	InstantDFM
Board Id			

Copper Layer Minima & Area - Original										
File	Pos.	Copper Width	Critical Copper Width	Trace Width	Critical Trace Width	Copper to Copper Clr.	Same Net Clr.	Copper Are	ea	
		mil	mil	mil	mil	mil	mil	inch ²	%	
Current-Sensor-Rev1_GTL	1	1.22	7.00	7.00	7.00	5.99	2.14	2.0391	82	
Current-Sensor-Rev1_GBL	2	1.09	7.00	7.00	7.00	6.00	10.15	2.0321	82	

Sopper Layer Millima - Copper VS Dilli - Original												
File	Pos.			Ring			Copper vs	s Drill Clr.	Copper to Outline CIr.			
		Overall	Via	Laser Via	Comp.	Mech.	Plated	NPTH	Overall	Pad to Outline	Track to Outline	Region to Outline
		mil	mil	mil	mil	mil	mil	mil	mil	mil	mil	mil
Current-Sensor- Rev1_GTL	1	6.00	6.00		29.92		11.99	25.68	19.94	20.80	>64.00	19.94
Current-Sensor- Rev1_GBL	2	6.00	6.00		29.92		12.00	25.68	19.94	20.80	>64.00	19.94

Drill Tools - Original													
File	Tool Nr.	Span	Type	Method	Filled Via	Counter	Dia.	Tol. Min	Tol. Plus	Holes (in PCB)	Moves (in PCB)	Double Hits (in File)	Predrill Hits (in File)
							mil	mil	mil				
Current-Sensor- Rev1_TXT	1	1-2	PTH	unknown	unknown	unknown	12.00	0.00	0.00	11	0	0	0
Current-Sensor- Rev1_TXT	2	1-2	PTH	unknown	unknown	unknown	28.00	0.00	0.00	110	0	0	0
Current-Sensor- Rev1_TXT	3	1-2	PTH	unknown	unknown	unknown	40.16	0.00	0.00	5	0	0	0
Current-Sensor- Rev1_TXT	4	1-2	PTH	unknown	unknown	unknown	140.00	0.00	0.00	2	0	0	0
Current-Sensor- Rev1_TXT	5	1-2	NPTH	unknown	unknown	unknown	118.11	0.00	0.00	4	0	0	0

Drill Tools - Drill vs Copper - Original											
File	Tool Nr.	Span	Туре	Method	Dia.	Min. Ring on Outer	Min. Ring on Inner	Min. Pad Size			
					mil	mil	mil	mil			
Current-Sensor-Rev1_TXT	1	1-2	PTH	unknown	12.00	6.00		24.00			
Current-Sensor-Rev1_TXT	2	1-2	PTH	unknown	28.00	10.98		49.96			
Current-Sensor-Rev1_TXT	3	1-2	PTH	unknown	40.16	29.92		100.00			
Current-Sensor-Rev1_TXT	4	1-2	PTH	unknown	140.00	>32.00		> 204.00			
Current-Sensor-Rev1_TXT	5	1-2	NPTH	unknown	118.11	>32.00					

1										
Sequences	- Original									
Span	Туре	Tools	Min. End Dia.	Max. End Dia.	Holes	Min. Ring on Outer	Min. Ring on Inner	Min. Hole to Copper Clr.	Min. Hole to Outline Clr.	Min. Slot to Outline Clr.
			mil	mil		mil	mil	mil	mil	mil
1-2	PTH	4	12.00	140.00	128	6.00		11.99	50.50	disabled
1-2	NPTH	1	118.11	118.11	4	>32.00		25.68	61.44	disabled
All	All	5	12.00	140.00	132	6.00		11.99	50.50	disabled

Integr8tor v2019.07-190709



BayArea DFM REPORT | quotes@bacircuits.com or 855-811-1975

qcw71leo.zip	ld.	39767 - QED OK
Feb 1, 2020 5:14:35 AM	Customer	InstantDFM
H	1	

Rout Tools - Original										
File	Tool Nr.	Туре	Tool Dia.	End Dia.	Draw Length	Nibble Count				
			mil	mil	mil					

Routed Holes - Original										
File	Hole Nr.	Instances	X Size	Y Size	Draw Length	Nibble Count				
			mil	mil	mil					

Solder Mask - O	riginal							
Side	Min. Mask to Mask Clr.	Min. Web	Min. Ring on Cu Defined Pads	Min. Ring on SM Defined Pads	Min. Mask to Copper Clr.	Fully Covered Via Holes	Partly Covered Via Holes	Half Mask Vias
	mil	mil	mil	mil	mil			
Тор	7.31	>10.00	4.00	>10.00	0.34	Yes	No	
Bottom	7.31	>10.00	4.00	>10.00	2.00	Yes	No	
Both	7.31	>10.00	4.00	>10.00	0.34	Yes	No	No

Files - Original					
Initial	Renamed	Format	Function	Position	Color
Current-Sensor-Rev1.GTP	Current-Sensor-Rev1_GTP	ger274x	paste	top	
Current-Sensor-Rev1.GTO	Current-Sensor-Rev1_GTO	ger274x	silk	top	white
Current-Sensor-Rev1.GTS	Current-Sensor-Rev1_GTS	ger274x	mask	top	red
Current-Sensor-Rev1.GTL	Current-Sensor-Rev1_GTL	ger274x	outer	1	
Current-Sensor-Rev1.GBL	Current-Sensor-Rev1_GBL	ger274x	outer	2	
Current-Sensor-Rev1.GBS	Current-Sensor-Rev1_GBS	ger274x	mask	bottom	red
Current-Sensor-Rev1.GBO	Current-Sensor-Rev1_GBO	ger274x	silk	bottom	white
Current-Sensor-Rev1.TXT	Current-Sensor-Rev1_TXT	excellon2	mixed	1-2	
Current-Sensor-Rev1.GBP	Current-Sensor-Rev1_GBP	ger274x	empty	none	
Current-Sensor-Rev1.GM1	Current-Sensor-Rev1_GM1	ger274x	mechanical	none	

Input Remarks - Original

Gerber import: Self-intersecting contours are detected, continuing with an interpretation of the contours. 'Current-Sensor-Rev1.GBO' (at line 1836)

Comments - Original

Integr8tor v2019.07-190709 The information on this document is not only based on files in a clearly defined format, but also on freely structured files and inference rules. Ucamco strives to make it as accurate as possible, but it cannot guarantee the result in all situations. This information is used at the sole risk of its user.